

The Haulotte® advantages

- Hydraulic differential lock for demanding rough terrain conditions
- 29 ft 10 in length for improved manoeuvrability.
- Large & robust slewing ring
- Simultaneous proportional controls for all movements.
- Side mounted engine for easy access & maintenance.
- Improved productivity through fast boom movement speeds.
- · Robust, reliable, easy to maintain.


STANDARD FEATURES


- · 4 wheel drive
- Tilt alarm
- 180° hydraulic platform basket rotation
- Silent pack Hatz diesel engine
- Free wheeling device
- Safe use in winds up to 28 mph
- Simple operational controls
- Battery emergency lowering system.
- · Slewing block pin
- Hourmeter
- Towing hooks / lifting brackets
- 110 V outlet

OPTIONS & ACCESSORIES

- 91 in x 32 in platform
- Rotating beacon
- Catalytic exhaust
- Work light
- Travel alarm
- Overload device
- Generator 3 kW
- 794 lb Platform Capacity with 37 mph wind. (Machine weight: 27,871 lb)







SPECIFICATIONS	
Working Height	67 ft 8 in
Platform Height	61 ft8 in
Horizontal Reach	56 ft 3 in
Platform Capacity	507 lb
⚠ Length	29 ft 10 in
③ Width	8 ft 2 in
⊙ Stowed Height	9 ft 5 in
• Wheelbase	8 ft 2 in
G Ground clearance	14 in
🙃 x 😘 Platform size	71 in x 32 in
Tailswing	42 in
Drive speed	0.9 - 3.1 mph
Outside turning radius	20 ft 2 in
Turntable Rotation - Continuous	360°
Platform Rotation	180°
Power source	Diesel 43.6 hp / 32.1 kW
Controls	Proportional
Gradeability	40%
Tires (Foam Filled)	15 R 22
Hydraulic tank	40 gal
Fuel tank	40 gal
Weight	25,909 lb

ANSI/SIA A92.5 and CSA/B354.4 Standards Compliance

Distributed By:



www.onesourcerental.com



HAULOTTE US Inc - 7135 STANDARD DRIVE - HANOVER MD 21076 - USA

PHONE: +1 410 712 4403 - FAX: +1 410 712 4419

Main Toll Free: +1 877-HAULOTTE - e-mail: sales@us.haulotte.com

Haulotte Group - La Péronnière - BP 9 -42152 l'Horme - France

Tél: +33 (0)4 77 29 24 24 - Fax: +33 (0)4 77 29 43 95 - e-mail: haulotte@haulotte.com - web: http://www.haulotte.com