The vsftpd backdoor exploit was executed successfully using Metasploit against the Metasploitable2 server. However, no direct alerts related to the exploit were generated in Wazuh because the target machine did not have a Wazuh agent installed. The SIEM system only monitored the Kali host, where authentication and privilege escalation events were detected and mapped to MITRE ATT&CK techniques.

The attacker IP address (10.0.2.15) was manually banned using CrowdSec to simulate containment. The decision was successfully added and verified using the cscli decisions list command. This demonstrates how security teams can block malicious IP addresses during incident response to prevent further exploitation attempts.

Incident Report

Executive Summary

A simulated attack targeting the VSFTPD service was conducted against the Metasploitable2 system. The attack exploited the VSFTPD 2.3.4 backdoor vulnerability using Metasploit. The activity was detected by Wazuh, which generated an alert indicating a potential exploitation attempt.

Timeline

15:10 — Attack initiated from Kali Linux
15:11 — Wazuh detected suspicious FTP activity
15:12 — Alert triaged by SOC analyst
15:15 — Attacker IP blocked using CrowdSec

Recommendations

Disable vulnerable FTP services, patch outdated software, implement firewall restrictions, and maintain continuous monitoring through SIEM tools.

Stakeholder Briefing

A simulated security incident was conducted to test our monitoring and response capabilities. An attacker attempted to exploit a known vulnerability in the VSFTPD service on a test server. The activity was quickly detected by our monitoring system, Wazuh, and investigated by the SOC team. The source of the attack was identified and immediately blocked using CrowdSec to prevent further access. The incident confirmed that our detection and response systems are functioning effectively. However, the test highlighted the importance of regularly updating systems and removing vulnerable services to reduce potential attack surfaces.