

Rings and Algebras in MAGMA

Silvia Properzi

January 13, 2026

Outline / Table of Contents

Basic ring constructions

substructures

Maps

Predicates for rings

Algebraic extensions

Other (approximate) constructions

Algebras

Additive and Multiplicative Structure

Changing the Base Ring

Integers, Residue Rings, and Fields

Rings of integers

- ▶ `Integers()`

Residue class rings

- ▶ `Integers(n)` creates $\mathbb{Z}/n\mathbb{Z}$
- ▶ This is a ring, not a field in general

Fields

- ▶ `Rationals()` for \mathbb{Q}
- ▶ `GF(p)` for \mathbb{F}_p

```
Z := Integers();  
Z12 := Integers(12);  
Q := Rationals();  
F5 := GF(5);
```

Polynomial Rings

Univariate polynomial rings

- ▶ $R\langle x \rangle := \text{PolynomialRing}(R)$

Multivariate polynomial rings

- ▶ $R\langle x, y \rangle := \text{PolynomialRing}(R, 2)$

Note

- ▶ Polynomial rings are exact rings.
- ▶ They are the basis for most constructions.

```
Z := Integers();  
R<x,y> := PolynomialRing(Z,2);
```

Fraction Fields and Rational Function Fields

For R an integral domain.

Field of fractions

► $F\langle t \rangle := \text{FieldOfFractions}(R)$

Note `FieldOfFractions` does not explicitly construct the inclusion $R \hookrightarrow \text{Frac}(R)$.

```
Z := Integers();
ZX<x> := PolynomialRing(Z);

FieldOfFractions(ZX);
// Univariate rational function field
// over Integer Ring
// Variables: $.1

F<t> := FieldOfFractions(ZX);
F!x; // t
```

Subrings

```
R := Integers();  
S, f := sub< R | 2 >;
```

- ▶ Subrings are defined by generators
- ▶ The output has the inclusion map

Ideals

```
R<x,y> := PolynomialRing(Rationals(), 2);  
I := ideal< R | x^2, y^2, x*y >;
```

Note:

```
R<x> := PolynomialRing(Integers(), 1);  
  
// ERROR: coefficient ring must be a field  
I := ideal< R | x^2 - 2 >;  
  
// Works (symbolic quotient)  
Q := quo< R | x^2 - 2 >;
```

- ▶ `ideal<R|...>` requires the coefficient ring to be a field
- ▶ Over \mathbb{Z} , general ideal machinery is unavailable

Homomorphisms via Generators

Ring homomorphisms are defined as maps or by images of generators

```
P<x> := PolynomialRing(Integers());  
R := quo< P | x^2 >;  
S := Integers(4);  
phi := hom< R -> S | 2 >; // x |-> 2  
phi(x);  
Kernel(phi);
```

Note: Relations are *not checked*

```
// x |-> 3 does NOT respect x^2 = 0  
psi := hom< R -> S | 3 >;  
psi(x^2) eq psi(x)^2; // false
```

- ▶ $\text{map}\langle R \rightarrow S \mid x \mapsto f(x) \rangle$ defines a function
- ▶ No algebraic properties are checked

Ring Predicates in MAGMA

- ▶ `IsCommutative(R)`
- ▶ `IsUnitary(R)`
- ▶ `IsFinite(R)`
- ▶ `IsOrdered(R)`
- ▶ `IsIntegralDomain(R)`
- ▶ `R eq S R ne S`
- ▶ `IsField(R)`
- ▶ `IsLocal(R)`
- ▶ `IsDivisionRing(R)`
- ▶ `IsEuclideanRing(R)`
- ▶ `IsMagmaEuclideanRing(R)`
- ▶ `IsPID(R)`
- ▶ `IsUFD(R)`
- ▶ `HasGCD(R)`
- ▶ `IsArtinian(R)`
- ▶ `IsNoetherian(R)`

Euclidean Ring Distinction in MAGMA: `IsEuclideanRing(R)` tests the mathematical property, while `IsMagmaEuclideanRing(R)` checks if MAGMA can actually run Euclidean algorithms.

Euclidean Rings in MAGMA

Note: A ring may be Euclidean in theory, but not "computably Euclidean" in MAGMA.

```
R<x> := PolynomialRing(Integers());  
Q := quo< R | x^2 - 2 >;  
IsEuclideanRing(Q); //true  
IsMagmaEuclideanRing(Q); // false
```

Explanation:

- ▶ $Q = \mathbb{Z}[x]/(x^2 - 2)$ is mathematically Euclidean. Hence `IsEuclideanRing(Q)` returns true.
- ▶ MAGMA does not implement the necessary Euclidean operations for this quotient. Therefore `IsMagmaEuclideanRing(Q)` returns false.

Algebraic Extensions: the Polynomial $x^2 + 5$

Let $f(x) = x^2 + 5$.

1. Quotient $\mathbb{Z}[x]/(x^2 + 5)$

```
Z := Integers();  
R<x> := PolynomialRing(Z);  
Q := quo<R | x^2 + 5>;  
Type(Q);    // RngUPolRes  
IsDomain(Q);  
IsUFD(Q); //fails  
IsPrime(Q!x); // fails
```

Algebraic Extensions: the Polynomial $x^2 + 5$

2. Algebraic extensions $\mathbb{Q}(\sqrt{-5})$ and $\mathbb{Z}[\sqrt{-5}]$

```
K2<a> := ext<Rationals() | x^2 + 5>;  
Type(K2); // FldNum  
Za:= ext<Integers() | x^2 + 2>;  
Type(Za); // RngOrd  
K2 eq NumberField(x^2 + 5); // false
```

Note: `Za<a> := ext<Integers() | x2 + 5>;` ERROR

Possible solution:

```
Zx<x> := PolynomialRing(Integers());  
Za := ext<Integers() | x^2 + 5>;  
a := Za.1; // a = 1  
b := Za.2 // b = sqrt(-5)  
alpha := 3 + 2*b;  
IsPrime(alpha);  
IsIrreducible(alpha);
```

Prime and Irreducible elements: number fields and ring of integers

3. Number Field $\mathbb{Q}(\sqrt{-5})$ and its ring of integers

```
Qx<x> := PolynomialRing(Rationals());  
K<a> := NumberField(x^2 + 5);  
Type(K);    // FldNum  
OK:=Integers(K);  
Type(OK); // RngOrd
```

If we now consider the integers,

```
OK := Integers(K);  
p := OK!a;  
IsIrreducible(p); // fails  
IsPrime(p); // fails  
I := ideal<OK | a>;  
IsPrime(I); // works  
IsMaximal(I); // fails
```

Local and Series Rings

p -adic fields

- ▶ `pAdicField(p)`

Power and Laurent series

- ▶ `PowerSeriesRing(R)`
- ▶ `LaurentSeriesRing(R)`

Note

- ▶ These are approximate rings with finite precision.

Free and Finitely Presented Algebras

Free associative algebras

- ▶ `FreeAlgebra(R,n)`

Finitely presented algebras

- ▶ Quotients of free algebras

```
k := GF(3);  
F<x,y> := FreeAlgebra(k,2);  
A := quo<F | x^2, y^2, x*y>;
```

- ▶ `MatrixAlgebra(R,n)`

Group algebras

- ▶ `GroupAlgebra(R,G)`

Jacobson radical

JacobsonRadical works for finite-dimensional algebras over fields.

```
M := MatrixAlgebra(Rationals(), 2);
X := M![1,0,0,0];
Y := M![0,1,0,0];
A := sub<M | X,Y>;
Dimension(A);    // 2
JacobsonRadical(A);
// Matrix Algebra [ideal of A] of degree 2
// and dimension 1 over Rational Field
```

It fails for finitely presented algebras (even if finite-dimensional).

```
F<x,y> := FreeAlgebra(Rationals(), 2);
B := quo<F | x^2,y^2,x*y-y*x>;
Dimension(B); // 4
JacobsonRadical(B); // fails:
// Runtime error in 'JacobsonRadical':
// Bad argument types Argument types given:
//AlgFP
```

Additive Group of a Ring

AdditiveGroup returns the additive group as an abelian group, along with a map to the ring.

```
R := Integers(12);  
A, phi := AdditiveGroup(R);  
phi; // map from A to R  
AdditiveGroup(Integers());  
//Abelian Group isomorphic to Z  
AdditiveGroup(GF(16));  
// Abelian Group isomorphic to  
// Z/2 + Z/2 + Z/2 + Z/2
```

Note: It doesn't work for infinite fields or polynomial rings.

```
AdditiveGroup(Rationals()); //fails  
  
P:=PolynomialRing(Integers())  
AdditiveGroup(P); // fails
```

Units of a Ring

```
R := Integers(12);  
U, f := UnitGroup(R);  
f; // map from U to R  
U<u,v> := UnitGroup(R);  
Generators(U) eq {u,v}; // true
```

Note: It doesn't work for infinite fields or polynomial rings.

```
UnitGroup(Rationals()); // fails  
Zx:=PolynomialRing(Integers())  
UnitGroup(Zx); // fails  
Qx:=PolynomialRing(Rationals())  
UnitGroup(Qx); // fails
```

Units in Matrix Rings

```
M := MatrixRing(Integers(9), 2);
A := M![1,2,3,4];
IsUnit(A);           //true
Inverse(A);          // fails
A^-1;                // works
UnitGroup(M);        //fails
```

Note: UnitGroup is only available for matrices over finite fields.

```
UnitGroup(MatrixRing(Rationals(), 2));
// Runtime error:
// Base field for algebra must be finite
```

```
UnitGroup(MatrixRing(Integers(7), 2)); //fails
M := MatrixRing(GF(7), 2);
b, G := UnitGroup(M); //b=true, G=GL(2, GF(7))
G; // prints the group and the two generators
b, G<A,B>:= UnitGroup(M); // A, B are the gens
```

Changing the Base Ring

- Magma supports coercion between polynomial rings

```
P<x> := PolynomialRing(Integers(), 1);  
Q<y> := PolynomialRing(Rationals(), 1);  
f := P!(x^2 + 2);  
g := Q!f; // Change base ring to Q
```

- ChangeRing allows base extension for algebras

```
k := FiniteField(3);  
F<x,y> := FreeAlgebra(k, 2);  
I := ideal< F | x^2, y^2, x*y >;  
A := quo< F | I >;  
L := FiniteField(9);  
AL := ChangeRing(A, L);
```