POWER QUALITY ANALYZERS

ALM 20

- 3 Voltage & 3 current Channels (neutral current calculated)
- Network Frequencies: 50 Hz, 60 Hz & 400 Hz (ideal for defense applications)
- 128 samples/cycle
- Quadruple backlit digital display
- Self-powered, via the phase
- Few weeks of measurement recording
- Recording: 1 sec, 1 min to 60 mins
- PC interface & Android application

- AC/DC Voltage: Upto 1,000 V Ph-N & 2,000 V Ph-Ph
- Power Measurements: kW, kVAr, kVA, PF & DPF
- Energy Measurements: kWh, kVArh (4 Quadrant), kVAh
- Crest factor & phase unbalance measurement
- THD (V, I) & Individual Harmonics: Upto 50th order

ALM 31

- 3 Voltage & 3 current Channels
- 5.7" color ¼ VGA TFT screen display
- Displays real time waveform
- Few hours/Weeks of measurement recording
- Recording Intervals: 1s, 5s, 20s, 1m, 2m, 5m, 10m, 15m
- PC interface
- Battery backup upto 13 hours
- AC/DC Voltage: Upto 1,000 V Ph-N & 2,000 V Ph-Ph
- Power Measurements: kW, kVAr, kVA, PF & DPF
- Energy Measurements: kWh, kVArh (4 Quadrant), kVAh
- Crest factor, K-factor & phase unbalance measurement
- THD (V, I) & Individual Harmonics: Upto 50th order
- Short flicker measurement (Pst)

ALM 36

- Complied with IEC 61000-4-30 Class B measurements
- 4 Voltage & 4 Current Channels

- 5.7” Color ¼ VGA TFT screen display
- Displays real time waveform
- Memory upto 2 GB
- Recording Intervals: 1s, 5s, 20s, 1m, 2m, 5m, 10m, 15m
- PC interface
- Alarms 10,000 of 40 conditions
- AC/DC voltage: Upto 1,000 V Ph-N & 2,000 V Ph-Ph
- Power Measurements: kW, kVAr, kVA, PF & DPF
- Energy Measurements: kWh, kVArh (4 Quadrant), kVAh
- Crest factor, K factor & phase unbalance, dip measurements
- Transients (Upto 210 counts) & TrueInrush (over a period of 10 minutes) function
- THD (V, I) & Individual Harmonics: Upto 50th order
- (Pst) Short & (Plt) Long term flicker measurements

CA 8345 CLASS A

- IEC 61000-4-30 Class A Ed 3.0 certified
- 4 Voltage & 4 Current Channels
- 512 samples/cycle
- 7” color LCD touch screen (WVGA)
- Memory upto 64 GB
- Trend Recording Period: 200ms to 2hrs
- PC interface
- Alarms 16,362, of 40 conditions
- Battery backup upto 10 hours
- AC/DC Voltage: Upto 1,000V Ph-N & 2,000V Ph-Ph
- Power Measurements: kW, kVAr, kVA, PF & DPF
- Energy Measurements: kWh, kVArh (4 Quadrant), kVAh
- THD (V, I), Crest factor, K-factor, phase unbalance, dip measurement
- Harmonics: Upto 127th order
- Interharmonics: Upto 126th order
- 2.5 µs transients capture & TrueInrush (over a period of 10 minutes) function
- (Pst) Short & (Plt) Long term flicker measurements
-

CT Specifications (Suitable for ALM XX Series)

Specifications	Ampflex A193 450 mm	Ampflex A193 800 mm	MN 93A	PAC 93	C 193	J 93
Dia (mm)	140	250	20	39	52	72

Maximum Current	10,000 Aac	10,000 Aac	Dual range 5 Aac & 100 Aac	1,000 Aac / 1,300 Adc	1,000 Aac	3,500 Aac / 5,000 Adc
Range	100 mA to 10,000 Aac	100 mA to 10,000 Aac	5 mA to 5 Aac / 100 mA to 100 Aac	1 A to 1,000 Aac / 1 A to 1,300 Adc	1 A to 1,000 Aac	50 A to 3,500 Aac / 50 A to 5,000 Adc
Accuracy	±2%	±2%	±0.7%	±3%	±0.2%	±1%
Safety	CAT IV 600 V/CAT III 1000 V	CAT IV 600 V/CAT III 1000 V	CAT IV 300 V/CAT III 600 V	CAT III 600 V	CAT IV 600 V	CAT IV 300 V / CAT III 600 V

DATAVIEW FOR KRYKARD POWER QUALITY ANALYSER ALM XX

- Recovery of the measurement data
- Stored in the instrument
- Backup of measurement files
- Opening of backup files
- Processing & creation of reports
- Export into Excel spreadsheets
- Export in pdf format
- Database management

THERMAL IMAGERS

MA 250

- IR Resolution: 256 × 192 (49,152 pixels)
- SuperIR Resolution: Yes, on captured images & live view
- Temperature Range: -20°C to 400°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 50° × 37.2°
- NETD: < 40 mK
- Focus: Fixed & minimum distance 0.2m
- Image Frequency: 50 Hz
- Image Modes: Thermal/PIP
- Communication Interface:
  USB-C Android, USB-C iOS, Lightning iOS
  (Includes a Lightning to USB-C adapter)

TC E050

- IR Resolution: 96 × 96 (9,216 pixels)
- SuperIR Resolution: 240 × 240
- Temperature Range: -20°C to 550°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 50° × 50°
- NETD: < 50 mK
- Focus: Fixed & minimum distance of 0.1m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion
- Visual Camera: 640 × 480 (0.3 MP)
- Display: 240 × 320 Resolution, 2.4" LCD Screen
- Battery Backup: Approximately 8 hours (Built-in)
- Memory: Built-in 4GB flash memory (30,000 images)

TC S030

- IR Resolution: 96 × 96 (9,216 pixels)
- SuperIR Resolution: Yes, on captured images & live view
- Temperature Range: -20°C to 350°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 50° × 50°
- NETD: < 50 mK
- Focus: Fixed Focus & minimum focus of 0.1m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending

- Visual Camera: 640 × 480 (0.3 MP)
- Display: 320 × 240 Resolution, 3.5" LCD touch screen
- Battery Backup: Approximately 4 hours (Built-in)
- Memory: Built-in 4GB (30,000 Images & 20 hours Video)

TC S240

- IR Resolution: 256 × 192 (49,152 pixels)
- SuperIR Resolution: Yes, on captured images & live view
- Temperature Range: -20°C to 400°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 50° × 37.2°
- NETD: < 40 mK
- Focus: Fixed & minimum distance 0.3m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" LCD touch screen with auto-rotation
- Battery Backup: Approximately 4 hours (Built-in)
- Memory: Built-in 16 GB (60,000 Images & 54 hours Video)

TC 2150

- IR Resolution: 192 × 144 (27,648 pixels)
- SuperIR Resolution: Yes, on captured images & live view
- Temperature Range: -20°C to 550°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 27.8° × 37.2°
- NETD: < 40 mK
- Focus: Fixed & minimum distance 0.3m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP
- Visual Camera: 1600 × 1200 (2 MP)
- Display: 240 × 320 Resolution, 3.2" LCD screen
- Battery Backup: Approximately 6 hours (Built-in)
- Memory: Built-in 16 GB (90,000 Images)

TC 2250

- IR Resolution: 256 × 192 (49,152 pixels)
- SuperIR Resolution: Yes, on captured images & live view
- Temperature Range: -20°C to 550°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 37.2° × 50.0°
- NETD: < 40 mK

- Focus: Fixed & minimum distance 0.3m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP
- Visual Camera: 1600 × 1200 (2 MP)
- Display: 480 × 640 Resolution, 3.2" LCD screen
- Battery Backup: Approximately 6 hours (Built-in)
- Memory: Built-in 16 GB (35,000 Images)

TC 3151

- IR Resolution: 192 × 144 (27,648 pixels)
- SuperIR Resolution: 384 × 288
- Temperature Range: -20°C to 550°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 37.2° × 27.8°
- NETD: < 40 mK
- Focus: Fixed & minimum distance 0.5m
- Image Frequency: 25 Hz
- Image modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" LCD touch screen
- Battery Backup: Approximately 6 hours (Interchangeable Battery)
- Memory: 32 GB Micro SD card (60,000 Images & 150 hours Video)

TC 3250

- IR Resolution: 256 × 192 (49,152 pixels)
- SuperIR Resolution: 512 × 384
- Temperature Range: -20°C to 550°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 25° × 18.8°
- NETD: < 40 mK
- Focus: Manual & minimum distance 0.1m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" LCD touch screen
- Battery Backup: Approximately 6 hours (Interchangeable Battery)
- Memory: 32 GB Micro SD card (60,000 Images & 150 hours Video)

TC 3360

- IR Resolution: 384 × 288 (110,592 pixels)
- SuperIR Resolution: 768 × 576
- Temperature Range: -20°C to 650°C

- Accuracy: ±2°C, ±2%
- Field of View (FOV): 41.1° × 30.5°
- NETD: < 30 mK
- Focus: Manual & minimum distance 0.1m
- Image Frequency: 30 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 64 GB Micro SD card (100,000 Images & 300 hours Video)

TC 3660

- IR Resolution: 640 × 480 (307,200 pixels)
- SuperIR Resolution: 1280 × 960
- Temperature Range: -20°C to 650°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 41.9° × 33.3°
- NETD: < 35 mK
- Focus: Manual & minimum distance 0.3m
- Image Frequency: 30 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 64 GB Micro SD card (100,000 Images & 300 hours Video)

TC P360

- IR Resolution: 384 × 288 (110,592 pixels)
- SuperIR Resolution: 768 × 576
- Temperature Range: -20°C to 650°C
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 24° × 18°
  (Optional lens available)
- NETD: ≤ 50 mK
- Focus: Auto & minimum distance 0.15m
- Image Frequency: 25 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 640 × 480 Resolution, 3.5" Capacitive touch LCD screen
- Battery Backup: 8 Hours (Built-in)
- Memory: 16GB TF card

TC 4360

- IR Resolution: 384 × 288 (110,592 pixels)
- SuperIR Resolution: 768 × 576
- Temperature Range: -20°C to 650°C
- Accuracy: ±1°C, ±1%
- Field of View (FOV): 25° × 19°
  (Optional lens available)
- NETD: < 35 mK
- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF & minimum distance 0.1m
- Image Frequency: 50 Hz
- Image Modes: Infrared/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 800 × 480 Resolution, 4.3" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 64 GB Micro SD Card (60,000 Images & 54 hours Video)

TC 4460/TC 4460H

- IR Resolution: 480 × 360 (172,800 pixels)
- SuperIR Resolution: 960 × 720
- Temperature Range: -20°C to 650°C (TC 4460) & -20°C to 2000°C (TC 4460H)
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 18.7° × 14°
  (Optional lens available)
- NETD: < 35 mK
- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF & minimum distance 0.25m
- Image Frequency: 50 Hz
- Image Modes: Infrared/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 800 × 480 Resolution, 4.3" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 64 GB Micro SD card (60,000 Images & 54 hours Video)

TC 4660/TC 4660H

- IR Resolution: 640 × 480 (307,200 pixels)
- SuperIR Resolution: 1280 × 960
- Temperature Range: -20°C to 650°C (TC 4660) & -20°C to 2000°C (TC 4660H)
- Accuracy: ±2°C, ±2%
- Field of View (FOV): 25° × 19°
  (Optional lens available)
- NETD: < 35 mK

- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF & minimum distance 0.25m
- Image Frequency: 50 Hz
- Image Modes: Infrared/Visual/Fusion/PI/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 800 × 480 Resolution, 4.3" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 64 GB Micro SD card (60,000 Images & 54 hours Video)

THERMAL CAMCORDERS

TCC 7460/TCC 742K

- IR Resolution: 480 × 360 (172,800 pixels)
- SuperIR Resolution: 960 × 720
- Temperature Range: -20°C to 650°C (TCC 7460) & -40°C to 2200°C (TCC 742K)
- Accuracy: ±1°C, ±1%
- Field of View (FOV):
  L6: 6° × 4.5°
  L9: 9° × 6.8°
  L19: 18.7° × 14°
  L37: 37.3° × 27.8°
- NETD: < 30 mK
- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF
- Minimum Focus Distance:
  L6: 2 m
  L9: 1 m
  L19: 0.15 m
  L37: 0.15 m
- Image Frequency: 30 Hz
- Image Modes: Infrared/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 1280 × 720 Resolution, 5" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 128 GB SD card (120,000 Images & 500 hours Video)

TCC 7660/TCC 762K

- IR Resolution: 640 × 480 (307,200 pixels)
- SuperIR Resolution: 1280 × 960
- Temperature Range: -20°C to 650°C (TCC 7660) & -40°C to 2200°C (TCC 762K)
- Accuracy: ±1°C, ±2%

- Field of View (FOV):
  L8: 8° × 6°
  L12: 12° × 9°
  L25: 24.8° × 18.7°
  L50: 50° × 37.3°
- NETD: < 30 mK
- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF
- Minimum Focus Distance:
  L8: 2 m
  L12: 1 m
  L25: 0.15 m
  L50: 0.15 m
- Image Frequency: 30 Hz
- Image Modes: Thermal/Visual/Fusion/PIP/Blending
- Visual Camera: 3264 × 2448 (8 MP)
- Display: 1280 × 720 Resolution, 5" LCD touch screen
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 128 GB SD card (120,000 Images & 500 hours Video)

TCC 812K

- IR Resolution: 1280 × 1024 (1,310,720 pixels)
- SuperIR Resolution: 2560 × 2048
- Temperature Range: -40°C to 2200°C
- Accuracy: ±1°C, ±1%
- Field of View (FOV):
  L8: 7.9° × 6.3°
  L12: 12° × 9.6°
  L25: 25° × 20°
  L50: 50° × 40°
- NETD: < 20 mK
- Focus: Laser Assisted AF, Continuous AF, AF, Manual, Touch AF
- Minimum Focus Distance:
  L8: 5 m
  L12: 1.65 m
  L25: 0.3 m
  L50: 0.2 m
- Image Frequency: 30 Hz
- Image Modes: Infrared/Visual/Fusion/PIP/Blending
- Visual Camera: 4208 × 3120 (13 MP)
- Display: 1920 × 1080 Resolution, 5.1" OLED touch screen, Lv 360 Cd/m²
- Battery Backup: Approximately 4 hours (Interchangeable Battery)
- Memory: 128 GB SD card (30,000 Images & 130 hours Video)

Thermal Camera Specifications Table

MODEL	TC E050	TC S030	TC S240	TC 2150	TC 2250
Thermal Resolution	96 × 96	96 × 96	256 × 192	192 × 144	256 × 192
Thermal Sensitivity (NETD)	< 50 mK	< 50 mK	< 40 mK	< 40 mK	< 40 mK
Field Of View (FOV)	50° × 50°	50° × 50°	50° × 37.2°	27.8° × 37.2°	37.2° × 50.0°
Spatial Resolution (IFOV)	8.89 mrad	8.89 mrad	3.43 mrad	3.3 mrad	3.3 mrad
Focus Mode	Fixed	Fixed	Fixed	Fixed	Fixed
Temperature Measurement Range	-20°C to 550°C	-20°C to 350°C	-20°C to 400°C	-20°C to 550°C	-20°C to 550°C
Image Frequency	25 Hz	25 Hz	25 Hz	25 Hz	25 Hz
Minimum Focus Distance	0.1m	0.1m	0.3m	0.3m	0.3m
Display	240 × 320 Resolution, 2.4” LCD Screen	320 × 240 Resolution, 3.5” LCD touch screen	640 × 480 Resolution, 3.5” LCD touch screen with auto-rotation	240 × 320 Resolution, 3.2” LCD Screen	480 × 640 Resolution, 3.2” LCD Screen
Digital Zoom	-	1.0× to 4.0× continuous	1.0× to 4.0× continuous	-	-
Image Modes	Thermal/Visual/Fusion	Thermal/Visual/Fusion/PIP/Blending	Thermal/Visual/Fusion/PIP/Blending	Thermal/Visual/Fusion/PIP	Thermal/Visual/Fusion/PIP
Storage	Built-in 4 GB eMMC	Built-in 4 GB flash memory	Built-in 16 GB flash memory	Built-in 16 GB flash memory	Built-in 16 GB flash memory

Image Storage Capacity	18,000 Images	30,000 Images	60,000 Images	90,000 Images	35,000 Images
Video Storage Capacity	-	20 hours	54 hours	-	-
Annotations	Laser	Note Annotations	Note Annotations	-	-
Laser	Yes	Yes	Yes	Yes	Yes
USB	Yes	Yes	Yes	Yes	Yes
Bluetooth	Yes	Yes	Yes	Yes	Yes
WiFi	-	-	Yes	-	-
Battery Life	Approximately 8 hours	Approximately 4 hours	Approximately 4 hours	Approximately 6 hours	Approximately 6 hours

Advanced Thermal Camera Specifications

MODEL	TC 3151	TC 3250	TC 3360	TC 3660	TC P360
Thermal Resolution	192 × 144	256 × 192	384 × 288	640 × 480	384 × 288
Thermal Sensitivity (NETD)	< 40 mK	< 40 mK	< 30mK	< 35mK	< 50mK
Field of View (FOV)	37.2° × 27.8°	25° × 18.8°	41.1° × 30.5°	41.9° × 33.3°	24° × 18°
Spatial Resolution (IFOV)	3.33 mrad	1.74 mrad	1.87 mrad	1.13 mrad	1.1 mrad
Focus Mode	Fixed	Manual Focus	Manual Focus	Manual Focus	Motor /Auto
Temperature Measurement Range	-20°C to 550°C	-20°C to 550°C	-20°C to 650°C	-20°C to 650°C	-20°C to 650°C

Image Frequency	25 Hz	25 Hz	30 Hz	30 Hz	50 Hz
Minimum Focus Distance	0.5m	0.1m	0.3m	0.3m	0.15m
Display	640 × 480 Resolution, 3.5" LCD touch screen	640 × 480 Resolution, 3.5" LCD touch screen	640 × 480 Resolution, 3.5" LCD touch screen	640 × 480 Resolution, 3.5" LCD touch screen	640 × 480 Resolution, 3.5" Capacitive touch LCD screen
Digital Zoom	1.0× to 8.0× continuous	1.0× to 8.0× continuous	1.0× to 8.0× continuous	1.0× to 8.0× continuous	1.0× to 10× continuous
Image Modes	Thermal/Visual/Fusion/PIP/Blending	Thermal/Visual/Fusion/PIP/Blending	Thermal/Visual/Fusion/PIP/Blending	Thermal/Visual/Fusion/PIP/Blending	IR/CCD/Duo Vision Duo Vision Plus
Storage	32 GB Micro SD Card	32 GB Micro SD Card	64 GB Micro SD Card	64 GB Micro SD Card	16 GB TF card
Image Storage Capacity	60,000 Images	60,000 Images	100,000 Images	100,000 Images	65,000+ Images
Video Storage Capacity	150 hours	150 hours	300 hours	300 hours	-
Annotations	Voice/Note Annotation	Voice/Note Annotation	Voice/Note Annotation	Voice/Note Annotation	Voice/Note Annotation
Laser	Yes	Yes	Yes	Yes	Yes
USB	Yes	Yes	Yes	Yes	Yes
Bluetooth	Yes	Yes	Yes	Yes	Yes

WiFi	Yes	Yes	Yes	Yes	Yes
Interchangeable Battery	-	-	-	-	Built-in
Battery Life	Approximately 6 hours	Approximately 6 hours	Approximately 4 hours	Approximately 4 hours	Approximately 8 hours

High-End Thermal Camera Specifications

MODEL	TC 4360	TC 4460	TC 4660	TCC 7460	TCC 7660	TCC 812K
Thermal Resolution	384 × 288	480 × 360	640 × 480	480 × 360	640 × 480	1280 × 1024
Thermal Sensitivity (NETD)	< 35 mK	< 35 mK	< 30 mK	< 30 mK	< 30 mK	< 20 mK
Field of View (FOV)	25° × 19°	18.7° × 14°	25° × 19°	L6: 6° × 4.5°; L9: 9° × 6.8°; L19: 18.7° × 14°; L37: 37.3° × 27.8°	L8: 8° × 6°; L12: 12° × 9°; L25: 24.8° × 18.7°; L50: 50° × 37.3°	L8: 7.9° × 6.3°; L12: 12° × 9.6°; L25: 25° × 20°; L50: 50° × 40°
Spatial Resolution (IFOV)	1.13 mrad	0.68 mrad	0.68 mrad	L6: 0.82 mrad; L9: 1.3 mrad; L19: 1.63 mrad; L37: 3.42 mrad	L8: 0.42 mrad; L12: 0.65 mrad; L25: 1.35 mrad; L50: 2.65 mrad	L8: 0.42 mrad; L12: 0.65 mrad; L25: 1.3 mrad; L50: 2.0 mrad

Focus mode	Laser Assisted AF/Continuous AF/AF/Manual Focus/Touch AF	Focus mode	Laser Assisted AF/Continuous AF/AF/Manual Focus/Touch AF	Focus mode	Laser Assisted AF/Continuous AF/AF/Manual Focus/Touch AF	Focus mode
Temperature measurement Range	-20°C to 650°C	-20°C to 650°C (in TC 4460H)	-20°C to 650°C (in TC 4660H)	-20°C to 2200°C (in TCC 742K)	-20°C to 2200°C (in TCC 762K)	40°C to 2200°C
Image Frequency	50 Hz	50 Hz	50 Hz	30 Hz	30 Hz	30 Hz
Minimum Focus Distance	0.1m	0.25m	0.25m	L6: 2m; L9: 1m; L19: 0.15m; L37: 0.15m	L8: 2m; L12: 1m; L25: 0.15m; L50: 0.15m	L8: 5m; L12: 1.65m; L25: 0.3m; L50: 0.2m
Display	800 × 480 Resolution, 4.3" LCD touch screen	Display	800 × 480 Resolution, 4.3" LCD touch screen	Display	800 × 480 Resolution, 4.3" LCD touch screen	1280 × 720 Resolution, 5" LCD touch screen
Digital Zoom	1.0× to 8.0× continuous	1.0× to 8.0× continuous	1.0× to 8.0× continuous	1.0× to 12.0× continuous	1.0× to 12.0× continuous	1.0× to 12.0× continuous
Image Modes	Infrared/Visual/Fusion/PIP/Blending	Image Modes	Infrared/Visual/Fusion/PIP/Blending	Image Modes	Infrared/Visual/Fusion/PIP/Blending	Image Modes
Storage	64 GB Micro SD Card	64 GB Micro SD Card	64 GB Micro SD Card	128 GB SD Card	128 GB SD Card	128 GB SD Card
Image Storage Capacity	60,000 Images	60,000 Images	60,000 Images	120,000 Images	120,000 Images	120,000 Images
Video Storage Capacity	54 hours	54 hours	54 hours	500 hours	500 hours	130 hours

Annotations	Voice/Text note	Annotations	Voice/Text note	Annotations	Voice/Text note	Annotations
Laser	Yes	Laser	Yes	Laser	Yes	Laser
USB	Yes	USB	Yes	USB	Yes	USB
GPS & Compass	Yes	GPS & Compass	Yes	GPS & Compass	Yes	GPS & Compass
HDMI Interface	Yes	HDMI Interface	Yes	HDMI Interface	Yes	HDMI Interface
Bluetooth	Yes	Bluetooth	Yes	Bluetooth	Yes	Bluetooth
WiFi	Yes	WiFi	Yes	WiFi	Yes	WiFi
Interchangeable Battery	Yes	Interchangeable Battery	Yes	Interchangeable Battery	Yes	Interchangeable Battery
Battery life	Approximately 4 hours	Battery life	Approximately 4 hours	Battery life	Approximately 4 hours	Battery life

INSULATION TESTERS

CA 6522/CA 6528

- Display: 4000 counts, double digital backlit LCD screen
- Logarithmic bargraph (CA 6522)
- Continuity at 200mA
  CA 6528: 0.02Ω - 40Ω CA 6522: 0.00Ω - 10.00Ω
- Visual alarm: Blue/Red backlighting (CA 6528)
- Timer (mins): Up to 39:59
- Automatic shutdown, Hold, Manual / Lock / Duration modes
- IP 40 (CA 6528), IP 54 (CA 6522)
- **Insulation**
  Test Voltage: 250 V, 500 V, 1000 V
  Range/Accuracy:
  CA 6522: 50 kΩ to 40 GΩ / ± (3% +2 counts)
  CA 6528: 50 kΩ to 11 GΩ / ± (1.5% R+10 pt)
- **Voltage**
  Range: Up to 700 V

CA 6524/CA 6526

- Display: 4000 counts, double + bargraph
- Continuity at 200mA (0.00Ω - 10.00Ω) / 20mA (0.0Ω - 100.0Ω)
- PI & DAR
- Visual Pass/Fail: Red/Green (CA 6526)
- Timer (mins): Up to 39:59
- Configurable alarms
- Memory:
  300 measurements (CA 6524)
  1300 measurements (CA 6526)
- Communication:
  Bluetooth (CA 6526)
- **Insulation**
  Test Voltage: 50 V, 100 V, 250 V, 500 V, 1000 V
  Test Current: 0.01 µA to 2 mA
  Range: 10 kΩ to 200 GΩ
  Accuracy: ± (3% +2 counts)
- **Voltage**
  Range: Up to 700 V
- **Capacitance**
  Range: 0.1 nF to 10 µF (**CA 6526**)

CA 6532/CA 6534/CA 6536

- Display: 4000 counts, double + bargraph
- PI & DAR (CA 6532)
- Continuity at 200mA (0.00Ω - 10.00Ω) / 20mA (0.0Ω - 100.0Ω)
- Timer (min:s): Up to 39:59
- Memory:
  1300 records (CA 6532 & 6534)
- Communication:
  Bluetooth (CA 6532 & 6534)
- **Test Voltage/Insulation Range**
  CA 6532: 50 V, 100 V / 10 kΩ to 20 GΩ for Telecommunications (maximum 100 Km line length)
  CA 6534: 10 V, 25 V, 100 V, 250 V, 500 V / 2 kΩ to 50 GΩ for electronics industries & electrostatic discharge
  CA 6536:
  10 V to 100 V in 1V step / 2 kΩ to 20 GΩ for Avionics, Space & Defense
  Test current: 0.01µA to 2mA
  Accuracy: ± (3% +2 counts)
- **Voltage Range**: Up to 700 V
- **Capacitance**: 0.1 nF to 10 nF (**CA 6532**)

CA 6505/CA 6545

- Display: Backlit LCD graphic display with bargraph
- Programmable test duration
- Automatic calculation of the DAR/PI
- DD calculation (CA 6545)
- Locking test voltage
- Programmable Alarms (CA 6545)
- Smoothing of Display (CA 6545)
- Automatic detection of the presence of AC or DC external voltage on terminals
- Auto power save mode to save battery power
- **Insulation**
  Test voltage (Fixed/Adjustable):
  500 V, 1000 V, 2500 V, 5000 V / 40 V to 5100 V in 10 V or 100 V increments
  Range: 10 kΩ to 10 TΩ
  Accuracy: ± 5% +3 pts
- **Voltage**
  Range: Up to 5100 V
- **Leakage Current**
  Up to 3 mA
- **Capacitance**
  Up to 49.99 F

CA 6547/CA 6549

- Large backlit LCD screen, with digital display & bargraph
- Automatic calculation of the DAR/PI/DD ratios
- Programmable alarms
- Displays an error code in an anomaly condition (CA 6549)
- Direct plotting resistance over time (R(t)) curves in display (CA 6549)
- Calculation of R at Reference Temperature (T°) (CA 6549)
- Memory: 128KB storage capacity
- Communication: USB (Two-Way)
- PC interface
- **Insulation**
  Test Voltage (Fixed/Adjustable): 500 V, 1000 V, 2500 V, 5000 V / 40 V to 5100 V in 10 V or 100 V increments
  Range: 10 kΩ to 10 TΩ
  Accuracy: ±5% +3 pts
- **Voltage**
  Range: Up to 5100 V
- **Leakage Current**
  Range: Up to 3 mA
- **Capacitance**
  Range: Up to 49.99 F

CA 6550/CA 6555

- Large graphical LCD display with backlight & bargraph
- Calculation of the DAR/PI/DD ratios
- Programmable test duration
- Timer (min:s): Up to 99:59
- Voltage ramp & step with “burn-in”, “early break” & “I-limit” modes
- Memory: 80,000 points
- Communication: USB
- PC interface
- **Test Voltage/Insulation range**
  CA 6550: 500 V, 1000 V, 2500 V, 5000 V, 10,000 V / 10 kΩ to 25 TΩ
  CA 6555: 500 V, 1000 V, 2500 V, 5000 V, 10,000 V, 15,000 V / 10 kΩ to 30 TΩ
  Accuracy: ±5% +3 pts
- **Voltage**
  Range: Up to 2500 V AC / Up to 4000 V DC
- **Leakage Current**
  Range: Up to 8 mA
- **Capacitance**
  Range: Up to 19.99 µF

OSCILLOSCOPES

OX 5022/OX 5042

- 3.5" colour TFT – Resolution 320 × 240 – LED backlighting
- Screenshot: Up to 100 files
- PC interface

Oscilloscope Mode

- Bandwidth & Channels:
  - 20 MHz & 2 isolated channels (OX 5022)
  - 40 MHz & 2 isolated channels (OX 5042)
- Input impedance: 1 MΩ ±0.5%, approximately 17 pF
- 2 MB for file storage
- 2,500 real acquisition points on screen

Multimeter Mode

- 2 channels, 8,000-count display + min/max bargraph
- Graphical recording: 2,700 measurements (5 min to 1 month)
- AC, DC & AC+DC voltages: 600 mV to 600 VRMS, 800 mV to 800 VDC
- Resistance & capacitance: 80 Ω to 32 MΩ & 5 nF to 5 mF

- Measures frequency, rotation speed, 3.3 V diode test, temperature

Harmonic Analyzer Mode

- 2 channels, 31 orders, frequency of fundamental from 40 to 450 Hz

OX 9062/OX 9102/ OX 9104/OX 9304

- 7" WVGA colour TFT LCD touch screen, 800 × 480 – LED backlighting
- 2,500 real acquisition points on screen
- PC interface

Oscilloscope Mode

- Bandwidth:
  - 60 MHz (OX 9062)
  - 100 MHz (OX 9102 & OX 9104)
  - 300 MHz (OX 9304)
- Channels:
  - 2 isolated channels (OX 9062 & OX 9102)
  - 4 isolated channels (OX 9104)
- Input impedance: 1 MΩ ± 0.5%, approximately 12 pF
- 20 automatic measurements per channel
- Memory: 2 GB

Multimeter Mode

- 2 or 4 channels – 8,000 counts
  min/max/frequency/relative – TRMS
- AC, DC & AC+DC voltages:
  600 mV to 600 VRMS, 800 mV to 800 VDC
- Resistance & capacitance: 80 Ω to 32 MΩ & 5 nF to 5 mF
- Frequency 200 kHz, Rotation speed,
  3.3 V diode test, temperature

Harmonic Analyzer Mode

- 2 or 4 (Based on model)
- Harmonics: Up to 63rd orders
- Fundamental frequency 40 to 450 Hz in auto or manual mode

Logger Mode

- Duration: 20,000s – Interval: 0.2s –

- Files: 100,000 measurements

EARTH TESTERS

CA 6424

- Backlit custom 206-segment LCD
- Auto Power off
- Noise indication
- Measurement Mode:
  V, I, R 2P (Ω), R 3P (Ω)
- Voltage: Up to 600 V

- 2P earth resistance/accuracy:
  0.05 Ω to 50 kΩ / ± (2%R + 1 count)
- 3P earth resistance/accuracy:
  0.5 Ω to 50.00 kΩ / ± (2%R + 1 count)
- RH stake resistance: 0.05 Ω to 49.99 kΩ
- UL voltage measurement: Up to 600 VAC
- Leakage current: Up to 60.00 A

CA 6460/CA 6462

- Large backlit digital display with 2,000 counts
- 3 fault presence indicators to validate measurement
- Battery
  CA 6460 – Non Rechargeable / Rechargeable Batteries
  CA 6462 – Rechargeable Batteries only
  - **3-in-1 tester**
    Resistivity: ("Wenner method" (4-rod method))
    Ground Resistance: "TAGG method" (62% method)
- **Resistance**
  Range: 0.01 Ω to 2,000 Ω (3 automatic ranges)
  Test current: 10 mA, 1 mA, 0.1 mA
  Accuracy: ±2% ±1 point
  Frequency: 128 Hz

CA 6470N/CA 6471

- Backlit LCD display featuring (3 simultaneous display levels)
- Noise interference detection
- Alarm function
- Memory: 512 memory locations
- Communication: USB

- **4-in-1 tester (CA 6470N)**:
  Earth, Resistivity, Coupling, Continuity
- **5-in-1 tester (CA 6471)**:
  Earth, Selective earth, Resistivity, Coupling, Continuity
- **3-pole, 4-pole measurements**
  Range: 0.01 Ω to 99.9 kΩ
  Frequency: 41 to 512 Hz
- **Selective 4-pole measurements, 2 clamps (CA 6471)**
  Range: 0.01 Ω to 500 Ω
  Frequency: 128 Hz, 1367 Hz, 1611 Hz, 1758 Hz
- **Resistivity**
  Range: 0.01 Ω to 99.9 kΩ
  Frequency: 128 Hz

CA 6472/CA 6474

- Backlit LCD display featuring (3 simultaneous display levels)
- Automatic & Expert mode
- Earth measurement on Pylons with earth cable (with CA 6474 option)
- Alarm function
- Memory: 512-record memory
- Communication: USB
- Measurement with CA 6474
  Range: 0.001 Ω to 99.9 kΩ
  Frequency: 41 to 5078 Hz
- **3P, 4P/4P Selective Method**:
  Range: 0.01 Ω to 99.9 kΩ
  Frequency: 41 to 5,078 Hz
- **Earth Measurement (2 clamps)**:
  Range: 0.01 Ω to 500 Ω
  Frequency: 1,367 Hz (auto) & 1,367 Hz, 1,611 Hz, 1,758 Hz (manual)
- **Resistivity**:
  Range: 0.01 Ω to 99.9 kΩ
  Frequency: 41 to 128 Hz
- **Earth Potential**:
  Range: 0.01 mV to 65.00 V
  Frequency: 41 to 128 Hz
- **DC Resistance**:
  Range: 0.001 Ω to 99.9 kΩ

CA 6417

- 35mm clamping diameter
- Large, 152-segment multi-function OLED display
- Display Counts: 1,500 counts (Loop ohmmeter) & 4,000-count display (Ammeter)

- Alarms
- HOLD & PRE-HOLD
- Auto power off
- Memory: 2,000 measurements
- Communication: Bluetooth
- PC interface & Android app
- **Loop Resistance**
  Range: Up to 1,500 Ω
  Accuracy: ±1.5% ±0.01
- **Frequency**
  2,083 Hz (Measurement frequency)
  50, 60, 128 or 2,083 Hz (Transposition frequency)
- **Loop Inductance**
  Range: Up to 500 µH
  Accuracy: ±3% ±r
- **Ground Voltage**: Up to 75 V
- **Current**
  Range: Up to 39.99 A
  Accuracy: ±2% ±r

CA 6418

- 32/55mm max. clamping diameter (Oblong head)
- Large, 152-segment multi-function OLED display
- Alarms
- Automatic calibration of the jaw gap
- HOLD: Manual or automatic PRE-Hold
- Auto power off
- Memory: 300 measurements (Time/date-stamped)
- **Loop Resistance**
  Range: Up to 1,200 Ω
  Accuracy: ± (1.5%R + 2r)
- **Current**
  Range: Up to 20 A
  Accuracy: ± (2%R + 200 µA)
- **Ground Voltage**
  Range: Up to 75 V

CLAMP METERS

F205/F404/F604

- Clamping diameter
  F205: 34 mm, F404: 48 mm, F604: 60 mm

- Display
  F205: 6000 counts backlit LCD
  F404 / F604: 10,000 counts backlit LCD
- Diode Test (Semiconductor function)
- Measures True Inrush, Min/Max, Peak+/Peak–
- Audible continuity (adjustable from 1 to 999 Ω)
- RELativ ΔX / ΔX/X (%) measurement
- Auto range, Hold & Auto power off
- Measures kW, kVAr, kVA & PF (F205)
- IP Rating: IP 40 (F205), IP 54 (F404 & F604)
- **Voltage V (AC/DC)**
  F205: Up to 1,200 V AC/DC
  F404 & F604: Up to 1,200 V AC / 1,700 V DC
- **Current I (AC/DC)**
  F205: Up to 600 A AC / 900 A DC
  F404: Up to 1,000 A AC / 1,500 A DC
  F604: Up to 2,000 A AC / 3,000 A DC
- **Accuracy (V & I)**: 1% of reading + 3 counts
- **Resistance**: Up to 99.99 kΩ
- **Temperature**: Up to 1000°C (**F404 & F604**)
- **1 phase & 3 phase power**: Up to 600 kW (**F205**)

F406/F606

- Specially designed for Photovoltaic applications with 1700 V DC
- Clamping diameter
  - F406: 48 mm
  - F606: 60 mm
- Display: 10,000 counts backlit LCD
- Diode Test (Semiconductor function)
- Measures True Inrush, Min/Max, Peak+/Peak–
- Audible continuity (adjustable from 1 to 999 Ω)
- RELativ ΔX / ΔX/X (%) measurement
- Auto range, Hold & Auto power off
- Measures kW, kVAr, kVA & PF
- **Voltage V (AC/DC)**: Up to 1,200 V AC / 1,700 V DC
- **Current I (AC/DC)**:
  - **F406**: Up to 1,000 A AC / 1,500 A DC
  - **F606**: Up to 2,000 A AC / 3,000 A DC
- **Accuracy (V & I)**: 1% of reading + 3 counts
- **Resistance**: Up to 99.99 kΩ
- **1 phase & 3 phase Power**:
  - **F406**: Up to 1,200 kW
  - **F606**: Up to 2,400 kW
- Voltage & Current **THDf / THDr**

F407/F607

- Clamping diameter
  - F407: 48 mm
  - F607: 60 mm
- Display: 10,000 counts backlit LCD
- Measures True Inrush, Min/Max, Peak+/Peak–
- Audible continuity (40 Ω)
- Auto range, Hold & Auto power off
- Measures kW, kVAr, kVA, PF & DPF
- Data recording & PC interface
- Communication: Bluetooth
- **Voltage V (AC/DC)**: Up to 1,000 V
- **Current I (AC/DC)**:
  - **F407**: Up to 1,000 A AC / 1,500 A DC
  - **F607**: Up to 2,000 A AC / 3,000 A DC
- **Accuracy (V & I)**: 1% of reading + 3 counts
- **Resistance**: Up to 99.99 kΩ
- **1 phase & 3 phase Power**:
  - **F407**: Up to 1,000 kW
  - **F607**: Up to 2,000 kW
- **Harmonic Analysis**:
  - Voltage & Current THDf / THDr
  - Individual Harmonics up to 25th order

DIGITAL MULTIMETERS

MTX 203

- Display: 6000 counts monochrome digital display with blue backlighting
- Audible continuity & Diode test
- VLowZ, HOLD, NCV
- Min, Max values
- IP 54
- **Voltage**
  - V (AC): 0.4 V to 600 V & 10 mV to 1000 V
  - V (AC/DC/AC+DC): 10 mV to 1000 V
- **Current**
  - A (AC): 2 mA to 10 A & 10 µA to 10 A
- **Resistance**
  - Range: Up to 40 MΩ
- **Capacitance**
  - Range: Up to 100 mF
- **Temperature**
  - Range: Up to 1,200°C

DMM 210/DMM 220/ DMM 230

- **Display**: 6,000 counts backlit with bargraph
- **Measurement Type**: Average (**DMM 210 & DMM 220**), TRMS (**DMM 230**)
- **Calibre Selection**: Autorange / Manual
- Audible continuity & Diode test
- Automatic shutdown (deactivatable)
- Relative mode – MIN, MAX
- **IP 67**
- **Voltage**
  - V(AC): 6 V to 1000 V
  - V(DC): 600 mV to 1000 V
- **AC bandwidth**: Up to 1 kHz
- **Current**
  - A (AC/DC): 600 µA to 10 A
- **Resistance**: 600 Ω to 60 MΩ
- **Frequency**: Up to 10 MHz
- **Capacitance**: Up to 1000 µF
  (*DMM 220 & DMM 230*)
- **Temperature**: Up to 750°C
  (*DMM 220 & DMM 230*)

DMM 240

- **Display**: 40,000 counts backlit with bargraph
- **Measurement Type**: TRMS
- **Calibre Selection**: Autorange / Manual
- Audible continuity & Diode test
- Automatic shutdown (deactivatable)
- **Relative mode** – MIN, MAX, PEAK (1 ms)
- **IP 67**
- **Voltage**
  V(AC/DC): 400 mV to 1000 V
- **AC bandwidth**: Up to 1 kHz
- **Current**
  A (AC/DC): 400 µA to 10 A
- **Resistance**: 400 Ω to 40 MΩ
- **Frequency**: Up to 100 MHz
- **Capacitance**: Up to 40 mF
- **Temperature**: Up to 1000°C

CA 5273/CA 5275/CA 5277

- **Display**: 2 × 6,000 counts with backlighting & bargraph
- Autorange / Deactivatable
- Automatic AC/DC detection (**CA 5273**)

- Audible continuity & Diode test
- Differential (ΔX) / RELative (ΔX/X%) measurement (**CA 5277**)
- 1 ms Peak+/Peak values (**CA 5277**)
- Hold
- **IP 54**
- **Voltage**
  - V (AC/DC): 600 mV to 1000 V (**CA 5273**)
  - V (AC/DC/AC+DC): 60 mV to 1000 V (**CA 5275 & CA 5277**)
- **AC bandwidth**
  - Up to 3 kHz (**CA 5273**)
  - 10 kHz (**CA 5275 & CA 5277**)
- **Current**
  - A (AC/DC): 20 mA to 10 A (**CA 5273**)
  - A (AC/DC/AC+DC): 6 mA to 10 A (**CA 5275 & CA 5277**)
- **Resistance**: Up to 60 MΩ
- **Frequency**: Up to 50 kHz
- **Capacitance**: Up to 60 mF
- **Temperature**: Up to 1,200°C (**CA 5273 & CA 5277**)

MTX 3291

- **Display**: 60,000 counts backlight digital monochrome
- **TRMS** value
- Audible continuity detection
  (600 Ω SIGNAL < 30 Ω ±5 Ω < 5 V)
- Diode test
- HOLD / Auto-HOLD
- **Communication**: USB
- PC interface
- **IP 67**
- **Voltage**
  V (AC/DC/AC+DC): Up to 1000 V
- **AC & AC+DC bandwidth**: 100 kHz
- **Current**
  A (AC/DC/AC+DC): Up to 20 A
- **Frequency**: Up to 600 kHz
- **Resistance**: Up to 60 MΩ
- **Capacitance**: Up to 60 mF
- **Temperature**: Up to 800°C

CA 5292/CA 5293

- **Display**: 4 × 100,000 count colour graphical with backlighting
- **TRMS** value
- Audible continuity detection
  (1000 Ω / SIGNAL < 20 Ω < 3.5 V) & Diode test

- Display of trends, multiple parameters & 600 Hz waveform
- HOLD / Auto-HOLD
- **Memory**
  - **CA 5292**: 10,000 measurements
  - **CA 5293**: 30,000 measurements
- **Communication**: USB, Bluetooth (optional)
- PC interface
- **IP 67**
- **Voltage**
  - V (AC/DC/AC+DC): Up to 1000 V Accuracy
  - V DC: 0.03% (**CA 5292**) & 0.02% (**CA 5293**)
  - V AC: 0.3%
  - AC & AC+DC bandwidth: Up to 100 kHz (**CA 5292**) & 200 kHz (**CA 5293**)
- **Current**
  - A (AC/DC/AC+DC): Up to 20 A
  - Accuracy: 0.08% (DC) & 0.3% (AC/AC+DC)
  - AC & AC+DC bandwidth: 50 kHz
- **Frequency**: Up to 5 MHz
- **Resistance**: Up to 100 MΩ
- **Capacitance**: Up to 10 mF
- **Temperature**: Up to 1200°C (with K thermocouple)

F65

- **Clamping diameter**: 28 mm
- **Display**: 10,000 counts backlit LCD
- Hold & Auto power off
- Audible Continuity (Buzzer < 35 Ω)
- Complied IEC 61557-13 standard
- **AC current**:
  - Range: 60 mA to 100 A
  - Accuracy: 1.2% ± 5 cts
- **Voltage (AC/DC)**: 600 V
- **Resistance & Continuity at** 1 kΩ
- **Frequency**: 5 Hz to 1 kHz

MICRO-OHMMETERS

CA 6240/CA 6255

- Large backlit LCD display
- Auto measurement mode
- Automatic "on the fly" or manual recording mode
- Auto power-off
- Automatic discharge (**CA 6255**)
- **Memory**

    - 100 measurements (**CA 6240**)
    - 1,500 measurements (**CA 6255**)
- **Communication**
    - Optical/USB link (**CA 6240**)
    - RS 232 link (**CA 6255**)
- PC interface
- **Resistance**
    - **CA 6240**: 5 μΩ to 399.9 Ω
    - **CA 6255**: 5 mΩ to 2,500 Ω
    - Accuracy: ± 0.25% ± 2 counts
- **Test current**
    - Range: Up to 10 A

CA 6292

- **Display**: Backlit LCD screen
  (4 lines of 20 characters)
- Internal cooling system
- Test mode: Normal or BSG (Both Sides Grounded)
- **Memory**: 8,000 measurements
- **Communication**: USB
- PC interface
- **Protection**: Voltage surges, short-circuits, overheating & overvoltages on the o/p terminals
- **Resistance**
    - Range: 0.1 μΩ to 1 Ω
    - Accuracy: ± 1%
- **Test Current**
    - Range: Up to 200 A
- **Current (optional MR6292 clamp, BSG mode)**
    - Range: Up to 50 A

INSTALLATION TESTERS

CA 6117

- **Display**: Large 5.7” backlit graphic colour LCD screen, 320 x 240 points
- An all-in-one instrument for testing electrical installations, compliant with international standards (IEC 60364-6, NF C 15-100, VDE 100, FD C 16-600, etc.) combining design, simplicity, performance, and precision.
- Suitable for all neutral systems (TT, TN, IT) and is ideal for all sectors like industries, tertiary and residential.
- Integrated fuse table for quick reading of the results on the instrument
- Li-ion battery for a longer battery life
- Measurement of voltage drop for correct sizing of conductor diameters
- Loop measurement with 1 mΩ resolution

- Continuity measurements at 12 mA or 200 mA
- **Memory**:
  - 3-level storage
  - 1,000 locations to record
- PC interface
- **Insulation Test Voltage**:
  50 / 100 / 250 / 500 / 1,000 V DC
  Range: 0.01 MΩ to 2 GΩ
- **Earth Resistance**:
  Upto 40 Ω (3-Pole) & 399.9 Ω (1P selective earth)
- **RCD**: AC, A and F-type RCDs, B, B+ & EV-type
- **Loop Impedance**: (Zs (L-PE) and Zi (L-N or L-L)) – 1P Live earth measurements
- **Voltage**: 550 VAC/DC
- **Current**: 199.9 A
- **Frequency**: 500 Hz
- **Phase Rotation**: 20 to 500 VAC
- **Active Power**: Upto 110 kW (1 phase) & 330 kW (3 phase)
- **Harmonics**: Upto 50th order

CA 6133

- **Display**: Custom 231-segment LCD with blue backlighting
- **Continuity measurement at 0.2A (200mA)**
- **Android application for Report generation**
- **Earth measurement by stake and loop methods**
- **Insulation testing**
- **RCD testing**: current and trip time
- **Automatic test sequences**
- **Power supply** by mains-rechargeable batteries, USB socket or vehicle cigarette lighter
- **Memory**: 30 sites × 99 tests
- **Insulation Test voltage**:
  250 V / 500 V / 1,000 V
  Range: 0.01 to 999.9 MΩ
- **Earth resistance**: Up to 2,000 Ω (3P method)
- **RCD test**: Type AC & RCDs: 30 mA, 100 mA, 500 mA, 650 mA
- **Loop impedance**: Earth loop (Zs), Fault loop (Zi) measurements
- **Voltage**: Up to 550 VAC & 800.0 VDC
- **Current**: Up to 200 A
- **Frequency**: Up to 999.9 Hz
- **Phase rotation**: 45 to 550 V

MULTI FUNCTIONAL METERS

DiGi 530S/DiGi 530H

- Accuracy Class 0.5s as per IEC 62053-22
- 3-line bright LCD display
- PT & CT programmable
- Password protection for setup page
- Load management feature
- RS485 port with Modbus RTU protocol and baud rate up to 38,400 bps
- Dimension: 96 mm × 96 mm × 83 mm
- Cut-Out: 90 × 90 mm (+/- 0.5 mm)
- RMS - V, U, I, In, Hz
- Power - kW, kVAr, kVA
- PF - Phase wise & Total
- Min, Max - V, I, Hz, kW
- Bi-directional energy measurements
- Energy - kWh, kVAh, kVArh
- THD - Voltage & Current
- Individual Harmonics up to 31st order *(DiGi 530H)*
- Demand - I, kW, kVAr, kVA *(DiGi 530H)*

DiGi 630S/DiGi 630D

- Accuracy Class 0.5s / Class 0.2s as per IEC 62053-22
- 3-line bright LCD display
- PT & CT programmable
- Password protection for setup page
- 4 DI, 2 DO *(DiGi 630D)*
- Screenshot recording for energy accounting
- RS485 port with Modbus RTU protocol and Baud rate up to 38,400 bps
- Modbus custom table
- Dimension: 96mm × 96mm × 83mm
- Cut-Out: 90 × 90 mm (+/- 0.5mm)
- RMS - V, U, I, In, Hz
- Power (kW, kVAr, kVA, PF) - Phase wise & Total
- Min, Max - V, I, Hz, kW (Real time stamping)
- Bi-directional, 4 Quadrant energy
- Dual Source Energy meter
- Energy - kWh, kVArh, kVAh
- Tariff energy recording
- THD - Voltage & Current
- Individual Harmonics up to 31st order
- Demand - I, kW, kVAr, kVA
- Demand control available in **DiGi 630D**
- Load management feature

DiGi 730S/DiGi 730D

- Accuracy Class 0.5s / class 0.2s as per IEC 62053-22

- 3-line bright LCD display
- PT & CT programmable
- Password protection for setup page
- Load management feature
- 6 Digital inputs
- 3DO & 1AO (only in **DiGi 730D**)
- Screenshot recording for energy accounting
- RS485 port with Modbus RTU protocol and baud rate up to 115,200 bps for faster communication
- Modbus custom table
- Dimension: 96mm × 96mm × 83mm
- Cut-Out: 90 × 90 mm (+/- 0.5mm)
- RMS - V, U, I, In, Hz
- Power (kW, kVAr, kVA, PF) - Phase wise & Total
- Min, Max - V, I, Hz, kW (Real time stamping)
- Bi-directional, 4-Quadrant energy
- Dual Source Energy meter
- Tariff Energy Recording (6 rates)
- Energy - kWh, kVAh, kVArh
- THD - Voltage & Current
- Individual Harmonics up to 51st order
- Measures Crest factor and K factor
- Demand monitoring - I, kW, kVAr, kVA
- Demand control available in **DiGi 730D**

DiGi 760

- Accuracy Class 0.2s as per IEC 62053-22
- TFT colorful LCD display with 320 × 240 resolution
- Real Time waveform Display
- CT/PT Programmable
- Real-time-clock for Min, Max, Time stamping
- Voltage swell/sag event recording with waveform
- Voltage input up to 480V
- 4AO, 8DI (Optional)
- Ethernet Port with Modbus TCP/IP protocol
- Modbus RS485 communication
- Dimension : 96 × 96 × 66mm
- Cut-Out : 90 × 90 mm (+/- 0.5mm)
- RMS - V, U, I, In, Hz
- Voltage – 3U, 3V, Current – 3I, In
- Powers – kW, kVA, kVAr – phase wise and total
- Bi-directional energy measurements
- 4-Quadrant Energy Data (on communication)
- Energy - kWh, kVAh, kVArh
- THD - Voltage & Current

- Individual harmonics on V & I up to 63rd order
- K-Factor, Crest Factor measurements
- ToU - 2 Tariff rates, 8 periods & 2 lists of tariff rate
- Demand : I, kW, kVAr, kVA

DiGi 820

- IEC 61000-4-30 Class A power quality monitoring meter
- Class 0.2s high accuracy energy measurement
- Sampling rate: 1024 samples/cycle
- Color LCD Display with resolution of 640 × 480
- Real-Time waveform display
- Power quality analysis – sag, swell, Transient, RVC
- 8DI, 2DO (Pulse) & 4 Relay
- Baud rate: 2400–38400bps
- Ethernet Port with Modbus TCP/IP protocol
- Modbus RS485 communication
- **Memory**: 8GB for data and event recording
- **RMS** – V, U, I, In, Hz
- **Voltage**: Phase, Line, Average & Phase Angle
- **Current**: Phase, Average Current & Phase Angle
- **Power** (kW, kVar, kVA) & **PF**: Phase & Total Power
- 4-Quadrant energy measurements
- **Harmonics & Inter-harmonics** up to 63th order and Harmonic energy up to 31st order
- Records 256 PQ events along with waveform
- Captures 20µs Voltage transients
- Multi-tariff energy: 4 tariff, 8 time period, 2 time zone
- **Demand monitoring & control**: I, kW, kVAr & kVA

Multy4

- **Backlit custom LCD display**
- **Accuracy Class 1.0** as per IEC 62053-21
  (accuracy includes CT errors)
- **Voltage input** up to 500 V
- **CT primary programmable** 2kV isolation
- **Password protection**
- **Load management module** (on communication)
- **Special high-accuracy CT** supplied with the meter
- **RS485 – Modbus RTU Protocol**
- **Dimensions**: 75mm (width) x 94mm (height) x 62mm (depth)
- **Single phase/Three phase**:
  12 × 1 phase / 4 × 3 phase
- **Common for 4 channels**:
  - Voltages L-N and L-L (C) & Frequency
  - Voltage Min and Max L-N and L-L (C)

- **For each of the 4 channels**:
    - Currents: Line
    - Max. Current: Phase-wise (C)
    - kW, kVAr, kVA & PF: Phase and Total
    - kWh, kVAh: Phase and Total

PLM R90

- **Installation**: 35mm DIN rail, standard DIN ED5002
- **Accuracy**: Class 0.5
- **Indicator**: LED indicates pulse output
- **Communication**: RS485 port, MODBUS-RTU or DL/T645 protocol (Optional)
- **Dimensions**: 100 × 36 × 65 mm (2 module)
- **RMS**: Voltage (V), Current (I)
- **Power**: kW
- **Energy**: kWh
- **Shunt**: 100A, 200A, 300A

PLM R91

- 35mm DIN installing in accordance with the standard **DIN ED5002**
- Active energy accuracy up to **Class 1.0** as per **IEC 62053-21**
- **6+1 digit LCD display** (999999.9 kWh)
- Passive pulse output; output signal complies with **DIN43864**
- **LED** indicates pulse output
- **RS485 port**, **Modbus-RTU** or **DTL645** (optional)
- **Dimensions**: 100 × 36 × 65 mm
- **RMS**: V, I, Hz
- **Power**: kW, kVAr, kVA, PF
- **Energy**: kWh, kVArh
- **Max. rate of current**: 63 A

PLM R93

- **35mm DIN** in accordance with the standard ED5002
- **kWh Class** 1.0 as per IEC 62053-21
- **7+1 digit LCD display** (9999999.9 kWh)
- **2 LED Pulse indicators** for kWh & kVArh
- **Displays** for phase sequence error indication
- **RS485 port** with Modbus-RTU protocol and baud rate of 2400, 4800, 9600
- **Dimension**: 72 × 100 × 65 mm
- **Cut-Out**: 50 × 50 mm
- **RMS** – V, I, Hz
- **Power** – kW, kVAr, kVA, PF
- **Bidirectional energy measurement**
- **Energy** – kWh, kVArh

- **Max. rate of current**: 63A
- **Multi tariff energy values**
- **kVAr & kVA** available on communication
- **Records historical data** of:
    - Present day data (15 mins)
    - Last 31 days
    - Last 12 months
    - Last 10 years

EON 4.0

- **Active energy accuracy**: up to Class 0.5
- **PT/CT programmable**
- **Password protection** for setup page
- **Auto Phase sequence adjustment**
- **2 DI Standard**, **2 DO (optional)**
- **Baud rate**: 4800 to 38400 bps
- **Memory**: Built-in memory, 7 days data storage for 5 mins data
    - *(EON 4.0G & EON 4.0E)*
- **Gateway function**: *(EON 4.0G & EON 4.0E)*

Communication Options:

- **EON 4.0S**: RS 485 Modbus-RTU protocol
- **EON 4.0G**: 4G wireless for MQTT
- **EON 4.0E**: LAN RJ45 LAN port for Modbus TCP / HTTP / MQTT
- **RMS**: V, I, Hz, V & I phase angle
- **Power**: kW, kVAR, kVA & PF
- **Bidirectional energy**
- **Energy**: kWh, kVARh, kVAh
- **Unbalance**: V & I
- **Individual Harmonics**: up to 63rd order
- **Demand**: I, kW & kVA
- **Historical energy data**:
    - Latest 10 years
    - Last 12 months
    - Last 31 days
- **Remote configuration**
- **10 seconds battery backup** to capture power interruption event

---

SERVO CONTROLLED VOLTAGE STABILISERS

- Up to 4000 kVA rating
- Microprocessor based Control

- VAF display
- Comprehensive Protection
- Preferred supplier for corporate customers
- IoT option available

Here is the extracted text from the image:

ISOLATION TRANSFORMERS

- Step-Up, Step-Down Auto Transformers
- Galvanic Isolation Transformers
- Shielded Ultra Isolation Transformers
- K-Rated Ultra Isolation Transformers
- Ratings: 3 kVA to 1000 kVA 3-Phase, 1 to 25 kVA 1-Phase
- Meets IS 11171 1985 Dry Type Transformer standards
- Double shielded for high Common Mode Noise Rejection (Ultra Isolation Transformers)

Here is the extracted text from the image:

STATIC VOLTAGE STABILISERS

- Ratings: 15 kVA to 200 kVA 3-Phase
- AC - AC PWM Switching topology, No-Harmonic distortion
- Noise Free - Silent Operation
- Any variation within Input range is corrected within 20ms
- Steady Output Voltage - No Hunting or Overshoot
- Single Phasing & Phase Reversal trip
- Spike & Surge Protection
- Static & Manual Bypass provision