INDIA'S POPULAR ENERGY MANAGEMENT BRAND

KRYKARD

MULTIFUNCTION
DEMAND MONITOR / CONTROLLER

DiGi 730 S / 730 D

MEASUREMENTS

Basic	V, U, I, In, Hz
Power	kW, kVA, kVAr, PF - Ph & Total
Demand	kW, kVA, kVAr
Energy	kWh, kVAh, kVArh
THD	V, U, I
Individual Harmonics	2 - 51 order

FEATURES

Energy

- 4 Quadrant measurements
- Import / Export monitoring
- Accuracy Class 0.2s & 0.5s as per IEC62053-22
- Dual source energy monitoring

Power Quality

- Up to 51st individual harmonic order
- Voltage Crest Factor
- Current K - Factor
- Unbalance V & I

Input / Output

- 6 digital inputs for status monitoring
- 1 pulse output for kWh
- 1 Analog output for DCS / BMS integration
- 3 Relay output for alarm / MD control (DiGi 730 D)

Powerful Communication

- RS-485 port with Modbus RTU protocol
- Up to 1,15,200 baud rate for faster communication
- Custom register table for faster communication

Rugged Performance

- Operating temperature range -25°C to 70°C
- Meets 4 kV standard for EMC surge as per IEC 61000-4-5
- Meets 4 kV standard for EMC EFT as per IEC 61000-4-4

General

- RTC clock for event time stamp
- Password protection for setup

+91 95000 97966 atandra.in enquiry@atandra.in

SPECIFICATIONS

KRYKARD

MEASUREMENTS & FEATURES			
Functions	**Parameters**	**DiGi 730 S**	**DiGi 730 D**
RMS measurements	V, U, I, Hz	Yes	Yes
	kW, kVA, kVAr, PF - Ph & Total	Yes	Yes
	Demand kW, kVA, kVAr	Yes	Yes
	Min/Max average value	Yes	Yes
Energy	kWh, kVAh, kVArh	Yes	Yes
	Bi-directional Energy	Yes	Yes
	Tariff Energy (6 sets)	Yes	Yes
PQ Parameters	THDi, THDu st	Yes	Yes
	Individual harmonics up to 51 order	Yes	Yes
	Unbalance V & I	Yes	Yes
	Voltage Crest Factor	Yes	Yes
	Current K Factor	Yes	Yes
Communication	Modbus RS 485	Yes	Yes
Input/output	Digital Inputs	6	6
	Relay Output (Demand Control DiGi 730 D only)	3	3
	Pulse Output	1	1
Other	Alarm Recording	Yes	Yes

TECHNICAL SPECIFICATIONS			
Auxiliary Supply	Voltage	AC / DC 80-270 V 50 / 60 Hz	
	Power Consumption	≤ 5 VA	
Voltage Input	Nominal Voltage	AC 110 / 400 V L-L	
	Resolution	0.1 V	
	Impedance	> 1.7 MΩ / Phase	
	Burden	< 0.1 VA / Phase	
	Overload	Continuous: 1.2 Vn, Instantaneous: 2 Vn/1 min	
	Frequency	45 - 65 Hz	
Current Input	CT Secondary Setting	5 A / 1 A Programmable	
	Resolution	1 mA	
	Impedance	≤ 20 mΩ / Phase	
	Burden	≤ 0.2 VA / Phase	
	Overload	Continuous: 2 In, Instantaneous: 20 In/1s	
Accuracy	Voltage and Current	0.2%	0.2%
	kW, kVAr, Power Factor	0.5%	0.5%
	kWh	Class 0.5s IEC62053-22	Class 0.5s IEC62053-22
Safety	Standard	300 V CAT III IEC 61010-1, Double Insulation	
Environmental Conditions	Operating Temperature	-25°C to 70°C	
	Relative Humidity	5% to 95% RH, No condensation	
	Operating Altitude	≤ 200 m	
Mechanical Features	Dimension	96 mm x 96 mm x 83 mm	
	Panel Cutout	92 mm x 92 mm	
	Ingress Protection	Front IP54, Back IP20	
Communication interface	RS 485	Modbus RTU	
Standards	Power Metering standard	IEC 61557-12, IEC 61326-1	
	EMC Surge	4 kV IEC 61000-4-5	
	EMC EFT	4 kV IEC 61000-4-4	
	EMC ESD	8 kV by contact, 14 kV by Air	

Atandra Energy Private Limited I No.5, Kumaran Street, Pazhavanthangal, Chennai, Tamil Nadu - 600 114

(ISO 9001:2015 | 14001 - 2015 | 45001 - 2015)

KRYKARD is a registered trademark owned by Atandra Energy Pvt. Ltd.

Revision: Aug 2024. Specifications are subject to change without prior notice.