DiGi 760 Multi-function Power Meter

KRYKARD

Salient Features

- Class 0.2s accuracy as per IEC 61000-4-30
- ToU - 2 tariff rates, 8 periods and 2 lists of tariff rate
- Real-time-clock
- Sampling rate @256 samples/cycle - excellent accuracy
- even on non-linear waveforms
- Voltage input upto 480V
- Voltage Sag / Swell Analysis
- SMPS power supply
- TFT colorful LCD display
- PT & CT programmable
- Password protection
- 8 active digital inputs Optional
- 8 passive digital inputs Optional
    - 4 Analog Outputs (4-20mA) Optional
    - Ethernet Port with Modbus TCP/IP protocol

0.2s Class Power Meter

Measurements

- Voltage – 3U, 3V
- Current – 3I, In
- Powers – kW, kVA, kVAr – phase wise and total
- PF – phase-wise and total
- Frequency
- kWh Export / Import on display,
- Quadrant Energy Data on communication
- kVAh
- Demand & Total Demand – kW,I
- THD – V & I
- Individual harmonics on V & I upto 63rd order
- K-Factor, Crest Factor

Specifications

Inputs	
Voltage	400V LL nominal; 480V LL continuous max
	PT primary programmable up to 6900
Current	5A nominal; 6A continuous max (measurement from 10mA)
	CT primary programmable up to 10000A
	CT secondary selectable as 1A or 5A
Burden	Voltage & Current input <2 VA
Overload	2 times of voltage continuous, 4 times/1ss4times of current continue, 10 times/1s
Sampling Rate	256 samples/cycle on all 3 Voltage and 3 Current channels simultaneously
Isolation	4kV
Impulse withstand Voltage	6kV(peak value), 1.2/50µs
Display	
Type	TFT colorful LCD
Auxiliary Supply	
Rated Power Supply Voltage	85 to 265 Vac 50Hz; 100 to 300 Vdc
Power Consumption	<10VA
Communication	
Ports	RS485 x 1; RJ45 x 1; Analog Inputs x 1
Ethernet	RJ45 port - Modbus TCP/IP with 16 bit CRC
RS485 Port	Protocol - Modbus RTU with 16 bit CRC; 2-wire Baud rate - 2400 bps to 38,400 bps; user-settable; Modbus ID -1 to 247
Analog Inputs	4 Nos 4-20mA Output - Optically isolated with internal power supply
Environment	
Operating Temperature	Operating: -20°C to +60°C
Storage Temperature	-40°C to +85°C
Humidity	<5% to 95% non-condensing
IP Rating	IP52 front and IP30 Case
Accuracy	
Voltage	0.1% of Reading (10% to 120% nominal)
Current	0.1% of Reading (1% to 120% nominal)
kW, kVA,	0.2% of Reading
kVAr	0.5% of Reading
PF	0.2% of Reading
Frequency	0.01Hz
kWh	Class 0.2s as per IEC 61000-4-30
kVArh	Class 2 as per IEC 61000-4-30
Mechanical	
Terminals	Rising Cage: 4mm^2 (12 AWG) cable max.
Case	PC/ABS Plastic FR Grade
Dimensions	96.00×96.00×66.6(with expansion module) (including LAN and Analog output modules; 72.5mm behind panel)
Weight	550 grams
Cut-out	90 x 90 mm (+/- 0.5mm)

atandra
measure. protect. conserve

Atandra Energy Private Limited
No. 5, Kumaran Street, Pazhavanthangal, Chennai - 600 114.
Tel: +91 44 4278 0600/ 4278 0700 | www.atandra.in

KRYKARD is a trademarregistered by Atandra Energy Pvt. Ltd.