Isolation & Auto Transformers

Designed to save energy costs while protecting your equipment

Transformers are critical equipment in the power supply chain of every industry and work 24/7 in most cases. The quality and efficiency of transformers therefore are very critical and make a significant difference to the industry both in terms of uptime and energy costs. Considering the importance of this, we are offering innovatively designed efficient transformers that help industries through superior performance and lower energy losses.

With over 250,000 installations in various applications, our transformers have a proven track record of performance over a long life-cycle.

Our product range includes:

- Ultra Isolation Transformers
- Galvanic Isolation Transformers
- Auto Transformers

Ultra Isolation Transformer (UIT)

A double wound transformer with multiple shielding for Capacitive or Faradic Isolation (reduction of capacitive coupling). This transformer has very high attenuation of Common Mode transients thus preventing passage of voltage transients, spikes and galvanic leakage in the Common Mode from reaching sensitive electronic equipment like computers,medical equipment and CNC machines.

It also addresses problems related to poor input neutral. The Ultra Isolation transformer can be designed to provide output voltages to suit machine requirement.

Salient Features

Low inter-winding capacitance
Good DC galvanic isolation
High attenuation - 100 dB in common mode up to 10 kHz
Optimum transformer design ensures good load regulation

KRYKARD®

Galvanic Isolation Transformer(GIT)

A double wound transformer, which provides galvanic isolation and hence addresses problems related to input neutral. The Galvanic Isolation Transformer can be designed to provide output voltages to suit machine requirement.

Auto Transformer

Auto transformer is a transformer with a single winding(and therefore is without isolation) designed to change the output voltage to suit machine requirement.

Technical Specifications

Parameter	3-Phase	1-Phase / 2-Phase
Rating	3kVA to 1000kVA	1kVA to 25kVA
Reference Standard	IS 11171 : 1985 (Reaffirmated 2006)	
Type of Transformer	Floor mounted, natural air-cooled / oil-cooled (depending on rating)	Dry type, floor mounted, natural air-cooled
Configuration	Delta / star 1:1 (or as per user specification)	1:1 (or as per user specification)
Default Vector Group	Dyn11	
Type of lamination	CRNO	
Winding	Copper Wire / Strip or Aluminium wire / strip	
Load Regulation	Better than 3%	
Class of insulation	Class H	
Efficiency	3 - 12 kVA (>95%) > 15 kVA (>97%) At rated input voltage and at 100% rated current of loads that are linear	
Insulation Strength	Withstands 2.5 kV for 1 minute (between windings & between windings and body)	
DC galvanic isolation	> 1000 Mega Ohms - for UIT > 100 Mega Ohms - for GIT	
Common Mode noise rejection (for UIT only)	Up to 10kHz > 100 dB 10 kHz to 50 kHz > 60 dB 50 kHz to 1 MHZ > 40dB	
Short Circuit Protection	HRC fuse at input provided as a standard / MCB / MCCB can be provided as an option	
Indications	LED Lamps for Output Presence Digital Voltmeter (DVM) - optional	
Housing	Sheet metal housing provided with Input / Output terminations	

Auto Transformer:

Auto Transformers are designed to customer requirement

atandra
measure. protect. conserve

Atandra Energy Private Limited

No. 5, Kumaran Street, Pazhavanthangal, Chennai - 600 114
Tel: +91 44 4278 0700 | 4278 0600
www.atandra.in | energy@atandra.in

Chennai | Coimbatore | Bengaluru | Hyderabad | Vishakapatnam | Mumbai | Pune
|Ahmedabad | New Delhi | Madurai | Kochi | Tirupur

OUR DEALER

Revision: March 2017. Specifications are subject to change without prior notice.
KRYKARD is a registered trademark owned by Atandra Energy Pvt. Ltd.