KRYKARD

MULTY 4

4 channel high accuracy meter for load energy management

MEASURES

Common for all channels:

- Voltages - L-N and L-L (C)
- Frequency
- Voltage Min and Max - L-N and L-L (C)

For each of the 4 channels:

- Currents - Line
- Max Currents - Phase-wise (C)
- Power Factor - phase and total
- kW, kVA, kVAr - Phase and total
- kWh - Phase wise and total
- kVAh - Phase wise and total

SALIENT FEATURES

- Accuracy Class 1.0 as per IEC 62053-21 (Accuracy includes CT Errors)
- 75mm (width) x 94mm (height) x 62mm (depth)
- Voltage input up to 500V
- CT Primary Programmable
- 2kV Isolation
- Password Protection
- Backlit custom LCD display
- Load Management Module
- Special high-accuracy CT supplied with the meter.

Use at:

- ► Loads
- ► Feeders

Applications:

- ► Power & Energy Monitoring

INPUTS	
Voltage	400V LL nominal; 500V LL continuous max
Current	100mA input
	Selection of 100A or 200A primary CT
Burden	Voltage & Current input <0.2 VA per phase each
Sampling Rate	64 samples/cycle on all 3 voltage and 3 current channels simultaneously
Isolation	2kV
Impulse withstand voltage	6kV (peak)
Cts	100 A ID 20 mm / 200 A ID 25 mm / 400 A ID 45 mm
DISPLAY	
Type	Back-lit Custom LCD – 4 digit 1 line
AUXILIARY SUPPLY	
Rating	85 to 265 Vac 50Hz; 100 to 300 Vdc
Burden	2VA
COMMUNICATION	
Protocol	MODBUS® RTU with 16 bit CRC; 2-wire
Baud Rate	4,800 bps, 9,600 bps

GENERAL	
Temperature	Operating: -10°C to +55°C ; Storage: -40°C to +70°C
Humidity	<5% to 95% non condensing
IP Rating	IP 52 front and IP 20 Case
ACCURACY	
V	0.5% of Reading (10% to 120% nominal)
I	0.5% of Reading (5% to 120% nominal)
kW, kVA	1% of Reading
kVAr	2% of Reading
PF	1% of Reading
Frequency	0.01%
kWh	Class 1 as per IEC 62053-21 including CT errors
kVArh	Class 2 as per IEC 62053-23
MECHANICAL	
Terminals	Rising Cage. 4mm^2 (12 AWG) cable max.
Case	PC/ABS Plastic FR Grade
Dimensions	75 x 94 x 58.6 mm
Din-Rail	35 mm
Weight	240 gm