PLMR90 DC Energy Meter

PLMR90
DC Energy Meter

KRYKARD PLMR90 is designed for scenarios such as DC panel, charging pile and telecom base stations. This meter series measures Voltage, Current, Power and Energy in DC system. It can be used as local display and used in measuring system.

Salient Features

- Real-time measurements of DC V,I, kW, kWh
- High accuracy: Class 0.5
- LED indicates pulse output
- RS485 port, MODBUS-RTU or DL/T645 protocol (optional)
- 35mm DIN rail installing, standard DIN ED5002
- Shunt: 100A, 200A, 300A

Technical Specifications

Power Supply	9 to 36VDC
Rated Voltage DC	0 to 1000VDC
Rated Current	100A, 200A, 300A (Depends on shunt)
Shunt	Rated Voltage: 75mV Accuracy: Class 0.2
Starting Current	0.002Ib
Pulse output	1 channel, pulse constant: 100 imp/kWh
Power loss	<1W
Communication	RS485 port MODBUS-RTU or DL/T645-2007 (settable) Address: 1 to 247 Baud rate: 1200, 2400, 4800, 9600, 19200bps
IP index	IP20
Dimension	100 x 36 x 65mm (2 module)
Power frequency withstand voltage	3000VAC
Insulation resistance	≧100mΩ
Impulse Voltage	6000V
Environment	Operating temperature: -20°C to +55°C Limit Temperature: -25°C to +70°C Storage Temperature: -30°C to +80°C Humidity: < 95%
EMC Standard	Electrostatic discharge immunity test: IEC 61000-4-2:2001 RF Electromagnetic Field Immunity test: IEC 61000-4-3:2002 Electrical fast transient immunity test: IEC 61000-4-4:2004 Surge immunity test: IEC 61000-4-5: 2005 Injected Current Immunity test: IEC61000-4-6:2006

atandra
measure. protect. conserve
Atandra Energy Private Limited
No. 5, Kumaran Street, Pazhavanthangal, Chennai - 600 114.
Tel: +91 44 4278 0600/ 4278 0700 | www.atandra.in | energy@atandra.in

OUR DEALER

Revision: Apr 2021. Specifications are subject to change without prior notice.
KRYKARD is a registered trademark owned by Atandra Energy Pvt. Ltd.