KRYKARD

Advanced thermal imaging camera with full function analysis

THERMAL IMAGERS

TC 3360

WIFI Bluetooth USB IP54

Thermal Resolution
384 x 288 (110,592 pixels)

Temperature Range
-20 °C to 650 °C (-4 °F to 1202 °F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports.

Data Storage
Removable 64 GB Micro SD Card with image and video storage capacity of 100,000 images and approx. 300 hours

Display
640 × 480 Resolution, 3.5" LCD Touch Screen

Thermal Sensitivity
NETD:< 35 mK (@ 25 °C, F#=1.0) with image frequency 50 Hz

High Image Quality
IR resolution of 384 x 288 (110,592 pixels), Super IR upscales IR resolution to 768 x 576 (442,368 pixels)

Interchangeable and rechargeable Li-ion battery
Includes 2 interchangeable batteries and a dual bay charger to provide you with up to 12 hours of operation.

Whats is included in the Kit?

- Thermal Imager with Wrist Strap
- Power Supply for Battery Charger
- USB 2.0 A to USB Type-C Cable
- Interchangeable and Rechargeable Li-ion Batteries (x2)
- Two-bay Battery Charger
- 64 GB Micro SD card
- Hard Carrying Case
- Calibration Certificate / Quick Start Guide

KRYKARD®

Model	TC 3360
Infrared Image	
IR Resolution	384 x 288 (110,592 pixels)
SuperIR	768 x 576 (442,368 pixels)
NETD	< 35 mK (@ 25 °C, F#=1.0)
Image Frequency	50 Hz
Detector Pitch	17 µm
Spectral Range	7.5 µm to 14 µm
Focal Length	6.4 mm
F-number	F1.0
Field of View (FOV)	41.1°×30.5°
Spatial Resolution (IFOV)	1.87 mrad
Min. Focus Distance / Focus Mode	0.1 m (0.32ft) / Manual Focus
Image Display	
Visual Camera	3264 × 2448 (8 MP)
Display	640 × 480 Resolution, 3.5" LCD Touch Screen
Digital Zoom	1.0 x to 8.0 x continuous
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Focus Mode Palette	Above / Below / Interval
Color Alarm	Above / Below / Interval / Insulation
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Measurement and Analysis	
Object Temperature Range	-20 °C to 650 °C (-4 °F to 1202 °F)
Accuracy	Max (±2°C/3.6°F, ±2%), for the ambient temp. 15°C to 35°C (59°F to 95°F) and object temp. above 0°C (32°F)
Measurement Tools	Center Spot, Hot Spot, Cold Spot User-definable: 10 spots, 1 line, 5 rectangles, and 5 circles
Level and Span Mode	Auto / Manual / 1-Tap Touch-screen
Data Storage and Communication	
Storage Media	Removable 64 GB Micro SD Card
Image / Video Storage Capacity / Video File Format	Approx. 100,000 Images / Approx. 300 hours / MP4 video
Annotations	Voice note: Max. 60 seconds; Text note: Max. 200 characters
General	
Wi-Fi	802.11 b / g / n (2.4 GHz and 5 GHz)
USB Interface	USB Type-C
Bluetooth	Bluetooth 4.2
Laser	Yes, Class II, Wavelength: 635 nm; Power: < 1 mW
Vibration / Shock	2g, IEC 60068-2-6 / 25g, IEC 60068-2-27
Battery Type / Operating Time	Interchangeable and rechargeable Li-ion battery / Approx. 4 hours
Safety / EMC	IEC 61010-1 / EN 50130-4, EN 55032, EN IEC 61000-3-2, EN 61000-3-3
Working Temperature Range	-20°C to 50°C (-4°F to 122°F)
Storage Temperature Range	-40°C to 70°C (-40°F to 158°F
Relative Humidity	< 95% non-condensing
Weight / Dimension	Approx. 720 g (1.59 lb) / 244 × 100 × 104 mm (9.6 × 3.9 × 4.1 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001

+91 95000 97966 atandra.in enquiry@atandra.in

Revision: November 2024. Specifications are subject to change without prior notice.