KRYKARD

Ultra-high performance and maximum flexibility

THERMAL CAMCORDER

Thermal imagers for professional application

TCC 812K

Thermal Resolution
1280 x 1024 (1310, 720 pixels)

Temperature Range
-40°C to 2200°C
(-40°F to 3992°F)

Field of View (FOV)
L8: 7.9° × 6.3°; L12: 12° × 9.6°; L25: 25° × 20°; L50: 50° × 40°

Digital Zoom
1.x to 12.x continuous

Display
1920 × 1080 Resolution, 5.1" OLED Touch Screen

Data Storage
Built-in 128 GB flash memory with image and video storage capacity of 30,000 images and approx. 130 hours (mp4 video)

Thermal Sensitivity
< 20 mK (@ 30 °C, F#=1.0)

Battery Operating Time
Approx. 4 hours continuous running

WIFI | Bluetooth | USB | IP54 | Compass | GPS

What is included in the Kit?

- Thermal Imager
- Wrist Strap
- 2-In-1 USB-C to USB-C/A Cable
- Hard Carrying Case
- Quick Start Guide
- Calibration Certificate

KRYKARD®

Model	TCC 812K
Infrared Image	
IR Resolution	1280 × 1024 (1310, 720 pixels)
SuperIR	2560 × 2048 (5,242,880 pixels)
NETD	＜20 mK (@ 30 °C, F#=1.0)
Image Frequency	30 Hz
Detector Pitch	12 µm
Spectral Range	7.5 to 14 µm
Focal Length	L8: 112.2 mm; L12: 72.9 mm; L25: 35 mm; L50: 17.6 mm
F-number	L8: F1.3; L12: F1.2; L25: F1.1; L50: F1.1
Field of View (FOV)	L8: 7.9° × 6.3°; L12: 12° × 9.6°; L25: 25° × 20°; L50: 50° × 40°
Spatial Resolution (IFOV)	L8: 0.11 mrad; L12: 0.17 mrad; L25: 0.34 mrad; L50: 0.68 mrad
Min. Focus Distance	L8: 5m (16.4 ft); L12: 1.65m (5.41 ft); L25: 0.3m (0.98 ft); L50: 0.2m (0.66 ft)
Focus Mode	Laser Assisted AF / Continuous AF / AF / Manual Focus / Touch AF
Image Display	
Visual Camera	4208 × 3120 (13 MP)
Display	1920 × 1080 Resolution, 5.1" OLED Touch Screen, Lv 360 Cd/m^2
Digital Zoom	1.x to 12.x continuous
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Measurement and Analysis	
Object Temperature Range	-40°C to 2200°C (-40°F to 3992°F)
Accuracy	Max. ± 2%
Measurement Tools	Center Spot, Hot Spot, Cold Spot User-definable: Delta T, 10 spots, 1 line, 5 rectangles, and 5 circles
Level and Span Mode	Auto / Manual / 1-Tap Touch-Screen
Data Storage and Communication	
Storage Media	Removable 128 GB SD Card
Image / Video Storage Capacity	Approx. 30,000 Images / Approx. 130 hours
Annotations	Voice note: Max. 60 seconds; Text note: Max. 200 characters
Image / Video File Format	Radiometric JPEG MP4 video and radiometric infrared video
General	
Wi-Fi / Bluetooth	802.11 b / g / n (2.4 GHz and 5 GHz) / Bluetooth 4.2
USB Interface	USB Type-C
Laser	Yes, Class II, Wavelength: 635 nm; Power: < 1 mW
GPS & Compass, HDMI Interface	Yes
Vibration / Shock	2 g, IEC 60068-2-6 / 25 g, IEC 60068-2-27
Battery Type / Operating Time	Interchangeable and rechargeable Li-ion battery / Approx. 4 hours
Safety / EMC	IEC 61010-1 / EN 301 489-1, EN 301 489-17, EN IEC 61000-6-2, EN IEC 61000-6-3, EN 61326-1
Operating Temperature / Relative Humidity	-20°C to 50°C (-4°F to 122 °F) ＜95% non-condensing
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Weight / Dimension	Approx. 1550 g (3.42 lb) (Without lens) 220.5 × 151.9 × 88.1 mm (8.68 × 5.98 × 3.47 in) (Without lens)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2025. Specifications are subject to change without prior notice.