KRYKARD®

Most Innovative Thermal Imaging Camera

THERMAL IMAGERS

TC P360

Field of View (FOV)
24° x 18°

Temperature Range
-20 °C to 650 °C (-4 °F to 1202 °F)

Measurement mode
8 movable spots, auto hot / cold spot, profile, 2 area boxes, isotherm, line

Data Storage
16 GB of external SD memory is available.

High Image Quality
IR resolution of 384 x 288

Display
3.5" Capacitive touch screen, digital zoom with 1x to 10x

Thermal Sensitivity
≤ 0.05°C@30°C

Built-in Li-ion battery
Built-in lithium-ion battery with an 8-hour battery life.

Bluetooth USB IP54

What is included in the Kit?

- Suitable Adapter
- 16 GB SD card
- Calibration Certificate
- Bluetooth headset
- USB Cable

TECHNICAL SPECIFICATION

KRYKARD®

Model	TC P360
Image Performance	
FOV / Min. focus distance	24° x 18°/ 0.15 m
Spatial resolution	1.1 mrad
Thermal Sensitivity	≤ 0.05°C @ 30°C
Detector Type	UFPA
Resolution	384 x 288
Spectral Range	8 - 14 um
Focus	Motor / Auto
Zoom	1 x to 10 x
Image Presentation	
Image mode	IR / CCD / Duo - vision / Duo - vision Plus
LCD display	3.5" Capacitive touch screen
Visible Pixels	High definition CCD , 5MP
Video Output	NTSC (60Hz) or PAL (50Hz) composite video
Temperature Measurement	
Measurement range	-20℃ to + 650℃，up to +1500℃ (optional)
Accuracy	±2° or ±2% of readings
Measurement mode	8 movable spots, auto hot / cold spot, profile, 2 area boxes, isotherm, line
Correction	Ambient temperature / Emissivity / Humidity / Distance
Pseudo-color	Iron, Iron inverted, Rainbow, Feather, Grey and Grey inverted
Alarm	Yes
Image storage	
Type	16 GB TF card
Image format	IR Image：.JPG (thermal/Visual) CCD Image：.JPG
Video Format	.MPEG
Annotation	Voice / Note Annotation
Power system	
Battery type	Built - in rechargeable lithium-ion battery
Charge Interface	Type - C
Battery Operating time	8 hours
Power Management	Auto shut off / Sleep mode
Environment specification	
Operating temperature range	-20°C to +50°C
Storage temperature range	-40°C to +70°C
Humidity	10% to 95%, non-condensing
Encapsulation	IP54
Shock / Vibration	25 G / 2 G
Drop resistance	2 m
Physical characteristic	
Size	232 mm × 115 mm × 168 mm
Weight	Less than 900 g
Tripod mounting	1 / 4"_20
Additional features	
Illuminator	Yes
Laser Pointer	Yes
Video Record	Yes
Ports	USB port , Analog video output
Bluetooth	Yes
Available Optional Lenses	7°, 12°, 48°

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: Oct 2024. Specifications are subject to change without prior notice.