High-performance handheld thermal camera for industrial, predictive, oil and gas, & utility maintenance inspections

THERMAL CAMCORDER

Thermal imagers for professional application

TCC 7460

Thermal Resolution
480 × 360 (172,800 pixels)

Display
1280 × 720 Resolution, 5”
LCD Touch Screen

Temperature Range
-20°C to 650°C
(-4°F to 1202°F)

Thermal Sensitivity
< 30 mK (@ 25 °C, F#=1.0)

Field of View (FOV)
L6: 6° × 4.5°; L9: 9° × 6.8°; L19: 18.7° × 14°; L37: 37.3° × 27.8°

Data Storage
Built-in 128 GB flash memory
with image and video storage capacity of 1,20,000 images and approx. 500 hours

Digital Zoom
1.x to 12.x continuous

Battery Operating Time
Approx. 4 hours continuous running

WIFI | Bluetooth | USB | IP54 | Compass | GPS

What is included in the Kit?

- Thermal Imager
- Wrist Strap
- 2-In-1 USB-C to USB-C/A Cable
- Hard Carrying Case
- Quick Start Guide
- Calibration Certificate

KRYKARD®

Model	TCC 7460
Infrared Image	
IR Resolution	480 × 360 (172,800 pixels)
SuperIR	960 x 720 (691,200 pixels)
NETD	< 30 mK (@ 25 °C, F#=1.0)
Image Frequency	30 Hz
Detector Pitch	17 µm
Spectral Range	7.5 to 14 µm
Focal Length	L6: 77.4 mm; L9: 51.4 mm; L19: 25.6 mm; L37: 12.6 mm
F-number	L6: F1.2; L9: F1.1; L19: F1.0; L37: F1.0
Field of View (FOV)	L6: 6° × 4.5°; L9: 9° × 6.8°; L19: 18.7° × 14°; L37: 37.3° × 27.8°
Spatial Resolution (IFOV)	L6: 0.22 mrad; L9: 0.33 mrad; L19: 0.66 mrad; L37: 1.35 mrad
Min. Focus Distance	L6: 2 m (6.56 ft); L9: 1 m (3.3 ft); L19: 0.15 m (0.49 ft); L37: 0.15 m (0.49 ft)
Focus Mode	Laser Assisted AF / Continuous AF / AF / Manual Focus / Touch AF
Image Display	
Visual Camera	3264 × 2448 (8 MP)
Display	1280 × 720 Resolution, 5” LCD Touch Screen
Digital Zoom	1.x to 12.x continuous
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Measurement and Analysis	
Object Temperature Range	-20°C to 650°C (-4°F to 1202°F)
Accuracy	Max. (± 2°C / 3.6°F, ± 2%)
Measurement Tools	Center Spot, Hot Spot, Cold Spot User-definable: Delta T, 10 spots, 1 line, 5 rectangles, and 5 circles
Level and Span Mode	Auto / Manual / 1-Tap Touch-Screen
Data Storage and Communication	
Storage Media	Removable 128 GB SD Card
Image / Video Storage Capacity	Approx. 120,000 Images / Approx. 500 hours
Annotations	Voice note: Max. 60 seconds; Text note: Max. 200 characters
Image / Video File Format	Radiometric JPEG / MP4 video and radiometric video
General	
Wi-Fi / Bluetooth	802.11 b / g / n (2.4 GHz and 5 GHz) / Bluetooth 4.2
USB Interface	USB Type-C
Laser	Yes, Class II, Wavelength: 635 nm; Power: < 1 mW
GPS & Compass, HDMI Interface	Yes
Vibration / Shock	2 g, IEC 60068-2-6 / 25 g, IEC 60068-2-27
Battery Type / Operating Time	Interchangeable and rechargeable Li-ion battery / Approx. 4 hours
Safety / EMC	IEC 61010-1 / EN 301 489-1, EN 301 489-17, EN IEC 61000-6-2, EN IEC 61000-64, EN 61326-1
Operating Temperature / Relative Humidity	-20°C to 50°C (-4°F to 122 °F) / < 95% non-condensing
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Weight / Dimension	Approx. 1451 g (3.2 lb) / 210.1 × 141.03 × 87.8 mm (8.27 × 5.55 × 3.45 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: October 2024. Specifications are subject to change without prior notice.