High performance compact thermal imaging camera for professionals

THERMAL IMAGERS

TC S030

Temperature Range
-20°C to 350°C (-4°F to 662°F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports.

Field of View (FOV)
50° × 50°

Thermal Resolution
96 × 96 (9, 216 pixels)

Data Storage
Built-in 4 GB flash memory with image and video storage capacity of 30,000 images and approx. 20 hours

Super IR
Upscales thermal resolution to 240 x 240 (57,600 Pixels) when viewing with 25 Hz image frequency

Portable Pocket-Sized
Easy to carry and hold having 3.5" LCD touch screen

Thermal Sensitivity
NETD: < 50 mK (@ 25 °C, F#=1.0)

Multiple Image Modes
Thermal, Fusion, PIP, Blending and Visual

Battery Operating Time
Approx. 4 hours continuous running

WIFI USB IP54

Whats is included in the Kit?

- Thermal Imager
- Wrist Strap
- 2-In-1 USB-C to USB-C/A Cable
- Soft Carrying Pouch
- Quick Start Guide
- Calibration Certificate

KRYKARD®

Model	TC S030
Infrared Image	
IR Resolution	96 × 96 (9, 216 pixels)
SuperIR	Yes, on captured images and live view
Distance to Spot Ratio (D:S)	112:1
NETD	< 50 mK (@ 25 °C, F#=1.0)
Image Frequency	25 Hz
Detector Pitch	12 µm
Spectral Range	7.5 to 14 µm
Focal Length	1.35 mm
F - number	F1.0
Field of View (FOV)	50° × 50°
Spatial Resolution (IFOV)	8.89 mrad
Min. Focus Distance	0.1 m (0.33 ft)
Focus Mode	Focus Free
Image Display	
Visual Camera	640× 480 (0.3 MP)
Display	320 × 240 Resolution, 3.5" LCD Touch Screen
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Digital Zoom	1.0 x to 4.0 x continuous
Measurement and Analysis	
Object Temperature Range	-20°C to 350°C (-4°F to 662°F)
Accuracy	Max. (± 2°C/3.6°F, ± 2%), for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
Measurement Tools	Center Spot, Hot Spot, Cold Spot
Level and Span Mode	Auto / Manual / 1-Tap Touch-screen
Data Storage and Communication	
Storage Media	Built-in 4 GB flash memory (user available storage space is less than the nominal capacity)
Image / Video Storage Capacity	Approx. 30,000 Images / Approx. 20 hours
Image / Video File Format	Radiometric JPEG / MP4 video
Annotations	Text note: Max. 255 characters
General	
Wi-Fi	802.11 b / g / n (2.4GHz)
USB Interface	USB Type-C
Power Supply	USB-C (5 V / 2 A)
Battery Type	Rechargeable Li-ion battery
Battery Operating Time	Approx. 6 hours
Power Saving Mode	Auto Power-off and manual sleep
Working Temperature Range	-10°C to 50°C (14°F to 122°F)
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Relative Humidity	< 95% non-condensing
Weight / Dimension	Approx. 380 g (0.84 lb) / 138.45 × 85.2 × 23.6 mm (5.45 × 3.35 × 0.93 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2024. Specifications are subject to change without prior notice.