Compact easy to use thermal imaging camera for daily operation

THERMAL IMAGERS

TC 2250

High Thermal Resolution
256 × 192 (49,152 pixels)

Field of View (FOV)
27.8° × 37.2°

Temperature Range
-20°C to 550°C (-4°F to 1022°F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports.

Data Storage
Built in 16G eMMC flash memory with image storage capacity of 35,000 images

25 Hz image frequency
Fast image frequency and ensures smooth video and accurate measurements

Display
480 × 640 Resolution, 3.2" LCD Screen

Thermal Sensitivity
NETD: < 40 mK (@ 25°C, F# = 1.0)

Multiple Image Modes
Thermal, Fusion, PIP, and Visual modes

Battery Operating Time
Up to 6 hours continuous running

WIFI USB IP54

Whats is included in the Kit?

- Thermal Imager
- Wrist Strap
- USB Cable
- Power Adapter
- Quick Start Guide
- Calibration Certificate

KRYKARD®

Model	TC 2250
Infrared Image	
IR Resolution	256 × 192 (49,152 pixels)
SuperIR	Yes, on captured thermal images
NETD	< 40 mK (@ 25 °C, F#=1.0)
Image Frequency	25 Hz
Detector Pitch	12 µm
Spectral Range	7.5 µm to 14 µm
Focal Length	3.6 mm
F - number	F1.0
Field of View (FOV)	37.2° × 50.0°
Spatial Resolution (IFOV)	3.3 mrad
Min. Focus Distance	0.3 m (0.98 ft)
Focus Mode	Focus Free
Image Display	
Visual Camera	1600 × 1200 (2 MP)
Display	480 × 640 Resolution, 3.2" LCD Screen
Color Alarm	Above alarm
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion
Image Modes	Thermal / Visual / Fusion / PIP
Measurement and Analysis	
Object Temperature Range	-20°C to 550°C (-4°F to 1022°F)
Accuracy	Max. (± 2°C/3.6°F, ± 2%), for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
Measurement Tools	Center Spot, Hot Spot, Cold Spot User-definable: 3 spots
Level and Span Mode	Auto / Manual
Data Storage and Communication	
Storage Media	Built - in 16G eMMC (user available storage space is less than the nominal capacity)
Image Storage Capacity	Approx. 35,000 Images
Image File Format	Radiometric JPEG
General	
Wi-Fi	802.11 b / g / n (2.4 GHz)
USB Interface	USB Type-C
LED Light	Yes
Power Supply	USB-C (5 V / 2 A)
Battery Type	Rechargeable Li-ion battery
Battery Operating Time	Approx. 6 hours
Drop Test Height	2 m (6.56 ft)
Working Temperature Range	-10°C to 50°C (14°F to 122°F)
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Relative Humidity	< 95% non-condensing
Weight	Approx. 380 g (0.84 lb)
Dimension	221.7 × 73.5 × 123.8 mm (8.73 × 2.89 × 4.87 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2024. Specifications are subject to change without prior notice.