Compact easy to use thermal imaging camera for daily operation

THERMAL IMAGERS

TC 4660H

Field of View (FOV) / Laser
25° × 19° / Long-distance laser light supplement

Temperature Range
-20 °C to 2000 °C (-4 °F to 3632 °F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports.

Data Storage
Removable 64 GB Micro SD Card with image and video storage capacity of 60,000 images and approx. 54 hours

Ultra High Resolution
Up to 640 x 480 (307,200 pixels) and @35mK NETD

Display
800 × 480 Resolution, 4.3" LCD Touch Screen, Digital zoom of 1.0x to 8.0x continuous

Fast Image Frequency
50 Hz with smooth and precise capturing

Interchangeable and rechargeable Li-ion battery
Includes 3 interchangeable batteries and a dual bay charger to provide you with up to 12 hours of operation.

WIFI Bluetooth USB

Whats is included in the Kit?

IP54 Compass GPS

- Thermal Imager with Hand Strap
- Mini HDMI to HDMI Cable
- Lens Cover
- Power Adapter, Charging Base
- USB 2.0 A to USB Type-C Cable
- Rechargeable Li-ion Batteries (x3)
- User manual, Packing list
- 64 GB Micro SD card
- Hard Carrying Case
- Calibration Certificate / Quick Start Guide

KRYKARD®

Model	TC 4660H
Infrared Image	
IR Resolution	640 x 480 (307,200 pixels)
SuperIR	1280 x 960 (1,228,800 pixels)
NETD	< 35 mK (@ 25 °C, F#=1.0)
Image Frequency	50 Hz
Detector Pitch	17 µm
Spectral Range	7.5 µm to 14 µm
Focal Length	25 mm
F-number	F1.0
Field of View (FOV)	25° × 19°
Spatial Resolution (IFOV)	0.68 mrad
Min. Focus Distance / Focus Mode	0.3 m (0.98 ft) / Laser Assisted AF / Continuous AF / AF / Manual Focus / Touch AF
Image Display	
Visual Camera	3264 × 2448 (8 MP)
Display / Digital Zoom	800 × 480 Resolution, 4.3" LCD Touch Screen / 1.0 x to 8.0 x continuous
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Focus Mode Palette	Above / Below / Interval
Color Alarm	Above / Below / Interval / Insulation / Condensation
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Measurement and Analysis	
Object Temperature Range	-20 °C to 2000 °C (-4 °F to 3632 °F)
Accuracy	Max (±2°C/3.6°F, ±2%)
Measurement Tools	Center Spot, Hot Spot, Cold Spot User-definable: 10 spots, 1 line, 5 rectangles, and 5 circles
Level and Span Mode	Auto / Manual / 1-Tap Touch-screen
Data Storage and Communication	
Storage Media	Removable 64 GB Micro SD Card
Image / Video Storage Capacity / Video File Format	Approx. 60,000 Images / Approx. 54 hours / MP4 video
Annotations	Voice note: Max. 60 seconds; Text note: Max. 200 characters
General	
Wi-Fi / Bluetooth	802.11 b/g/n (2.4 GHz and 5 GHz) / Bluetooth 4.2
USB Interface	USB Type-C
Laser	Yes, Class II, Wavelength: 635 nm; Power: < 1 mW
GPS & Compass, HDMI Interface	Yes
Vibration / Shock	2 g, IEC 60068-2-6 / 25 g, IEC 60068-2-27
Battery Type / Operating Time	Interchangeable and rechargeable Li-ion battery / Approx. 4 hours
Safety / EMC	IEC 61010-1 / EN 301 489-1, EN 301 489-17, EN IEC 61000-6-2, EN IEC 61000-6-3, EN IEC 61326-1, EN IEC 61326-2-2
Operating Temperature / Relative Humidity	-20°C to 60°C (-4°F to 140°F) / < 95% non-condensing
Storage Temperature Range	-20°C to 50°C (-4°F to 122°F)
Weight / Dimension	Approx. 1058 g (2.33 lb) / 284.7 × 120.6 × 124.5 mm (11.21 × 4.75 × 4.9 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2024. Specifications are subject to change without prior notice.