IR Performance, Surprisingly Affordable, and Absolutely Brilliant

THERMAL IMAGERS

TC E050

Thermal Resolution
96 × 96 (9,216 pixels)

Field of View (FOV)
50° × 50°

Temperature Range
-20°C to 550°C (-4°F to 1022°F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports.

Data Storage
Built in 4 GB flash memory with image storage capacity of 30,000 images

50° Wide Angle Lens
Ensures large area scanning to deduct flaws like leaking, insulation issues, etc.

Super IR
Upscales thermal resolution up to 240 × 240 (57,600 pixels)

Thermal Sensitivity
NETD: < 50 mK (@ 25°C, F# = 1.0)

Dual Camera Thermal Imager
3 image mode
Thermal/Fusion/Visual modes

Battery Operating Time
Approx. 8 hours continuous running time

WIFI

IP54

Laser

Whats is included in the Kit?

- Thermal Imager
- Wrist Strap
- 2-In-1 USB-C to USB-C/A Cable
- Quick Start Guide
- Calibration Certificate
- Soft Carrying Pouch (Optional)

KRYKARD®

Model	TC E050
Infrared Image	
IR Resolution	96 × 96 (9,216 pixels)
SuperIR	240 × 240 (57,600 pixels)
Distance to Spot Ratio (D:S)	112:1
Image Frequency	25 Hz
NETD	< 50 mK (@ 25°C, F# = 1.0)
Detector Pitch	12 µm
Spectral Range	7.5 µm to 14 µm
Focal Length	1.35 mm
F - number	F1.0
Field of View (FOV)	50° × 50°
Spatial Resolution (IFOV)	8.89 mrad
Min. Focus Distance	0.1 m (0.33 ft)
Focus Mode	Focus Free
Image Display	
Display	240 × 320 Resolution, 2.4"LCD Screen
Image Modes	Thermal / Visual / Fusion
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion
Color Alarm	Above alarm
Visual Camera	640 × 480
Measurement and Analysis	
Object Temperature Range	-20°C to 550°C (-4°F to 1022°F)
Accuracy	Max (±2°C/3.6°F, ±2%) at ambient temperature 25°C (77°F) and object temperature above 0°C (32°F)
Measurement Tools	Center Spot, Hot Spot, Cold Spot
Level and Span Mode	Auto / Manual
Data Storage and Communication	
Storage Media	Built-in 4 GB flash memory
Image Storage Capacity	Approx. 30,000 Images
General	
USB Interface	USB Type-C
Laser	Yes, Class II
Battery Type	Rechargeable Li-ion battery
Battery Operating Time	Approx. 8 hours
Protection Level	IP54
Drop Test Height	2 m (6.56 ft)
Working Temperature Range	-10°C to 50°C (14°F to 122°F)
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Relative Humidity	< 95% non-condensing
Weight / Dimension	Approx. 380 g (0.84 lb) / 196 × 117 × 59 mm (7.7" × 4.6" × 2.3")

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2024. Specifications are subject to change without prior notice.