High performance compact thermal imaging camera for professionals

THERMAL IMAGERS

TC S240

Temperature Range
-20°C to 400°C (-4°F to 752°F)

KRYKARD Analyzer Software
Included software offers flexible ways (points, lines, rectangles, circles, polygons) to analyze thermographic info of captured pictures, and generate reports

Field of View (FOV)
50° × 37.2°

Thermal Resolution
256 × 192 (49, 152 pixels)

Super IR
Upscales thermal resolution to 240 x 240 (57,600 Pixels) when viewing with 25 Hz image frequency

Thermal Sensitivity
NETD: < 40 mK (@ 25°C, F# = 1.0)

Data Storage
Built-in 16 GB flash memory with image and video storage capacity of 60,000 images and approx. 54 hours

Battery Operating Time
Approx. 4 hours continuous running

WIFI USB USB IP54

Whats is included in the Kit?

- Thermal Imager
- Wrist Strap
- 2-In-1 USB-C to USB-C/A Cable
- Soft Carrying Pouch
- Quick Start Guide
- Calibration Certificate

KRYKARD®

Model	TC S240
Infrared Image	
IR Resolution	256 × 192 (49,152 pixels)
SuperIR	Yes, on captured images and live view
NETD	< 40 mK (@ 25 °C, F#=1.0)
Image Frequency	25 Hz
Detector Pitch	12 µm
Spectral Range	7.5 µm to 14 µm
Focal Length	3.5 mm
F - number	F1.1
Field of View (FOV)	50° × 37.2°
Spatial Resolution (IFOV)	3.43 mrad
Min. Focus Distance	0.3 m (0.98 ft)
Focus Mode	Focus Free
Image Display	
Visual Camera	3264 × 2448 (8 MP)
Display	640 × 480 Resolution, 3.5" LCD Touch Screen with auto-rotation
Digital Zoom	1.0 x to 4.0 x continuous
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow, Red Hot, Fusion, Rain, Blue Red
Image Modes	Thermal / Visual / Fusion / PIP / Blending
Measurement and Analysis	
Object Temperature Range	-20°C to 400°C (-4°F to 752°F)
Accuracy	Max (±2°C/3.6°F, ±2%), for the ambient temp. 15°C to 35°C (59°F to 95°F) and object temp. above 0°C (32°F)
Measurement Tools	Center Spot, Hot Spot, Cold Spot
Level and Span Mode	Auto / Manual / 1-Tap Touch-screen
Data Storage and Communication	
Storage Media	Built-in 16 GB flash memory (user available storage space is less than the nominal capacity)
Image / Video Storage Capacity	Approx. 60,000 Images / Approx. 54 hours
Annotations	Text note: max. 255 characters
Image / Video File Format	Radiometric JPEG / MP4 video (25 Hz) and Radiometric video (5 Hz)
General	
Wi-Fi	802.11 b / g / n (2.4 GHz and 5 GHz)
USB Interface	USB Type-C
Bluetooth	Bluetooth 4.2, supports wireless headsets
Power Supply	USB-C (5 V / 2 A)
Power Saving Mode	Auto Power-off and manual sleep
Battery Type	Rechargeable Li-ion battery
Battery Operating Time	Approx. 4 hours
Working Temperature Range	-10°C to 50°C (-4°F to 122°F)
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Relative Humidity	< 95% non-condensing
Weight / Dimension	Approx. 380 g (0.84 lb) / 138.5 × 85.2 × 23.6 mm (5.45 × 3.35 × 0.93 in)

Atandra Energy Private Limited
No. 5, Kumaran St., Pazhavanthangal, Chennai - 600 114
KRYKARD is a registered trademark owned by Atandra Energy Private Limited
ISO 9001:2015 | 14001 - 2015 | 45001 - 2015 | 500001
+91 95000 97966 atandra.in enquiry@atandra.in
Revision: July 2024. Specifications are subject to change without prior notice.