queries.sql

```sql
CREATE TABLE Students (
    StudentID INT PRIMARY KEY,
    StudentName VARCHAR(50),
    Age INT
);
INSERT INTO Students (StudentID, StudentName, Age) VALUES
(101, 'Arun', 20),
(102, 'Bala', 21),
(103, 'Charan', 19);
SELECT * FROM Students;
```

I/O | AI Agent | 62 ms

STDIN

Output:

```
+-----------+-------------+------+
| StudentID | StudentName | Age  |
+-----------+-------------+------+
|       101 | Arun        |   20 |
|       102 | Bala        |   21 |
|       103 | Charan      |   19 |
+-----------+-------------+------+
```

queries.sql

```sql

CREATE TABLE Departments (
    DepartmentID INT PRIMARY KEY,
    DepartmentName VARCHAR(50)
);

CREATE TABLE Employees (
    EmployeeID INT PRIMARY KEY,
    EmployeeName VARCHAR(50),
    DepartmentID INT,
    FOREIGN KEY (DepartmentID)
    REFERENCES Departments(DepartmentID)
);

INSERT INTO Departments VALUES
(10, 'CSE'),
(20, 'ECE'),
(30, 'IT');

INSERT INTO Employees VALUES
(101, 'Ravi', 10),
(102, 'Priya', 20),
(103, 'Kumar', 10);

SELECT * FROM Departments;
SELECT * FROM Employees;
```

I/O | AI Agent

STDIN

Output:

```
+--------------+----------------+
| DepartmentID | DepartmentName |
+--------------+----------------+
|           10 | CSE            |
|           20 | ECE            |
|           30 | IT             |
+--------------+----------------+
+------------+--------------+--------------+
| EmployeeID | EmployeeName | DepartmentID |
+------------+--------------+--------------+
|        101 | Ravi         |           10 |
|        102 | Priya        |           20 |
|        103 | Kumar        |           10 |
+------------+--------------+--------------+
```

Ready

queries.sql

```sql
CREATE TABLE Users (
    UserID INT PRIMARY KEY,
    UserName VARCHAR(50),
    Email VARCHAR(100) UNIQUE
);

INSERT INTO Users VALUES
(1, 'Arun', 'arun@gmail.com'),
(2, 'Bala', 'bala@gmail.com');

SELECT * FROM Users;

```

I/O | AI Agent

STDIN

Output:

```
+--------+----------+----------------+
| UserID | UserName | Email          |
+--------+----------+----------------+
|      1 | Arun     | arun@gmail.com |
|      2 | Bala     | bala@gmail.com |
+--------+----------+----------------+
```

```sql

CREATE TABLE CollegeStudents (
    StudentID INT PRIMARY KEY,
    StudentName VARCHAR(50),
    Age INT CHECK (Age >= 18)
);

INSERT INTO CollegeStudents
VALUES (101, 'Arun', 20);

SELECT * FROM CollegeStudents;

CREATE TABLE ExamResults (
    StudentID INT PRIMARY KEY,
    Marks INT CHECK (Marks BETWEEN 0 AND 100)
);

INSERT INTO ExamResults VALUES (101, 85);

SELECT * FROM ExamResults;


```

STDIN

Output:

```
+-----------+-------------+------+
| StudentID | StudentName | Age  |
+-----------+-------------+------+
|       101 | Arun        |   20 |
+-----------+-------------+------+
+-----------+-------+
| StudentID | Marks |
+-----------+-------+
|       101 |    85 |
+-----------+-------+
```

```sql

CREATE TABLE Orders (
    OrderID INT PRIMARY KEY,
    ProductName VARCHAR(50),
    Status VARCHAR(20) DEFAULT 'Pending'
);

INSERT INTO Orders (OrderID, ProductName)
VALUES (101, 'Laptop');

INSERT INTO Orders
VALUES (102, 'Mouse', 'Delivered');

SELECT * FROM Orders;


```

STDIN

Output:

```
+---------+-------------+-----------+
| OrderID | ProductName | Status    |
+---------+-------------+-----------+
|     101 | Laptop      | Pending   |
|     102 | Mouse       | Delivered |
+---------+-------------+-----------+
```

queries.sql

```sql

CREATE TABLE Teachers (
    TeacherID INT PRIMARY KEY,
    TeacherName VARCHAR(50) NOT NULL,
    Salary DECIMAL(10,2)
);

INSERT INTO Teachers
VALUES (101, 'Ravi', 45000);

SELECT * FROM Teachers;


```

I/O | AI Agent

STDIN

Output:

```
+-----------+-------------+----------+
| TeacherID | TeacherName | Salary   |
+-----------+-------------+----------+
|       101 | Ravi        | 45000.00 |
+-----------+-------------+----------+
```