INTERNSHIP TECHNICAL REPORT

Explainable AI Framework for Heart Disease Risk Prediction using XGBoost, SHAP, and LIME

Name: V.Venkata Jagan & P. Ritwik Ratan

Abstract

Artificial Intelligence (AI) and Machine Learning (ML) have shown immense potential in predicting complex conditions such as heart disease from multifaceted patient health metrics. However, the inherent "black-box" nature of advanced predictive models, such as Extreme Gradient Boosting (XGBoost) and deep neural networks, heavily limits their practical deployment in real-world clinical settings, where transparency, accountability, and mechanistic understanding are paramount. This project directly addresses the crucial interpretability problem by designing and deploying an end-to-end Explainable AI (XAI) framework that not only achieves high predictive accuracy for cardiovascular risk but also mathematically justifies its individual predictions to medical professionals. An XGBoost classifier was trained and rigorously validated on the benchmark UCI Heart Disease dataset (comprising 303 patient records with 13 distinct clinical features), achieving an accuracy of 80.33% with balanced precision and recall. To overcome the model's opacity and build clinical trust, two industry-leading XAI methodologies were integrated into the diagnostic pipeline: SHAP (Shapley Additive Explanations) for cooperative game theory-based global and local feature attribution, and LIME (Local Interpretable Model-agnostic Explanations) for generating local, interpretable surrogate decision rules. Furthermore, this study introduces a novel "Consistency Score" metric, designed to quantify the mathematical agreement between SHAP and LIME regarding the primary risk-driving factors for any individual patient's diagnosis. The complete predictive pipeline was successfully deployed as a full-stack application, utilising a high-performance asynchronous FastAPI backend to serve the ML models, coupled with a modern, interactive React.js glassmorphic dashboard for seamless clinician interaction. The experimental results conclusively demonstrate that highly accurate, complex machine learning ensembles can be made transparent, interpretable, and trustworthy for healthcare screening without compromising their core predictive capabilities.

Keywords: Explainable AI, Cardiovascular Disease, XGBoost, SHAP, LIME, Clinical Decision Support Systems, Machine Learning Interpretability, Predictive Analytics.

1. Introduction

Cardiovascular diseases (CVDs) remain the leading cause of mortality globally, taking an estimated 17.9 million lives each year according to the World Health Organization. Predictive modelling in cardiology is a cornerstone for early diagnosis, triage, and preventative care. The rapid digitisation of electronic health records (EHR) combined with state-of-the-art advances in machine learning has enabled the creation of automated risk classification systems that approach, and sometimes exceed, human expert-level diagnostic accuracy. Despite this significant technical progress, the clinical utility of advanced non-linear classifiers remains heavily dependent on the clinician's ability to logically trust and understand the model's output.

In a clinical screening context, a prediction isolated from its underlying rationale carries an unacceptable level of risk. Physicians cannot blindly rely on a "black box" to dictate patient treatment efficacy, as algorithmic errors or biases could lead to catastrophic false negatives (missed diagnoses) or false positives (unnecessary invasive procedures). The UCI Heart Disease dataset—a widely recognised and intensely studied benchmark in cardiovascular predictive modelling—contains 13 key clinical features, including resting blood pressure, serum cholesterol, fasting blood sugar, and maximum heart rate achieved. Classifiers trained on such data naturally discover intricate multi-dimensional correlations that yield high accuracy but fail to communicate *why* a specific patient's profile triggered a high-risk flag.

This internship project presents a comprehensive, end-to-end pipeline that trains a robust XGBoost classifier on the UCI dataset, integrates both SHAP and LIME to generate multi-faceted local and global explanations, and introduces a custom comparative consistency metric. The primary goal is to empirically demonstrate that Explainable AI (XAI) based clinical decision support systems yield a meaningful improvement in diagnostic transparency—thereby reducing the risk of automation bias and fostering verifiable trust in AI-driven healthcare tools.

1.1 Objectives

• Design, tune, and train a highly accurate XGBoost ensemble classifier specifically optimised for tabular medical data execution within a feasible inference time constraint.

• Implement and integrate SHAP to generate both global feature importance rankings across the dataset and local instance-level explanations for individual patients.

• Implement and integrate LIME to generate local, linear surrogate rule-based explanations, providing an alternative interpretability lens.

• Construct a comparative analysis framework to calculate a "Consistency Score" that mathematically measures the agreement between SHAP and LIME concerning the top primary risk factors.

• Architect and deploy a full-stack, production-ready web application (utilising a FastAPI Python backend and a React.js frontend) that provides real-time patient data upload, risk classification, and interactive, clinician-friendly XAI visualisations.

1.2 Novelty and Primary Contribution

The core novelty of this work lies in its comparative study of consistency and reliability between SHAP and LIME explicitly tailored for clinical decision support. While many contemporary applications bolt on a single XAI method as an afterthought, the proposed pipeline exhibits stable, verifiable transparency by actively cross-validating the explanations generated by two distinctly different mathematical frameworks. By enforcing this consistency check, the system provides a meta-level of confidence to the clinician. Furthermore, the complete pipeline from raw dataset ingestion to full-stack web deployment is thoroughly documented and highly reproducible, successfully bridging the well-known gap between theoretical machine learning performance and practical clinical interpretability.

2. Background and Related Work

2.1 Deep Learning and ML for Heart Disease Classification

Since its introduction by Detrano et al. (1989), the UCI Heart Disease dataset has served as a foundational benchmark for algorithmic diagnostics. Historically, studies employing Logistic Regression, Support Vector Machines (SVM), and standard Random Forests established baseline accuracies clustering in the 75–85% range. More recent explorations have applied deep neural networks; however, these often suffer from overfitting on small-to-medium tabular datasets. These comparative results strongly motivate the use of Extreme Gradient Boosting (XGBoost), introduced by Chen and Guestrin (2016), as a well-calibrated, highly competitive baseline for binary disease classification due to its superior regularisation, handling of sparse tabular data, and overall gradient boosting efficiency.

2.2 The "Black Box" Problem in Medical AI

While modern ensemble methods and deep neural networks easily achieve state-of-the-art accuracy, their decision boundaries are profoundly non-linear and mathematically opaque to human inspection. Within the healthcare sector, regulatory standards (such as the GDPR's implicit "Right to Explanation") and strict medical ethical guidelines increasingly mandate transparency for automated decisions. As noted by Ghassemi et al. (2021) and Amann et al. (2020), traditional "black-box" models cannot synthesise genuinely understandable reasoning, which severely limits their clinical deployment, as doctors cannot verify if the model is relying on sound biological principles or spurious dataset artefacts.

2.3 Explainable AI (SHAP and LIME)

The field of Explainable AI (XAI) has emerged precisely to solve this opacity issue. Lundberg and Lee (2017) introduced SHAP (Shapley Additive Explanations), establishing a unified measure of feature importance grounded in cooperative game theory. SHAP ensures a mathematically fair distribution of a prediction's total probability across its constituent features. Conversely, Ribeiro et al. (2016) introduced LIME (Local Interpretable Model-agnostic Explanations), which operates by perturbing input data to approximate any complex black-box model locally with an easily interpretable linear model. This project relies on the distinct methodologies of both approaches to provide comprehensive, multi-angle clinical explanations that can be cross-referenced for validity.

3. Methodology

3.1 Dataset Specification

The standard UCI Heart Disease dataset (Cleveland database) was utilised. It comprises detailed clinical metrics from 303 unique patients. The 13 clinical features provide rich, multi-dimensional detail required for learning cardiovascular-characteristic patterns, encompassing demographic details (age, sex), symptomatic reports (chest pain type, exercise-induced angina), and physiological measurements (cholesterol, resting blood pressure, ST depression).

Dataset Attribute	Value Specification
Dataset Name	UCI Heart Disease Dataset (Cleveland)
Total Instances	303 patient records
Benign (No Disease) Samples	138 records (45.5% of dataset)
Malignant (Heart Disease) Samples	165 records (54.5% of dataset)
Class Imbalance Ratio	Malignant : Benign ≈ 1.2 : 1
Train / Test Data Split	80% train (242 samples) / 20% test (61 samples) — stratified

Table 1: UCI Heart Disease Dataset Statistics

3.2 Data Preprocessing

A rigorous and unified preprocessing pipeline was applied prior to both classifier training and XAI model initialisation to guarantee stability:

• Normalisation (Feature Scaling): Standard normalisation using Scikit-Learn's `StandardScaler` was applied to ensure all continuous variables possess zero mean and unit variance. This step is a strict requirement to prevent gradient explosion in XGBoost and to ensure fair, unskewed distance calculations during LIME's neighborhood perturbation.

• Train/Test Split: An 80/20 stratified partition was executed, yielding 242 training records and 61 testing records. The stratification ensures that the ratio of benign to malignant cases is identical across both sets. The test split was held completely unseen during training to ensure a fair, unbiased evaluation of both predictive accuracy and explainer fidelity.

3.3 Phase 1 — Baseline XGBoost Classifier Training

An XGBoost classifier was trained to perform the core binary risk classification. The gradient boosting framework operates by iteratively adding weak decision trees to correct the residual errors of preceding trees. The architecture hyper-parameters were systematically tuned to achieve an optimal balance between maximal diagnostic accuracy and computational efficiency.

Hyperparameter	Configured Value
Base Architecture	XGBoost Classifier (`XGBClassifier`)
Number of Estimators (Trees)	100
Learning Rate (eta)	0.1
Max Tree Depth	5
Loss Objective Function	Binary Logarithmic Loss (`binary:logistic`)

Table 2: XGBoost Baseline Classifier Configuration

3.4 Phase 2 & 3 — SHAP and LIME Integration

• SHAP Implementation: SHAP was integrated using the highly optimised `TreeExplainer`, designed specifically for tree-based ensemble models. The explainer computes exact Shapley values, mathematically representing the exact marginal contribution of each clinical feature (e.g., how much + or - percentage risk did 'Cholesterol' add) to the final prediction probability.
• LIME Implementation: LIME was integrated using the `LimeTabularExplainer`. When a prediction is requested, LIME generates a massive neighborhood of synthetic, slightly altered patient profiles around the input data. It predicts outcomes for these synthetic profiles using the black-box XGBoost model, and then fits a highly interpretable, proximity-weighted Ridge regression model to explain the local decision boundary.

3.5 Phase 4 — Consistency Analysis & API Dashboarding

A programmatic, mathematical heuristic was designed to compare the outputs of the two explainers in real-time:

$$\text{Consistency Score} = (|\text{Top 5 SHAP Features} \cap \text{Top 5 LIME Features}| / 5) \times 100$$

This score quantifies clinical reliability. The raw predictions, probabilities, SHAP arrays, LIME rules, and Consistency Scores were wrapped into asynchronous REST endpoints using the FastAPI framework, allowing them to be seamlessly consumed by the React.js frontend interface.

4. System Architecture and Workflow

The complete project pipeline comprises a strictly sequential architecture, where data flows from the raw CSV ingress, through statistical normalisation, into the primary predictive engine, and subsequently branches out to the dual XAI analytical engines. The system's design heavily prioritises clinical reproducibility, strict separation of concerns (backend computation vs. frontend rendering), and high modularity.




Figure 1: Complete XAI System Architecture Pipeline

5. Experimental Results

5.1 Baseline Classifier Performance

The XGBoost predictive model, trained on the normalised dataset, achieved the following robust performance metrics when evaluated strictly against the completely unseen held-out test set of 61 patient records:

Evaluation Metric	Recorded Value
Overall Accuracy	80.33%
Precision (Macro Average)	81.00%
Recall (Macro Average)	81.00%
F1-Score (Macro Average)	80.00%

Table 3: Predictive Performance on the 61-Record Test Set

Key analytical observations from the model evaluation:
• The model achieves a highly stable 80.33% accuracy, effectively identifying the non-linear, complex cardiovascular patterns present in the clinical data.
• The tightly balanced Precision (81%) and Recall (81%) metrics indicate that the model possesses highly reliable detection rates for malignant cases without suffering from an inflated false-positive rate.

5.2 XAI Consistency Analysis

During live clinical testing through the application, the mathematical consistency between SHAP and LIME outputs was continuously logged and monitored. For predictions exhibiting high statistical confidence (probability scores > 85%), both SHAP and LIME consistently yielded high Consistency Scores (routinely > 80%). Critically, both frameworks predominantly agreed on identifying key clinical cardiovascular indicators such as 'ca' (number of major vessels affected), 'cp' (chest pain classification type), and 'oldpeak' (ST depression induced by exercise) as the primary driving factors behind the prediction. This algorithmic consensus validates that the XGBoost model has successfully learned clinically sound medical patterns rather than arbitrary dataset noise.

5.3 Full-Stack Web Application Deployment

A production-ready, interactive React.js application was engineered to serve as the clinician-facing interface, validated locally with the asynchronous FastAPI backend. The interface incorporates premium, glassmorphic UI elements and dynamic data visualisations using Recharts.



Figure 2: The React.js XAI Medical Dashboard Interface

6. Novelty and Technical Contributions

The primary technical significance and novelty of this clinical AI engineering work lies in four highly interconnected structural contributions:

1. Application of XAI over Black-Box for True Clinical Trust:

While standard models like Random Forests and XGBoost have been heavily explored for raw disease prediction, they suffer from severe opacity. By embedding SHAP and LIME deeply into the prediction pipeline, this framework provides a principled, generative, and mathematical basis for every decision, shifting the paradigm from 'blind prediction' to 'justified diagnosis'.

2. Consistency-Oriented Clinical Evaluation:

The vast majority of existing ML classification literature optimises for and exclusively reports raw accuracy as the sole performance metric. This project explicitly rejects that limitation, instead introducing and targeting 'Explainability Fidelity'—measured via the custom Consistency Score—as the primary clinical objective for assessing model deployment readiness.

3. Resource-Efficient, Low-Latency Architecture:

The proposed technology stack (XGBoost, FastAPI, React) was deliberately selected and designed for extremely fast, standard CPU/GPU execution without requiring massive server-cluster institutional resources. Real-time inference and explanation generation occur in milliseconds.

4. End-to-End Reproducible Engineering Pipeline:

The complete lifecycle—from raw CSV file ingestion, strict statistical preprocessing, XGBoost training, dual-explainer integration, all the way to responsive React web deployment—is fully implemented, highly documented, and cleanly modular.

7. Conclusion and Future Work

7.1 Conclusion

This project successfully presented and deployed a complete, end-to-end pipeline for XAI-based risk prediction specifically applied to complex heart disease clinical data. All stated technical and diagnostic objectives were achieved. A highly robust XGBoost model was trained, securing a strong accuracy of 80.33% alongside remarkably stable gradient convergence. Both SHAP and LIME were flawlessly integrated into the backend architecture to dissect and explain individual predictions on demand.

Critically, evaluating these dual predictions using the newly introduced Consistency Score yielded a tangible, quantifiable metric for establishing AI trust. The dynamic visual explanations generated by the React.js dashboard represent the most clinically vital outcome of the project, corresponding to a direct, actionable reduction in the restrictive "black box" AI barrier.

The central, concluding finding is that highly complex, highly accurate machine learning architectures—when intelligently paired with rigorous XAI frameworks—can generate critical health risk predictions with more than sufficient interpretability to serve as an indispensable, trustworthy support tool for modern medical practitioners.

7.2 Limitations

• Data Volume Constraints: The model was trained on a relatively small historical dataset (303 instances). Extended training on massive, modern, multi-hospital EHR databases would definitively yield higher base accuracy and better generalisation.
• Data Dimensionality: The input format relies strictly on tabular clinical metrics. The model currently lacks the capability to ingest unstructured data forms, such as raw, textual physician diagnostic notes or visual ECG waveform signals.
• Clinical Validation Boundary: Formal clinical validation by a board of certified cardiologists was not performed; consequently, the results represent highly promising research-level software engineering rather than immediately deployable clinical-grade medical diagnostic hardware.

7.3 Future Work

• Extended Generalisation: Expand the training pipeline to incorporate much larger, multi-centric cardiovascular datasets (e.g., MIMIC-III integrations) for higher-fidelity predictions and demographic diversity.
• Multi-Modal AI Architectures: Implement multi-modal deep learning systems capable of ingesting and correlating raw 2D ECG image data seamlessly alongside standard tabular clinical metrics.
• Cloud Deployment: Containerise the application using Docker and deploy the complete system architecture onto scalable cloud infrastructure (such as AWS, Google Cloud, or Render) for public accessibility, broader load testing, and clinical beta evaluations.
• Formal Clinical Study: Conduct a rigorous clinical validation study in partnership with cardiologists to gather annotated, professional feedback regarding the actual, on-the-ground utility of the SHAP and LIME visual explanations.

References

[1] Chen, T., & Guestrin, C. (2016). XGBoost: A scalable tree boosting system. Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 785-794.

[2] Lundberg, S. M., & Lee, S. I. (2017). A unified approach to interpreting model predictions. Advances in Neural Information Processing Systems, 30.

[3] Ribeiro, M. T., Singh, S., & Guestrin, C. (2016). "Why should I trust you?" Explaining the predictions of any classifier. Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 1135-1144.

[4] Detrano, R., Janosi, A., Steinbrunn, W., Pfisterer, M., Schmid, J. J., Sandhu, S., ... & Froelicher, V. (1989). International application of a new probability algorithm for the diagnosis of coronary artery disease. The American Journal of Cardiology, 64(4), 304-310.

[5] Amann, J., Blasimme, A., Vayena, E., Frey, D., & Madai, V. I. (2020). Explainability for artificial intelligence in healthcare: a multidisciplinary perspective. BMC Medical Informatics and Decision Making, 20(1), 1-9.

[6] Ghassemi, M., Oakden-Rayner, L., & Beam, A. L. (2021). The false hope of current approaches to explainable artificial intelligence in health care. The Lancet Digital Health, 3(11), e745-e750.

[7] Krittanawong, C., Zhang, H., Wang, Z., Aydar, M., & Kitai, T. (2020). Artificial intelligence in precision cardiovascular medicine. Journal of the American College of Cardiology, 117(21), 2657-2664.

[8] Guidotti, M., Monreale, A., Ruggieri, S., Turini, F., Giannotti, F., & Pedreschi, D. (2018). A survey of methods for explaining black box models. ACM computing surveys (CSUR), 51(5), 1-42.

[9] Molnar, C. (2020). Interpretable Machine Learning: A Guide for Making Black Box Models Explainable. Lulu.com.

[10] Ali, M. M., Paul, B. K., Abo, K., et al. (2021). Heart disease prediction using machine learning algorithms. Microprocessors and Microsystems, 81, 103859.

[11] Sutton, R. T., Pincock, D., Baumgart, D. C., Sadowski, D. C., Fedorak, R. N., & Kroeker, K. I. (2020). An overview of clinical decision support systems: benefits, risks, and strategies for success. NPJ digital medicine, 3(1), 1-10.

[12] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., ... & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python. Journal of Machine Learning Research, 12, 2825-2830.