

Exercise 3: Using Different Appenders

Step 1: pom.xml

```
<dependencies>

    <dependency>
        <groupId>org.slf4j</groupId>
        <artifactId>slf4j-api</artifactId>
        <version>1.7.30</version>
    </dependency>

    <dependency>
        <groupId>ch.qos.logback</groupId>
        <artifactId>logback-classic</artifactId>
        <version>1.2.3</version>
    </dependency>

</dependencies>
```

Step 2: Create **logback.xml**

Create the file inside:
src/main/resources/logback.xml

XML

```
<configuration>

    <!-- Console Appender -->
    <appender name="console"
        class="ch.qos.logback.core.ConsoleAppender">

        <encoder>
            <pattern>
                %d{HH:mm:ss.SSS} [%thread] %-5level %logger{36} - %msg%n
            </pattern>
        </encoder>

    </appender>

    <!-- File Appender -->
    <appender name="file"
        class="ch.qos.logback.core.FileAppender">
```

```

<file>app.log</file>

<encoder>
  <pattern>
    %d{HH:mm:ss.SSS} [%thread] %-5level %logger{36} - %msg%n
  </pattern>
</encoder>

</appender>

<!-- Root Logger -->
<root level="debug">

  <appender-ref ref="console"/>

  <appender-ref ref="file"/>

</root>

</configuration>

```

Step 3: Java Program

```

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class LoggingAppenderExample {

  private static final Logger logger =
    LoggerFactory.getLogger(LoggingAppenderExample.class);

  public static void main(String[] args) {

    logger.trace("Trace Message");

    logger.debug("Debug Message");

    logger.info("Information Message");

    logger.warn("Warning Message");

```

```
        logger.error("Error Message");  
    }  
}
```

Output

INFO Employee Name : Kowshik

INFO Employee Age : 21

INFO Employee Salary : 45000.5

INFO Employee Kowshik is 21 years old and earns 45000.5