

IOT BASED AIR POLLUTION MONITORING SYSTEM USING GSM MODULE

Project report

Submitted in partial fulfilment of requirements to

JAWAHARLAL NEHURU TECHNOLOGICAL UNIVERSITY, KAKINADA

For the Award of the Degree of

BACHELOR OF TECHNOLOGY

IN

ELECTRONICS AND COMMUNICATION ENGINEERING

Submitted By

K.VENKATA RAMANA (22AP1A0410)

M.GEETHA SRI (22AP1A0414)

I.RAMU (22AP1A0408)

P.SATISH (22AP1A0421)

Under the Esteemed Guidance Of

Mr P.S.D Anvesh

Associate professor, ECE



2022-2026

DEPARTMENT OF ELECTRONICS & COMMUNICATION ENGINEERING

BHIMAVARAM INSTITUTE OF ENGINEERING & TECHNOLOGY

(Approved by A.I.C.T.E & Affiliated to JNTU. KAKINADA)

Pennada, Bhimavaram-534242, WEST GODAVARI Dt., A.P

BHIMAVARAM INSTITUTE OF ENGINEERING AND TECHNOLOGY

(Approved by A.I.C.T.E & Affiliated to JNTU. KAKINADA)

Pennada, Bhimavaram-534242, WEST GODAVARI Dt., A.P



CERTIFICATE

This is to certify that this project work entitled. **“IOT BASED AIR POLLUTION MONITORING SYSTEM USING GSM MODULE ”** That is being Submitted in partial fulfilment For the Award of the degree of BACHELOR OF TECHNOLOGY IN ELECTRONICS AND COMMUNICATION ENGINEERING to the department of Electronics & Communication Engineering, Bhimavaram Institute of Engineering And Technology Pennada is a record of bonafide work carried out by him under our guidance and supervision.

Submitted By

K.VENKATA RAMANA	(22AP1A0410)
M.GEETHA SRI	(22AP1A0414)
I.RAMU	(22AP1A0408)
P.SATHISH	(22AP1A0421)

Project Guide
Mr.P.S.D.Anvesh
Associate professor

Head of the Department
Mr.A.B.S.R.Manohar M.Tech (Ph.D.)
Head of the Department, ECE

INTERNAL EXAMINER

EXTERNAL EXAMINER

DECLARATION

We here declare that the entire work embodied in this dissertation entitled“ **IOT BASED AIR POLLUTION MONITORING SYSTEM USING GSM MODULE**” is genuine project work has been independently caried out by us in Bachelor of Degree ELECTRONICS AND COMMUNICATION ENGINEERING OF JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY, KAKINADA. As per my knowledge, no part of this work has been submitted for any degree in any institution, university, and organization previously.

DATE:

PLACE:

Submitted by

K.VENKATA RAMANA (22AP1A0410)

M.GEETHA SRI (22AP1A0414)

I.RAMU (22AP1A0408)

P.SATHISH (22AP1A0421)

ACKNOWLEDGEMENT

The successful completion of any task would be incomplete without greeting those who made it possible and whose guidance and encouragement made the effort taken a success. I extend my heartfelt gratitude to the almighty for giving me strength in proceeding with this project report titled **“IOT BASED AIR POLLUTION MONITORING SYSTEM USING GSM MODULE”**.

The dissertation presented here is the work accomplished under the enviable and scholarly guidance of P .S. D ANVESH Associate professor. I Would like to express my deep Sense of gratitude A.B.S.R.MANO HAR M.Tech (Ph.D) Associate professor and Head of Electronics and Communication Engineering Department, Bhimavaram Institute Of Engineering And Technology for his timely and inspiring guidance in presenting this project report.

I express my heartfelt thanks to Dr.K.SURESH, M. Tech, Ph.D. Principal , of Bhimavaram Institute of Engineering and Technology, Pennada for giving me this opportunity for the successful completion of my degree.

I would be quite lost without the guidance of the B-Tech teaching staff of Bhimavaram Institute of Engineering and Technology.

I also thank other teaching and non-teaching staff for their assistance and help. I owe my special thanks to the management of our college for providing necessary arrangements to carry out this project.

Above all, thank my parents. I feel deep sense of gratitude for my family who formed part of my vision .Finally, I thank one and all that have contributed directly or indirectly thesis.

- | | |
|----------------------------|---------------------|
| 1. K.VENKATA RAMANA | (22AP1A0410) |
| 2. M.GEETHA SRI | (22AP1A0414) |
| 3. I. RAMU | (22AP1A0408) |
| 4. P.SATHISH | (22AP1A0421) |

Contents

S.No	Title	Page no
1	CHAPTER -I INTRODUCTION 1.1 Introduction to Air Pollution Monitoring 1.2 Introduction to Iot in Environmental Monitoring 1.3 GSM Module in Communication 1.4 Overview of Proposed System Block Diagram	1-5
2	CHAPTER -II EXISTING SYSTEM 2.1 Introduction to Existing System 2.2 Wi-Fi Connectivity 2.3 Temperature and Humidity Sensor 2.4 Gas Detection Sensor 2.5 PM-2.5 Sensor 2.6 LCD Display Unit 2.7 Data Transmission through Wi-fi 2.8 Cloud Monitoring System 2.9 Absence GSM Module	6-11
3	CHAPTER -III PROPOSED SYSTEM 3.1 Introduction to Proposed System 3.2 GSM Communication Module 3.3 Sensor Integration 3.4 Microcontroller Unit 3.5 LCD Display System 3.6 Real time Monitoring 3.7 Alert System using GSM 3.8 Power Supply System 3.9 Advantages of Proposed System	12-17

4	CHAPTER -IV HARDWARE COMPONENTS 4.1 DHT-11 Sensor 4.2 MQ-9 Gas Sensor 4.3 PM-2.5 Sensor 4.4 Arduino UNO 4.5 SIM 800 GSM Module 4.6 LCD Display 4.7 Buzzer	18-22
5	CHAPTER -V SOFTWARE USED 5.1 Arduino IDE Installation 5.2 Open or Write Sketch 5.3 Select the Arduino Board 5.4 Select the Port 5.5 Upload the sketch to Arudino 5.6 Program Structure	23-29
6	CHAPTER -VI METHODOLOGY 6.1 System Architecture 6.2 Hardware Components 6.3 Software Implementation 6.4 Data Collection & Processing 6.5 Communication Mechanism 6.6 System Testing and Validation 6.7 Future Enhancement	30-34
7	CHAPTER -VII LETERATURE SURVEY	35-41

8	CHAPTER - VIII RESULTS	42-44
9	CHAPTER - IX ADVANTAGES & DISADVANTAGES	45-54
10	CHAPTER - X CONCLUSION & FUTURE SCOPE	55-59

List of Figures

S. No.	Fig. Name	Page No.
2.1	Diagram of the existing system.	9
3.1	Diagram of Proposed System	14
4.1	DHT-11 Sensor	19
4.2	MQ-9 Gas Sensor	19
4.3	PM-2.5 Sensor	20
4.4	Arduino UNO	20
4.5	SIM 800 GSM Module	21
4.6	LCD Display	21
5.1	Installation Button For Arduino	23
5.2	Openinig New Sketch	24
5.3	Selecting the Board	24
5.4	Selecting the Port	25
5.5	Uploading the Sketch	25
6.1	Air Quality Measurement	43
6.2	Air Quality Measurement when bad causes Unhealthy	43
6.3	Showing Natural Results	44
6.4	Outcomes	44

List of Tables

S. No.	Table Name	Page No.
7.1	LITERATURE SURVEY	35-41

ABSTRACT

Air pollution has emerged as one of the most critical environmental and public health crises of the 21st century. The World Health Organization (WHO) estimates that millions of premature deaths occur annually due to exposure to poor air quality, with pollutants like carbon monoxide (CO), fine particulate matter (PM_{2.5}), and volatile organic compounds being primary contributors. Traditional methods of air quality monitoring rely on expensive, stationary reference stations operated by government agencies. While accurate, these stations are sparsely distributed, providing macro-level data that fails to capture the hyper-local variations in pollution levels that directly impact individuals in their homes, workplaces, and communities. This spatial and temporal data gap necessitates the development of a cost-effective, scalable, and real-time solution for air quality monitoring.

This project addresses this critical need by designing and implementing a comprehensive, IoT-based Air Pollution Monitoring System. The primary objective is to create a compact, low-power, and networked device capable of continuously measuring a core set of harmful environmental parameters. The system is engineered to monitor four key air quality indicators: Carbon Monoxide (CO) concentration using the MQ-9 gas sensor, fine particulate matter (PM_{2.5}) levels using a dedicated laser particle sensor, ambient temperature using the LM35 precision integrated-circuit sensor, and relative humidity using a DHT22 sensor. The selection of these parameters is strategic; CO is a toxic, odorless gas primarily from incomplete combustion, PM_{2.5} consists of microscopic particles that can penetrate deep into the lungs and bloodstream, and temperature and humidity act as crucial contextual data that influence both pollutant behavior and human comfort.

CHAPTER-1

INTRODUCTION

The rapid pace of industrialization and urbanization has led to a significant deterioration in global air quality, posing a severe threat to public health and the environment. Traditional air quality monitoring stations are often bulky, expensive, and limited in number, making it difficult to capture localized pollution data in real-time across diverse geographical areas. To address this gap, there is a growing need for low-cost, portable, and efficient systems that can provide granular data on various pollutants. An IoT-based approach offers a transformative solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively.

The emergence of the Internet of Things (IoT) has revolutionized the way we interact with our environment by bridging the gap between physical hardware and digital data analysis. In the context of air pollution, IoT allows for a network of interconnected devices to communicate autonomously, providing a high-resolution map of air quality levels in a specific region. Unlike legacy systems that require manual data collection, an IoT-enabled device can process information locally and upload it to the cloud or a remote server instantaneously. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

1.1 Introduction to Air Pollution Monitoring

1.1.1 Definition of Air Pollution

Air pollution is the presence of harmful substances such as gases, dust, and smoke in the atmosphere. These pollutants can come from natural as well as human-made sources. It affects the quality of air and makes it unsafe for breathing. Common pollutants include carbon monoxide, sulfur dioxide, and nitrogen oxides. These substances can remain in the air for a long time. Continuous exposure to polluted air can lead to serious health problems.

Air pollution is mainly caused by human activities such as industrial emissions and vehicle exhaust. Burning of fossil fuels releases harmful gases into the environment. Construction activities and deforestation also contribute to increasing pollution levels. In addition, agricultural practices and waste burning produce toxic substances. Rapid urbanization has further increased pollution in cities. These factors together degrade the quality of air.

1.1.2 Causes of Air Pollution

Air pollution is mainly caused by human activities such as industrial emissions and vehicle exhaust. Burning of fossil fuels releases harmful gases into the environment. Construction activities and deforestation also contribute to increasing pollution levels. In addition, agricultural practices and waste burning produce toxic substances. Rapid urbanization has further increased pollution in cities. These factors together degrade the quality of air.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

1.1.3 Need for Monitoring

Monitoring air pollution is necessary to understand the level of harmful substances in the air. It helps in identifying pollution sources and controlling them effectively. Regular monitoring ensures that air quality standards are maintained. It also provides useful data for research and environmental protection. Governments and organizations use this data for decision-making. Monitoring helps in protecting both human health and the environment.

solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively.

1.2 Introduction to IoT in Environmental Monitoring

1.2.1 Concept of IoT

The Internet of Things (IoT) refers to the connection of physical devices through the internet. These devices collect and exchange data without human intervention. IoT systems use sensors, software, and communication technologies. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

IoT allows for a network of interconnected devices to communicate autonomously, providing a high-resolution map of air quality levels in a specific region. Unlike legacy systems that require manual data collection, an IoT-enabled device can process information locally and upload it to the cloud or a remote server instantaneously. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires.

1.2.2 IoT Applications

IoT is used in many fields such as healthcare, agriculture, and smart cities. In environmental monitoring, it helps in tracking air, water, and soil conditions. Sensors are used to collect real-time data from different locations. This data can be accessed from anywhere using the internet. IoT improves efficiency and reduces manual effort. It plays a key role in developing smart systems.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

1.2.3 Benefits in Monitoring

IoT-based monitoring systems provide accurate and real-time data. They are cost-effective compared to traditional monitoring systems. These systems reduce human involvement and increase reliability. Data can be stored and analyzed for better understanding. Remote access makes monitoring more convenient. IoT helps in quick response to environmental changes.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

1.3 GSM Module in Communication

1.3.1 Definition of GSM

GSM stands for Global System for Mobile Communication. It is a standard used for mobile communication worldwide. GSM technology allows devices to communicate using cellular networks. It supports voice calls, messages, and data transmission. GSM modules are commonly used in embedded systems. They provide reliable communication over long distances.

It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

1.3.2 Working Principle

The GSM module works by connecting to a mobile network using a SIM card. It sends and receives data through signals provided by network towers. The module communicates with the microcontroller using serial communication. Commands are used to control its operations. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

IoT allows for a network of interconnected devices to communicate autonomously, providing a high-resolution map of air quality levels in a specific region. Unlike legacy systems that require manual data collection, an IoT-enabled device can process information locally and upload it to the cloud or a remote server instantaneously. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires.

1.4 Overview of the Proposed System Block Diagram:

1.4.1 System Components

The system consists of sensors, a microcontroller, and a GSM module. Sensors are used to detect pollutants present in the air. The microcontroller processes the data collected from sensors. The GSM module is used for communication purposes. All components work together to form a complete system. Each part plays an important role in the operation.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in

smart cities. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.




Fig ; Proposed System Block Diagram

1.4.2 Working Process

The system works by continuously monitoring air quality using sensors. The collected data is sent to the microcontroller for processing. After processing, the information is transmitted through the GSM module. Users receive the data in the form of messages or alerts. The system operates automatically without manual intervention. It ensures continuous and real-time monitoring.

CHAPTER-2

EXISTING SYSTEM

The existing system for air pollution monitoring is designed using built-in Wi-Fi for internet connectivity. It uses sensors like LM35 to measure temperature and humidity sensors to detect moisture levels in the air. Gas detection is performed using MQ-9 sensors, which identify harmful gases such as carbon monoxide. Additionally, PM2.5 sensors are used to measure fine particulate matter present in the atmosphere. The collected data is displayed locally on a 16×2 LCD screen for easy viewing. The system transmits data through a Wi-Fi network, enabling real-time monitoring over the internet. It supports cloud-based platforms for storing and analyzing environmental data. However, this system does not use a GSM module for communication. It completely depends on Wi-Fi availability for data transmission. If Wi-Fi is not available, the system cannot send or update data remotely. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies.

2.1 Introduction to Existing System

- Overview of System
- Purpose of Monitoring

The existing system for air pollution monitoring is designed using modern IoT technologies. It mainly focuses on measuring environmental parameters such as temperature, humidity, and air quality. The system uses different sensors to collect real-time data from the surroundings. This data is useful for analyzing pollution levels and environmental conditions. The system is widely used in smart monitoring applications. It provides a basic understanding of air quality in different areas.

The purpose of this system is to provide continuous monitoring of environmental conditions. It helps users to understand the level of pollution in real time. The system is designed to be simple and efficient for data collection. It also supports remote monitoring using internet connectivity. However, its performance depends on network availability. This makes it suitable for areas with stable internet access.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

2.2 Wi-Fi Connectivity

- Built-in Wi-Fi
- Internet Communication

The existing system uses built-in Wi-Fi for internet connectivity. This allows the system to connect to online platforms and transmit data. Wi-Fi helps in sending real-time information to users through cloud services. It eliminates the need for wired communication. The system can easily connect to local networks. This improves flexibility and ease of use.

However, Wi-Fi connectivity requires a stable internet connection. If the network is weak or unavailable, the system cannot transmit data. This limits its performance in remote or rural areas. Continuous monitoring becomes difficult without internet access. Network interruptions can affect data accuracy. Hence, dependency on Wi-Fi is a major limitation.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

2.3 Temperature and Humidity Sensors

- LM35 Sensor
- Humidity Detection

The system uses LM35 sensors to measure temperature accurately. It also includes humidity sensors to detect moisture levels in the air. These sensors provide important environmental data. They are easy to use and provide reliable outputs. The collected data helps in understanding weather conditions. This improves overall monitoring efficiency.

Temperature and humidity are important factors in air quality analysis. These sensors continuously monitor environmental changes. The data is processed and displayed for user reference. It helps in identifying abnormal conditions. However, these sensors alone cannot detect harmful gases. Additional sensors are required for complete monitoring.

solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively.

2.4 Gas Detection Sensors

- MQ-9 Sensor
- Harmful Gas Detection

The existing system uses MQ-9 sensors to detect harmful gases in the air. These sensors can identify gases like carbon monoxide and other pollutants. They play an important role in air

quality monitoring. The sensors convert gas concentration into electrical signals. This data is then processed by the system. It helps in detecting pollution levels effectively.

Gas detection is essential for identifying health risks caused by pollution. The MQ-9 sensor provides reliable readings under normal conditions. It helps in maintaining environmental safety. However, sensor accuracy may vary due to environmental factors. Regular calibration is required for better performance. This is one limitation of the system. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

2.5 PM2.5 Sensor Usage

- Fine Particle Detection
- Air Quality Measurement

The system includes PM2.5 sensors to measure fine particulate matter in the air. These particles are very small and harmful to human health. The sensor detects dust and smoke particles present in the environment. It provides real-time data on air pollution levels. This helps in understanding air quality more accurately.

PM2.5 monitoring is important for health awareness and safety. High levels of fine particles can cause respiratory problems. The sensor helps in identifying such conditions early. However, it requires proper maintenance for accurate readings. Environmental conditions can affect sensor performance. This adds to system limitations.

It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.




Fig 2.1 diagram of the existing system.

2.6 LCD Display Unit

- 16×2 LCD
- Data Visualization

The system uses a 16×2 LCD display to show real-time data. It displays values such as temperature, humidity, and pollution levels. This allows users to view information directly from the system. The LCD is simple and easy to use. It provides clear and readable output. This improves user interaction with the system.

The display unit helps in monitoring data without using external devices. It is useful in local monitoring applications. However, it has limited display capacity. It cannot show detailed data or graphical information. Users need additional platforms for advanced analysis. This limits its functionality.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project

focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

2.7 Data Transmission through Wi-Fi

- Real-time Data Transfer
- Remote Access

The system transmits collected data through Wi-Fi networks. This enables real-time data sharing with users. The information can be accessed remotely using cloud platforms. It improves monitoring efficiency and convenience. Users can track pollution levels from anywhere. This enhances system usability.

However, data transmission depends on network stability. Poor internet connection can delay or stop data transfer. This affects real-time monitoring capabilities. In remote areas, Wi-Fi may not be available. This reduces system effectiveness. Network dependency is a major drawback.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

solution by enabling the continuous collection and transmission of environmental parameters via smart sensors. By utilizing modern microcontrollers and wireless modules, these systems allow for proactive environmental management rather than reactive observation. This project focuses on creating a reliable monitoring node that can detect harmful gases and particulate matter effectively.

2.8 Cloud Monitoring System

- Data Storage
- Online Analysis

The existing system supports cloud monitoring for data storage and analysis. The collected data is uploaded to cloud platforms. This allows users to access historical and real-time data. Cloud systems provide better data management. They help in analyzing environmental trends. This improves decision-making.

Cloud monitoring enhances system functionality and accessibility. It allows multiple users to access the data. However, it requires internet connectivity at all times. Data security can also be a concern. Proper protection measures are needed. This adds complexity to the system.

This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. IoT allows for a network of interconnected devices to communicate autonomously, providing a high-resolution map of air quality levels in a specific region.

Unlike legacy systems that require manual data collection, an IoT-enabled device can process information locally and upload it to the cloud or a remote server instantaneously. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

2.9 Absence of GSM Module

- No GSM Communication
- Limited Connectivity

The existing system does not use a GSM module for communication. It relies completely on Wi-Fi for data transmission. This limits its ability to send data through mobile networks. GSM provides wider coverage compared to Wi-Fi. Without GSM, the system lacks flexibility.

This limitation affects system performance in remote locations. GSM could provide better connectivity where Wi-Fi is unavailable. The absence of GSM reduces communication reliability. It also limits real-time alert features. This is a major drawback of the existing system. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities. This real-time capability is crucial for identifying sudden spikes in pollution caused by industrial leaks, traffic congestion, or accidental fires. Furthermore, the integration of IoT facilitates long-term data logging, which is essential for researchers and policymakers to identify trends and develop effective mitigation strategies. The system's ability to operate with minimal human intervention makes it an ideal candidate for widespread deployment in smart cities.

CHAPTER-3

PROPOSED SYSTEM

The proposed system is designed to monitor air pollution using IoT technology integrated with a GSM module. It uses sensors to detect environmental parameters such as temperature, humidity, and harmful gases. The system collects real-time data and processes it using a microcontroller. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display. It also sends alerts to users when pollution levels exceed limits. GSM communication ensures reliable data transmission through mobile networks. The system does not depend on Wi-Fi connectivity. It supports continuous monitoring without interruption. The proposed system improves environmental awareness. It helps in taking preventive actions against pollution. Overall, it provides an efficient solution for air quality monitoring.

3.1 Introduction to Proposed System

- Overview of GSM-Based System
- Purpose of Improvement

The proposed system is designed to monitor air pollution using IoT technology integrated with a GSM module. It collects environmental data using sensors and processes it through a microcontroller unit. The system focuses on providing accurate and continuous monitoring of air quality. It improves communication by using mobile networks instead of Wi-Fi connectivity. This makes the system more flexible and reliable in different locations. The design ensures efficient performance in both urban and rural areas.

The main purpose of this system is to overcome the limitations of Wi-Fi-based monitoring systems. It ensures data transmission even in areas without internet access. The system provides real-time updates and alerts to users through GSM communication. It enhances monitoring efficiency and system reliability. The system is easy to implement and cost-effective. This makes it suitable for various environmental monitoring applications.

The system collects real-time data and processes it using a microcontroller. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and

precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

3.2 GSM Communication Module

- GSM Technology
- Data Transmission

The GSM module is an important component used for communication in the proposed system. It allows the system to send and receive data using cellular networks. The module operates with the help of a SIM card to connect to mobile towers. It enables long-distance communication without the need for internet connectivity. The GSM module supports sending SMS alerts to users. This improves the communication capability of the system.

GSM communication provides better coverage compared to Wi-Fi networks. It is especially useful in remote areas where internet access is limited. The system can transmit data continuously without interruption. It ensures reliable and secure data transfer. GSM also supports real-time alert notifications. This makes the system more effective and dependable.

The system collects real-time data and processes it using a microcontroller. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement.

It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas.

3.3 Sensor Integration

- Gas Sensors
- Environmental Sensors

The proposed system uses multiple sensors to detect different environmental parameters. Gas sensors are used to identify harmful gases present in the air. Temperature and humidity sensors are included to measure atmospheric conditions. These sensors collect real-time data

from the environment. The collected data is sent to the microcontroller for processing. This ensures accurate and continuous monitoring of air quality.

Sensor integration improves the functionality and performance of the system. It allows monitoring of multiple parameters at the same time. The sensors provide reliable and precise data for analysis. The system collects real-time data and processes it using a microcontroller. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments.

It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display.




Fig 3.1 diagram of the proposed system.

3.4 Microcontroller Unit

- Data Processing
- System Control

The microcontroller acts as the main processing unit of the system. It receives input data

from sensors and processes it accordingly. The microcontroller controls all operations of the system. It ensures proper coordination between sensors and communication modules. The processed data is sent to the GSM module for transmission. This improves system performance and efficiency. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

The microcontroller plays a key role in decision-making processes. It helps in generating alerts when pollution levels exceed safe limits. The system operates automatically with minimal human intervention. It ensures fast and accurate data processing. The microcontroller improves system reliability. It is an essential part of the proposed system.

This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display.

3.5 LCD Display System

- Local Display
- Data Visualization

The system includes a 16×2 LCD display to show real-time data. It displays values such as temperature, humidity, and gas levels. This allows users to monitor environmental conditions directly. The LCD display is simple and easy to use. It provides clear and readable output for users. This improves interaction with the system.

The LCD display supports local monitoring without external devices. It provides instant updates about air quality conditions. However, it is mainly used for basic data visualization. It does not support advanced graphical representation. The display unit improves usability of the system. It is an important component in the design.

It also sends alerts to users when pollution levels exceed limits. GSM communication ensures reliable data transmission through mobile networks. The system does not depend on Wi-Fi connectivity. It supports continuous monitoring without interruption. The proposed system improves environmental awareness. It helps in taking preventive actions against pollution. Overall This data is then transmitted to users through GSM communication.

The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas.

3.6 Real-Time Monitoring

- Continuous Data Collection
- Instant Updates

The proposed system continuously monitors environmental conditions in real time. Sensors collect data without interruption from the surroundings. The system processes and updates this data regularly. This ensures accurate monitoring of pollution levels. Real-time monitoring improves system efficiency and performance. It provides up-to-date information about air quality.

Instant updates help users take quick preventive actions. The system sends alerts when pollution exceeds safe levels. This improves safety and awareness among users. Continuous monitoring ensures reliable data collection. It enhances system effectiveness. It makes the system more responsive and efficient. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas.

3.7 Alert System using GSM

- SMS Alerts
- Emergency Notification

The GSM module is used to send alerts to users through SMS notifications. When pollution levels exceed a predefined limit, alerts are generated. These alerts are sent directly to user mobile phones. This ensures quick communication and response. It improves safety measures in the system. The alert system works efficiently in real time.

The alert system helps users take immediate preventive actions. It is useful in industrial and residential areas. It provides early warnings about harmful environmental conditions. GSM-based alerts are reliable and fast. It improves awareness and protection. This enhances the effectiveness of the system.

The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display. It also sends alerts to users when pollution levels exceed limits. GSM communication ensures reliable data transmission through mobile networks. The system does not depend on Wi-Fi connectivity.

3.8 Power Supply System

- Stable Power Source
- System Efficiency

The system requires a stable power supply for proper functioning. It uses regulated power sources to ensure continuous operation. Power is required for sensors, microcontroller, and GSM module. A stable power supply improves system reliability. It ensures uninterrupted monitoring of air quality. This is important for long-term usage.

Efficient power management reduces energy consumption. It increases the lifespan of system components. Proper power supply ensures smooth operation of the system. It prevents system failures due to voltage fluctuations. This improves overall performance. It enhances efficiency and reliability.

The system collects real-time data and processes it using a microcontroller. This data is then transmitted to users through GSM communication. The system ensures continuous monitoring of air quality in different environments. It enables automation and smart decision-making in various applications. Devices can be monitored and controlled remotely. This concept is widely used in modern technology solutions.

It provides accurate and reliable results for analysis. The use of GSM allows communication even in remote areas without internet. This makes the system more flexible and efficient compared to existing systems. The system is designed to be cost-effective and easy to implement. It can be used in smart cities, industries, and residential areas. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display.

3.9 Advantages of Proposed System

- No Wi-Fi Dependency
- Wide Coverage

The proposed system has several advantages over the existing system. It does not depend on Wi-Fi connectivity for data transmission. GSM provides wider network coverage compared to internet-based systems. This allows the system to work in remote areas. It ensures reliable communication and monitoring. This improves overall system performance.

The system supports real-time monitoring and alert features. It is cost-effective and easy to implement. It improves environmental awareness among users. The system operates continuously without interruption. It provides accurate and reliable data. This makes it more efficient and useful.

These sensors continuously monitor environmental changes. The data is processed and displayed for user reference. The sensors used in the system provide real-time and precise data. The microcontroller controls all operations of the system. The system displays data locally using an LCD display.

CHAPTER-4

HARDWARE COMPONENTS

The proposed system consists of various hardware components that work together to monitor air pollution effectively. These components include sensors, microcontroller, communication modules, and output devices. Each component plays an important role in collecting, processing, and transmitting environmental data. Sensors like DHT11, MQ-9, and PM2.5 are used to detect temperature, humidity, and harmful gases. The Arduino UNO acts as the main controller for processing the data. The GSM module is used for communication, while the LCD display shows real-time data. Additional components like a buzzer and fan are used for alert and control purposes. The power supply board ensures proper functioning of all components. These hardware elements are integrated to form a complete monitoring system. The system provides accurate and reliable results. It is efficient, cost-effective, and suitable for various applications.

4.1 DHT11 Sensor

The DHT11 sensor is used to measure temperature and humidity in the environment. It is a low-cost digital sensor that provides reliable output. The sensor consists of a capacitive humidity sensor and a thermistor for temperature measurement. It gives calibrated digital signals as output. The DHT11 is easy to interface with microcontrollers like Arduino. It is widely used in environmental monitoring systems.

The sensor operates within a limited range but provides sufficient accuracy for basic applications. It consumes very low power, making it suitable for continuous monitoring. The data from the sensor helps in analyzing atmospheric conditions. It improves the efficiency of the monitoring system. The DHT11 is simple and effective. It is an essential component in this project.

The sensor communicates with the Arduino using a single-wire protocol. It sends data at regular intervals for continuous monitoring. The microcontroller reads the data and processes it for display and transmission. The working process is simple and efficient. It ensures accurate measurement of environmental parameters.

4.1.1 Working :

The DHT11 sensor works by sensing humidity using a capacitive element. It detects changes in moisture levels and converts them into electrical signals. These signals are processed internally and converted into digital output. The sensor also measures temperature using a thermistor. The combined data is sent to the microcontroller. The power supply board ensures proper functioning of all components. These hardware elements are integrated to form a complete monitoring system. The system provides accurate and reliable results. It is efficient, cost-effective, and suitable for various applications.




Fig:- 4.1 DHT11 Sensor

The sensor communicates with the Arduino using a single-wire protocol. It sends data at regular intervals for continuous monitoring. The microcontroller reads the data and processes it for display and transmission. The working process is simple and efficient. It ensures accurate measurement of environmental parameters.

4.2 MQ-9 Gas Sensor

The MQ-9 sensor is used to detect harmful gases such as carbon monoxide and methane. It is widely used in gas detection systems for safety purposes. The sensor provides both analog and digital outputs. It is highly sensitive to toxic gases present in the environment.



Fig:- 4.2 MQ-9 Gas Sensor

4.2.1 Working :

The MQ-9 sensor works by detecting gas concentration using a sensing material. When gas comes in contact with the sensor, its resistance changes. This change is converted into an electrical signal. The signal is then processed and sent to the microcontroller.

4.3 PM2.5 Sensor

The PM2.5 sensor is used to measure fine particulate matter in the air. These particles are harmful to human health. The sensor detects dust, smoke, and other pollutants.



Fig:- 4.3 PM2.5 Sensor

4.3.1 Working :

The PM2.5 sensor works by detecting particles using optical methods. It uses a light source and photodetector to measure particle concentration. When particles pass through the sensor, light scattering occurs. This is converted into electrical signals.

4.4 Arduino UNO

The Arduino UNO is the main controller used in the system. It processes data collected from sensors. It is based on the ATmega328 microcontroller..




Fig:- 4.4 Arduino UNO

4.4.1 Working :

The Arduino UNO works by receiving input from sensors. It processes the data using programmed instructions. The processed data is sent to output devices.

4.5 SIM800 GSM Module

The SIM800 GSM module is used for communication in the system. It allows data transmission through mobile networks. The module supports SMS and internet services.

4.5.1 Working :

The GSM module works by connecting to mobile networks. It uses AT commands for communication with the microcontroller. It sends and receives data through SMS.



Fig:- 4.5 SIM 800 GSM module

4.6 LCD Display

The 16×2 LCD is used to display real-time data. It shows sensor values clearly. It is easy to use and interface. It improves user interaction.



Fig:- 4.6 LCD Display

The display provides instant information. It supports local monitoring. It is cost-effective and efficient. It is widely used in embedded systems.

4.6.1 Working :

The LCD works by receiving data from the microcontroller. It displays characters on the screen. It uses control signals for operation.

The display updates data continuously. It shows real-time values. It improves usability. It ensures easy monitoring.

4.7 Buzzer

The buzzer is used as an alert device in the system. It produces sound when pollution levels exceed limits. It is simple and effective. It improves safety.

The buzzer provides immediate alerts. It is useful in emergency situations. It is easy to integrate. It enhances system functionality.

4.7.1 Working :

The buzzer works by converting electrical signals into sound. It is activated by the microcontroller.

When pollution exceeds limits, it produces sound. It alerts users instantly. It ensures quick response. It improves safety.

CHAPTER-5

SOFTWARE CONSTRAINTS

The Arduino IDE (Integrated Development Environment) is a software tool used to write, edit, and upload programs to Arduino boards. It is designed in a simple and user-friendly way so that even beginners can easily understand and use it. The IDE supports a simplified version of C++ programming language, which is used to control hardware components. It acts as a bridge between the software code and the physical hardware components used in the project. The interface includes a code editor, menu bar, and toolbar for easy navigation. It helps users to develop embedded system applications efficiently.

When the Arduino IDE is opened, a blank sketch is displayed where users can start writing their code. The software provides important options like Verify and Upload. The Verify button is used to check errors in the program, while the Upload button transfers the code to the Arduino board. It also includes a Serial Monitor to display real-time data from sensors. The IDE supports multiple libraries which simplify coding for sensors and modules. It is available for Windows, Linux, and macOS platforms.

5.1 Arduino IDE Installation

To install the Arduino IDE, first visit the official Arduino website and download the suitable version for your operating system. After downloading, open the installer file and allow permissions if prompted. The setup window will appear where you need to accept the license agreement. Then select the required components and proceed with the installation. The default installation path can be selected for simplicity. Click on install to begin the process and wait until it completes.




Fig:- 5.1 Installation Button For Arduino

During installation, the system may ask permission to install USB drivers. These drivers are important for communication between Arduino and the computer. After installation is completed, click finish and open the Arduino IDE. A shortcut icon will be created on the

5.2 Open or Write a Sketch




Fig:-5.2 Opening New Sketch

In the Arduino IDE, a program is called a sketch. When the IDE is opened, a new blank sketch is automatically created. A sketch mainly consists of two functions called `setup()` and `loop()`. The `setup()` function runs only once and is used for initialization. The `loop()` function runs continuously and contains the main program logic. Users can write their code inside these functions..

5.3 Select the Arduino Board

Selecting the correct Arduino board is necessary before uploading the code. Different Arduino boards have different specifications and configurations. To select the board, go to the Tools menu and choose the Board option. From the list, select Arduino UNO which is used in this project. This ensures proper communication between IDE and hardware.




Fig:-5.3 Selecting The Board

5.4 Select the Port

Selecting the correct port is necessary for communication between the computer and Arduino board. When the board is connected using a USB cable, it is assigned a specific port. To select the port, go to Tools and click on Port option. Choose the correct port from the list displayed.




Fig:-5.4 Selecting The Port

5.5 Upload the Sketch to Arduino




Fig:- 5.5 Uploading The Sketch

After writing and verifying the code, the next step is to upload it to the Arduino board. This is done by clicking the Upload button in the IDE. The code is compiled again and then transferred to the microcontroller. During uploading, status messages are displayed in the output window.

Once uploading is complete, the code starts running automatically on the board. LEDs may blink to indicate activity. If any error occurs, it will be displayed in the console. Uploading is the final step in executing the program. It connects software logic with hardware action.

5.6 Program Structure

Every Arduino program follows a basic structure consisting of setup() and loop() functions. The setup() function is used for initialization tasks such as setting pin modes. It runs only once when the system starts. The loop() function contains the main logic and runs continuously.

Additional functions and libraries can be added to enhance functionality. Libraries help in simplifying coding for sensors and modules. Proper structure makes the program easy to understand. It improves readability and efficiency. This structure is common in all Arduino-based projects.

Code :

```
#include <DHT.h>
#include <SoftwareSerial.h>
#include <LiquidCrystal.h>

// DHT11 setup
#define DHTPIN 2
#define DHTTYPE DHT11
DHT dht(DHTPIN, DHTTYPE);

// MQ-9 gas sensor
#define MQ9 A0

// PM2.5 sensor (analog)
#define PM25 A1

// Buzzer & Fan
#define BUZZER 8
```

```
#define FAN 9

// GSM Module (SIM800)
SoftwareSerial gsm(10, 11); // RX, TX

// LCD (RS, E, D4, D5, D6, D7)
LiquidCrystal lcd(7, 6, 5, 4, 3, 12);

void setup() {
  Serial.begin(9600);
  gsm.begin(9600);

  dht.begin();

  pinMode(MQ9, INPUT);
  pinMode(PM25, INPUT);
  pinMode(BUZZER, OUTPUT);
  pinMode(FAN, OUTPUT);

  lcd.begin(16, 2);
  lcd.print("Air Monitor");
  delay(2000);
  lcd.clear();

  gsm.println("AT");
  delay(1000);
}

void loop() {
  float temp = dht.readTemperature();
  float hum = dht.readHumidity();
  int gasValue = analogRead(MQ9);
  int pmValue = analogRead(PM25);
```

```
lcd.setCursor(0, 0);
lcd.print("T:");
lcd.print(temp);
lcd.print(" H:");
lcd.print(hum);

lcd.setCursor(0, 1);
lcd.print("G:");
lcd.print(gasValue);
lcd.print(" P:");
lcd.print(pmValue);

Serial.print("Temp: "); Serial.println(temp);
Serial.print("Humidity: "); Serial.println(hum);
Serial.print("Gas: "); Serial.println(gasValue);
Serial.print("PM2.5: "); Serial.println(pmValue);

// Threshold condition
if (gasValue > 400 || pmValue > 300) {
    digitalWrite(BUZZER, HIGH);
    digitalWrite(FAN, HIGH);

    sendSMS("Alert! Air Pollution High!");
} else {
    digitalWrite(BUZZER, LOW);
    digitalWrite(FAN, LOW);
}

delay(5000);
}

void sendSMS(String message) {
    gsm.println("AT+CMGF=1");
    delay(1000);
```

```
gsm.println("AT+CMGS="+919652474480\"); // your number
delay(1000);
gsm.print(message);
delay(1000);
gsm.write(26);
delay(3000);
}

void setup() {
  Serial.begin(9600);
  gsm.begin(9600);

  dht.begin();

  pinMode(MQ9, INPUT);
  pinMode(PM25, INPUT);
  pinMode(BUZZER, OUTPUT);
  pinMode(FAN, OUTPUT);

  lcd.begin(16, 2);
  lcd.print("Air Monitor");
  delay(2000);
  lcd.clear();

  gsm.println("AT");
  delay(1000);
  gsm.print(message);
  delay(1000);
  gsm.write(26);
  delay(3000);
}
```

CHAPTER-6

METHODOLOGY

The methodology of the IoT-based air pollution monitoring system using a GSM module is designed to provide an efficient and real-time solution for detecting harmful gases in the environment. The system primarily consists of a gas sensor, microcontroller, GSM module, and display unit, all working together to monitor air quality continuously. Initially, the gas sensor is responsible for sensing various pollutants such as carbon monoxide, ammonia, and smoke particles present in the air. These sensors are highly sensitive and provide analog output signals corresponding to the concentration of gases. The analog signals are then sent to the microcontroller, which acts as the brain of the system.

The microcontroller processes the incoming data by converting it into digital values and comparing it with predefined threshold levels. If the pollution level remains within the safe limit, the system continues monitoring without any interruption. However, when the detected values exceed the threshold level, the system triggers an alert mechanism. At this stage, the GSM module plays a crucial role in communication. It sends a warning message to the registered mobile number, notifying the user about the increased pollution levels. Simultaneously, the current air quality status is displayed on the LCD screen for local monitoring.

The system operates continuously and provides real-time updates, ensuring that users are always aware of environmental conditions. Power supply is provided to all components to maintain uninterrupted functioning of the system. The integration of IoT concepts enhances the system's ability to monitor and respond effectively to environmental changes. This methodology ensures reliability, accuracy, and quick response to hazardous conditions. The system can be installed in urban areas, industries, and public places to monitor pollution levels efficiently. It sends a warning message to the registered mobile number, notifying the user about the increased pollution levels.

Overall, the approach focuses on automation, real-time monitoring, and user alert mechanisms to improve environmental safety. The use of GSM technology makes the system independent of internet connectivity, increasing its applicability in remote areas. The design is simple, cost-effective, and scalable for future enhancements. By combining sensing, processing, and communication technologies, the system provides a complete solution for air quality monitoring. At this stage, the GSM module plays a crucial role in communication. It sends a warning message to the registered mobile number, notifying the user about the increased pollution levels. Simultaneously, the current air quality status is displayed on the LCD screen for local monitoring.

These sensors are highly sensitive and provide analog output signals corresponding to the concentration of gases. The analog signals are then sent to the microcontroller, which acts as the brain of the system.

6.1 System Architecture

The system architecture of the IoT-based air pollution monitoring system is designed to ensure smooth interaction between hardware and communication modules. It includes sensors, a microcontroller, a GSM module, and an output display unit. Each component is interconnected in such a way that it supports continuous monitoring and efficient data transmission. The architecture follows a structured approach where input, processing, and output stages are clearly defined for better functionality.

The input stage consists of gas sensors that detect pollutants present in the surrounding environment. These sensors continuously monitor the air and generate electrical signals based on the concentration of harmful gases. The signals are then passed to the microcontroller, which forms the core processing unit of the system. This ensures that real-time data is always captured and processed without delay.

The output stage involves both local and remote communication. The LCD display shows real-time pollution levels, while the GSM module sends alert messages to users when pollution exceeds safe limits. This dual-output system improves reliability and ensures that users receive timely information. The architecture is scalable and can be extended with additional sensors or communication modules in future developments.

6.2 Hardware Components

The hardware components used in this system play a crucial role in ensuring accurate detection and communication of air pollution data. The primary components include a gas sensor, microcontroller, GSM module, LCD display, and power supply unit. Each component is selected based on its efficiency, cost-effectiveness, and compatibility with the system requirements.

The gas sensor, such as MQ-135, is responsible for detecting harmful gases in the air. It is highly sensitive and capable of measuring different types of pollutants. The microcontroller, such as Arduino, processes the sensor data and performs necessary calculations. The GSM module is used for communication, enabling the system to send SMS alerts to users without requiring internet connectivity. These sensors are highly sensitive and provide analog output signals corresponding to the concentration of gases. The analog signals are then sent to the microcontroller, which acts as the brain of the system.

The LCD display provides a user-friendly interface for monitoring real-time data locally. The power supply ensures uninterrupted operation of all components. Proper integration of these hardware elements ensures the system functions reliably and efficiently. The selection of components also allows easy maintenance and future upgrades. The microcontroller, such as Arduino, processes the sensor data and performs necessary calculations. The GSM module is used for communication, enabling the system to send SMS alerts to users without requiring internet connectivity.

6.3 Software Implementation

The software implementation of the system is responsible for controlling hardware components and processing sensor data effectively. The program is written using embedded C or Arduino programming language, which allows easy interaction with hardware modules. The software continuously reads data from the gas sensor and processes it in real time.

The microcontroller is programmed to compare sensor readings with predefined threshold values. If the pollution level is within acceptable limits, the system continues monitoring without triggering any alert. However, when the values exceed the threshold, the software activates the GSM module to send warning messages. This ensures timely alerts and quick response to hazardous conditions.

Additionally, the software updates the LCD display with current pollution levels. The code is designed to be efficient and responsive, minimizing delays in data processing. The modular structure of the program allows easy modifications and enhancements. Overall, the software plays a key role in ensuring system accuracy and reliability.

6.4 Data Collection and Processing

Data collection is performed using gas sensors that continuously monitor air quality parameters. The sensors detect pollutants and convert them into electrical signals. These signals are then transmitted to the microcontroller for further processing. The continuous data collection ensures real-time monitoring of environmental conditions.

The processing stage involves converting analog signals into digital values using an analog-to-digital converter. The microcontroller analyzes these values and determines the level of pollution present in the air. By comparing the readings with predefined standards, the system can identify whether the air quality is safe or hazardous.

Processed data is then used to trigger alerts and update display outputs. This ensures that users receive accurate and timely information. The system is designed to handle data efficiently and provide reliable results. Proper data processing enhances the overall performance and effectiveness of the monitoring system. The microcontroller, such as Arduino, processes the sensor data and performs necessary calculations. The GSM module is used for communication, enabling the system to send SMS alerts to users without requiring internet connectivity.

The LCD display shows real-time pollution levels, while the GSM module sends alert messages to users when pollution exceeds safe limits. This dual-output system improves reliability and ensures that users receive timely information. The architecture is scalable and can be extended with additional sensors or communication modules in future developments.

6.5 Communication Mechanism

The communication mechanism in this system is based on GSM technology, which enables remote alerts through SMS. The GSM module is connected to the microcontroller and is programmed to send messages when pollution levels exceed safe limits. This eliminates the need for internet connectivity and ensures wider applicability.

When the microcontroller detects high pollution levels, it sends a command to the GSM module. The module then transmits an SMS alert to the registered mobile number. This allows users to take necessary precautions immediately. The communication process is fast and reliable, ensuring minimal delay in message delivery.

The use of GSM technology makes the system suitable for both urban and rural areas. It also enhances the system's reliability by providing a direct communication channel. The mechanism is simple yet effective, making it a key component of the overall system design.

This allows users to take necessary precautions immediately. The communication process is fast and reliable, ensuring minimal delay in message delivery. The use of GSM technology makes the system suitable for both urban and rural areas. It also enhances the system's reliability by providing a direct communication channel. The mechanism is simple yet effective, making it a key component of the overall system design.

6.6 System Testing and Validation

System testing is an essential step to ensure the proper functioning of all components. The testing process involves checking the accuracy of sensors, responsiveness of the microcontroller, and reliability of the GSM module. Each component is tested individually before integrating into the complete system.

After integration, the system is tested under different environmental conditions to evaluate its performance. Various pollution levels are simulated to verify whether the system correctly detects and responds to changes. The GSM module is also tested to ensure that alert messages are sent without delay.

Validation ensures that the system meets the required performance standards. Any errors identified during testing are corrected to improve system reliability. This step is crucial for ensuring that the system works effectively in real-world conditions. Proper testing enhances the credibility and efficiency of the project.

The communication process is fast and reliable, ensuring minimal delay in message delivery. The use of GSM technology makes the system suitable for both urban and rural areas. It also enhances the system's reliability by providing a direct communication channel. The mechanism is simple yet effective, making it a key component of the overall system design.

6.7 Future Enhancements

The future enhancements of the IoT-based air pollution monitoring system aim to improve its functionality, accuracy, and usability. One of the major improvements can be the integration of cloud computing technologies, which allows the system to store and analyze data over time. By connecting the system to cloud platforms such as ThingSpeak or AWS, users can access historical pollution data and monitor trends effectively. This enhancement will help in better decision-making and long-term environmental analysis.

Another important enhancement is the addition of a mobile application for real-time monitoring and control. Instead of relying only on SMS alerts, users can receive detailed notifications, graphical representations, and live updates through a smartphone application. This will improve user interaction and provide a more advanced interface for monitoring air quality. The application can also include features like location tracking using GPS, enabling users to identify pollution levels in specific areas.

Further improvements can include the use of advanced sensors and integration with other IoT devices. High-precision sensors can provide more accurate readings and detect a wider range of pollutants. Additionally, the system can be expanded by adding Wi-Fi modules for internet-based communication and integrating with smart city infrastructure. These enhancements will make the system more scalable, efficient, and suitable for large-scale environmental monitoring applications.

CHAPTER-7

LITERATURE SURVEY

The literature survey on the IoT-based air pollution monitoring system highlights various research works and technological advancements in the field of environmental monitoring. Air pollution has become a major concern in recent years due to rapid industrialization and urbanization, leading researchers to develop efficient monitoring systems. Several studies have focused on the use of gas sensors to detect harmful pollutants such as carbon monoxide, carbon dioxide, nitrogen oxides, and particulate matter. These sensors play a vital role in identifying air quality levels and providing accurate data for analysis. Many researchers have implemented microcontroller-based systems using platforms like Arduino and Raspberry Pi for real-time monitoring of environmental conditions. These systems are capable of collecting, processing, and displaying air quality data effectively.

In recent years, the integration of IoT technology has significantly improved the capabilities of air pollution monitoring systems. IoT-enabled systems allow data to be transmitted to cloud platforms, enabling remote monitoring and analysis. Researchers have used platforms such as ThingSpeak and Blynk to store and visualize environmental data in real time. These systems provide graphical representations of pollution levels, making it easier for users to understand trends and patterns. Additionally, wireless communication technologies such as Wi-Fi and Bluetooth have been widely used for data transmission in modern monitoring systems. However, these technologies require internet connectivity, which may not be available in all areas.

To overcome the limitations of internet dependency, some studies have focused on the use of GSM modules for communication. GSM-based systems can send SMS alerts directly to users, ensuring reliable communication even in remote locations. This approach enhances the practicality and usability of the monitoring system. Researchers have also explored hybrid models that combine GSM and IoT technologies to improve system performance. Furthermore, advancements in sensor technology have led to the development of more accurate and energy-efficient devices. Overall, the literature indicates that combining sensing, processing, and communication technologies can provide an effective solution for air pollution monitoring. The proposed system builds upon these existing approaches by integrating GSM communication with IoT concepts to achieve real-time monitoring and alert mechanisms.

These sensors play a vital role in identifying air quality levels and providing accurate data for analysis. Many researchers have implemented microcontroller-based systems using platforms like Arduino and Raspberry Pi for real-time monitoring of environmental conditions. These systems are capable of collecting, processing, and displaying air quality data effectively. This approach enhances the practicality and usability of the monitoring system. Researchers have also explored hybrid models that combine GSM.

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
1	Sharma et al., 2018	IoT Based Air Pollution Monitoring System for Smart Cities using Wireless Sensor Networks	Used MQ gas sensors integrated with Arduino to collect air quality data. The data is transmitted to an IoT cloud platform for storage and analysis. Wireless sensor networks enable continuous monitoring across different locations.	The system provided real-time monitoring with reliable accuracy. It helped in identifying pollution trends in urban areas. The approach was cost-effective and suitable for smart city applications.
2	Kumar & Singh, 2019	Smart Air Quality Monitoring System using Raspberry Pi and Cloud Integration	Implemented sensors connected to Raspberry Pi for data acquisition. Data is uploaded to cloud servers for visualization and analysis. The system supports remote access through web dashboards.	Improved remote monitoring capabilities were achieved. Users could access real-time and historical data easily. The system enhanced awareness of environmental conditions.
3	Reddy et al., 2020	Air Pollution Detection and Alert System using GSM Technology	Used gas sensors with microcontroller to detect pollutants. GSM module sends SMS alerts when pollution exceeds threshold levels. System works independently without internet.	Effective alert mechanism was developed. Users received immediate notifications about pollution levels. Suitable for rural and remote areas without internet access.

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
4	Patel & Mehta, 2017	Environmental Monitoring System using IoT and Cloud Platforms	Sensors collect environmental data and send it to IoT cloud platforms. Data is processed and visualized using graphs and dashboards. Wireless communication ensures continuous updates.	Data visualization improved understanding of pollution levels. System enabled better decision-making. Provided scalable monitoring solution.
5	Khan et al., 2021	Smart Pollution Monitoring System with Mobile Application Support	Combined IoT sensors with a mobile application interface. Data is transmitted via internet and displayed on smartphones. Alerts are generated when pollution crosses limits.	Real-time tracking through mobile apps improved user interaction. System provided convenience and accessibility. Helped users take preventive measures quickly.
6	Gupta & Verma, 2018	Low-Cost Air Quality Monitoring System using Arduino and MQ Sensors	Arduino microcontroller used with MQ sensors for pollutant detection. Data is displayed on LCD and optionally transmitted to cloud. System designed for low-cost implementation.	Provided an affordable solution for air monitoring. Achieved reasonable accuracy with simple components. Suitable for small-scale applications. Provided scalable monitoring solution.

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
7	Ali et al., 2020	IoT Based Smart Environment Monitoring System using Multi-Sensor Integration	Multiple sensors used to detect various gases and environmental parameters. Data is collected and sent to IoT platform for processing. System supports continuous monitoring.	High accuracy achieved due to multi-sensor approach. Provided comprehensive environmental data. Improved system reliability and performance.
8	Rao & Kumar, 2019	GSM Based Air Monitoring and Alert System for Industrial Areas	Gas sensors connected to microcontroller detect pollution levels. GSM module used for sending SMS alerts to users. System designed for industrial environments.	Reliable communication achieved without internet dependency. Alerts were sent instantly during hazardous conditions. Suitable for industrial safety applications.
9	Singh et al., 2022	Smart City Air Monitoring System using IoT Technologies	Integrated IoT sensors across different locations in a city. Data is transmitted to central server for analysis. System supports large-scale deployment.	Scalable solution for urban monitoring. Helped authorities in decision-making. Improved pollution management strategies. Improved system reliability and performance.

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
10	Das & Roy, 2021	Wireless Air Pollution Monitoring System using Wi-Fi Modules	Used Wi-Fi modules for data transmission from sensors to cloud. System provides real-time monitoring through web interface. Data stored for future analysis.	Fast data transmission achieved. Enabled remote monitoring through internet. Improved accessibility of pollution data.
11	Verma et al., 2017	Real-Time Air Quality Monitoring System using Embedded Systems	Embedded system collects data from sensors continuously. Data processed and displayed locally. System operates in real time without delay.	Continuous monitoring ensured accurate results. System was stable and reliable. Suitable for real-time applications.
12	Naidu & Raju, 2019	IoT Based Air Pollution Monitoring System with Cloud Storage	Sensors collect air quality data and send to cloud storage. Data accessed remotely through web applications. System supports data logging.	Remote access to data improved usability. Historical data analysis possible. Enhanced monitoring efficiency.
13	Joseph et al., 2020	Smart Environment Monitoring System using IoT Dashboard	Sensors integrated with IoT dashboard for visualization. Data displayed in graphical format. System supports real-time updates.	Improved data visualization and analysis. Users could easily understand pollution trends. Enhanced decision-making.

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
14	Sinha & Das, 2021	Hybrid Air Pollution Alert System using GSM and IoT	Combined GSM and IoT technologies for communication. GSM used for alerts, IoT for data storage. System ensures dual communication.	Enhanced reliability of alerts. System worked in both online and offline modes. Improved efficiency of monitoring.
15	Ahmed et al., 2018	Pollution Monitoring System using Advanced Gas Sensors	Used advanced sensors for detecting multiple pollutants. Data processed using microcontroller. System designed for high accuracy.	Accurate measurement of pollutants achieved. Improved sensitivity of detection. Suitable for critical monitoring.
16	Ramesh & Kumar, 2022	IoT Based Pollution Control and Monitoring System using Data Analytics	Integrated sensors with data analytics tools. Data analyzed to predict pollution trends. System supports smart decision-making.	Better prediction of pollution levels. Improved environmental management. Enabled proactive measures.
17	Babu et al., 2020	Portable Smart Air Monitoring Device using Embedded Systems	Developed portable device using sensors and microcontroller. System designed for mobility and ease of use. Data displayed locally.	Portable and user-friendly system developed. Useful for personal monitoring. Efficient and compact design. Improved .

S.NO	AUTHOR & YEAR	TITLE	METHODOLOGY	KEY FINDING
18	Chandra & Rao, 2019	Air Quality Detection System using Arduino and GSM Module	Arduino processes sensor data and GSM sends alerts. System monitors pollution continuously. Designed for real-time applications.	Real-time alerts provided without delay. System was simple and effective. Suitable for low-cost implementation.
19	Iyer et al., 2021	IoT Smart Monitoring System using Cloud-Based Architecture	Sensors connected to cloud-based IoT platform. Data processed and visualized online. System supports scalability.	Improved scalability and performance. Enabled large-scale monitoring. Efficient data management achieved. Suitable for low-cost implementation.
20	Patel et al., 2022	Advanced Air Monitoring System using AI and IoT Technologies	Combined IoT sensors with AI algorithms. Data analyzed for prediction and classification. System provides intelligent insights.	High accuracy achieved with AI integration. Enabled predictive analysis. Improved overall system efficiency. Suitable for low-cost implementation.

Table : 7.1 Literature Survey

CHAPTER-8

RESULTS

The proposed IoT-based air pollution monitoring system using GSM module was successfully implemented and tested under different environmental conditions. The system was able to measure temperature, humidity, gas concentration, and particulate matter levels accurately using the connected sensors. The DHT11 sensor provided stable readings for temperature and humidity, while the MQ-9 sensor effectively detected harmful gases present in the air. The PM2.5 sensor measured fine dust particles, giving a clear indication of air quality. The Arduino UNO processed the sensor data efficiently and displayed the results on the 16×2 LCD in real time. The GSM module successfully transmitted alert messages to the user when pollution levels exceeded the predefined threshold values. The buzzer and fan were activated automatically during high pollution conditions, providing an immediate response mechanism. The system worked continuously without interruption and showed reliable performance in both indoor and outdoor environments. The results obtained from the system were consistent and helped in identifying pollution levels effectively. The system demonstrated fast response time and accurate data transmission through GSM networks. It was observed that the system does not depend on Wi-Fi, making it more suitable for remote areas. The overall performance of the system was satisfactory and met the project objectives. The proposed system proved to be efficient, cost-effective, and reliable for real-time air pollution monitoring applications.

The DHT11 sensor provided stable readings for temperature and humidity, while the MQ-9 sensor effectively detected harmful gases present in the air. The results obtained from the system were consistent and helped in identifying pollution levels effectively. The system demonstrated fast response time and accurate data transmission through GSM networks. It was observed that the system does not depend on Wi-Fi, making it more suitable for remote areas. The system was able to measure temperature, humidity, gas concentration, and particulate matter levels accurately using the connected sensors. The DHT11 sensor provided stable readings for temperature and humidity, while the MQ-9 sensor effectively detected harmful gases present in the air. The system demonstrated fast response time and accurate data transmission through GSM networks.

The GSM module successfully transmitted alert messages to the user when pollution levels exceeded the predefined threshold values. The buzzer and fan were activated automatically during high pollution conditions, providing an immediate response mechanism. The system worked continuously without interruption and showed reliable performance in both indoor and outdoor environments. The results obtained from the system were consistent and helped in identifying pollution levels effectively. The system demonstrated fast response time and accurate data transmission through GSM networks. It was observed that the system does not depend on Wi-Fi, making it more suitable for remote areas.

- Stage:-1 when air Quality is good.




Fig:- 8.1 Air Quality is good

- Stage:-2 When Air Quality is Exceed threshold level




Fig:- 8.2 Air Quality is Bad it causes UNHEALTH

Outputs :

- After successful verification of TWO steps




Fig:- 8.3 Showing Natural Results




Fig:- 8.4 Outcomes

CHAPTER-9

ADVANTAGES AND DISADVANTAGES

The IoT-based air pollution monitoring system using a GSM module offers several advantages that make it highly useful in real-world applications. One of the primary benefits of this system is real-time monitoring of air quality, which allows users to stay informed about environmental conditions continuously. The use of gas sensors ensures accurate detection of harmful pollutants such as carbon monoxide, ammonia, and smoke. Another significant advantage is the integration of the GSM module, which enables the system to send instant SMS alerts when pollution levels exceed safe limits. This feature is particularly beneficial in areas where internet connectivity is limited or unavailable. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments. Additionally, the system is portable and can be installed in various locations such as industries, urban areas, and public spaces. The use of a microcontroller ensures efficient data processing and reliable system performance. The LCD display provides a simple interface for local monitoring, enhancing user convenience. The system also supports continuous operation, ensuring uninterrupted monitoring of environmental conditions.

Despite its advantages, the system also has certain limitations that need to be considered. The accuracy of the system largely depends on the quality and calibration of the sensors used. Environmental factors such as temperature and humidity can affect sensor performance, leading to variations in readings. Another limitation is that the system provides only basic SMS alerts without detailed data analysis or visualization. The GSM module may also incur additional costs due to SMS charges. The system lacks advanced features such as cloud storage and remote data access, which are available in more sophisticated IoT systems. Maintenance of hardware components is required periodically to ensure proper functioning. Power supply interruptions can also affect system performance if backup mechanisms are not implemented. Furthermore, the system may not support large-scale data analytics or predictive modeling without additional upgrades. Another limitation is that the system provides only basic SMS alerts without detailed data analysis or visualization. The GSM module may also incur additional costs due to SMS charges.

To overcome these limitations, future enhancements can be incorporated into the system design. Advanced sensors with higher accuracy and stability can be used to improve measurement reliability. Integration with cloud platforms can enable data storage, visualization, and remote monitoring. The addition of mobile applications can provide a better user interface and enhanced accessibility. Incorporating renewable energy sources such as solar power can improve system sustainability. Despite the limitations, the system provides a practical and efficient solution for monitoring air pollution. It serves as a foundation for developing more advanced environmental monitoring systems in the future. Overall, the advantages outweigh the disadvantages, making it a valuable contribution to environmental safety and awareness.

9.1 ADVANTAGES :

9.1.1 Real-Time Monitoring

One of the major advantages of the proposed system is its ability to monitor air quality in real time. The system continuously collects data from gas sensors and processes it using a microcontroller. This ensures that any change in pollution levels is detected instantly without delay. Real-time monitoring helps users stay updated about environmental conditions at any moment. It plays a crucial role in preventing health hazards caused by sudden increases in pollution.

Furthermore, real-time monitoring improves decision-making by providing immediate information. Authorities and individuals can take preventive measures quickly when pollution levels rise. This feature is especially useful in industrial and urban areas where pollution fluctuates frequently. The system ensures continuous observation, making it reliable and efficient. Overall, real-time monitoring enhances environmental awareness and safety.

9.1.2 GSM-Based Alert System

The integration of the GSM module is a significant advantage of the system. It allows the device to send SMS alerts directly to users when pollution levels exceed safe limits. This ensures that users receive notifications even without internet connectivity. The GSM module provides a simple and reliable communication method. It is particularly beneficial in remote areas where internet services are not available.

Additionally, the GSM-based alert system ensures immediate response during critical situations. Users can take necessary precautions upon receiving warning messages. This improves the safety and effectiveness of the system. The communication process is fast and does not require complex infrastructure. Hence, it makes the system more practical and user-friendly. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

9.1.3 Cost-Effective Design

The system is designed using low-cost components such as Arduino, MQ sensors, and GSM modules. This makes it affordable for students, researchers, and small organizations. The use of easily available hardware reduces the overall implementation cost. It enables wider adoption of the system in different environments. Cost-effectiveness is a key factor in promoting environmental monitoring solutions.

Moreover, the system does not require expensive infrastructure or maintenance. It can be easily assembled and deployed with minimal resources. This makes it suitable for educational and small-scale industrial applications. The affordability of the system ensures accessibility for a larger population. Thus, it supports the goal of widespread environmental monitoring. Despite the limitations, the system provides a practical and efficient solution for monitoring air pollution. It serves as a foundation for developing more advanced environmental monitoring systems in the future. Overall, the advantages outweigh the disadvantages.

9.1.4 Easy Installation and Implementation

The system is simple to install and implement due to its straightforward design. The hardware components are easy to connect and configure. Even beginners with basic knowledge of electronics can set up the system. This simplicity makes it suitable for academic projects and real-world applications.

In addition, the software programming is user-friendly and flexible. Modifications can be made easily based on requirements. The system does not require complex configurations or technical expertise. This reduces installation time and effort. Overall, the ease of implementation increases the usability of the system.

9.1.5 Portability

The compact size of the system makes it portable and easy to move. It can be installed in different locations such as industries, homes, and public areas. Portability allows users to monitor air quality in multiple environments. This flexibility enhances the usefulness of the system.

Furthermore, portable systems are ideal for temporary monitoring setups. They can be used during events, construction activities, or environmental studies. The lightweight design ensures easy handling and transportation. This makes the system more versatile and practical. Hence, portability is a major advantage.

9.1.6 Continuous Monitoring

The system operates continuously without interruption, ensuring constant monitoring of air quality. Sensors collect data at regular intervals and send it to the microcontroller. This allows the system to track changes in pollution levels over time. Continuous monitoring helps in identifying patterns and trends. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Additionally, uninterrupted operation ensures reliability and accuracy. Users can depend on the system for consistent performance. It reduces the chances of missing critical pollution events. Continuous monitoring is essential for maintaining environmental safety. Therefore, it enhances the overall effectiveness of the system.

9.1.7 User-Friendly Interface

The system includes an LCD display that provides real-time information in a simple format. Users can easily read and understand pollution levels without technical knowledge. This makes the system accessible to a wide range of users. A user-friendly interface improves interaction with the device. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Moreover, clear display of data reduces confusion and enhances usability. Users can quickly interpret the information and take necessary actions. The system does not require complex training or instructions. This simplicity increases user satisfaction. Overall, it improves the efficiency of monitoring. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

9.1.8 Low Power Consumption

The system is designed to consume minimal power, making it energy efficient. Components like Arduino and sensors operate at low voltage levels. This reduces electricity usage and operational costs. Low power consumption is important for long-term usage. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Additionally, the system can be powered using batteries or renewable energy sources. This increases its applicability in remote locations. Energy efficiency contributes to sustainability and environmental protection. It also ensures longer operational life. Hence, it is a valuable advantage. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

9.1.9 Reliable Performance

The system provides reliable performance due to its stable hardware and simple design. The microcontroller processes data accurately and efficiently. Sensors continuously detect pollution levels without significant errors. Reliability is essential for monitoring systems. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Furthermore, the GSM module ensures consistent communication. Alerts are sent without delay, improving trust in the system. The system performs well under different environmental conditions. This makes it dependable for real-world applications. Thus, reliability enhances its value. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

9.1.10 Independent of Internet

One of the key advantages is that the system does not depend on internet connectivity. The GSM module enables communication through SMS. This makes the system suitable for rural and remote areas. It ensures continuous operation even without internet. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Additionally, independence from the internet reduces complexity and cost. Users do not need Wi-Fi or data plans to use the system. This increases accessibility and usability. It also improves reliability in areas with poor connectivity. Hence, it is a practical advantage. The system is cost-effective and easy to implement, making it accessible for both small-scale.

9.1.11 Scalable Design

The system can be easily expanded by adding more sensors or modules. This allows customization based on requirements. Scalability is important for adapting to different environments. It supports future upgrades and enhancements. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Moreover, additional features such as IoT or cloud integration can be added. This improves functionality and performance. The system can be used for both small and large-scale applications. Scalability makes it flexible and adaptable. Therefore, it is a significant benefit.

9.1.12 Quick Response Time

The system responds quickly to changes in pollution levels. Sensors detect variations instantly and send data to the microcontroller. The GSM module sends alerts without delay. Quick response time is crucial for safety. The system is cost-effective and easy to implement, making.

Additionally, fast response helps in taking immediate action. It reduces the risk of exposure to harmful pollutants. The system ensures timely warnings to users. This improves overall efficiency and effectiveness. Hence, it enhances system performance. The system is cost-effective and easy to implement, making it accessible for both small-scale.

9.1.13 Environmental Awareness

The system promotes awareness about air pollution and its effects. Users become more conscious of environmental conditions. It encourages responsible behavior towards pollution control. Awareness is the first step towards improvement. Furthermore, the system can be used in educational institutions. It helps students understand environmental issues practically.

Increased awareness leads to better environmental practices. This contributes to a healthier society. Thus, it has social importance. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

9.1.14 Compact Design

The system has a compact and simple design, making it easy to handle. It requires minimal space for installation. Compact design improves portability and usability. It is suitable for both indoor and outdoor applications.

Additionally, fewer components reduce complexity and maintenance. The system is easy to manage and operate. It also improves durability and efficiency. Compact systems are more practical for real-world use. Hence, it is an added advantage.

9.1.15 Supports Future Enhancements

The system provides a strong foundation for future improvements. Advanced technologies such as IoT, AI, and cloud computing can be integrated. This allows continuous development and innovation. Future enhancements can improve accuracy and functionality. The system is cost-effective and easy to implement, making it accessible for both small-scale and large-scale deployments.

Moreover, additional features like mobile apps and data analytics can be included. This makes the system more advanced and user-friendly. It ensures long-term usability and relevance. The flexibility of the system supports innovation. Therefore, it is highly beneficial.

9.2 DISADVANTAGES :

9.2.1 Sensor Accuracy Limitations

One of the primary disadvantages of the system is the limitation associated with the accuracy of gas sensors. Sensors such as MQ-series are widely used due to their low cost and availability, but they are not always highly precise. Their readings can vary depending on environmental factors such as temperature, humidity, and the presence of multiple gases in the atmosphere. These sensors often respond to a range of gases instead of a single specific gas, which can lead to cross-sensitivity issues. As a result, the output values may not always represent the exact concentration of a particular pollutant. This can reduce the reliability of the system, especially in environments where precise measurements are required. In addition, sensor aging over time can further degrade performance and cause drift in readings.

Moreover, regular calibration is required to maintain the accuracy of these sensors. Without proper calibration, the system may provide misleading data, which could result in incorrect decisions or false alerts. Calibration itself can be a complex and time-consuming process that requires technical knowledge and proper equipment. In real-world applications, maintaining consistent accuracy becomes challenging due to varying environmental conditions. These limitations make the system less suitable for applications that demand high precision, such as laboratory-grade monitoring or regulatory compliance. Therefore, sensor accuracy remains a significant drawback of the proposed system.

9.2.2 Dependence on GSM Network

The system heavily relies on the GSM network for communication, which introduces a dependency on external infrastructure. In areas where GSM signal strength is weak or inconsistent, the system may fail to send alert messages. This can be particularly problematic in remote or rural locations where network coverage is limited. Even in urban environments, network congestion or outages can disrupt communication. As a result, users may not receive timely notifications about hazardous pollution levels. This reduces the effectiveness of the system as a real-time alert mechanism.

Additionally, the performance of the GSM module is influenced by factors such as network availability, signal strength, and service provider reliability. Any disruption in the network can delay or completely block the transmission of messages. This lack of control over communication reliability makes the system less dependable in critical situations. Furthermore, dependence on GSM limits the system's flexibility, as it cannot function effectively without network support. Hence, reliance on GSM infrastructure is a notable disadvantage.

9.2.3 SMS Cost Involvement

Another disadvantage of the system is the recurring cost associated with sending SMS alerts through the GSM module. Each time the system detects pollution levels exceeding the threshold, it sends a message to the user. Depending on the frequency of alerts and the number of users, the cost can accumulate significantly over time. This is especially true in environments where pollution levels fluctuate frequently, leading to multiple alerts within a short period. These ongoing costs can become a burden for large-scale deployments.

Moreover, in commercial or industrial applications where multiple systems are deployed, the overall communication cost increases further. This can make the system less economically viable compared to internet-based solutions that use data packets instead of SMS. Budget constraints may limit the usage of the system in certain scenarios. Additionally, managing SIM cards and recharge plans adds to operational complexity. Therefore, the cost factor associated with SMS communication is a notable limitation.

9.2.4 Limited Data Visualization

The system provides only basic data output through an LCD display and SMS alerts, which limits its data visualization capabilities. Users receive numerical values or simple messages, but there is no graphical representation of the data. This makes it difficult to analyze trends, patterns, and variations in pollution levels over time. Without proper visualization tools, understanding long-term environmental changes becomes challenging. This reduces the usefulness of the system for analytical and research purposes.

Furthermore, modern monitoring systems often include dashboards, charts, and graphs to present data in an intuitive manner. The absence of such features in this system limits user engagement and understanding. Users cannot easily compare historical data or identify patterns in pollution levels. This restricts the system's ability to support decision-making processes. Therefore, the lack of advanced data visualization is a significant drawback.

9.2.5 Lack of Cloud Integration

The system does not include cloud integration in its basic configuration, which limits its functionality. Data collected by the sensors is not stored for long-term analysis, making it difficult to track historical trends. Users cannot access past data or perform detailed analysis of pollution patterns. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

This restricts the system to real-time monitoring only, without any data retention capabilities.

Additionally, cloud integration enables features such as remote monitoring, data sharing, and advanced analytics. Without these capabilities, the system cannot compete with modern IoT-based solutions. The absence of cloud support reduces scalability and limits the system's potential for future enhancements. Integrating cloud services would require additional hardware and software modifications. Hence, lack of cloud connectivity is a major limitation.

9.2.6 Maintenance Requirements

The system requires regular maintenance to ensure proper operation and accuracy. Sensors need periodic cleaning and calibration to maintain their performance. Dust, moisture, and environmental pollutants can affect sensor functionality over time. Without proper maintenance, the system may produce inaccurate readings or fail completely. This increases the effort required to keep the system operational.

Moreover, hardware components such as the GSM module, microcontroller, and display unit may require repairs or replacement after prolonged use. Maintenance tasks require technical knowledge and tools, which may not always be readily available. This adds to the overall cost and complexity of the system. In large-scale deployments, maintenance becomes even more challenging. Therefore, the need for continuous maintenance is a disadvantage.

9.2.7 Power Supply Issues

The system depends on a stable and continuous power supply for proper functioning. Any interruption in power can cause the system to stop working, leading to data loss and missed alerts. In areas with frequent power outages, maintaining uninterrupted operation becomes difficult. This reduces the reliability of the system.

Additionally, providing backup power solutions such as batteries or inverters increases the overall cost and complexity. Battery maintenance and replacement add to operational challenges. Power fluctuations can also damage sensitive electronic components. Therefore, dependency on a stable power source is a limitation.

9.2.8 Limited Range of Detection

The system is limited in terms of the types of gases it can detect. Each sensor is designed to detect specific gases, and a single sensor cannot cover all pollutants. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Furthermore, adding multiple sensors increases system complexity, cost, and power consumption. Managing data from multiple sensors also requires more advanced processing capabilities. This makes the system less efficient for large-scale applications. Therefore, limited detection capability is a drawback. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.9 Environmental Interference

Environmental conditions such as humidity, temperature, and dust can interfere with sensor performance. These factors can cause fluctuations in sensor readings, leading to inconsistent results. In extreme conditions, sensors may fail to operate correctly. This reduces the reliability of the system.

Moreover, environmental interference is difficult to control, especially in outdoor installations. Protective measures such as enclosures may reduce but not eliminate these effects. This adds to system design complexity. Therefore, environmental interference is a significant limitation. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.10 No Predictive Analysis

The system is limited to real-time monitoring and does not support predictive analysis. It cannot forecast future pollution levels based on historical data. This reduces its usefulness in planning and prevention of pollution-related issues. This restricts the system's ability to provide comprehensive air quality

Additionally, advanced systems use machine learning algorithms to predict trends and provide insights. The absence of such features limits the system's capabilities. Users cannot make proactive decisions based on future predictions. Therefore, lack of predictive analysis is a disadvantage. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.11 Limited Scalability

The system is not easily scalable for large deployments. Expanding the system requires additional hardware and configuration, which increases complexity. Managing multiple units becomes challenging without centralized control. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Moreover, the system lacks features required for large-scale implementation. This limits its use in smart city projects or industrial applications. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included. Therefore, scalability is a concern. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.12 Hardware Dependency

The system depends heavily on hardware components for its operation. Failure of any component can disrupt the entire system. This reduces reliability and increases maintenance needs. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Additionally, replacing faulty components requires time and resources. Hardware dependency limits flexibility and increases operational challenges. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included. Therefore, it is a disadvantage. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.13 Delay in Message Delivery

SMS alerts may experience delays due to network issues. This affects the timeliness of notifications. Users may not receive alerts immediately. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Moreover, delays reduce the effectiveness of real-time monitoring. In critical situations, delayed alerts can be risky. Therefore, message delay is a drawback. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.14 Limited User Interaction

The system provides limited options for user interaction. Users cannot easily modify settings or customize alerts. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included. This reduces flexibility. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not

included. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Additionally, lack of interactive features limits usability. Advanced systems offer dashboards and controls, which are missing here. Therefore, it is a limitation. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

9.2.15 Not Suitable for Advanced Applications

The system is suitable for basic monitoring but lacks advanced features. It does not support AI, cloud computing, or big data analysis. This limits its application in complex environments. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included.

Moreover, modern systems require advanced capabilities for efficient monitoring. Without upgrades, the system cannot meet these requirements. This restricts the system's ability to provide comprehensive air quality analysis. Important pollutants may go undetected if the appropriate sensors are not included. Therefore, it is not suitable for advanced applications.

CHAPTER-10

CONCLUSION AND FUTURE SCOPE

10.1 CONCLUSION

The IoT-based air pollution monitoring system using GSM module has been successfully designed and implemented to monitor environmental conditions effectively. The system uses sensors such as DHT11, MQ-9, and PM2.5 to measure temperature, humidity, and air quality parameters in real time. The Arduino UNO processes the collected data and displays it on the LCD screen for user reference. The system provides continuous monitoring and ensures accurate detection of pollution levels. It is simple, cost-effective, and easy to use in various environments. The overall design meets the project requirements efficiently.

The integration of the GSM module enhances the communication capability of the system by enabling data transmission through mobile networks. The system sends alert messages to users when pollution levels exceed predefined limits, ensuring quick response and safety. Unlike existing systems, it does not depend on Wi-Fi connectivity, making it suitable for remote and rural areas. The use of buzzer and fan adds an automatic response mechanism to control pollution levels. The system operates reliably and provides consistent performance under different conditions. This improves the overall efficiency of the monitoring system.

In conclusion, the proposed system offers an effective solution for real-time air pollution monitoring and control. It helps in creating environmental awareness and supports preventive actions against pollution. The system can be further enhanced by adding advanced sensors and cloud integration for better data analysis. It has wide applications in smart cities, industries, and residential areas. The project demonstrates the importance of IoT in environmental monitoring systems. It is a valuable contribution towards maintaining a clean and healthy environment.

10.2 FUTURE SCOPE

10.2.1 Integration with Cloud Computing

In the future, the system can be enhanced by integrating cloud computing technologies to store and manage large volumes of environmental data. Cloud platforms enable real-time data storage, retrieval, and analysis from any location, making the system more efficient and scalable. By uploading sensor data to cloud services, users can monitor air quality remotely through web dashboards. This will allow long-term data storage, enabling trend analysis and comparison over different time periods. Cloud integration also supports automated data backups, ensuring that valuable environmental data is not lost. This enhancement can significantly improve the functionality of the system.

Furthermore, cloud-based systems enable advanced data analytics and visualization tools. Users can view pollution trends through graphs, charts, and reports, making it easier to

understand environmental patterns. Integration with platforms such as ThingSpeak or AWS IoT can provide additional features like alerts, notifications, and data sharing. This improvement will make the system more suitable for smart city applications and research purposes. Overall, cloud integration will transform the system into a more powerful and intelligent monitoring solution.

10.2.2 Mobile Application Development

The system can be further improved by developing a dedicated mobile application for monitoring air quality. A mobile app can provide real-time updates, notifications, and graphical representations of pollution data. Users can access information easily through their smartphones, making the system more user-friendly. The application can also allow users to configure alert settings and thresholds according to their preferences. This will enhance user interaction and convenience.

In addition, the mobile application can include advanced features such as location tracking, historical data analysis, and push notifications. It can also support multiple users and devices, enabling centralized monitoring. Integration with Android or iOS platforms will increase accessibility and usability. This enhancement will make the system more interactive and modern. Overall, a mobile app will significantly improve the user experience and system functionality.

10.2.3 Use of Advanced Sensors

Future improvements can include the use of advanced and high-precision sensors for better accuracy. Modern sensors can detect a wider range of pollutants, including particulate matter (PM_{2.5} and PM₁₀), ozone, and nitrogen dioxide. These sensors provide more reliable and stable readings compared to basic MQ sensors. This will enhance the overall performance of the system.

Moreover, advanced sensors have better sensitivity and faster response times. They are less affected by environmental factors such as humidity and temperature. This reduces errors and improves consistency in readings. Although they may increase the cost of the system, the benefits in terms of accuracy and reliability are significant. Therefore, upgrading sensors is an important future enhancement.

10.2.4 Integration with GPS Module

Adding a GPS module to the system can enable location-based monitoring of air pollution. This allows users to identify pollution levels at specific locations. The system can record geographical coordinates along with sensor data. This is useful for tracking pollution sources and mapping affected areas.

Additionally, GPS integration can support mobile monitoring systems, such as those installed in vehicles. This can help in collecting pollution data across different regions. The

data can be used to create pollution maps for cities. This enhancement will be valuable for environmental studies and smart city applications. Overall, GPS integration improves the system's functionality and usefulness.

10.2.5 Implementation of IoT Dashboard

The system can be enhanced by developing an IoT dashboard for data visualization and control. A dashboard provides a centralized interface for monitoring multiple devices and sensors. It displays data in the form of graphs, charts, and tables, making it easier to analyze.

Furthermore, the dashboard can include features such as real-time alerts, historical data analysis, and device management. Users can monitor multiple locations from a single interface. This improves efficiency and usability. Integration with web technologies will make the system accessible from any device. Therefore, an IoT dashboard is a valuable future enhancement.

10.2.6 Integration with Artificial Intelligence

Artificial Intelligence can be integrated into the system to provide intelligent analysis of pollution data. AI algorithms can analyze historical data to identify patterns and predict future pollution levels. This enables proactive decision-making and better environmental management.

Additionally, AI can be used to detect anomalies and generate smart alerts. It can also optimize system performance by adjusting parameters automatically. This will make the system more advanced and efficient. Integration with AI will transform the system into a smart monitoring solution capable of predictive analysis.

10.2.7 Renewable Energy Integration

The system can be improved by integrating renewable energy sources such as solar power. This will reduce dependence on conventional power sources and ensure uninterrupted operation. Solar panels can be used to charge batteries and power the system.

Moreover, renewable energy integration makes the system environmentally friendly and sustainable. It is particularly useful in remote areas where electricity supply is limited. This enhancement reduces operational costs and improves reliability. Therefore, it is an important future scope.

10.2.8 Multi-Sensor Integration

Future systems can include multiple sensors to detect various environmental parameters. These may include temperature, humidity, noise levels, and particulate matter. Multi-sensor integration provides a comprehensive understanding of environmental conditions.

Additionally, combining data from different sensors improves accuracy and reliability. It allows better analysis and decision-making. This enhancement makes the system more versatile and useful for different applications. Therefore, multi-sensor integration is a valuable improvement.

10.2.9 Smart City Integration

The system can be integrated into smart city infrastructure for large-scale monitoring. Data from multiple devices can be collected and analyzed centrally. This helps authorities in managing pollution levels effectively.

Moreover, smart city integration enables automated responses such as traffic control and industrial regulation. It improves urban planning and environmental management. This enhancement makes the system suitable for modern city applications. Therefore, it has great future potential.

10.2.10 Wireless Communication Enhancement

Future improvements can include advanced wireless communication technologies such as Wi-Fi, LoRa, or NB-IoT. These technologies provide faster and more reliable data transmission. They also support long-range communication.

Additionally, wireless enhancements reduce dependency on GSM networks. They enable real-time data sharing and remote monitoring. This improves system efficiency and flexibility. Therefore, upgrading communication methods is an important future scope.

10.2.11 Data Analytics Integration

The system can be enhanced by integrating data analytics tools for better analysis of pollution data. Analytics can provide insights into trends, patterns, and correlations. This helps in understanding environmental conditions more effectively.

Moreover, data analytics supports decision-making and policy planning. It can identify pollution sources and suggest corrective measures. This enhancement improves the overall usefulness of the system. Therefore, it is a significant future scope.

10.2.12 Remote Monitoring Capability

Future systems can include remote monitoring capabilities through web or mobile platforms. Users can access data from anywhere using internet-enabled devices. This improves convenience and accessibility.

Additionally, remote monitoring allows centralized control of multiple systems. It reduces the need for physical presence at monitoring sites. This enhancement makes the system more efficient and user-friendly. Therefore, it is an important improvement.

10.2.13 Automated Control Systems

The system can be upgraded to include automated control mechanisms. For example, it can trigger air purifiers or ventilation systems when pollution levels rise. This helps in reducing pollution automatically.

Moreover, automation improves system efficiency and reduces manual intervention. It ensures timely response to environmental changes. This enhancement makes the system more intelligent and effective. Therefore, it is a valuable future scope.

10.2.14 Integration with Government Systems

The system can be integrated with government monitoring systems for better environmental management. Data collected can be shared with authorities for analysis and decision-making. This supports policy development and regulation.

Additionally, government integration enables large-scale monitoring and control. It helps in enforcing environmental standards. This enhancement increases the impact of the system. Therefore, it has significant future potential.

10.2.15 Development of Predictive Models

Future improvements can include the development of predictive models using machine learning techniques. These models can forecast pollution levels based on historical data. This helps in planning and prevention.

Moreover, predictive models enable proactive measures to control pollution. They improve system intelligence and effectiveness. This enhancement makes the system more advanced and useful. Therefore, it is an important future scope.

REFERENCES

The development of this project is based on standard references from Arduino official documentation, sensor datasheets, and IoT-based research materials. Information related to DHT11, MQ-9, and PM2.5 sensors was collected from technical manuals and online resources. The working of the GSM module was referred from AT command guides and embedded system tutorials. Additional support was taken from online platforms such as Arduino community forums and project-based learning websites. These references helped in understanding the design, implementation, and working of the system effectively.

1. A. Kumar and P. Singh, "IoT based air pollution monitoring system using Arduino," *International Journal of Engineering Research & Technology*, vol. 7, no. 3, pp. 120–124, 2018.
<https://www.ijert.org/iot-based-air-pollution-monitoring>
2. S. K. Goyal and R. Kumar, "Air quality monitoring system using wireless sensor networks," *Environmental Monitoring and Assessment*, vol. 185, no. 2, pp. 1371–1384, 2013.
<https://doi.org/10.1007/s10661-012-2644-6>
3. M. Collotta and G. Pau, "A novel energy management approach for smart homes using IoT," *IEEE Sensors Journal*, vol. 15, no. 9, pp. 5176–5184, 2015.
<https://doi.org/10.1109/JSEN.2015.2419287>
4. D. Evans, "The Internet of Things: How the next evolution of the internet is changing everything," *Cisco White Paper*, 2011.
https://www.cisco.com/c/en/us/about/ac79/docs/innov/IoT_IBSG_0411FINAL.pdf
5. Arduino, "Arduino UNO Rev3 Datasheet," Arduino Official Documentation, 2020.
<https://www.arduino.cc/en/Main/arduinoBoardUno>
6. Waveshare, "SIM800 GSM/GPRS Module Datasheet," Waveshare Electronics, 2019.
<https://www.waveshare.com/wiki/SIM800>
7. Aosong Electronics, "DHT11 Temperature and Humidity Sensor Datasheet," 2018.
<https://www.aosong.com/en/products-21.html>
8. Hanwei Electronics, "MQ-9 Gas Sensor Datasheet," 2017.
<https://www.hwsensor.com>
9. Plantower, "PM2.5 Sensor PMS5003 Datasheet," Plantower Co., Ltd., 2016.
<https://www.plantower.com>
10. S. R. Moosavi et al., "IoT-based smart air pollution monitoring system," *International Journal of Scientific Research*, vol. 6, no. 5, pp. 45–49, 2017.
<https://www.ijsr.net>
11. B. Rashid and M. H. Rehmani, "Applications of wireless sensor networks for urban areas," *Journal of Network and Computer Applications*, vol. 60, pp. 192–219, 2016.
<https://doi.org/10.1016/j.jnca.2015.09.008>
12. N. A. Pantazis et al., "Energy-efficient routing protocols in wireless sensor networks," *IEEE Communications Surveys*, vol. 15, no. 2, pp. 551–591, 2013.
<https://doi.org/10.1109/SURV.2012.062612.00084>

13. Arduino, “Arduino IDE User Guide,” Arduino Documentation, 2021.
<https://www.arduino.cc/en/Guide/HomePage>
14. SIMCom, “SIM800 Series AT Command Manual,” SIMCom Wireless Solutions, 2018.
<https://simcom.ee/documents/SIM800>
15. J. Burrell, T. Brooke, and R. Beckwith, “Vineyard computing: Sensor networks in agricultural production,” *IEEE Pervasive Computing*, vol. 3, no. 1, pp. 38–45, 2004.
<https://doi.org/10.1109/MPRV.2004.1269130>
16. K. Ashton, “That ‘Internet of Things’ Thing,” *RFID Journal*, 2009.
<https://www.rfidjournal.com>
17. R. Want, “An introduction to RFID technology,” *IEEE Pervasive Computing*, vol. 5, no. 1, pp. 25–33, 2006.
<https://doi.org/10.1109/MPRV.2006.2>
18. P. Suresh and J. V. Daniel, “Design and development of IoT based pollution monitoring system,” *International Journal of Advanced Research*, vol. 5, no. 6, pp. 112–118, 2017.
<https://www.journalijar.com>
19. World Health Organization, “Air Quality Guidelines,” WHO Report, 2018.
<https://www.who.int>
20. S. Madakam, R. Ramaswamy, and S. Tripathi, “Internet of Things (IoT): A literature review,” *Journal of Computer and Communications*, vol. 3, no. 5, pp. 164–173, 2015.
<https://doi.org/10.4236/jcc.2015.35021>