TEST PLAN

KAN-1 | Register an account

Account and identity feature | DRAFT - pending human review

Ticket status: In Progress **Issue type: Story**

Source: Jira KAN-1. Scope and scenarios below are based on the ticket; unspecified behavior is flagged for clarification.

Components, linked issues, attachments, fix versions, and sprint: none recorded in retrieved Jira fields.

Company context

Walmart Data Ventures is a Walmart commercial data and insights business unit that monetizes first-party retail data for suppliers, merchants, and brands.

- Scintilla (formerly Walmart Luminate) is the commerce intelligence platform.
- The platform supports inventory management, retail media, and in-store optimization.
- Supplier visibility spans customer behavior and business performance across the U.S., Mexico, and Canada.
- Supplier collaboration includes events such as Inspire; the company focuses on actionable intelligence for assortment and customer experience.

1. Scope & objectives

Ticket goal

As a shopper, I want to create an account so that I can save my details and manage orders.

In scope

Registration with valid required details and applicable terms; duplicate email/phone handling; required-field and invalid-field inline validation; confirmation; protection of passwords and verification codes from logs and plain-text responses.

Out of scope

Post-registration account management, order management, and recovery/sign-in implementation beyond verifying the duplicate-registration route described in the ticket.

Objective

Verify each stated acceptance criterion with observable outcomes, confirm no account is created after invalid submissions, and check that passwords and verification codes are not exposed in logs or responses.

Ticket acceptance criteria (source)

AC1: Given valid required details and acceptance of applicable terms, when registration is submitted, an account is created and confirmation is shown.

AC2: Given the email or phone is already registered, when registration is submitted, a clear message is shown with a route to sign in or recover access.

AC3: Given required fields are missing or invalid, when registration is submitted, inline validation identifies the fields and no account is created.

AC4: Passwords and verification codes are never displayed in logs or returned in plain text.

2. Requirement checklist and gaps

Statuses: PRESENT = stated in the ticket; AMBIGUOUS = mentioned without enough detail to test precisely; MISSING = not specified. Each unresolved item below needs author confirmation.

PRESENT | Functional - User goal / story: Shopper wants an account to save details and manage orders.

PRESENT | Functional - Testable acceptance criteria: Four observable criteria are supplied.

PRESENT | Functional - Happy path: Valid details + applicable terms -> account + confirmation.

PRESENT | Functional - Negative / error paths: Duplicate identity and missing/invalid fields are described; exact errors are not.

MISSING | Functional - Boundary / empty states: What are field length, format, empty, whitespace, and maximum-value rules?

MISSING | Functional - State transitions: What are registration, verification, pending, and completed states and transitions?

MISSING | Data & environment - Test data: Which required fields and safe test identities are available?

MISSING | Data & environment - Environment / flags: Which environment, configuration, and feature flags apply?

MISSING | Data & environment - Dependencies / integrations: Which identity, email/SMS verification, and account services are dependencies?

MISSING | Data & environment - Preconditions / setup: How should existing accounts, terms version, and test environment be prepared?

MISSING | Non-functional - Performance / load: What response-time and concurrency targets apply?

AMBIGUOUS | Non-functional - Security / authorization: Secret non-disclosure is required; roles, abuse controls, and authorization expectations are not specified.

MISSING | Non-functional - Accessibility: What keyboard, screen-reader, focus, and error-announcement expectations apply?

MISSING | Non-functional - Internationalization: Which locales, scripts, phone formats, and translated messages are supported?

AMBIGUOUS | Non-functional - Audit / observability: Logs must not expose secrets; approved event fields, retention, and redaction checks are unspecified.

MISSING | Cross-cutting - Regression impact: Which existing sign-in, recovery, and account flows are affected?

MISSING | Cross-cutting - Compatibility / migration: Are there existing account or data migration compatibility requirements?

MISSING | Cross-cutting - Device / browser matrix: Which browsers, devices, and responsive breakpoints are in scope?

MISSING | Cross-cutting - Rollback / feature flag: Is registration gated, and what rollback behavior is expected?

AMBIGUOUS | Clarity - Unambiguous wording: "Applicable terms", "required details", "clear message", and "route" need precise definitions.

MISSING | Clarity - Defined terms: Define account creation success, registered identity, and verification code lifecycle.

MISSING | Clarity - Design reference: Provide the approved registration and validation designs, if applicable.

Questions for the ticket author

- Which fields are required, what formats and length limits apply, and how are email and phone normalized for duplicate detection?

- What exactly constitutes acceptance of the applicable terms? Which version/link is displayed, and what happens when terms are not accepted?

- What are the exact success, duplicate, and field-validation messages and the sign-in/recovery destinations?

- Is verification required? What code format, expiry, retry, resend, and lockout behavior should be tested?

- What test environment, feature flags, safe test data, integrations, and setup steps are available?

- Which roles, abuse/rate-limit controls, browser/device/localization requirements, accessibility criteria, and performance targets apply?

- Which events may be logged, and how can QA inspect logs and responses to verify passwords/codes are redacted?

- What regression flows, sprint/fix version, release timeline, and rollback behavior are in

scope?

3. Test scenarios

Priorities: P0 = core registration/security outcome; P1 = stated validation and duplicate paths; P2 = exploratory follow-up where requirements are not yet defined. Gap-tagged scenarios are questions to resolve, not assumed product behavior.

TS-01 | P0 | Positive | AC1

Submit valid required details and accept terms; verify account creation and visible confirmation.

TS-02 | P1 | Negative | AC2

Submit using an already-registered email; verify a clear message and sign-in or recovery route.

TS-03 | P1 | Negative | AC2

Submit using an already-registered phone; verify a clear message and sign-in or recovery route.

TS-04 | P1 | Negative | AC3

Submit with each required field omitted in turn; verify inline identification and no account creation.

TS-05 | P1 | Negative | AC3 / author to define formats

Submit malformed values for required fields using author-approved formats; verify inline identification and no account creation.

TS-06 | P0 | Security | AC4

Inspect application/API responses and available logs for a valid submission; confirm password and verification code are never returned in plain text or logged.

TS-07 | P0 | Security | AC4 / verification flow TBD

Repeat secret-exposure checks for validation errors, duplicate identity, and verification failure paths where supported.

TS-08 | P1 | Boundary | AC3 / gap: field constraints

Exercise empty, whitespace-only, minimum/maximum lengths, and boundary values for every field once constraints are specified.

TS-09 | P1 | Boundary | AC2 / gap: normalization

Try email/phone case, whitespace, and formatting variations against an existing identity after normalization rules are confirmed.

TS-10 | P2 | Negative | AC1 / gap: terms behavior

Test unaccepted terms and verify expected submission behavior after the author clarifies terms requirements.

TS-11 | P2 | Cross-role | Gap: roles / authorization

Compare permitted and restricted registration access only after supported roles and authorization rules are specified.

TS-12 | P2 | Resilience | Gaps: state / abuse controls

Explore repeated or concurrent submissions and verification retries after expected idempotency, throttling, and retry rules are specified.

4. Test data & environment

Data: Use synthetic, QA-approved registration identities only. Prepare one unused email/phone pair for the happy path and pre-existing accounts for duplicate checks. Confirm approved field values and verification fixtures before execution.

Secrets: Use test-only passwords and codes. Do not place them in screenshots, test reports, command output, or logs. Verify redaction in approved observability tools.

Environment / flags: Not specified in KAN-1; author/QA owner to identify a non-production environment, configuration, and feature-flag state.

Roles / permissions: Shopper is the only persona named. Additional roles and access rules are not specified.

Dependencies: Registration/account service and any email/SMS verification dependency are not detailed in the ticket.

5. Risks & assumptions

Assumptions

Scenarios use only the four acceptance criteria as requirements. ’Applicable terms’ and ’required details’ are not expanded into guessed fields or behaviors. Company context is included for reference, not treated as a product requirement.

Risks

Unspecified field rules can make validation results non-deterministic; duplicate detection may vary with identity normalization; verification, abuse controls, and logging inspection may need service-owner support. Secret leakage is a high-impact risk and should be checked on every relevant response/log path.

6. Entry / exit criteria

Entry

Approved non-production environment and feature-flag state; confirmed required fields, formats, terms version, verification rules, and safe test data; access to registration and approved log/response inspection.

Exit

All confirmed AC-mapped P0/P1 scenarios executed; no unresolved critical defects; no account created for invalid submissions; duplicate guidance is verified; password/code exposure checks pass; gaps and blocked scenarios are documented. QA owner reviews and approves this draft.

7. Resource allocation

Proposed roles (no named owners assigned): QA owner to coordinate and sign off; QA tester to execute UI/API scenarios; identity/service owner to provide test accounts, verification fixtures, environment details, and approved log access; product/ticket author to resolve requirement questions.

8. Timelines and sprint details

KAN-1 is In Progress. No sprint, fix version, release date, or estimates were present in the Jira fields retrieved. Test dates and duration are not assigned; schedule after open questions and environment readiness are confirmed.

Human review gate

I assumed

Only the ticket story and four listed acceptance criteria are requirements; no unspecified form field, verification, role, message, or release behavior is assumed.

I could not confirm

Required field list and validation constraints; terms acceptance rules; exact messages/routes; verification behavior; environment/data; roles; performance, accessibility, localization, compatibility, and release expectations.

Open questions blocking sign-off

Resolve the author questions in section 2, especially field/terms rules, verification, test setup, and evidence access for secret redaction. Mark any inapplicable checklist gaps explicitly.

DRAFT - NOT APPROVED. QA owner: review, answer or disposition open questions, edit scenarios, and approve before test cases or automation are created.