Lab3 Intro
Improving Area and Resources

Vivado HLS 2013.3 Version
ZedBoard

Objectives

- **After completing this lab, you will be able to:**
  - Manage BRAM and DSP48 resource utilization
  - Improve memory bandwidth
  - Balance resource utilization and performance
  - Distinguish between DATAFLOW directive and Configuration Command functionality

The Design

- **The design under consideration is a Discrete Cosine Transformation (DCT) function on a 8x8 block of data**
  - The top-level function dct implements 2D DCT algorithm by first processing each row of the input array via a 1D DCT then processing the columns of the resulting array through the same 1D DCT. It calls read_data, dct_2d, and write_data functions.
  - The read_data function consists of two loops – RD_Loop_Row and RD_Loop_Col.
  - The write_data function is defined consists of two loops to perform writing the result.

```
78 void dct(short input[N], short output[N])
79 {
80
81     short buf_2d_in[DCT_SIZE][DCT_SIZE];
82     short buf_2d_out[DCT_SIZE][DCT_SIZE];
83
84     // Read input data. Fill the internal buffer.
85     read_data(input, buf_2d_in);
86
87     dct_2d(buf_2d_in, buf_2d_out);
88
89     // Write out the results.
90     write_data(buf_2d_out, output);
91 }
```



Procedure

- Compile the design in command mode and perform C-verification
- Open the project in Vivado HLS GUI, synthesize, and review results
- Simulate the design
- Improve performance using pipeline
- Optimize fine-grained parallelism
- Improve memory bandwidth
- Apply DATAFLOW directive to improve performance
- Apply RESHAPE directive and analyze

Summary

- In this lab, you learned various techniques to improve the performance and balance resource utilization. PIPELINE directive when applied to outer loop will automatically cause the inner loop to unroll. When a loop is unrolled, resources utilization increases as operations are done concurrently. Partitioning memory may improve performance but will increase BRAM utilization. When INLINE directive is applied to a function, the lower level hierarchy is automatically dissolved. When DATAFLOW directive is applied, the default memory buffers (of ping-pong type) are automatically inserted between the top-level functions and loops. The RESHAPE directive will allow multiple accesses to BRAM, however, care should be taken if a single element requires modification as it will result in read-modify-write operation for the entire word. The Analysis perspective and console logs can provide insight on what is going on.