Block and Port Level Protocols

Vivado HLS 2013.3 Version

Objectives

- **After completing this module, you will be able to:**
  - List the types of IO abstracted in Vivado HLS
  - List various basic and optional IO ports handled in Vivado HLS
  - State how a design can be synthesized as combinatorial and sequential
  - Distinguish between block-level and port-level IO protocols
  - State how pointer interfaces are implemented

Outline

- *Introduction*
- Block Level Protocols
- Port Level Protocols
- Summary

The Key Attributes of C code : IO

Code

```
void fir (

  data_t *y,
  coef_t c[4],
  data_t x

 ) {

  static data_t shift_reg[4];
  acc_t acc;
  int i;

  acc=0;
  loop: for (i=3;i>=0;i--) {
    if (i==0) {
      acc+=x*c[0];
      shift_reg[0]=x;
    } else {
      shift_reg[i]=shift_reg[i-1];
      acc+=shift_reg[i]  *   c[i];
}
  }
  *y=acc>>2;
}
```

Functions: All code is made up of functions which represent the design hierarchy: the same in hardware

Input & Outputs: The arguments of the top-level function must be transformed to hardware interfaces with an IO protocol

Types: All variables are of a defined type. The type can influence the area and performance

Loops: Functions typically contain loops. How these are handled can have an impact on area and performance.

Arrays: Arrays are used often in C code. They can impact the device area and become performance bottlenecks.

Operators: Operators in the C code may require sharing to control area or be assigned to specific hardware implementations to meet performance

Example 101 : Combinational Design

- **Simple Adder Example**
  - Output is the sum of 3 inputs

```
#include "adders.h"
int adders(int in1, int in2, int in3) {

        int sum;
        sum = in1 + in2 + in3;
        return sum;
}
```

- **Synthesized with 100 ns clock**
  - All adders can fit in one clock cycle
  - **Combinational design**




```
================================================================
== Performance Estimates
================================================================
+ Summary of timing analysis:
    * Estimated clock period (ns): 3.45
+ Summary of overall latency (clock cycles):
    * Best-case latency:    0
    * Average-case latency: 0
    * Worst-case latency:   0
```

  - The function return becomes RTL port ap_return
  - No handshakes are required or created in this example

Example 102: Sequential Design

- **The same adder design is now synthesized with a 3ns clock**
  - The design now takes more than 1 cycle to complete
  - Vivado HLS creates a **sequential** design with the default port types



- **By Default ..**
  - Block level handshake signals are added to the design

Vivado HLS IO Options

- **Vivado HLS has four types of IO**
  1. Data ports created by the original top-level C function arguments
  2. IO protocol signals added at the Block-Level
  3. IO protocol signals added at the Port-Level
  4. IO protocol signals added externally as Pcore Interfaces
- **Data Ports**
  - These are the function arguments/parameters
- **Block-Level Interfaces (optional)**
  - An interface protocol which is added at the block level
  - Controls the addition of block level control ports: start, idle, done, and ready
- **Port-Level interfaces (optional)**
  - IO interface protocols added to the individual function arguments
- **Pcore interfaces (optional)**
  - Added as external adapters when exported as an IP

Vivado HLS Basic Ports

Adder Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;
        *sum = in1 + in2 + *sum;
         temp = in1 + in2;

        return  temp;
}
```



- **Clock added to all sequential RTL blocks**
  - One clock per function/block
  - SystemC designs may have a unique clock for each CTHREAD
- **Reset added to all sequential RTL blocks**
  - Only the FSM and any variables initialized in the C are reset by default
  - Reset and polarity options are controlled via the RTL Configuration
    - Solutions/Solution Settings...
- **Optional Clock Enable**
  - An optional clock enable can be added via the sequential RTL configuration
  - When de-asserted it will cause the block to “freeze”
    - All connected blocks are assumed to be using the same CE
    - When the IO protocol of this block freezes, it is expected other blocks do the same
    - Else a valid output may be read multiple times

Vivado HLS Optional IO : Function Arguments

Adder Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;
        *sum = in1 + in2 + *sum;
         temp = in1 + in2;

        return  temp;
}
```



- **Function Arguments**
  - Synthesized into data ports
- **Function Return**
  - Any return is synthesized into an output port called ap_return
- **Pointers (& C++ References)**
  - Can be read from and written to
  - Separate input and output ports for pointer reads and writes
- **Arrays (not shown here)**
  - Like pointers can be synthesized into read and/or write ports

Vivado HLS Optional IO : Block Level Protocol

Adder Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;
        *sum = in1 + in2 + *sum;
         temp = in1 + in2;

        return  temp;
}
```

Synthesis



- **Block Level Protocol**
  - An IO protocol added at the RTL block level
  - Controls and indicates the operational status of the block
- **Block Operation Control**
  - Controls when the RTL block starts execution (ap_start)
  - Indicates if the RTL block is idle (ap_idle) or has completed (ap_done)
- **Complete and function return**
  - The ap_done signal also indicates when any function return is valid
- **Ready (not shown here)**
  - If the function is pipelined an additional ready signal (ap_ready) is added
  - Indicates a new sample can be supplied before done is asserted

Vivado HLS Optional IO : Port IO Protocols

Adder Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;
        *sum = in1 + in2 + *sum;
         temp = in1 + in2;

        return  temp;
}
```

Synthesis



- **Port IO Protocols**
  - An IO protocol added at the port level
  - Sequences the data to/from the data port
- **Interface Synthesis**
  - The design is automatically synthesized to account for IO signals (enables, acknowledges etc.)
- **Select from a pre-defined list**
  - The IO protocol for each port can be selected from a list
  - Allows the user to easily connect to surrounding blocks
- **Non-standard Interfaces**
  - Supported in C/C++ using an arbitrary protocol definition
  - Supported natively in SystemC

Vivado HLS Interfaces Summary

- **Where do you find the summary?**
  - In the Synthesis report



Vivado HLS Optional IO : IP Adapters

Adder Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;

        *sum = in1 + in2 + *sum;
        temp = in1 + in2;

        return temp;
}
```

Synthesis



- Added when the IP block is exported
- Available in the IP directory
  - "ip", "sysgen" or "pcore"

Outline

- Introduction
- *Block Level Protocols*
- Port Level Protocols
- Summary

AP_START: Pulsed



- **Input Data**
  - Can be applied when ap_idle goes low
    - The first read is performed 1 clock cycle after idle goes low
  - Input reads can occur in any cycle up until the last cycle
- **Output Data**
  - Any function return is valid when ap_done is asserted high
  - Other outputs may output their data at any time after the first read
    - The output can only be guaranteed to be valid with ap_done if it is registered
    - It is recommended to use a port level IO protocol for other outputs

AP_START: Constant High



- **Input and Output data operations**
  - As before
- **The key difference here is that the design is never idle**
  - The next data read is performed immediately

Pipelined Designs



- After reset, ap_ready goes high if idle is high
- Start applied : Idle goes low, apply first data
- **Inputs will be read when ap_ready is high and idle is low**
- Output ap_done goes high on the final cycle
- Idle goes high one cycle after done
- The block waits for next start

- **Input Data**
  - Will be read when ap_ready is high and ap_idle is low
    - Indicates the design is ready for data
  - Signal ap_ready will change at the rate of the throughput
- **Output Data**
  - As before, function return is valid when ap_done is asserted high
  - Other outputs may output their data at any time after the first read
    - It is recommended to use a port level IO protocol for other outputs

This example shows an II of 2

Pipelined Designs: Throughput = 1



- Will start with ap_start
- Will keep reading input data since throughput = 1
- After the first output, ap_done will remain high
- If ap_start goes is sampled low, ap_ready will go low immediately

- **Input Data when TP=1**
  - It can be expected that ap_ready remains high and data is continuously read
  - The design will only stop processing when ap_start is de-asserted
- **Output Data when TP=1**
  - After the first output, ap_done will remain high while there are samples to process
    - Assuming there is no data decimation (output rate = input rate)

Disabling Block Level Handshakes

- **Block Level Handshakes can be disabled**
  - Select the function in the directives tab, right-click
    - Select Interface & then **ap_ctrl_none** for no block level handshakes
    - Select Interface & then **ap_ctrl_hs** to re-apply the default




```
# Tcl commands

set_directive_interface -mode ap_ctrl_none “dct“
# Default is on
# set_directive_interface -mode ap_ctrl_hs “dct“
```

- **Requirement: Manually verify the RTL**
  - Without block level handshakes autosim cannot verify the design
    - Will only work in simple combo and TP=1 cases
    - Handshakes are required to know when to sample output signals

It is recommended to leave the default and use Block Level Handshakes

AP_CTRL_CHAIN

- **Protocol to support pipeline chains: ap_ctrl_chain**
  - Similar to ap_ctrl_hs but with additional signal ap_continue
  - Allows blocks to be easily chained in a pipelined manner
  - ap_ctrl_chain protocol provides back-pressure in systems



AP_CTRL_CHAIN



- Asserting the ap_continue signal Low informs the design that the downstream block that consumes the data is not ready to accept new data
- When ap_continue is asserted Low, the design stalls when it reaches the final state of the current transaction: the output data is presented on the interface, the ap_done signal can be asserted High and the design remains in this state until ap_continue is asserted High

Outline

- Introduction
- Block Level Protocols
- *Port Level Protocols*
- Summary

Port Level IO protocols

- **We've seen how the function return is validated**
  - The block level output signal ap_done goes high to indicate the function return is valid
  - This allows downstream blocks to correctly sample the output port



- **For other outputs, Port Level IO protocols can be added**
  - Allowing upstream and downstream blocks to synchronize with the other data ports
  - The type of protocol depends on the type of C port
    - Pass-by-value scalar
    - Pass-by-reference pointers (& references in C++)
    - Pass-by-reference arrays

The starting point is the type of argument used by the C function

Let's Look at an Example

```
#include "adders.h"
int adders(int in1, int in2, int *sum) {

        int temp;

         *sum = in1 + in2 + *sum;
         temp = in1 + in2;

        return  temp;
}
```

"Sum" is a pointer which is read and written to : an Inout

The port for "Sum" can be any of these interface types

The default for port for "Sum" will be type ap_ovld

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface | Unsupported Interface

Key:
- I : input
- IO : inout
- O : output
- D : Default Interface

Interface Types

- **Multiple interface protocols**
  - Every combination of C argument and port protocol is not supported
  - It may require a code modification to implement a specific IO protocol

Key:
I : input
IO : inout
O : output
D : Default Interface

No IO Protocol

Wire handshake protocols

Memory protocols : RAM
: FIFO

Bus protocols

Block Level Protocol

Block level protocols can be applied to the return port - but the port can be omitted and just the function name specified

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface Unsupported Interface

Default IO Protocols

- **The default port protocols**
  - Inputs: ap_none
  - Outputs: ap_vld
  - Inout: ap_ovld
    - In port gets ap_none
    - Out port gets ap_vld
  - Arrays: ap_memory
  - All shown as the default (D) on previous slide
- **Result of the default protocols**
  - No protocol for input ports
    - They should be held stable for the entire transaction
    - There is no way to know when the input will be read
  - Output writes have an accompanying output valid signal which can be used to validate them
  - Arrays will default to RAM interfaces (2-port RAM is the default RAM)

The Vivado HLS shell/console always shows the results of interface synthesis

```
@I [RTGEN-500] Setting interface mode on port 'dct/input_r' to 'ap_memory'.
@I [RTGEN-500] Setting interface mode on port 'dct/output_r' to 'ap_memory'.
@I [RTGEN-100] Finished creating RTL model for 'dct'.
```

Specifying IO Protocols

- **Select the port in the Directives pane to specify a protocol**
  - Select the port
  - Right-click and choose Interface
  - Select the protocol from the drop-down menu
- **Or apply using Tcl or Pragma**



Interface Types

Multiple interface protocols

- Every combination of C argument and port protocol is not supported
- It may require a code modification to implement a specific IO protocol

Key:
I : input
IO : inout
O : output
D : Default Interface

No IO Protocol

Wire handshake protocols

Memory protocols : RAM
: FIFO

Bus protocols

Block Level Protocol

Block level protocols can be applied to the return port - but the port can be omitted and just the function name specified

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface Unsupported Interface

No IO Protocol

- **AP_NONE: The default protocol for input ports**
  - Protocol ap_none means that no additional protocol signals are added
  - The port will be implemented as just a data port
- **Other ports can be specified as ap_none**
  - Except arrays which must be a RAM or FIFO interface
- **AP_STABLE: An ap_none with fanout benefits**
  - The ap_stable type informs High-Level Synthesis that the data applied to this port remains stable during normal operation, but is not a constant value that could be optimized, and the port is not required to be registered
  - Typically used for ports that provides configuration data - data that can change but remains stable during normal operation (configuration data is typically only changed during or before a reset)

Interface Types

- **Multiple interface protocols**
  - Every combination of C argument and port protocol is not supported
  - It may require a code modification to implement a specific IO protocol

Key:
I : input
IO : inout
O : output
D : Default Interface

No IO Protocol

Wire handshake protocols

Memory protocols : RAM
: FIFO

Bus protocols

Block Level Protocol

Block level protocols can be applied to the return port - but the port can be omitted and just the function name specified

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface Unsupported Interface

Wire Protocols

- **The wire protocols add a valid and/or acknowledge port to each data port**
- **The wire protocols are all derivatives of protocol ap_hs**
  - ap_ack: add an acknowledge port
  - ap_vld: add a valid port
  - ap_ovld: add a valid port to an output
  - ap_hs: adds both
- **Output control signals are used to inform other blocks**
  - Data has been read at the input by this block (ack)
  - Data is valid at the output (vld)
  - The other block must accept the control signal (this block will continue)
- **Input control signals are used to inform this block**
  - The output data has been read by the consumer (ack)
  - The input from the producer is valid (vld)
  - **This block will stall** while waiting for the input controls

Wire Protocols: Ports Generated

- **The wire protocols are all derivatives of protocol ap_hs**
  - Inputs
    - Arguments which are only read
    - The valid is input port indicating when to read
    - Acknowledge is an output indicating it was read
  - Outputs
    - Arguments which are only written to
    - Valid is an output indicating data is ready
    - Acknowledge is an input indicating it was read
  - Inouts
    - Arguments which are read from and written to
    - These are split into separate in and out ports
    - Each half has handshakes as per Input and Output

ap_hs is compatible with AXI-Stream







Handshake IO Protocol



- *After start, idle goes low and the RTL operates <u>until a read is required</u>*
- The RTL will stall (wait) until the input valid is asserted
- If there is more than one input valid, each can stall the RTL
- It will acknowledge on the same cycle it reads the data (reads on next clock edge)
- An output valid is asserted when the port has data
- The RTL will stall (hold the data and wait) until an input acknowledge is received
- *Done will be asserted when the function is complete*

Other Handshake Protocols

- **The other wire protocols are derivatives of ap_hs in behavior**
  - Some subtleties are worth discussing when the full two-way handshake is **not** used
- **Using the Valid protocols (ap_vld, ap_ovld)**
  - Outputs: Without an associated input acknowledge it is a requirement that the consumer takes the data when the output valid is asserted
    - Protocol ap_ovld only applies to output ports (is ignored on inputs)
  - Inputs: No particular issue.
    - Without an associated output acknowledge, the producer does not know when the data has been read (but the done signal can be used to update values)
- **Using the Acknowledge Protocol (ap_ack)**
  - Outputs: Without an associated output valid the consumer will not know when valid data is ready but the design will stall until it receives an acknowledge (**Dangerous**: Lock up potential)
  - Inputs: Without an associated input valid, the design will simply read when it is ready and acknowledge that fact.

Registering IO Reads and Writes

- **Vivado HLS does not register Input and Outputs by default**
  - It will chain operations to minimize latency
  - The inputs will be read when the design requires them
  - The outputs will be written as soon as they are available



- **Inputs and outputs can be registered**
  - Inputs will be registered in the first cycle
    - Input pointers and partitioned arrays will be registered when they are required
  - Outputs will be registered and held until the next write operation
    - Which for scalars will be the next transaction (can't write twice to the same port) unless the block is pipelined



Interface Types

- **Multiple interface protocols**
  - Every combination of C argument and port protocol is not supported
  - It may require a code modification to implement a specific IO protocol

Key:
I : input
IO : inout
O : output
D : Default Interface

No IO Protocol

Wire handshake protocols

Memory protocols : RAM
: FIFO

Bus protocols

Block Level Protocol

Block level protocols can be applied to the return port - but the port can be omitted and just the function name specified

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface Unsupported Interface

Memory IO Protocols

- **Memory protocols can be inferred from array and pointer arguments**
  - Array arguments can be synthesized to RAM or FIFO ports
    - When FIFOs specified on array ports, the ports must be read-only or write-only
  - Pointer (and References in C++) can be synthesized to FIFO ports
- **RAM ports**
  - Support arbitrary/random accesses
  - May be implemented with Dual-Port RAMs to increase the bandwidth
    - The default is a Dual-Port RAM interface
  - Requires two cycles read access: generate address, read data
    - Pipelining can reduce this overhead by overlapping generation with reading
- **FIFO ports**
  - Require read and writes to be sequential/streaming
  - Always uses a standard FIFO (single-port) model
  - Single cycle for both reads and writes

Memory IO Protocols: Ports Generated

- **RAM Ports**
  - Created by protocol ap_memory
  - Given an array specified on the interface
  - Ports are generated for data, address & control
    - Example shows a single port RAM
    - A dual-port resource will result in dual-port interface
  - Specify the off-chip RAM as a Resource
    - Use the RESOURCE directive on the array port
- **FIFO Ports**
  - Created by protocol ap_fifo
  - Can be used on arrays, pointers and references
  - Standard Read/Write, Full/Empty ports generated
    - Arrays: must use separate arrays for read and write
    - Pointers/References: split into In and Out ports

```
#include "ram.h"
void ram (int d[DEPTH], ...) {
  ...
}
```


```
#include "fifo.h"
void fifo (int d_o[DEPTH],
           int d_i[DEPTH]) {

  ...
}
```

Memory IO Protocol (ap_memory)



- *After start, idle goes low and the RTL operates*
- When a read is required, an address is generated and CE asserted high
- Data is available on data input port d_q0 in the next cycle
- The read operations may be pipelined
- When a write is required, the address and data are placed on the output ports
- Both CE &WE are asserted high
- Writes may be pipelined
- *Done will be asserted when the function is complete*

There is no stall behavior initiated by a RAM interface

FIFO IO Protocol (ap_fifo, Read)



- *After start, idle goes low and the RTL operates <u>until a read is required</u>*
- The RTL will stall (wait) until the empty_n is asserted high to indicate data is available
- As soon as data is available, the fifo read port will go high
- Reads will occur when required, so long as data is available (empty_n is high)

FIFO IO Protocol (ap_fifo, Write)



- When ready, data will be written to the output port
- The RTL will then stall and hold the data until the FIFO is no longer full (full_n high)
- As soon as data can written, write is asserted high
- A write will occur when required if there is room in the fifo (full_n high)
- *Done will be asserted when the function is complete*

Interface Types

- **Multiple interface protocols**
  - Every combination of C argument and port protocol is not supported
  - It may require a code modification to implement a specific IO protocol

Key:
I : input
IO : inout
O : output
D : Default Interface

No IO Protocol

Wire handshake protocols

Memory protocols : RAM
: FIFO

Bus protocols

Block Level Protocol

Block level protocols can be applied to the return port - but the port can be omitted and just the function name specified

Argument Type	Variable			Pointer Variable			Array			Reference Variable		
	Pass-by- value			Pass-by-reference			Pass-by-reference			Pass-by-reference		
Interface Type	I	IO	O	I	IO	O	I	IO	O	I	IO	O
ap_none	D			D						D		
ap_stable												
ap_ack												
ap_vld						D						D
ap_ovld					D						D	
ap_hs												
ap_memory							D	D	D			
ap_fifo												
ap_bus												
ap_ctrl_none												
ap_ctrl_hs			D									
ap_ctrl_chain												

Supported Interface Unsupported Interface

Bus IO Protocol

- **Vivado HLS supports a Bus IO protocol**
  - It is that of a generic bus
    - Not an industry standard
  - Can be used to communicate with a bus bridge
  - The Vivado HLS bus protocol is principally used to connect to adapters
- **The Bus IO protocol supports memcpy**
  - The bus IO protocol supports the C function memcpy
  - This provides a high performance interface for bursting data in a DMA like fashion
- **The Bus IO protocol supports complex pointer arithmetic at the IO**
  - Pointers at the IO can be synthesized to ap_fifo or ap_bus
    - If using ap_fifo, the accesses must be sequential
    - If pointer arithmetic is used, the port must use ap_bus

Standard and Burst Mode

Standard Mode

- Each access to the bus results in a request then a read or write operation
- Multiple read or writes can be performed in a single transaction

Single read and write in Standard Mode

```
void foo (int *d) {
  static int acc = 0;
  int i;

    acc += d[i];
    d[i] = acc;
}
```

Multiple reads and writes in Standard Mode

```
#in
void foo (int *d) {
  static int acc = 0;
  int i;

  for (i=0;i<4;i++) {
    acc += d[i];
    d[i] = acc;
  }
}
```

```
void foo (int *d) {
  static int acc = 0;
  int i;

  for (i=0;i<4;i++) {
    acc += *(d+i);
    *(d+i) = acc;
  }
}
```

Burst Mode

- Use the memcpy command
- Copies data between array & a pointer argument
- The pointer argument can be a bus interface
  - This example uses a size of 4
  - This is more efficient for higher values

Burst Mode

```
void foo (int *d) {
  int buf1[4], buf2[4];
  int i;

  memcpy(buf1,d,4*sizeof(int));

  for (i=0;i<4;i++) {
    buf2[i] = buf1[3-i];
  }

  memcpy(d,buf2,4*sizeof(int));
}
```

Bus IO Protocol: Ports Generated

- **Bus request then access protocol**
  - The protocol will request a read/write bus access
  - Then read or write data in single or burst mode

```
#include “foo.h"

void foo (int *d) {
  …
}
```



Input Ports	Description
d_datain	Input data.
d_req_full_n	Active low signal indicates the bus bridge is full. The design will stall, waiting to write.
d_rsp_empty_n	Active low signal indicates the bus bridge is empty and can accept data.

Output Ports	Description
d_dataout	Output data.
d_req_write	Asserted to initiate a bus access.
d_req_din	Asserted if the bus access is to write. Remains low if the access it to read.
d_rsp_read	Asserted to start a bus read (completes a bus access request and starts reading data)
d_address	Offset for the base address.
d_size	Indicates the burst (read or write) size.

Standard Mode: The address port gives the index address e.g. *(d+i), addr = value of “i”

Bus IO Protocol (Standard, Read)

```
void foo (int *d) {
    static int acc = 0;
    int i;
    for (i=0;i<4;i++) {
        acc += d[i+1];
        d[i] = acc;
    }
}
```



- *After start, idle goes low and the RTL operates <u>until a read is required</u>*
- A req_write high with req_din low indicates a read request
- A read address is supplied: value is the pointer index value
- The RTL will stall (wait) until the empty_n is asserted high to indicate data is available
- As soon as data is available, rsp_read will go high
- Reads will occur when required, so long as data is available (empty_n is high)

Bus IO Protocol (Standard, Write)

```
void foo (int *d) {
    static int acc = 0;
    int i;
    for (i=0;i<4;i++) {
        acc += d[i+1];
        d[i] = acc;
    }
}
```



- *After start, idle goes low and the RTL operates <u>until a write is required</u>*
- When a write is required, data and address are applied
- The RTL will stall (wait) until the full_n is asserted high to indicate space is available
- As soon as data is available, rsp_write and req-din will go high
- A req_write high with req_din high indicates a write request
- There is no acknowledge for writes in this interace
- Write will occur when required, so long as data is available (full_n is high)

Bus IO Protocol (Burst, Read)

```
void foo (int *d) {
    int buf1[4], buf2[4];
    int i;
    memcpy(buf1,d,4*sizeof(int));

    for (i=0;i<4;i++) {
          buf2[i] = buf1[3-i];
     }
     memcpy(d,buf2,4*sizeof(int));
}
```



- *Similar to a Standard Mode*
- *This example uses a burst=4*

- The base address is zero
- The burst size is placed on port size

- All reads are done consecutively
- The empty_n signal will stall the RTL until data is available

Bus IO Protocol (Burst, Write)

```
void foo (int *d) {
    int buf1[4], buf2[4];
    int i;
    memcpy(buf1,d,4*sizeof(int));

    for (i=0;i<4;i++) {
          buf2[i] = buf1[3-i];
     }
     memcpy(d,buf2,4*sizeof(int));
}
```



- *Similar to a Standard Mode*
- *This example uses a burst=4*

- The base address is zero
- The burst size is placed on port size

- All writes are done consecutively
- The full_n signal will stall the RTL until data is available

Outline

- Introduction
- Block Level Protocols
- Port Level Protocols
- *Summary*

Summary

- **Vivado HLS has four types of IO**
  - Data ports created by the original C function arguments
  - IO protocol signals added at the Block-Level
  - IO protocol signals added at the Port-Level
  - IO protocol signals added externally as Pcore Interfaces
- **Block Level protocols provide default handshake**
  - Block Level handshakes are added to the RTL design
  - Enables system level control & sequencing
- **Port Level Protocols provide wide support for all standard IO protocols**
  - The protocol is dependent on the C variable type