

Keycloak Integration with Transact Explorer

Title	Keycloak integration with transact explorer.
Client	Tamweel Aloula
Author	Hamza Ur Rahman
Version	1.1
Last updated	2026-02-09

Keycloak Integration with Transact Explorer	1
Pre-requisites:	3
Configuring Keycloak Server.....	3
Adding a Realm.....	3
Generating Encoded Public Key	4
Configuring LDAP	10
Configuring email verification (OPTIONAL)	12
Configuring API war (tb-server.war).....	14
Wb-INF property:	14
JWTTokenValidator Filter	14
JWT Algorithm.....	15
Validating Signature	15
Validating Claims.....	16
Extracting Claim	17
Clock Skewness (Clock difference)	17
IDP Server Details	17
User Principle	18
Configuring UI war (transact-explorer-wa.war)	18
WEB-INF Property	18
WEB-INF/classes/spring-oidc-authenticator.xml	18
Configuring Users in Transact	20

Pre-requisites:

1. Both Keycloak and Transact endpoints must be accessible only over HTTPS. HTTP must be disabled or redirected to HTTPS, and all redirects/callback URLs must use https://.


Configuring Keycloak Server

To configure the Keycloak server, ensure that you have access to the Keycloak admin console.

Adding a Realm

To add a Realm,

1. Log in to Keycloak admin console using the default credentials.
2. Enter the necessary details and create a realm named 'transact' (or create it with any name but make sure it is used in all other places in the below sections appropriately).



The screenshot shows the Keycloak Admin Console interface. On the left is a sidebar with a menu including 'Transact', 'Configure', 'Realm Settings', 'Clients', 'Client Scopes', 'Roles', 'Identity Providers', 'User Federation', 'Authentication', 'Manage', 'Groups', 'Users', 'Sessions', 'Events', 'Import', and 'Export'. The main panel is titled 'Transact' and has tabs for 'General', 'Login', 'Keys', 'Email', 'Themes', 'Localization', 'Cache', 'Tokens', 'Client Registration', 'Client Policies', and 'Security Defenses'. The 'General' tab is active, showing configuration fields: 'Name' (transact), 'Display name' (transact), 'HTML Display name' (transact), 'Frontend URL' (empty), 'Enabled' (ON), 'User-Managed Access' (OFF), and 'Endpoints' (OpenID Endpoint Configuration, SAML 2.0 Identity Provider Metadata). 'Save' and 'Cancel' buttons are at the bottom.

3. After creating the realm, go to the **Keys** tab and note down the Public Key text for the RS256 algorithm.



You have now successfully added a Realm.


Generating Encoded Public Key

Copy the above RSA Public Key and follow the below instructions:

1. Go to <http://www.utilities-online.info/base64/#.X5ay8m5uJpw>.
2. Paste the copied RSA Public Key in the left textbox and click **Encode**. On right side, you could see base64 encoded key generated.
3. Note down this encoding public key, which needs to be placed in the XML files of WARs.

Base64 encoder/decoder online

In this page you can encoder or decoder in Base64 a string and viceversa.




You have now successfully generated an encoded public key.


Adding Client

To add a client to the created realm,

1. On the left-navigation pane, select **Transact** > **Clients**.
2. On the **Clients** pane, click **Create**. The Add Client page appears.



3. Enter the following details and click **Save**:
 - a. Client ID as TransactExplorer.
 - b. Client Protocol as openid-connect.



You have successfully created the Transact Explorer client.

4. On the TransactExplorer page, navigate to the **Settings** tab, enter the details (shown in the screenshot), and click **Save**.

KEYCLOAK

Transact

Configure

- Realm Settings
- Clients**
 - Client Scopes
 - Roles
 - Identity Providers
 - User Federation
 - Authentication

Manage

- Groups
- Users
- Sessions
- Events
- Import
- Export

Clients > TransactExplorer

TransactExplorer

Settings Keys Roles Client Scopes Mappers Scope Revocation Sessions Offline Access Installation

Client ID TransactExplorer

Name TransactExplorer

Description TransactExplorer

Enabled ON

Always Display in Console OFF

Consent Required OFF

Login Theme

Client Protocol openid-connect

Access Type public

Standard Flow Enabled ON

Implicit Flow Enabled OFF

Direct Access Grants Enabled ON

OAuth 2.0 Device Authorization Grant Enabled OFF

Front Channel Logout OFF

Root URL http://localhost:9089/transact-explorer-wa

* Valid Redirect URIs http://localhost:9089/transact-explorer-wa/*

Base URL

Base URL

Admin URL http://localhost:9089/transact-explorer-wa/

Logo URL

Policy URL

Terms of service URL

Web Origins http://localhost:9089

Backchannel Logout URL

Backchannel Logout Session Required ON

Backchannel Logout Revoke Offline Sessions OFF

> Fine Grain OpenID Connect Configuration

> OpenID Connect Compatibility Modes

> Advanced Settings

> Authentication Flow Overrides

Save Cancel

5. Navigate to the **Mappers** tab to create a new mapper with 't24son' as a user attribute.

KEYCLOAK

Clients > TransactExplorer > Mappers > t24 user details

T24 User Details

Protocol openid-connect

ID 5d462155-b83a-4122-8de3-9ff6604ef18a

Name t24 user details

Mapper Type User Attribute

User Attribute t24son

Token Claim Name t24son

Claim JSON Type String

Add to ID token ☒ ON

Add to access token ☒ ON

Add to userinfo ☒ ON

Multivalued ☐ OFF

Aggregate attribute values ☐ OFF

You have successfully created the Transact Explorer client and added the user attribute.

Adding Users

To add users in Keycloak,

1. On the left-navigation pane, select Users. The User pane appears.
2. Click **Add user** to create new users.

RED HAT SINGLE SIGN-ON Admin

Transact-dev

Configure

- Realm Settings
- Clients
- Client Scopes
- Roles
- Identity Providers
- User Federation
- Authentication

Manage

- Groups
- Users**
- Sessions
- Events
- Import
- Export

Users

ID	Username	Email	Last Name	First Name	Actions
d40867a2-9185-49fb-9fe6...	farhan01	farhan@gmail.com	khan	farhan	Edit Impersonate Delete
0ae49376-1025-4b72-8f2e...	hamza02	hamza.rahman@systemsit...	Rahman	Hamza Ur	Edit Impersonate Delete
4d64533e-9043-4100-9057...	test1	test@test.com	test	test	Edit Impersonate Delete
2532d57d-0c7d-413c-94f2...	wajahat.ali	wajahat.ali@tamilweelaloula...	ali	wajahat	Edit Impersonate Delete
651215a2-dc41-42e6-873b...	wajahat01	wajahat@test.com	wajahat	wajahat	Edit Impersonate Delete

3. In the user page, enter the username and first name, and click **Save**.

Hamza02 

Details | Attributes | **Credentials** | Role Mappings | Groups | Consents | Sessions

ID

0ae49376-1025-4b72-8f2e-83d1d8999b56

Created At

2/9/26 11:54:24 AM

Username

hamza02

Email

hamza.rahman@systems ltd.com

First Name

Hamza Ur

Last Name

Rahman

User Enabled ?

ON

Email Verified ?

OFF

Required User Actions ?

✕ Update Password

✕ Verify Email

Impersonate user ?

Impersonate

Save

Cancel

4. Edit the user and go to the **Attributes** tab to add the t24son attribute. t24son name should be same as the sign-on name of the USER applications in Transact. For example, if user **sign.on** name is HAMZA02 the value against t24son should be same(HAMZA02)

KEYCLOAK

Transact

Configure

- Realm Settings
- Clients
- Client Scopes
- Roles
- Identity Providers
- User Federation
- Authentication

Manage

- Groups
- Users**
- Sessions
- Events
- Import
- Export

Users: 1 author

Author

Details | **Attributes** | Credentials | Role Mappings | Groups | Consents | Sessions

Key	Value	Actions
t24son	AUTHOR	Delete
		Add

Save

Cancel

After saving the changes, the **Credentials** tab appears.

5. Navigate to the **Credentials** tab and set the password for the user. Keep the Temporary toggle ON to enable the user to reset the password on first login.

Users > ssouser

Ssouser

Details Attributes **Credentials** Role Mappings Groups Consents Sessions

Manage Credentials

Position	Type	User Label	Data
Set Password			

Password

Password Confirmation

Temporary ☒ ON

Set Password

6. Navigate to the **Role Mappings** tab and add all the Available Roles into Assigned Roles.

Users > hamza02

Hamza02

Details Attributes Credentials **Role Mappings** Groups Consents Sessions

Realm Roles

Available Roles ⓘ

Add selected >

Assigned Roles ⓘ

default-roles-transact-dev

« Remove selected

Effective Roles ⓘ

default-roles-transact-dev
offline_access
uma_authorization

Client Roles

Select a client...

You have now successfully created a user, added the attribute, and assigned necessary roles to the user.

Configuring LDAP

To perform authentication using LDAP please follow the steps bellow:

Navigate to user federation -> add provider -> ldap

RED HAT SINGLE SIGN-ON

Transact-dev

Configure

- Realm Settings
- Clients
- Client Scopes
- Roles
- Identity Providers
- User Federation**
- Authentication

Manage

- Groups
- Users
- Sessions
- Events

User Federation

ID	Enabled	Provider Name	Priority	Actions
ldap	true	Ldap	0	Edit

Add provider...

Add provider...

kerberos

ldap

in settings, fill out the fields as following and test the connection and authentication:

User Federation > Ldap

Ldap

Settings Mappers

Required Settings

Provider ID: f70f2b4a-80ac-4c63-bd29-813572c1a8cf

Enabled: ON

Console Display Name: ldap

Priority: 0

Import Users: ON

Edit Mode: READ_ONLY

Sync Registrations: ON

* Vendor: Active Directory

* Username LDAP attribute: sAMAccountName

* RDN LDAP attribute: cn

* UUID LDAP attribute: objectGUID

* User Object Classes: *

* Connection URL: ldap://vm-tam-dc.tamweel-aloula.com:389

Test connection

* User Object Classes ?	*	
* Connection URL ?	ldap://vm-tam-dc.tamweel-aloula.com:389	Test connection
* Users DN ?	DC=Tamweel-Aloula,DC=com	
Custom User LDAP Filter ?	(sAMAccountName=*)	
Search Scope ?	Subtree	
* Bind Type ?	simple	
* Bind DN ?	CN=Ldap User,CN=Managed Service Accounts,DC=Tamweel-Aloula,DC=com	
* Bind Credential ?	*****	Test authentication

After the connection and authentication is successful, navigate to mappers and create a mapper as shown bellow:

[User Federation](#) > [Ldap](#) > [LDAP Mappers](#) > t24son-from-sAMAccountName


T24son-from-sAMAccountName 

ID	b205bdc0-cab4-44ae-a790-f3a9840aab61
Name *	t24son-from-sAMAccountName
Mapper Type	user-attribute-ldap-mapper
User Model Attribute	t24son
LDAP Attribute	sAMAccountName
Read Only	☒ ON
Always Read Value From LDAP	☒ ON
Is Mandatory In LDAP	☐ OFF
Attribute default value	
Is Binary Attribute	☐ OFF
	Save Cancel


after configuring LDAP user can login with LDAP credentials but the same user must exist in transact and “preauthenticated” attribute is set on that user.

Configuring email verification (OPTIONAL)

Email verification can be turned on in Realm setting as shown bellow.



But only this options won't be able to send the email, we need to do the SMTP server configuration in the bellow section:



After making the required settings above these conditions must be true:

- The user record in Keycloak has a valid Email value (Users -> user -> Details -> Email).
- “Verify Email” is enabled as a Required Action (Authentication -> Required Actions -> Verify Email enabled) or you manually click “Send Verify Email” for the user.
- SMTP “Test connection” succeeds.

- Keycloak can reach the SMTP host/port from OKE (no NSG/Security List/NetworkPolicy blocking egress).
- The SMTP server accepts your “From” address and credentials (if authentication is enabled).

Configuring API war (tb-server.war)

Transact Browser uses IRIS framework internally to connect with Transact. Configuration of JWT is almost same as IRIS framework.

Wb-INF property: please add bellow property in JAVA-OPTS for app.

-Dcom.temenos.te.api.enableJWTtokenFilter=true

```
APP_JAVA_OPTS: "-XX:MetaspaceSize=96M
-XX:MaxMetaspaceSize=1024m
-Djava.net.preferIPv4Stack=true
-Djboss.modules.system.pkgs=org.jboss.byteman
-Djava.awt.headless=true
-Xms4G -Xmx6G
-Dtemn.msf.stream.vendor.outbox=kafka
-Dclass.outbox.dao=com.temenos.inboxoutbox.data.sql.OutboxDaoImpl
-Dtemn.outbox.events.delivery.direct=true
-Dtemn.msf.ingest.is.cloud.event=true
-Dtemn.msf.stream.kafka.bootstrap.servers=10.100.4.23:32092
-Dtemn.msf.disable.outbox.cleanup=true
-Dtemn.msf.producer.max.block=2000
-Dcom.temenos.te.api.cors.allow.origin=https://t24app-dev.nonprod-oke.tamweel-aloula.com/
-Dtemn.outbox.retry.count=0
-Dcom.temenos.te.api.helpTextLocation=/opt/HELP.TEXT/HelpText
-Diris.startup.warmup.onload=true
-Diris.startup.aawarmup.onload=true
-Diris.warmup.meta.api.companyid=SA0011001
-Dcom.temenos.te.api.enableJWTtokenFilter=true"
```

The following sections describe the changes that need to be made in **tb-server.war\WEB-INF\classes\spring-jwt-iris-authentication.xml**.

JWTTokenValidator Filter

Enable the JWTTokenValidator filter.

```

1 <?xml version="1.0" encoding="UTF-8"?>
2 <beans xmlns="http://www.springframework.org/schema/beans" xmlns:security="http://www.springframework.org/schema/security"
3       xmlns:context="http://www.springframework.org/schema/context" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
4       xsi:schemaLocation="http://www.springframework.org/schema/beans
5                           http://www.springframework.org/schema/beans/spring-beans.xsd
6                           http://www.springframework.org/schema/security
7                           http://www.springframework.org/schema/security/spring-security.xsd
8                           http://www.springframework.org/schema/context
9                           http://www.springframework.org/schema/context/spring-context.xsd">
10
11
12 <context:component-scan base-package="com.temenos.security.oidc, com.temenos.irf.web.security.jwt.parser" />
13 <context:spring-configured />
14
15 <security:http entry-point-ref="authenticationEntryPoint">
16   <security:custom-filter after="BASIC_AUTH_FILTER" ref="jwtTokenValidationFilter" />
17   <security:session-management>
18     <security:concurrency-control max-sessions="1" />
19   </security:session-management>
20   <security:csrf disabled="true"/>
21   <security:anonymous enabled="false"/>
22   <!-- Uncomment the below tag to enable the CORS mechanism using Spring configuration
23   <security:cors configuration-source-ref="corsSource"/> -->
24 </security:http>
25
26 <beans:bean id="corsSource" class="org.springframework.web.cors.UrlBasedCorsConfigurationSource">
27   <beans:property name="corsConfigurations">
28     <beans:map>
29       <beans:entry key="/**">
30         <beans:bean class="org.springframework.web.cors.CorsConfiguration">

```

Please ensure this custom-filter is enabled to authenticate the JWT token. By default this would be enabled.

JWT Algorithm

Add the idTokenSignedAlg property.

The token is validated against the algorithm provided in the configuration and the original value available in the JWT token. If the two values mismatch, Transact browser server ignores the request and sends unauthorized response back.

```
<beans:property name="idTokenSignedAlg" value="RS256" />
```

It is assumed that the token is having the RS256 algorithm and value is updated accordingly.

```

<!-- Start Relying Party -->
<beans:bean id="relyingPartyConfig" class="com.temenos.security.oidc.common.RelyingPartyConfig">
  <beans:property name="RelyingPartyClientMap">
    <beans:map>
      <beans:entry key="iris" value-ref="relyingPartyClientTE" />
    </beans:map>
  </beans:property>
  <beans:property name="currentRP" value="iris" />
</beans:bean>

<beans:bean id="relyingPartyClientTE" class="com.temenos.security.oidc.common.RelyingPartyClient">
  <beans:property name="idTokenSignedAlg" value="RS256" />
</beans:bean>
<!-- END Relying Party -->

```

Validating Signature

You can enable or disable the signature validation feature using the below property. By default, this property is set to False. To enable the signature validation, set the below property to true.

```
<beans:property name="idTokenSigned" value="true" />
```



Validating Claims

You can validate the claims that are present in the JWT token. ClaimValidator is a generic validator for various claims available in the token, where each instance of the ClaimValidator would validate one specific claim. The claim that needs to be validated is injected into the instance.

The following are the claims' default validators are supported for.

- exp
- iss
- iat

Add the claims in the below section to validate them.

```

spring-jwt-iris-authenticator.xml
85      <beans:property name="idTokenSigned" value="true" />
86    </beans:bean>
87
88    <beans:bean id="customSignature" class="com.temenos.irf.web.security.jwt.validator.CustomSignatureValidator"/>
89
90    <!-- Validations -->
91    <!-- Default claims validated are "exp", "iss", "iat" -->
92    <beans:bean id="claim" class="com.temenos.security.oidc.token.validator.ClaimValidator">
93      <beans:property name="claims">
94        <beans:list>
95          <beans:ref bean="exp" />
96          <beans:ref bean="iss" />
97          <beans:ref bean="iat" />
98        </beans:list>
99      </beans:property>
100    </beans:bean>
101

```

specify the claims available in JWT token for validation

Extracting Claim

Comment the claims mentioned in the below screenshot.

Claims specified in the below highlighted section are extracted from JWT token and set in request header. Transact Browser does not require any such token to be extracted and set in request header.

```

spring-jwt-iris-authenticator.xml
124    the jwt claim,
125    and value indicates if this claim needs to be mapped to any other user defined header names -->
126    <beans:bean id="requiredFields" class="com.temenos.irf.web.security.jwt.parser.RequiredFieldsExtractor">
127      <beans:property name="claimsToExtract">
128        <beans:map>
129          <!-- <beans:entry key="OsToken" value="OsToken" /> -->
130          <!-- <beans:entry key="DefaultCompany" value="DefaultCompany" /> -->
131        </beans:map>
132      </beans:property>
133    </beans:bean>
134    <!-- End Claims Extraction -->

```

Comment these lines

Clock Skewness (Clock difference)

There are cases where time difference (in seconds advanced or delayed) can occur between the JWT token provider and the server in which Transact Browser Server is deployed. You can configure the Transact Browser Server to ignore a specific amount of time difference (in seconds). You can configure this using the below property (in seconds). The default value is zero.

<beans:property name="expiryDelayAllowance" value="0" />

```

spring-jwt-iris-authenticator.xml
72
73    <!-- OIDC Authenticator -->
74
75    <beans:bean id="oidcAuthenticatorConfig" class="com.temenos.security.oidc.common.OidcAuthenticatorConfig">
76      <beans:property name="authHeaders">
77        <beans:set>
78          <beans:value>Authorization</beans:value>
79        </beans:set>
80      </beans:property>
81      <beans:property name="expiryDelayAllowance" value="0" />
82    </beans:bean>
83

```

IDP Server Details

User Principle

Transact Browser Server requires a SIGN.ON.NAME to connect with Transact. You can specify the claim name, in which the sign-on name of Transact is available. Here, you have specified the 't24son' claim, where Transact sign-on name is available.

Sign-on name and username are different in Transact. Principle claim should hold the sign-on name of the Transact user instead of the username.

```
<!-- OIDC provider Server -->
<beans:bean id="oidcProviderServer" class="com.temenos.security.oidc.common.OidcProviderServer">
  <beans:property name="issuer" value="https://rhpm-uat.tamweel-aloula.com:643/auth/realms/transact-dev" />
  <beans:property name="pkEncoded" value="
TUIJQk1qQU5CZ2tkaGtpRz13MEJBuUVGQFPQ0FR0EFNSU1CQ24LQ0FRUFsTUE4OFZteWYrQW1Ob1V6K1lKbzhWYV10REZ5am5RaUF2RTZlNEh2Zk50bC9WKzNGMlFQVG1lYWNPZWRRhOUhVODF6WT1hY1
gxY3Q3xRGYm10WgdVzcrRHQxQ2pjQzZlajJGSUV6eHNaczNlZ0FUS0xPWXk1Z3RjOUM2Mk5jUFBYkVnRkNNclJabHZkeVFBTTZsOHZBZG9Dazg4YnBPZWdDQULYSkxKZk9XMSwRmxIcTNYbXBpdzJkQ
00xY3RubTdaZVVxc0JoU1kwVVVUU9DeWdJZmlten1sbz14aTdOTnB5WGVTeK42Rz1zTXgrZHNuWFZHRUY3Y2xFWnZORFUzMS9YQnd5NHhRL1VVSkhXbUvVn9FYnpXWHF0Uk1yS0kaG1TRUh1VkY4ZkFO
Ri9WRVksN09zN3ZNaHprendUejBOQ3dCSkNSbXRGMhVbUJZSXdJREFRQUI=" />
  <beans:property name="pkCertEncoded" value="" />
  <beans:property name="pkCertFilePath" value="" />
  <beans:property name="pkJwsUri" value="" />
  <beans:property name="decryptingJwkEncoded" value="" />
  <beans:property name="principalClaim" value="t24son" />
</beans:bean>
<!-- End OIDC provider Server -->
```

Configuring UI war (transact-explorer-wa.war)

Configuring the **transact-explorer-wa.war** file involves the below-mentioned changes in the **web.xml** and **spring-oidc-authenticator.xml** files.

WEB-INF Property:

Please add below mentioned property in JAVA_OPTS of web:

-Dcom.temenos.te.ui.enableOpenIdConnectFilter=Y

```
WEB_JAVA_OPTS: "-XX:MetaspaceSize=96M
-XX:MaxMetaspaceSize=1024m
-Djava.net.preferIPv4Stack=true
-Djboss.modules.system.pkgs=org.jboss.byteman
-Dcom.temenos.te.ui.tbServerUrl=https://t24app-dev.nonprod-oke.tamweel-aloula.com/tb-server
-Dcom.temenos.te.ui.sessionTimeout=30
-Dcom.temenos.te.ui.commandLineEnable=true
-Dcom.temenos.te.ui.fileUploadPath=/shares/tafjud/UPLOADS/
-Dcom.temenos.te.ui.CrossDomainPolicyValue=none
-Djava.awt.headless=true
-Xms4G -Xmx6G
-Dcom.temenos.te.ui.enableOpenIdConnectFilter=Y"
```

WEB-INF/classes/spring-oidc-authenticator.xml

Perform the below configurations:

- Set the serverLogoutParameter tag to 'logouturl' in case of SSO. By default, this tag is set to 'commonAuthLogout'.

```
<beans:bean id="oidcAuthenticatorConfig" class="com.temenos.security.oidc.common.OidcAuthenticatorConfig">
  <beans:property name="authHeaders">
    <beans:set>
      <beans:value>Authorization</beans:value>
    </beans:set>
  </beans:property>
  <beans:property name="ignoredUriPatterns">
    <beans:set>
      <beans:value></beans:value>
    </beans:set>
  </beans:property>
  <beans:property name="useRefreshToken" value="true" />
  <beans:property name="savedIdTokenParam" value="savedIdToken" />
  <beans:property name="savedRefreshTokenParam" value="savedRefreshToken" />
  <beans:property name="queryParameter" value="queryParameter" />
  <beans:property name="tokenEndpointTimeout" value="10000" />
  <beans:property name="expiryDelayAllowance" value="0" />
  <beans:property name="tokenIdleTimeout" value="-1" />
  <beans:property name="enableSessionInvalidate" value="true" />
  <!-- commonAuthLogout is the logout parameter specific to wso2 Identity server as per the specification to clear the registered commonAuthId cookie during initial authentication.
  The logout parameter variable (commonAuthLogout) may vary for different identity servers. Hence the variable is parameterized. If required, please update the correct parameter value based on the identity server used.
  In order to use logout url to kill the session at Identity server use the value as "logouturl" then only logoutEndpoint will taken into consideration for logout mechanism.
  Don't forget to provide logoutEndpoint url when you specific the value as "logouturl" -->
  <beans:property name="serverLogoutParameter" value="logouturl" />
</beans:bean>
```

Logout URL should be configured as "logoutredirect" for keycloak above 18 releases.

Logout URL should be configured as "logouturl" for keycloak below 18 releases.

- Set the properties under 'oidcProviderServerTE' as shown in the below screenshot. You can get the Issuer and Endpoints URL from the metadata file.
- Set the value of the pkEncoded property to the encoded public key. Refer to the [Generating Encoded Public Key](#) section.
- Set the principalClaim property to t24son.

```
<!-- OIDC provider Server Updated on 1252026 by HAMZA -->

<beans:bean id="oidcProviderServerTE" class="com.temenos.security.oidc.common.OidcProviderServer">
  <beans:property name="issuer" value="https://rhpam-uat.tamweel-aloula.com:643/auth/realms/transact-dev" />
  <beans:property name="authzEndpoint" value="https://rhpam-uat.tamweel-aloula.com:643/auth/realms/transact-dev/protocol/openid-connect/auth" />
  <beans:property name="tokenEndpoint" value="https://rhpam-uat.tamweel-aloula.com:643/auth/realms/transact-dev/protocol/openid-connect/token" />
  <beans:property name="logoutEndpoint" value="https://rhpam-uat.tamweel-aloula.com:643/auth/realms/transact-dev/protocol/openid-connect/logout" />
  <beans:property name="pkEncoded" value="
  "TUIJQk1qU5CE2txaGtpRz13MEJBuUUVGQUPFQ0FROEFNSU1CQ2dLQ0FRRUFTsTUE4OFZteWYrQW10b1V6K11KbzhWYV10REZ5am5RaUF2RTZ1NEh2Zk50bC9WKzNGM1FQVG1iYWNFZWRR0UhuVODF6WT1hY1
  gxYkw3QzR0Ym10WGdnVzsrRHQxQ2pjQzZiajJGSTV6eHNacozN1Z0FUS0xPWXk1Z3RjOUM2Mk5jUFBYYkVnRkN0clJabHZkeVFBTTZzOHBBZG9Darg4YnBPZWdQU1Y9kKZk9XMSwRmXicTNYbXBpdsJkQ
  00xY3RubTdaZVvXc0J0U1kVwVVSU9DeWdJ2mtlenlsbzl4aTd0TnB5WGVTEk42Rz1zTXgrZHNuWFZRRUY3Y2xPwNORFVzMS9YQnd5NHhRL1VVSkhXbUVAvm9FYnpXWHF0UklyS0tkaG1TRUhl1VY4ZkFO
  Ri9WRVks5N09zN3ZNaHprendUeJBOQ3dC5kNSbXRGdmhVbUJZSXdJREFRQUi=" />
  <beans:property name="pkCertEncoded" value="" />
  <beans:property name="pkCertFilePath" value="" />
  <beans:property name="pkCertFilePath" value="" />
  <beans:property name="pkJwksUri" value="" />
  <beans:property name="decryptingJwkEncoded" value="" />
  <beans:property name="principalClaim" value="t24son" />
</beans:bean>
<!-- End OIDC provider Server -->

<!-- Relying Party -->
```

- Under relyingPartyClientTE, set the following properties:

clientId as TransactExplorer (this is the name of client created under Keycloak).

redirectUri as <http://<host>:<port>/transact-explorer-wa>.

idTokenSignedAlg as R256.

```

<!-- HAMZA Updated on 1252026 -->
<beans:bean id="relyingPartyClientTE" class="com.temenos.security.oidc.common.RelyingPartyClient">
  <beans:property name="tokenEndpointAuthMethod" value="" />
  <beans:property name="grantType" value="AUTHORIZATION_CODE" />
  <beans:property name="scope" value="openid profile" />
  <beans:property name="clientId" value="TransactExplorer" />
  <beans:property name="redirectUri" value="https://t24web-dev.nonprod-oke.tamweel-aloula.com/transact-explorer-wa" />
  <beans:property name="idTokenSignedAlg" value="RS256" />
  <beans:property name="idTokenEncryptedAlg" value="" />
</beans:bean>

<beans:bean id="defaultClientSecretProvider" class="com.temenos.security.oidc.filter.DefaultClientSecretProvider">
  <beans:constructor-arg value="" />
</beans:bean>

<!-- END Relying Party -->

```

Configuring Users in Transact

Transact must know that authentication is performed outside Transact, that is in IDP or Web service layer, so that Transact does not perform the usual credential validation for the user. You need to set the PREAUTHENTICATED attribute for the user in Transact. The T24son user attribute set to Keycloak users should match with the **Sign-On** name in Transact.

USER, / AUTHORISER

Rpt To Receive 1

Rpt Copies 1

Last Spool Date 1

Last Spool Time 1

Amount Format

☐ Global User

Max Sessions

Attributes 1
Superuser

Attributes 2
Preauthenticated

Dispo Officer

Dispo Rights 1

Sign On Item 1

Sign Off Item

Process Plant 1

USER, 1 AUTHORISER

USER, X