DongHwa Entec

DESIGN DATE LIST

CUSTOMER	R.S.H.I
SHIP NO.	H1149/50/51/52/53
CLASS	ABS
ITEM NAME	45M³ Tank Cleaning Heater (1set/ship)

1. DESIGN DATE

H/EXCHANGER TYPE	SHELL & TUBE	
	SHELL SIDE	TUBE SIDE
FLUID	STEAM	S.W
FLOW RATE	18271.3 (Kg/hr)	180 (m³/hr)
INLET TEMP.	164.2 (℃)	20 (℃)
OUTLET TEMP.	90 (℃)	80 (℃)
OPERATING PRESS.	6.0 (Kg/cm² G)	16.0 (Kg/cm² G)
DESIGN PRESS.	7.0 (Kg/cm² G)	17.0 (Kg/cm² G)
HYDRO'C TEST PRESS.	10.50 (Kg/cm² G)	25.5 (Kg/cm² G)
VELOCITY	- (m/sec)	1.55 (m/sec)
PRESSURE DROP.	- (Kg/cm² G)	0.30 (Kg/cm² G)
NO. OF PASS	1	2
CLEANLINESS FACTOR (%)	85	
JOINT EFFICIENCY (%)	70	

2. NOZZLE SIZE *MAKER SUPPLY COUNTER FLANGES

PART NAME	BORE	FLANGE RATING	DWG.NO.
S.W IN&OUT CONN. SIZE	200A	JIS 16K S.O. F.F	I
STEAM INLET CONN. SIZE	200A	JIS 10K S.O. F.F	II
DRAIN OUT CONN. SIZE	150A	JIS 10K S.O. F.F	III

3. ACCESSORIES

RELIEF V/V (25A x 50A)	SETTING PRESS 17Kg/cm² G
SAFETY V/V (25A x 50A)	SETTING PRESS 7Kg/cm² G
LEVEL CONTROL VALVE	JIS 10K-65A WITH/CONTROLLER

4. TUBE SIZE : ø16 x 1t

5. STANDARD TYPE : TCH-55-3