```python
#find the sum of all elements
numbers=[5,10,15,20]
total=sum(numbers)
print("sum:",total)
```
[21]

```
sum: 50
```

```python
#Remove element 3 from the list
numbers=[1,2,3,4,5]
numbers.remove(3)
print(numbers)
```
[20]

```
[1, 2, 4, 5]
```

```python
#Add number 100 to the list[1,2,3,4]
numbers=[1,2,3,4]
numbers.append(100)
print(numbers)
```
[18]

```
[1, 2, 3, 4, 100]
```

```python
#print first and last element of a list[10,20,30,40,50]
numbers=[10.20,30,40,50]
print("First element:",numbers[0])
print("Second element:",numbers[-1])
```

[17]

```
First element: 10.2
Second element: 50
```

```python
#count a list of 5 numbers and print  all elements
numbers=[1,2,3,4,5]
for num in numbers:
    print(num)
```

[14]

```
1
2
3
4
5
```

```python
#2.tuples(immutable,ordered,allows duplicates)
print("\n===TUPLE EXAMPLE===")
coordinates=(10.5,20.3,10.5)
print("Tuple:",coordinates)
print("First coordinate:",coordinates[-1])
x,y,z=coordinates
print(f"Unpacked:{x},{y},{z}")

```

[7]

```
===TUPLE EXAMPLE===
Tuple: (10.5, 20.3, 10.5)
First coordinate: 10.5
Unpacked:10.5,20.3,10.5
```

```python
print("===LIST EXAMPLE===")
fruits=["apple","banana","cherry","apple"]
print("Original List:",fruits)
#Add element
fruits.append("orange")
#Remove element
if"banana" in fruits:
    fruits.remove("banana")
    #Acess by index
    print("first fruit:",fruits[0])
    #list comprehension
    upper_fruits=[fruit.upper() for fruit in fruits]
    print("uppercase Fruits:",upper_fruits)
```

✓ [5] 84ms

```
===LIST EXAMPLE===
Original List: ['apple', 'banana', 'cherry', 'apple']
first fruit: apple
uppercase Fruits: ['APPLE', 'CHERRY', 'APPLE', 'ORANGE']
```

```python
#Find maximum and minimum
numbers=[8,3,9,1,6]
print("Maximum:",max(numbers))
print("Minimum:",min(numbers))
```

[22]

```
Maximum: 9
Minimum: 1
```