

Ex No: 7**IPC USING SHARED MEMORY****Date: 19.02.2025**

Aim:

To write a C program to implement Inter Process Communication (IPC) using shared memory between sender and receiver processes.

Algorithm:**Sender Process**

1. Set the size of the shared memory segment.
2. Allocate the shared memory segment using `shmget()`.
3. Attach the shared memory segment using `shmat()`.
4. Write a string to the shared memory segment using `sprintf()`.
5. Set delay using `sleep()`.
6. Detach shared memory segment using `shmdt()`.

Receiver Process

1. Set the size of the shared memory segment.
 2. Allocate the shared memory segment using `shmget()`.
 3. Attach the shared memory segment using `shmat()`.
 4. Print the shared memory contents sent by the sender process.
 5. Detach shared memory segment using `shmdt()`.
-

Program Code: sender.c

```
#include <stdio.h>

#include <sys/ipc.h>

#include <sys/shm.h>

#include <unistd.h>

#include <string.h>

int main() { key_t key = ftok("shmfile",65); // Generate unique key int shmid

    = shmget(key, 1024, 0666|IPC_CREAT); // Create shared memory

    char *str = (char*) shmat(shmid, (void*)0, 0); // Attach to shared memory


    sprintf(str, "Welcome to Shared Memory");

    printf("Message Sent: %s\n", str);


    sleep(5); // Delay to allow receiver to read

    shmdt(str); // Detach from shared memory


    return 0;

}
```

receiver.c

```
#include <stdio.h>

#include <sys/ipc.h>

#include <sys/shm.h>

#include <unistd.h>


int main() { key_t key = ftok("shmfile",65); // Generate same key int shmid =

    shmget(key, 1024, 0666|IPC_CREAT); // Access shared memory

    char *str = (char*) shmat(shmid, (void*)0, 0); // Attach to shared memory
```

```
printf("Message Received: %s\n", str);

shmdt(str); // Detach from shared memory shmctl(shmid,
IPC_RMID, NULL); // Destroy the shared memory return 0;
}
```

Sample Output:**Terminal 1:**

```
[root@localhost student]# gcc sender.c -o sender
```

```
[root@localhost student]# ./sender
```

```
Message Sent: Welcome to Shared Memory
```

Terminal 2:

```
[root@localhost student]# gcc receiver.c -o receiver
```

```
[root@localhost student]# ./receiver
```

```
Message Received: Welcome to Shared Memory
```

Result:

Thus, the C program for Inter Process Communication (IPC) using shared memory was successfully executed, and the message was successfully passed from the sender process to the receiver process.