

Ex. No: 5 System Calls Programming

Date: 18.02.2025

Aim:

To experiment with system calls using fork(), execlp() and pid() functions.

Algorithm:

1. Start

- Include the required header files: stdio.h, stdlib.h, and unistd.h.

2. Variable Declaration

- Declare an integer variable pid to hold the process ID.

3. Create a Process

- Call the fork() function and store the return value in pid.
 - If fork() returns:
 - -1: Forking failed.
 - 0: This is the child process.
 - Positive value: This is the parent process.

4. Print Statement Executed Twice ○

Print:

- THIS LINE EXECUTED TWICE

5. Check for Process Creation Failure

- If pid == -1, print:
 - CHILD PROCESS NOT CREATED
 - Exit the program.

6. Child Process Execution ○ If pid ==

0, print:

- The process ID of the child using getpid().
- The parent process ID of the child using getppid().

7. Parent Process Execution

- If pid > 0, print:
 - The process ID of the parent using getpid().
 - The parent's parent process ID using getppid().

8. Final Print Statement ○ Print: ○ IT

CAN BE EXECUTED TWICE

9. End

Program Code:

```
// filename: systemcall.c

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int main() {
    int pid;

    pid = fork(); // Create new process

    printf("THIS LINE EXECUTED TWICE\n");

    if (pid == -1) {
        printf("CHILD PROCESS NOT CREATED\n");
        exit(0);
    }
}
```

```
    }

    if (pid == 0) { printf("Child Process ID: %d\n", getpid());
        printf("Parent Process ID of Child: %d\n", getppid());
    } else {
        printf("Parent Process ID: %d\n", getpid()); printf("Parent's
        Parent Process ID: %d\n", getppid());
    }

    printf("IT CAN BE EXECUTED TWICE\n");
    return 0;
}
```

Sample Output:

THIS LINE EXECUTED TWICE

Parent Process ID: 12345

Parent's Parent Process ID: 1000

IT CAN BE EXECUTED TWICE

THIS LINE EXECUTED TWICE

Child Process ID: 12346

Parent Process ID of Child: 12345

IT CAN BE EXECUTED TWICE

Result:

The program was successfully executed. It demonstrated the use of system calls `fork()`, `getpid()`, and `getppid()` to manage parent and child processes.