

VSM Store - One-Page App Summary

Evidence: README.md, package.json, src/main.tsx, src/App.tsx, src/hooks/useProducts.ts, src/services/products.service.ts, src/stores/cart.st

What it is

- VSM Store is a React + TypeScript PWA e-commerce app for Vape Store Mexico with a public storefront.
- The same SPA also includes a lazy-loaded admin panel routed under /admin.

Who it is for

- Primary persona: retail customers in Mexico buying vape and 420 products online.
- Formal persona detail docs (age/segment profiles): Not found in repo.

What it does

- Section-based catalog browsing for /vape and /420 with slug/category navigation.
- Live product discovery via /buscar and service-layer ilike search on name/description.
- Cart with local persistence (Zustand key vsm-cart) plus stock/price revalidation.
- Authenticated area: profile, addresses, order history/detail, loyalty, and notifications.
- Checkout and payment status routes (/checkout, /payment/success|failure|pending).
- Admin console for products, orders, categories, brands, tags, customers, coupons, and settings.

How it works (repo-evidence architecture)

- UI shell: React Router + lazy pages in src/App.tsx split storefront and /admin flows.
- Root providers in src/main.tsx: Theme, Auth, React Query, Helmet, Safety, ErrorBoundary.
- Data flow: components -> hooks (useProducts) -> services (getProducts) -> Supabase client.
- Supabase client reads VITE_SUPABASE_URL and VITE_SUPABASE_ANON_KEY from env.
- Services query tables such as products; React Query manages caching and stale times.
- State and platform: cart persisted in localStorage; /sw.js service worker adds PWA behavior.

How to run (minimal)

1. Install dependencies: npm install
2. Copy .env.example to .env and set VITE_SUPABASE_URL + VITE_SUPABASE_ANON_KEY.
3. Apply SQL migrations from supabase/migrations in order (single command: Not found in repo).
4. Start dev server: npm run dev (Vite default URL is http://localhost:5173).