## NASIC problem specification

## Bryan O'Gorman

### May 2016

## 1 Introduction

#### Notation:

- $\bullet$  I: num. airfields
- $\bullet$  J: num. tasks
- L: num. aircraft types
- b(i, l): num. l-type aircraft available at airfield i
- B(i): max. num. aircraft able to be dispatched from airfield i
- A(l): total num. l-type aircraft available
- m(j, l): how much l-type aircraft contribute to task j
- M(j): how much task j needs
- r(l, l', j): how much coverage l'-type aircraft provide for l-type aircraft executing task j
- R(i,j,l): how much coverage each l-type aircraft from airfield i executing task j needs
- C(i, j, l): Range of l-type aircraft from airfield i executing task l
- h(l): Range of l-type aircraft
- N(i,j): set of airfields from which an aircraft can cover another aircraft executing task j from airfield i
- Q(i, j, l, i'): set of aircraft types in airfield i' that can cover an l-type aircraft from airfield i executing task j

## 2 Constraints

• Limited cover availability: Only certain aircrafts from certain airfields are available for cover

$$y_{i,l,i',j',l'}$$
 only for  $i \in N(i',j')$  and  $l \in Q(i',j',l',i)$  (1)

• Limited airfield and type resource: The sum of *l*-type primary and cover aircrafts dispatched from a airfield *i* cannot exceed the number of *l*-type aircrafts stationed there

$$\sum_{j} x_{i,j,l} + \sum_{i',j',l'} y_{i,l,i',j',l'} \le b(i,l) \qquad \forall i,l$$
 (2)

• Limited airfield resource: The sum of any type of primary and cover aircrafts dispatched from a airfield *i* cannot exceed the total number aircrafts stationed there

$$\sum_{j,l} x_{i,j,l} + \sum_{l,i',j',l'} y_{i,l,i',j',l'} \le B(i) \qquad \forall i$$
 (3)

• Limited type resource: The sum of *l*-type primary and cover aircrafts dispatched from all airfield cannot exceed the total number of *l*-type aircrafts

$$\sum_{i,j} x_{i,j,l} + \sum_{i,i',j',l'} y_{i,l,i',j',l'} \le A(l) \qquad \forall l$$
 (4)

• Tasks must be fulfilled: The sum of contributions of all aircrafts dispatched to fulfill task j must exceed the resource needed by that task

$$\sum_{i,l} m(j,l) x_{i,j,l} \ge M(j) \qquad \forall j \tag{5}$$

• Aircraft range is limited: We can not dispatch aircrafts for tasks j if the necessary range is beyond the maximum range of these aircrafts

$$h(l) < C(i, j, l) \Rightarrow x_{i, j, l} = 0 \qquad \forall i, j, l \tag{6}$$

• Cover must be provided: The sum of cover contributions to must exceed the cover needed.

$$\sum_{i',l'} r(l,l',j)y_{i',l',i,j,l} \ge R(i,j,l) \qquad \forall i,j,l$$
(7)

## 3 Instance ensembles

Simplifications:

- Set  $A(l) = \sum_{i} b(i, l)$
- Set  $B(i) = \sum_{l} b(i, l)$
- Have  $y_{i,l,i',j',l'}$  only when  $(i,l) \in K_2(i',j',l')$
- Have  $x_{i,j,l}$  only when  $l \in K_1(i,j)$
- r(l, l', j) = r(j) = 1
- R(i, j, l) = R(i, j) = 1

Oversimplifications:

- L = 1
- $\bullet$  I small
- $\bullet$  J small
- m(j, l) = 1
- M(j) small
- b(i, l) = b(i)
- (Maybe)  $K_2(i', j', l') = I \times L = I \times \{1\}$

• (Maybe)  $K_1(i,j) = L$ 

Remaining:

• *I*, *J*, *L* 

• b(i, l)

• m(j,l), M(j)

• r(l, l', j), R(i, j, l)

•  $N(i,j), C(i,j,l), h(l), Q(i,j,l,i') \Rightarrow K_1, K_2$ 

Reduced problem:  $\mathbf{x} = \{x_{i,j}\}, \, \mathbf{y} = \{y_{i,i',j'}\}$ 

• Constraint (1) always fulfilled

• Constraint (2)  $\forall i: \sum_{j} x_{i,j} + \sum_{i',j'} y_{i,i',j'} \leq b(i,l)$ 

• Constraint (3)  $\forall i: \sum_{j} x_{i,j} + \sum_{i',j'} y_{i,i',j'} \leq B(i)$ 

• (4) implies (2)

• Constraint (5)  $\forall j : \sum_{i} x_{i,j} \geq M(j)$ 

• Constraint (6) always fulfilled

• Constraint (7)  $\forall i, j: \sum_{i'} y_{i',i,j} \geq 1$ 

(For all sums,  $j \in [J], i \in [I]$ .)

• I = 2, 3, 4

• J = I, 2I, 3I

• M(j) = 1, 2, 3

•  $b(i) = 1, 2, \dots, 5$ 

Is this hard?

# 4 QUBO

## 4.1 Reduced problem

Variables

•  $x_{i,j} \in \{0, 1, \dots, b(i)\}$ 

•  $y_{i,i',j'}\{0,1,\ldots,b(i)\}$ 

1. Binary representation of  $x_{i,j}$  and  $y_{i,i',j'}$ :

$$x_{i,j} = \sum_{\alpha=0}^{D_i - 1} 2^{\alpha} x_{i,j,\alpha} + (b(i) - 2_i^D + 1) \sum_{\alpha=0}^{b(i) - 2_i^D + 1} \frac{\alpha x_{i,j,D_i + \alpha}}{(b(i) - 2_i^D + 1)}$$
$$y_{i,i',j'} = \sum_{\alpha=0}^{D_i} 2^{\alpha} y_{i,i',j',\alpha} + (b(i) - 2_i^D + 1) \sum_{\alpha=0}^{b(i) - 2_i^D + 1} \frac{\alpha y_{i,i',j',D_i + \alpha}}{(b(i) - 2_i^D + 1)}$$

with  $D_i = \log_2 b(i) \in \mathbb{N}$ .

2. Unary representation of  $x_{i,j}$  and  $y_{i,i',j'}$ :

$$x_{i,j} = \sum_{\alpha=0}^{b(i)} \alpha x_{i,j,\alpha}$$
$$y_{i,j} = \sum_{\alpha=0}^{b(i)} \alpha y_{i,i',j,\alpha}$$

QUBO contribution to ensure a single value of each variable

$$C_{\text{one}} = \sum_{ij} \left( \sum_{\alpha=0}^{b(i)} x_{i,j,\alpha} - 1 \right)^2 + \sum_{ii'j} \left( \sum_{\alpha=0}^{b(i)} y_{i,i',j,\alpha} - 1 \right)^2$$

• Incorporation of constraint (2):

$$0 \le b(i) - \sum_{j} x_{i,j} - \sum_{i',j'} y_{i,i',j'} \le b(i)$$
=: $z_i^1$ 

Binary representation of the slack variable  $z_i^1$ :

$$z_i^1 = \sum_{\alpha=0}^{D_i} 2^{\alpha} z_{i,\alpha}$$

QUBO contribution

$$C_2 = \sum_{i} \left( b(i) - \sum_{j} x_{i,j} - \sum_{i',j'} y_{i,i',j'} - z_i^1 \right)^2$$