

✓ Practical Introduction to Deep Learning Basics

```
import tensorflow as tf
from tensorflow import keras

import numpy as np
import matplotlib.pyplot as plt

print(tf.__version__)
```

↗ 2.18.0


✓ Load Data

```
mnist = tf.keras.datasets.mnist
(x_train, y_train), (x_test, y_test) = mnist.load_data()
#(x_train, y_train), (x_test, y_test) = mnist.load_data(path='/gpfs/projects/nct00/nct00002/basics-utils/mnist.npz')
```

↗ Downloading data from <https://storage.googleapis.com/tensorflow/tf-keras-datasets/mnist.npz>
11490434/11490434 — 2s 0us/step

```
import matplotlib.pyplot as plt
plt.imshow(x_train[8], cmap=plt.cm.binary)
```

↗ <matplotlib.image.AxesImage at 0x7e82fbbb3e50>



```
print(y_train[8])
```

↗ 1

```
print(x_train.ndim)
```

↗ 3

```
print(x_train.shape)
```

↗ (60000, 28, 28)

```
print(x_train.dtype)
```

↗ uint8

✓ Prepare data

```
x_train = x_train.astype('float32')
x_test = x_test.astype('float32')
```

```
x_train /= 255
x_test /= 255
```

```
x_train = x_train.reshape(60000, 784)
x_test = x_test.reshape(10000, 784)
```

```
print(x_train.shape)
print(x_test.shape)
```

```
(60000, 784)
(10000, 784)
```

```
from tensorflow.keras.utils import to_categorical
```

```
print(y_test[0])
```

```
7
```

```
print(y_train[0])
```

```
5
```

```
print(y_train.shape)
```

```
(60000,)
```

```
print(x_test.shape)
```

```
(10000, 784)
```

```
y_train = to_categorical(y_train, num_classes=10)
y_test = to_categorical(y_test, num_classes=10)
```

```
print(y_test[0])
```

```
[0. 0. 0. 0. 0. 0. 0. 1. 0. 0.]
```

```
print(y_train[0])
```

```
[0. 0. 0. 0. 0. 1. 0. 0. 0. 0.]
```

```
print(y_train.shape)
```

```
(60000, 10)
```

```
print(y_test.shape)
```

```
(10000, 10)
```

✓ Define Model

```
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Dense , Input

model = Sequential()
model.add(Input(shape=(784,))) # Define the input shape here
model.add(Dense(10, activation='sigmoid'))
model.add(Dense(10, activation='softmax'))
```

Se muestra un resumen del modelo tal como se tiene tras las instrucciones anteriores

```
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
dense (Dense)	(None, 10)	7,850
dense_1 (Dense)	(None, 10)	110

Total params: 7,960 (31.09 KB)

Trainable params: 7,960 (31.09 KB)

✓ Compile model (configuration)

```
model.compile(loss="categorical_crossentropy",
              optimizer="sgd",
              metrics = ['accuracy'])
```

✓ Training the model

```
model.fit(x_train, y_train, epochs=5)
```

```
Epoch 1/5
1875/1875 ————— 5s 2ms/step - accuracy: 0.3374 - loss: 2.1362
Epoch 2/5
1875/1875 ————— 5s 3ms/step - accuracy: 0.6992 - loss: 1.4774
Epoch 3/5
1875/1875 ————— 4s 2ms/step - accuracy: 0.7957 - loss: 1.0544
Epoch 4/5
1875/1875 ————— 4s 2ms/step - accuracy: 0.8322 - loss: 0.8225
Epoch 5/5
1875/1875 ————— 5s 3ms/step - accuracy: 0.8518 - loss: 0.6885
<keras.src.callbacks.history.History at 0x7e82f6369550>
```

✓ Evaluation the model

```
test_loss, test_acc = model.evaluate(x_test, y_test)
```

```
313/313 ————— 2s 4ms/step - accuracy: 0.8540 - loss: 0.6551
```

```
print('Test accuracy:', test_acc)
```

```
Test accuracy: 0.871999979019165
```

```
# Look at confusion matrix
#Note, this code is taken straight from the SKLEARN website, an nice way of viewing confusion matrix.
def plot_confusion_matrix(cm, classes,
                          normalize=False,
                          title='Confusion matrix',
                          cmap=plt.cm.Blues):
    """
    This function prints and plots the confusion matrix.
    Normalization can be applied by setting `normalize=True`.
    """
    plt.imshow(cm, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()
    tick_marks = np.arange(len(classes))
    plt.xticks(tick_marks, classes, rotation=45)
    plt.yticks(tick_marks, classes)

    if normalize:
        cm = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis]

    thresh = cm.max() / 2.
    for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
        plt.text(j, i, cm[i, j],
                 horizontalalignment="center",
                 color="white" if cm[i, j] > thresh else "black")


    plt.tight_layout()
    plt.ylabel('Observación')
    plt.xlabel('Predicción')
```

```

from collections import Counter
from sklearn.metrics import confusion_matrix
import itertools

# Predict the values from the validation dataset
Y_pred = model.predict(x_test)
# Convert predictions classes to one hot vectors
Y_pred_classes = np.argmax(Y_pred, axis = 1)
# Convert validation observations to one hot vectors
Y_true = np.argmax(y_test, axis = 1)
# compute the confusion matrix
confusion_mtx = confusion_matrix(Y_true, Y_pred_classes)
# plot the confusion matrix
plot_confusion_matrix(confusion_mtx, classes = range(10))

```




Use the model

```

x_test_old = x_test.reshape(10000, 28,28)
plt.imshow(x_test_old[11], cmap=plt.cm.binary)

```



```
predictions = model.predict(x_test)
```

313/313 ————— 1s 2ms/step

```
np.argmax(predictions[11])
```

6

```
print(predictions[11])
```

```
[0.02460003 0.07596562 0.22225824 0.07534765 0.07584362 0.07906184
 0.3106948  0.00432798 0.12130976 0.01059039]
```

```
np.sum(predictions[11])
```

```
0.99999994
```

✓ Convolutional Neural Network

```
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Conv2D
from tensorflow.keras.layers import MaxPooling2D
from tensorflow.keras.layers import Dense
from tensorflow.keras.layers import Flatten
from tensorflow.keras.layers import Input
```

```
model = Sequential()
model.add(Input(shape=(28, 28, 1))) # Define the input shape here
model.add(Conv2D(32, (5, 5), activation='relu'))
model.add(MaxPooling2D((2, 2)))
model.add(Conv2D(64, (5, 5), activation='relu'))
model.add(MaxPooling2D((2, 2)))
```

```
from tensorflow.keras.layers import Dense
from tensorflow.keras.layers import Flatten
```

```
model.add(Flatten())
model.add(Dense(10, activation='softmax'))
model.summary()
```

```
Model: "sequential_1"
```

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 24, 24, 32)	832
max_pooling2d (MaxPooling2D)	(None, 12, 12, 32)	0
conv2d_1 (Conv2D)	(None, 8, 8, 64)	51,264
max_pooling2d_1 (MaxPooling2D)	(None, 4, 4, 64)	0
flatten (Flatten)	(None, 1024)	0
dense_2 (Dense)	(None, 10)	10,250

```
Total params: 62,346 (243.54 KB)
Trainable params: 62,346 (243.54 KB)
Non trainable params: 0 (0.00 KB)
```

```
from tensorflow.keras.utils import to_categorical
```

```
#mnist = tf.keras.datasets.mnist(train_images, train_labels), (test_images, test_labels) = mnist.load_data(path='/gpfs/projects/nct00/n')
```

```
mnist = tf.keras.datasets.mnist
(train_images, train_labels), (test_images, test_labels) = mnist.load_data()
```

```
print (train_images.shape)
print (train_labels.shape)
train_images = train_images.reshape((60000, 28, 28, 1))
train_images = train_images.astype('float32') / 255
```

```
test_images = test_images.reshape((10000, 28, 28, 1))
test_images = test_images.astype('float32') / 255
```

```
train_labels = to_categorical(train_labels)
test_labels = to_categorical(test_labels)
```

```
print (train_images.shape)
print (train_labels.shape)
```

```
(60000, 28, 28)
(60000,)
(60000, 28, 28, 1)
(60000, 10)
```

```
model.compile(loss='categorical_crossentropy',
              optimizer='sgd',
```

```
metrics=['accuracy'])
```

```
model.fit(train_images, train_labels, batch_size=100, epochs=5, verbose=1)
```

```
↗ Epoch 1/5  
600/600 ————— 4s 3ms/step - accuracy: 0.5847 - loss: 1.5815  
Epoch 2/5  
600/600 ————— 4s 4ms/step - accuracy: 0.9181 - loss: 0.2799  
Epoch 3/5  
600/600 ————— 2s 3ms/step - accuracy: 0.9439 - loss: 0.1900  
Epoch 4/5  
600/600 ————— 2s 3ms/step - accuracy: 0.9555 - loss: 0.1525  
Epoch 5/5  
600/600 ————— 2s 3ms/step - accuracy: 0.9638 - loss: 0.1247  
<keras.src.callbacks.history.History at 0x7e82d00fb2d0>
```

```
test_loss, test_acc = model.evaluate(test_images, test_labels)
```

```
print('Test accuracy:', test_acc)
```

```
↗ 313/313 ————— 2s 5ms/step - accuracy: 0.9687 - loss: 0.1160  
Test accuracy: 0.972100019454956
```