1. Define a macro to swap the specified bits in a given integer?
   You need to accept the 32-bit data and bit positions from the user and swap them.
   For example, if the integer value is 0x12345678 and if the entered bit positions (0-31) are 1,4 then output should be 0x1234566A
   Before swapping, 0001 0010 0011 0100 0101 0110 0111 1000
   After swapping, 0001 0010 0011 0100 0101 0110 0110 1010
   #define SWAPBITS(DATA,B1POS,B2POS) _____
2. Define a macro to swap the specified nibbles in a given integer?
   You need to accept the 32-bit data and nibble positions from the user and swap them.
   For example, if the integer value is 0x12345678 and if the entered nibble positions (0-7) are 0, 5 then output should be 0x12845673
   Before swapping, 0x12345678
   After swapping, 0x12845673
   #define SWAPNIBBLES(DATA,N1POS,N2POS) _____
3. Define a macro to swap the specified bytes in a given integer?
   You need to accept the 32-bit data and byte positions from the user and swap them.
   For example, if the integer value is 0x12345678 and if the entered byte positions (0-3) are 0,2 then output should be 0x12785634
   Before swapping, 0x12345678
   After swapping, 0x12785634
   #define SWAPBYTES(DATA,B1POS,B2POS) _____