Static Member functions

static member functions of a class can only access the static members of that class.

static members functions does not demand object to invoke it.
It can be called directly with class name.
Static members of a class comes into existence before objects creation.

Constant members of a class

constant data member of aclass should be initialised only through constructor, once initialised cannot be changable.
To initialise the constant data members we have a seperate syntax

Assume ABC is a class

```
ABC():constantdatamem(val)
{

}
```

```
Class ABC
{ int x;
  const int y;
  public:
   ABC( ) : y(10)
   {
    cout<<"enter x";
    cin>>x;
   }
ABC(int a, int b) : y(b)
{
  x = a;
}
```

Which memory segment constant datamember stored?
It depends on how and where the object is created.

if object is created inside the function its a local object so in satck segment and const data member memory is labeled as read only block

Constant member functions:

member functions of a class are divided into two categories.
mutator member functions
Accessor member functions

mutator members functions can access and modify the data members of a class.
By default member functions of a class are mutators.

Accessor member functions can only access the data members but cannot modify them.
Accessor member functions also called as constant member functions or Read only member functions.

Constant objects should be initialised only through constructor, once initialised its data members values cannot be changeable. Constant objects can only invoke constant member functions, they cannot invoke mutator functions

mutable storage class

mutable storage class is applicable only to the data members of a class.
When we declare data members as mutable . their values can be changeble in constant functions as well as constant objects.