Constant Data Members:

Data members of a class can be declared as constant. Constant data members should be initialized only through constructors. Once initialized, a const data member may never be modified, not even in the constructor or destructor.

Example :

```
#include<iostream>

using namespace std;

class ABC

{

     const int data;

     public: ABC():data(10) // const data member initialization

                {

                     cout<<"data initialized"<<endl;

                }

                void Display()

                {

                     cout<<"data:"<<data<<endl;

                }

};

main()

{
```

Vector India

```
ABC obj;

obj.Display();

}
```

Output:

```
data : 10
```

Constant Member Function:

The const member functions are the functions which are declared as constant in the program. The object called by these functions cannot be modified. It is recommended to use const keyword so that accidental changes to object are avoided.

A const member function can be called by any type of object. Non-const functions can be called by non-const objects only.

```
datatype function_name const();
```

Example:

```
#include<iostream>
using namespace std;
class ABC
{
      int data;
      public: void setData(int d)
                {    data=d;
                }
            void getData()const // constant member function
                {
```


Vector India

```
                    cout<<data<<endl;
                }
};
main()
{
     ABC obj;
     obj.setData(20);
     obj.getData();
}
Output :
20
```

Constant Object:

Like member functions and member function arguments, the objects of a class can also be declared as **const**. an object declared as const cannot be modified and hence, can invoke only const member functions as these functions ensure not to modify the object.
A const object can be created by prefixing the const keyword to the object declaration. Any attempt to change the data member of const objects results in a compile-time error.
Syntax:

```
const Class_Name Object_name;
```

Vector India