File Handling

Files are used to store data in a storage device permanently. File handling provides a mechanism to store the output of a program in a file and to perform various operations on it.

A stream is an abstraction that represents a device on which operations of input and output are performed. A stream can be represented as a source or destination of characters of indefinite length depending on its usage.

In C++ we have a set of file handling methods. These include ifstream, ofstream, and fstream. These classes are derived from fstrembase and from the corresponding iostream class. These classes, designed to manage the disk files, are declared in fstream and therefore we must include fstream and therefore we must include this file in any program that uses files.

In C++, files are mainly dealt by using three classes fstream, ifstream, ofstream.

- ofstream: This Stream class signifies the output file stream and is applied to create files for writing information to files
- ifstream: This Stream class signifies the input file stream and is applied for reading information from files
- fstream: This Stream class can be used for both read and write from/to files.

All the above three classes are derived from fstreambase and from the corresponding iostream class and they are designed specifically to manage disk files.
C++ provides us with the following operations in File Handling:

- Creating a file or opening a file
- Reading data from file
- Writing new data to file
- Closing a file

Opening a File

Generally, the first operation performed on an object of one of these classes is to associate it to a real file. This procedure is known to open a file.

We can open a file using any one of the following methods:
1. First is bypassing the file name in constructor at the time of object

creation.
2. Second is using the open() function.

To open a file we use open() function

Syntax :

```
void open(const char* file_name,ios::openmode mode);
```

The first argument specifies the name and location of the file to be opened

The second argument represents the mode in which the file has to be opened. The following modes are used as per the requirements.

Sr.No	Mode Flag & Description
1	**ios::app** Append mode. All output to that file to be appended to the end.
2	**ios::ate** Open a file for output and move the read/write control to the end of the file.
3	**ios::in** Open a file for reading.
4	**ios::out** Open a file for writing.
5	**ios::trunc** If the file already exists, its contents will be truncated before opening the file.

You can combine two or more of these values by **OR**ing them together. For example if you want to open a file in write mode and want to truncate it in case that already exists, following will be the syntax −

```
ofstream outfile;
outfile.open("file.dat", ios::out | ios::trunc );
```

Similar way, you can open a file for reading and writing purpose as follows −

```
fstream  afile;
afile.open("file.dat", ios::out | ios::in );
```

Closing a File

When a C++ program terminates it automatically flushes all the streams, release all the allocated memory and close all the opened files. But it is always a good practice that a programmer should close all the opened files before program termination.

Following is the standard syntax for close() function, which is a member of fstream, ifstream, and ofstream objects.

```
void close();
```

Writing to a File

While doing C++ programming, you write information to a file from your program using the stream insertion operator (<<) just as you use that operator to output information to the screen. The only difference is that you use an **ofstream** or **fstream** object instead of the **cout** object.

Reading from a File

You read information from a file into your program using the stream extraction operator (>>) just as you use that operator to input information from the keyboard. The only difference is that you use an **ifstream** or **fstream** object instead of the **cin** object.

```
#include <fstream>
#include <iostream>
using namespace std;

int main () {
   char data[100];

   // open a file in write mode.
   ofstream outfile;
   outfile.open("file.txt");

   cout << "Writing to the file" << endl;
```

Vector India

```
   cout << "Enter your name: ";
   cin.getline(data, 100);

// write inputted data into the file.

   outfile << data << endl;

   cout << "Enter your age: ";
   cin >> data;


   // again write inputted data into the file.
   outfile << data << endl;

   // close the opened file.
   outfile.close();

// open a file in read mode.

   ifstream infile;
   infile.open("file.txt");

   cout << "Reading from the file" << endl;
   infile >> data;

   // write the data at the screen.
   cout << data << endl;

   // again read the data from the file and display it.
   infile >> data;
   cout << data << endl;

   // close the opened file.
   infile.close();

   return 0;
}
```

Output:

```
Writing to the file
```

Vector India

```
Enter your name: Rajesh

Enter your age: 25
Reading from the file
Rajesh
25
```

File Position Pointers

Both **istream** and **ostream** provide member functions for repositioning the file-position pointer. These member functions are **seekg** ("seek get") for istream and **seekp** ("seek put") for ostream.

The argument to seekg and seekp normally is a long integer. A second argument can be specified to indicate the seek direction. The seek direction can be **ios::beg** (the default) for positioning relative to the beginning of a stream, **ios::cur** for positioning relative to the current position in a stream or **ios::end** for positioning relative to the end of a stream.

The file-position pointer is an integer value that specifies the location in the file as a number of bytes from the file's starting location. Some examples of positioning the "get" file-position pointer are −

```
// position to the nth byte of fileObject (assumes ios::beg)
fileObject.seekg( n );

// position n bytes forward in fileObject
fileObject.seekg( n, ios::cur );

// position n bytes back from end of fileObject
fileObject.seekg( n, ios::end );

// position at end of fileObject
fileObject.seekg( 0, ios::end );
```

Vector India