ls

↓

file names

file1 file2 file3

stat System call :-

① what permisions required to delete a file.?

Epoch Time :-

↳ Integer

UNIX Official release date

1970 Jan 1st 00:00:01

Epoch → 1'

↓

Secs → 1970 jan 1st 00:00:01

1970 jan 2nd 00:00:01

24 hrs 0 min 0 sec

↓

24X60X60

54X365 X 24 X60X60

Q Find the library fn/system call to convert epoch time to human readable time?

# Hard link

→ Giving another name to the same data.

→ If original file name is removed then also can access the data through another name given.

$ ln filename hardlinkname

file → inode num → Inode

another file → Inode num → Inode

# Soft link (Symbolic link)

→ Shortcut ICON for easy access

→ If the file referred is removed then link will crash.

$ ln -s filename softlinkname

attribute  Soft link  attribute original file

Umask 0002

000 000 010

~Umask 111 111 101

max file permissions possible for .c file

110 110 110

110 110 100

111 111 101

a.out

111 111 111

111 111 101

Chmod → change mode bits

## Umask

→ It is to set the mode bits of a file getting created in the current shell.

$umask u_val

~(u_val)
& max. possible mode bits for a file

→ mode bits assigned to the file created.

## Chmod

→ To change the mode bits of a existing file.

$ sudo chmod modebits filename