```
#include<stdio.h> #include<unistd.h> #include<fcntl.h>

int main(int argc,char *argv[])

{       int fd;

        char ch='A';

        struct flock v;

fd=open(argv[1],O_CREAT|O_WRONLY,0660);                 //opening a file in
writeonly mode

        v.l_type=F_WRLCK;                               //giving write lock

        v.l_whence=0;

        v.l_start=0;

        v.l_len=0;

        v.l_pid=0;

        fcntl(fd,F_SETLKW,&v);

        //fcntl will test for lock.

        //if lock is applied , then process blocked

        //if lock not applied, then, apply the lock, and process continues.

        puts("application 1 is writing");

        while(1)

        {

                write(fd,&ch,1);                //data writing into the file

                sleep(1);

                if (ch=='Q')

                        break;

                ch++;

        }       }
```

```
#include<stdio.h>
#include<unistd.h>
#include<fcntl.h>
int main(int argc,char *argv[])
{
        int fd;
        char ch='0';
        struct flock v;
        fd=open(argv[1],O_CREAT|O_WRONLY,0660);                 //opening a
file in writeonly mode
        v.l_type=F_WRLCK;                               //giving write lock
        v.l_whence=0;
        v.l_start=0;
        v.l_len=0;
        v.l_pid=0;
        fcntl(fd,F_SETLKW,&v);                                  //setting lock and wait
        puts("application 22 is writing");
        while(1)
        {
                write(fd,&ch,1);                //data writing into the file
                sleep(1);
                if (ch=='9')
                        break;
                ch++;
        }       }
```