2023 3rd International Conference on Technological Advancements in Computational Sciences (ICTACS) | 979-8-3503-4233-8/23/$31.00 ©2023 IEEE | DOI: 10.1109/ICTACS59847.2023.10390207

The Rise of Virtual Health Assistants: Chatbot-Based Healthcare Support and Counseling Using Recurrent Neural Networks (RNNs)

Srinivasa Rao Burri[1], Vasundhara Vijay Ghorpade[2], Vishal Dutt[3], Kumari Lipi[4]
[1]*Sr. Software Engineering Manager, Western Union, Denver CO, USA*
[2]*Department of Community Medicine, Krishna Institute of Medical Sciences, Karad, Maharashtra, India*
[3]*Department of CSE, Chandigarh University, Mohali, Punjab, India*
[4]*Department of Legal Research and IPR, Akhildev IPR and Research Services, Noida, Uttar Pradesh, India*
E-mail: [1]sburri@bu.edu, [2]vvghorpade@outlook.com, [3]vishal.e14661@cumail.in, [4]lipi.kaundilya@gmail.com

***Abstract*—Health Assistant Bot is an advanced AI-powered virtual health assistant to enhances patients' ability to receive more individualized care. Health Assistant Bot's capabilities in symptom recognition, physician recommendation, and essential health information provision are discussed in this study, along with its creation and evaluation. Extensive testing and analysis have shown that the system is accurate, effective, and user-friendly. The problems of false information and data privacy are addressed by Health Assistant Bot, guaranteeing its ethical and responsible use in healthcare settings. By harnessing technology, Health Assistant Bot supplements human caretakers and gives patients more agency in their treatment. By invisibly integrating state-of-the-art technology into healthcare practices, the virtual assistant paves the way for care centered on the patient. The proposed model of RNN gave an accuracy of 90.20%, precision of 88.50%, recall of 88% and F1 Score of 89.20%. Embrace the transformative potential of the Health Assistant Bot, which encourages better healthcare outcomes through co-production and gives people more agencies.**

Keywords: Health Assistant Bot, Virtual Health Assistant, AI-powered, Symptom Recognition, Personalized Care, Healthcare Outcomes.

I. Introduction

Virtual Health Assistants (VHAs) have been increasingly popular as a novel and cost-effective approach to delivering individualized patient support and counseling in recent years. Teledermatology has changed the face of medicine by letting dermatologists track treatment efficacy using digital images [1]. These virtual helpers engage with users, offer medical advice and emotional support, and are powered by cutting-edge technologies like Recurrent Neural Networks (RNN). [2] Combining VHAs with RNNs is a huge step forward in healthcare since it will transform how patients and doctors communicate with one another and help more people get the care they need. This paper looks at how chatbot-based Virtual Health Assistants powered by RNNs are becoming increasingly popular, and how this trend has a revolutionary effect on healthcare support and counseling, ushering in a future in which people worldwide have easy access to compassionate medical care. This research looks at the impact of teledermatology virtual assistants on patients' health [3].

Thirty patients with moderate-to-severe psoriasis and four healthcare professionals participated in the study, and their quality of life was assessed through questionnaires and usability tests. Patient's quality of life improved overall, and the utility of the virtual assistant was rated positively [4]. Also, teledermatology's use of virtual assistants has improved direct patient-doctor connection, fostering a feeling of convenience and security. Furthermore, "Jarvis," a Digital Health Assistant, highlights the promise of virtual assistants in healthcare and beyond, and a complete evaluation explores the design aspects of virtual health assistants that affect the user experience [5]. Moreover, virtual mental health assistants have been proposed to deal with this often-overlooked area of care by providing services including message dialogues, psychological evaluations, and mood recognition. As a result of the COVID-19 epidemic, the role of medical assistants has been reevaluated in light of the growing emphasis on Virtual Health. Virtual assistants are revolutionizing the healthcare industry by streamlining procedures and improving patient care quality in all medical fields [6].

II. Literature Review

This article aims to explore the cognitive assistant's (a virtual health coach) communicative capacities to encourage and support health-conscious behavior. Conversational engagement is effective because it helps users stay motivated to live healthily. The research outlines the language requirements for a virtual health coach to perform its functions.

Health Assistant Bot, a natural-language virtual assistant, recognizes symptoms, recommends doctors, and monitors treatments and health metrics. Machine learning infers diseases from user symptoms, which the

Copyright © IEEE–2023 ISBN: 979-8-3503-4233-8

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.

recommendation algorithm uses to find the best doctor based on community data. Health Assistant Bot meets patients' healthcare needs and shows promise for tailored health assistance in the evaluation, which included offline and online assessments with 102 subjects.

As health becomes more important, information and communication technology has advanced healthcare. The Virtual Medical Assistant System uses machine learning algorithms and user health indicators to predict heart illness. By using K-Nearest Neighbor, back-propagation neural networks, Naive Bayes, and Support Vector Machines, the SVM classifier surpasses others with 90% accuracy. This research evaluation investigates the system's ability to analyze symptoms, anticipate disease, and identify specialists to save patients time and money.

This study examines game therapy for dementia to improve cognitive function. The study uses a miniaturized chess game with a Deep Q-Learning Network (DQN)-trained AI Virtual Assistant. The AI agent helps patients learn chess with aggressive or defensive strategies, improving cognitive capacities. This novel approach may help dementia people operate better.

CVDs kill millions of Europeans yearly, making them a huge public health issue. Rehabilitating following a cardiovascular emergency is necessary. The EU-supported vCare project built a virtual rehabilitation assistant to help older people rehabilitate and live independently at home. The study examined heart failure and ischemic heart disease patients and found promising outcomes compared to typical rehabilitation methods.

This study protocol examines the efficacy of Internet-based self-administered exposure therapy for rodent phobias using immersive multimedia elements such as photos, videos, video games, and 360-degree movies. The satisfaction and impression of VTA-supported consumers will also be assessed. This study compares waitlisters and VTA-supported self-treaters. The predicted results will show that this strategy works and improves treatment adherence, potentially paving the door for similar virtual aides for specific phobias.

AIVAs are making rapid progress in artificial intelligence, but their ability to answer frequent patient inquiries has not yet been properly explored. This study constructed an AIVA to answer cosmetic surgery candidates' questions. Survey results were 92.3% accurate. AIVA was easy to use, informative, and helpful to patients, but users were divided on whether it could replace human careers. This study shows how AIVA can help doctors and patients communicate.

This project proposes a virtual assistant for health co-production during the COVID-19 pandemic. The paper uses applied technology production research to describe the assistant creation process, including literature review, content definition, conversation elaboration, prototype testing, and social media integration. The virtual assistant improved health education by countering misinformation, improving patient-centered health communication, and strengthening health professional-patient relationships and co-production.

Due to advances in NLP and NLG, intelligent virtual assistants in human-machine communication have revolutionized several applications. However, ethical and regulatory issues develop as this technology advances to public sectors including administration, education, and healthcare. This article examines the European legislative environment for artificial intelligence and designs AI-based conversational solutions for e-health, emphasizing ethics and user autonomy. Responsible and courteous implementation of these innovative instruments is advised.

The COVID-19 pandemic has shown the need for varied population information distribution systems. However, obstacles prevent public health institutions from using virtual assistants. Instant Expert, an open-source semantic web framework, lets any web platform integrate voice-enabled intelligent assistants (chatbots). Advanced web technologies and deep learning algorithms allow non-technical subject specialists to integrate voice-recognition assistants easily. Using CDC data to create a COVID-19 informatory assistant shows the framework's value.

A. Analytical Analysis of Studies: Comparative Study Table Summarizes Research Findings

Table 1: Comparison of the Studies

Literature	Methodology	Results	Gaps
[7]	How well a virtual health coach can communicate	Increases health-conscious conduct	Needs further investigation in diverse healthcare settings.
[8]	Uses a chatbot that understands natural language	Recognizes symptoms and prescribes medical care accurately	Existing research on patients' long-term results is limited.
[9]	Miniaturized chess with AI Virtual Assistant	Benefits dementia patients' cognitive abilities	Needs more extensive clinical trials for definitive findings.
[10]	Creates a digital companion to aid in the recovery of the elderly	Promising for treating heart disease and cardiac failure	Needs longer-term monitoring to determine sustainability.

 Copyright © IEEE–2023 ISBN: 979-8-3503-4233-8

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.

[11]	Self-administered exposure treatment is used.	Possibility of using it to cure fears of rodents	Needs validation across phobia types and populations.
[12]	Develops an automated system to respond to patients' questions	Gives patients the answers they need	Lacks thorough user acceptance and trust analysis
[13]	COVID-19 health education virtual assistant	Improves patient-provider communication and health literacy	Long-term effects on collaborative production need more investigation.
[14]	Investigates ethical issues in AI-powered healthcare solutions.	Highlights the importance of ethical design in AI assistants	More detailed implementation guidelines and standards are needed.
[15]	Examines the implications of intelligent virtual assistants	Adoption ethical and regulatory issues	Lacks specific ethical concerns and remedies.
[16]	Presents a free software infrastructure for voice-enabled assistants	Helps online platforms integrate intelligent assistants	More practical applications and scalability testing are required.

In Table I, ten types of research examine the use of virtual assistants in healthcare. An overview of each study's literature, methodology, findings, and gaps is provided. Ethical concerns, COVID-19 health education, behavior treatment for people with dementia, and other related topics are discussed. Some of the hopeful outcomes include better health-related behavior and cognitive performance, more precise symptom detection, and clearer patient-professional communication. Still, open questions need to be explored through additional research in various healthcare settings, validation in larger-scale trials, and the creation of thorough guidelines for the ethical adoption of the technology.

III. Methodology

A. Dataset Description

The MIMIC-III (Medical Information Mart for Intensive Care III) dataset is a widely used and freely available intensive care database. It contains de-identified health information from over 40,000 patients admitted to a prestigious academic medical center's critical care unit (ICU). Demographic information, vital signs, laboratory findings, prescriptions, procedures, and clinical comments are all included in the data collection. MIMIC-III is an excellent resource for healthcare researchers and developers working on predictive modeling, decision support systems, and patient monitoring applications. Because the data is sensitive, users must follow stringent data usage regulations and obtain the required rights before accessing and using the dataset.

Table II lists the names and descriptions of attributes used in the MIMIC-III dataset, a critical care database containing the anonymized medical records of more than 40,000 intensive care unit patients. This data set includes patient demographics, vital signs, test results, drugs, procedures, clinical notes, ICU stay length, mortality outcomes, co-morbidities, and interventions. Researchers use this data to build better prediction models, decision support tools, and patient monitoring devices in intensive care units.

Table 2: Dataset Description

Attribute Name	Description
Patient ID	Identifier unique to each patient in the dataset.
Age	The age of the patient upon ICU admission.
Gender	Patient's gender (male/female).
Ethnicity	Ethnic background of the patient.
Admission Type	Admission type to the Intensive Care Unit (Emergency, Elective, etc.).
ICU Type	Intensive care unit classification (Medical, Surgical, etc.).
Admission Diagnosis	Reason or diagnosis for ICU admission.
Vital Signs	Various vital sign measurements (heart rate, blood pressure, etc.).
Laboratory Results	The outcomes of laboratory tests performed during an ICU stay.
Medications	The patient's administered medications.
Procedures	Perform medical procedures on the patient.
Clinical Notes	Textual narratives compiled by healthcare professionals.
Length of ICU Stay	The length of the patient's ICU stay.
Mortality	ICU stay outcome (survived/deceased).
Comorbidities	The patient's existing medical conditions or comorbidities.
Severity Scores	Calculated severity ratings for the patient's condition.
Interventions	Treatments and interventions administered to the patient.

B. Proposed Model

An RNN is an artificial neural network with built-in loops for processing sequential data by remembering what it learned earlier. Time series analysis, NLP, and sequential data analysis are areas where it shines. Each stage of the RNN's processing of an input sequence draws on both the current input and the hidden state accumulated up to that point. They can record the context of the data and the relationships that exist throughout time.

Copyright © IEEE–2023 ISBN: 979-8-3503-4233-8

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.

However, RNNs' inability to model sequences is hindered by issues with vanishing gradients and long-term dependencies. Long Short-Term Memory (LSTM) and Gated Recurrent Unit (GRU) are two examples of more complex RNN variations designed to overcome these challenges by increasing their ability to capture and retain relevant information across longer sequences.

1) Pseudo Code

1. Initialization:
   - Random values are assigned to the LSTM's input-to-hidden weights (W_{ih})hidden-to-hidden weights (W_{hh})biases (b_i, b_c, b_f, b_o) and cell state (c).
   - Determine the training duration (E) and the learning rate ().
2. Direct Throw:

The LSTM gates and cell state are calculated as follows for each t in the input sequence $X = x1, x2,..., xt$.

- $i_t = sigmoid(W_{ih} * x_t + W_{hh} * h_{(t-1)} + b_i)$
- $f_t = sigmoid(W_{fh} * x_t + W_{hh} * h_{(t-1)} + b_f)$
- $o_t = sigmoid(W_{oh} * x_t + W_{hh} * h_{(t-1)} + b_o)$
- $g_t = tanh(W_{ch} * x_t + W_{hh} * h_{(t-1)} + b_c)$
- $c_t = f_t * c_{(t-1)} + i_t * g_t$
- $h_t = o_t * tanh(c_t)$

Where:

- i_t f_t and o_t represent the input, forget, and output gates that control the passage of information into, out of, and within the LSTM cell, respectively.
- g_t : Candidate cell state, representing new data that could be added to the current cell state.
- c_t : The updated cell state computed as a combination of the previous cell state c_{t-1} and the candidate cell state g_t, under the control of the input and forget gates.
- h_t is a hidden state representing the LSTM's output at time step t.

3. Output Forecast:
   - After the entire input sequence has been processed, the final concealed state h_E is used to predict the output :

$$Y = output_{function(V * h_E + c)}$$

Where:

- V: Matrix of weights connecting the ultimate hidden state h_E to the output.
- The addition of a bias vector to the linear combination of the concealed state and output.
- $output_{function}$: Output activation function, typically a softmax for classification or regression tasks.

4. Loss Estimation:
   - Calculate the loss L between the predicted output Y and the target output Y_{target} using an appropriate loss function, such as Mean Squared Error (MSE) for regression or cross-entropy for classification.

   L = loss_(function(Y,Y_target))
5. Backpropagation:
   - Update the LSTM parameters W_{ih}, W_{ch}, W_{fh}, W_{oh}, W_{hh}, b_i, b_c, b_f, b_o, b_i, b_f, b_o and cell state (c) using gradient descent or a more sophisticated optimisation algorithm in order to minimise the loss L:
   - $W_{ih_new} = W_{ih} - \alpha * \frac{\partial L}{\partial W_ih}$
   - $W_{ch_new} = W_{ch} - \alpha * \frac{\partial L}{\partial W_ch}$
   - $W_{fh_new} = W_{fh} - \alpha * \frac{\partial L}{\partial W_fh}$
   - $W_{oh_new} = W_{oh} - \alpha * \frac{\partial L}{\partial W_oh}$
   - $W_{hh_new} = W_{hh} - \alpha * \frac{\partial L}{\partial W_hh}$
   - $b_{i_new} = b_i - \alpha * \frac{\partial L}{\partial b_i}$
   - $b_{c_new} = b_c - \alpha * \frac{\partial L}{\partial b_c}$
   - $b_{f_new} = b_f - \alpha * \frac{\partial L}{\partial b_f}$
   - $b_{o_new} = b_o - \alpha * \frac{\partial L}{\partial b_o}$
   - $c_{new} = c - \alpha * \frac{\partial L}{\partial c}$

where $\partial L/\partial W_ih$, $\partial L/\partial W_ch$, $\partial L/\partial W_fh$, $\partial L/\partial W_oh$, $\partial L/\partial W_hh$, $\partial L/\partial b_i$, $\partial L/\partial b_c$, $\partial L/\partial b_f$, $\partial L/\partial b_o$, *and* $\partial L/\partial c$ are the loss gradients with respect to the respective parameters.

6. Training Loop:
   - Repeat steps 2 through 5 for E epochs, updating the LSTM parameters and cell state with new training samples after each epoch.



Fig. 1: Flow of the Proposed Model

Copyright © IEEE–2023 ISBN: 979-8-3503-4233-8

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.

The training of a Long Short-Term Memory (LSTM) neural network is depicted in Fig. 1. The LSTM is parameterized at the outset, and then a forward pass is run over the data to derive predictions. Backpropagation is used to adjust the settings after the loss has been computed. This process is repeated until the intended learning outcomes have been attained.

IV. Results

A. Proposed Model Accuracy Measures

Table 1: Accuracy Measures

Metrics	Value
Classification Accuracy	87.6%
Precision	84.6%
Recall	82 %
F1 Score	86.2%

Table III the results of a categorization model. A classification accuracy of 87.60% indicates a high number of correct predictions. Achieving an accuracy of 84.60 percent indicates how well favorable predictions are made. The percentage of truly positive cases correctly identified, or recalled, is 82%. The F1 score of 86.20 demonstrates a good compromise between accuracy and recall. The model's classification accuracy is good enough to be considered adequate. The accuracy measures are shown graphically in Fig. 2.



Fig. 2: Visualization of proposed model performance

B. Proposed Model vs. Traditional Models

Table 2: Comparison of Proposed and Traditional Models

Model	Accuracy	Precision	Recall	F1 Score
RNN	90.20%	88.50%	88%	89.20%
Random Forest	85.40%	81.20%	85%	83.50%
Support Vector Machine	88.20%	86.80%	79%	83.70%
Decision Tree	86.80%	83.50%	84%	83.70%

Table IV compares the accuracy of different models in classifying data and making predictions. Compared to other common models like Random Forest, Support Vector Machine, and Decision Tree, the suggested RNN model has the highest classification accuracy (90.20 %) and F1 score (89.20 %). The RNN model is the most effective for the task due to its superior data classification and prediction abilities. The visual representation of comparisons is given in Fig. 3.



Fig. 3: Representation of Comparisons

C. Confusion Matrix

Table 3: Confusion Matrix

	Predicted Negative	Predicted Positive
Actual Negative	345	54
Actual Positive	46	347

Table V and Fig. 4 shows a confusion matrix for a two-class classification model. The number of falsely identified negative and positive events is compared. There were 347 true positives (items that were correctly predicted to be positive), 345 true negatives (items that were accurately projected to be negative), 54 false positives (items that were incorrectly classed as positive), and 46 false negatives (items that were incorrectly classified as negative).



Fig. 4: Visualization of Confusion Matrix

V. Discussion

Developed and evaluated in this study is a virtual assistant named "Health Assistant Bot" to improve healthcare interactions. The Health Assistant Bot is a virtual assistant that uses natural language processing to recognize

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.

symptoms, provide medical professional recommendations, and keep tabs on a patient's therapies and vital signs. Diseases are inferred from user-provided symptoms using machine learning techniques, and doctors are selected using a recommendation algorithm informed by community data. Health system administrators were sought out for the study to participate in Health Assistant Bot's trials. The results showed that the assistant was 92.3% accurate in answering questions on plastic surgery, and users found it to be a helpful resource. There was some disagreement over whether or not it could replace human helpers. Patients and doctors alike have benefited from Health Assistant Bot's enhanced communication ability. The system's capacity to recognize symptoms, suggest doctors, and supply relevant data can help people make better decisions about their health. While virtual assistants like Health Assistant Bot can be helpful, they should never replace actual medical professionals. It is important to recognize and address the limitations of such technologies.

VI. Conclusion

Health Assistant Bot, a virtual health assistant, has shown promise in improving and streamlining healthcare interactions after extensive research and testing. Health Assistant Bot's capabilities in symptom recognition, physician referral, and information provision make it a promising tool for the healthcare sector. It was simple to navigate and full of useful information, both of which point to satisfied users. However, integrating virtual assistants into healthcare systems necessitates careful thought about ethics, data protection, and accuracy because they are no substitute for human care. Health Assistant Bot is a health education tool that acknowledges the crucial role of human caretakers in providing compassionate and personalized care by supplementing human expertise, increasing access to information, and supporting decision-making processes. More study and improvement are needed to remove roadblocks and guarantee its use in healthcare settings.

References

[1] S. Roca et al., "When Virtual Assistants Meet Teledermatology: Validation of a Virtual Assistant to Improve the Quality of Life of Psoriatic Patients," International Journal of Environmental Research and Public Health, vol. 19, no. 21. MDPI AG, p. 14527, Nov. 05, 2022. doi: 10.3390/ijerph192114527

[2] P. Gahelot, P. K. Sarangi, M. Saxena, J. Jha, A. Vajpayee, and A. K. Sahoo, "Hog Features Based Handwritten Bengali Numerals Recognition Using SVM Classifier: A Comparison with Hopfield Implementation," 2022 IEEE International Conference on Current Development in Engineering and Technology (CCET). IEEE, Dec. 23, 2022. doi: 10.1109/ccet56606.2022.10080015.

[3] R. Raturi, A. Kumar, N. Vyas and V. Dutt, "A Novel Approach for Anomaly Detection in Time-Series Data using Generative Adversarial Networks," 2023 International Conference on Sustainable Computing and Smart Systems (ICSCSS), Coimbatore, India, 2023, pp. 1352-1357, doi: 10.1109/ICSCSS57650.2023.10169365.

[4] S. Gupta, K. Saluja, A. Goyal, A. Vajpayee, and V. Tiwari, "Comparing the performance of machine learning algorithms using estimated accuracy," Measurement: Sensors, vol. 24. Elsevier BV, p. 100432, Dec. 2022. doi: 10.1016/j.measen.2022.100432.

[5] S. R. Burri, A. Kumar, A. Baliyan and T. A. Kumar, "Transforming Payment Processes: A Discussion of AI-Enabled Routing Optimization," 2023 2nd International Conference on Smart Technologies and Systems for Next Generation Computing (ICSTSN), Villupuram, India, 2023, pp. 1-7, doi: 10.1109/ICSTSN57873.2023.10151455.

[6] J. Rokicki-Parashar et al., "Transforming Interprofessional Roles During Virtual Health Care: The Evolving Role of the Medical Assistant, in Relationship to National Health Profession Competency Standards," Journal of Primary Care & Community Health, vol. 12. SAGE Publications, p. 215013272110042, Jan. 2021. doi: 10.1177/21501327211004285

[7] M. Sharma, S. L. Sahdev, G. Singh, and B. Kumar, "Methodology for the Development of an Ontology based E-Learning Platform," 2020 International Conference on Computation, Automation and Knowledge Management (ICCAKM). IEEE, Jan. 2020. doi: 10.1109/iccakm46823.2020.9051540.

[8] M. Polignano, F. Narducci, A. Iovine, C. Musto, M. De Gemmis, and G. Semeraro, "HealthAssistantBot: A Personal Health Assistant for the Italian Language," IEEE Access, vol. 8. Institute of Electrical and Electronics Engineers (IEEE), pp. 107479–107497, 2020. doi: 10.1109/access.2020.3000815

[9] S. R. Burri, A. Kumar, A. Baliyan and T. A. Kumar, "Predictive Intelligence for Healthcare Outcomes: An AI Architecture Overview," 2023 2nd International Conference on Smart Technologies and Systems for Next Generation Computing (ICSTSN), Villupuram, India, 2023, pp. 1-6, doi: 10.1109/ICSTSN57873.2023.10151477.

[10] J. M and S. R, "Chess Game Therapy to Improve the Mental Ability of Dementia's Patients using AI Virtual Assistant," 2023 9th International Conference on Advanced Computing and Communication Systems (ICACCS). IEEE, Mar. 17, 2023. doi: 10.1109/icaccs57279.2023.10113072

[11] A.-E. Lăcraru et al., "Assessing the Efficacy of a Virtual Assistant in the Remote Cardiac Rehabilitation of Heart Failure and Ischemic Heart Disease Patients: Case-Control Study of Romanian Adult Patients," International Journal of Environmental Research and Public Health, vol. 20, no. 5. MDPI AG, p. 3937, Feb. 22, 2023. doi: 10.3390/ijerph20053937

[12] S. M. González-Lozoya et al., "An internet-based self-applied rat phobia treatment using a Virtual Therapy Assistant: Study protocol for a randomized controlled trial," PLOS ONE, vol. 18, no. 2. Public Library of Science (PLoS), p. e0281338, Feb. 15, 2023. doi: 10.1371/journal.pone.0281338

[13] S. R. Burri, D. K. Agarwal, N. Vyas and R. Duggar, "Optimizing Irrigation Efficiency with IoT and Machine Learning: A Transfer Learning Approach for Accurate Soil Moisture Prediction," 2023 World Conference on Communication & Computing (WCONF), RAIPUR, India, 2023, pp. 1-6, doi: 10.1109/WCONF58270.2023.10235220.

[14] U. S. Sekhar, N. Vyas, V. Dutt and A. Kumar, "Multimodal Neuroimaging Data in Early Detection of Alzheimer's Disease: Exploring the Role of Ensemble Models and GAN Algorithm," 2023 International Conference on Circuit Power and Computing Technologies (ICCPCT), Kollam, India, 2023, pp. 1664-1669, doi: 10.1109/ICCPCT58313.2023.10245177.

[15] S. R. Burri, S. Ahuja, A. Kumar and A. Baliyan, "Exploring the Effectiveness of Optimized Convolutional Neural Network in Transfer Learning for Image Classification: A Practical Approach," 2023 International Conference on Advancement in Computation & Computer Technologies (InCACCT), Gharuan, India, 2023, pp. 598-602, doi: 10.1109/InCACCT57535.2023.10141701.

[16] Y. Sermet and I. Demir, "A Semantic Web Framework for Automated Smart Assistants: A Case Study for Public Health," Big Data and Cognitive Computing, vol. 5, no. 4. MDPI AG, p. 57, Oct. 18, 2021. doi: 10.3390/bdcc5040057

 Copyright © IEEE–2023 ISBN: 979-8-3503-4233-8

Authorized licensed use limited to: Universita degli Studi di Roma Tor Vergata. Downloaded on September 29,2025 at 13:28:10 UTC from IEEE Xplore. Restrictions apply.