[Normal] Override Runtime Database limits ACU

By Tiago Oliveira 1 min 42 Add a reaction

This Change is part of the RDM - Change Catalog Runtime Data Model UNDEFINED.

1. Summary

In situations where Customers are hitting performance issues in runtime due to database high load, we can override the “contracted limits” (from License Definition) to temporarily mitigate end users impact.

For that, we need to add some annotations to the Environment being affected which will lead Terraform to apply such chances on the limits without any downtime.

2. General Information

Change Type	Normal
Change Risk	Low
Downtime Involved	No
Rollback Available	Yes
Implementation Team	SRE
Component(s)/Asset(s)	RDS Runtime Instance

Impact Description	Low runtime Performance due to database high load

Updated Sep 20, 2025 Edit

3. Pre-requisites

Inputs for execution

- Ring; `<ring>`
- Stamp (rundev, runnp or runp); `<stamp>`
- Region; `<region>`
- Environment key; `<environment_key>`
- Min ACUs (`<min_acu>`) and/or Max ACUs (`<max_acu>`) override value
  - Valid values for serverless v2: [0.5 - 128.0].

Technical requirements

- Kubectl
- Neoctl

Communication

N/A

Expected duration

- Override Max | Min ACUs ~ 1min

4. Implementation Plan

Implementation actions

The following actions need to be performed in order to enable Performance Insights & Enhanced Monitoring:

1. Using `kubectl` access the required ring, stamp and region by executing the following command:
   a.
   ```
   neoctl config use-kubeconfig <ring> <stamp> --region <regio
   ```

2. View the current ACUs
   a.
```
aws rds describe-db-clusters \
```

Updated Sep 20, 2025 Edit

3. For the environment, execute:
   a. If you want to override MinACUs
      i.
```
kubectl annotate --overwrite Environment <environment_key
```
      ii. Currently we have a limitation on product where we can'
   b. If you want to override MaxACUs
      i.
```
kubectl annotate --overwrite Environment <environment_key
```
4. (Optional) if changing MinAcus from 0 to another value:
   a.
```
aws rds modify-db-cluster --db-cluster-identifier env-<envi
  --serverless-v2-scaling-configuration MinCapacity=<min_ac
```
   b. While we don't migrate to Compositions or upgrade the module in REDI, this step is necessary.

Testing and validation plan

Ensure (in a matter of 10min max) that the terraform changed the min/max ACUs in such database.
For that, open AWS Console for the Runtime AWS account matching the specified `<ring> <stamp> <region>`, go over to RDS, and look for the `<environment_key>` and you should see that the instances are now configured with the overridden values.

Rollback plan

In order to remove the overrides, the following command would be executed:

-
```
kubectl annotate Environment <environment_key> runtimedb.outsy
```


```
kubectl annotate Environment <environment_key> runtimedb.outsy
```

5. Post Implementation

Updated Sep 20, 2025 Edit

- ```
  kubectl annotate Environment <environment_key> runtimedb.outsy
  ```


```
kubectl annotate Environment <environment_key> runtimedb.outsy
```


Related content Send feedback

[Normal] Avoid DB restart by increasing min ACU and apply os upgrade
António Caeiro

Adjust Resource Capacity
Joana Pequito

ICE | Change - Update workspace variables for stamp_max_capacity
Adonis Dutra

[Standard] Request limit increase for AWS RDS Cluster Parameter groups
Pedro Cardoso

ICE | Raise tenants limits on stamp
David Lopes

Runtime Data Model Repositories
Mariana Cabeda

Add a comment RDM-CATALOG-ITEM Add a reaction
```

Updated Sep 20, 2025

Edit