[Standard] Realm Replay Tenant for PIM access

By Mark Bonnot 1 min 10 Add a reaction

1. Summary

Tenant or environment is not working properly in a given stamp, PIM support is not able to access a Tenant. To bring back it up we need to perform a “realm replay” operation.

The effect of a replay is localized to the particular realm, and doesn’t affect other realms. For example, a replay of a tenant doesn’t affect the environments in that tenant (or in other tenants, for that matter).

> ⚠ If the realm is not down, a replay will cause it to be deleted and recreated, causing all users in that realm to be logged out.

2. General Information

Change Type	NORMAL
Change Risk	LOW
Category	Replay Realm
Operation	HTTP API call to replay realm
Implementation Team	Identity Core, SRE
Downtime Involved	No
Rollback Available	No

Impact Description	None.
RFC Request	https://outsystemsrd.atlassian.net/browse/RFC 3449
Incident	https://outsystemsrd.atlassian.net/browse/RDP1

3. Pre-requisites

Inputs for execution

- realm id `8a424fac-f6bb-4c26-9eed-8eb20ce8c839`
- tenant prefix: `woningnet`
- ring: `GA`
- region `eu-central-1`
- stamp: `platform`

Technical requirements

- Requires `kubectl`, `curl` to be installed. kubectl to port forward (you can use OpenLens)
- Requires the ability to connect to a given stamp's EKS cluster. (NeoCtl)

Communication

After the operation has been done, please let the Identity Core team know on #rd-identity-teams, or reach out to the Identity engineer that has been working closely with you, if applicable.

Expected duration

5 minutes

Implementation actions

1. Connect to the `platform` stamp with PowerUser in the given ring and region. in our case, `GA, eu-central-1`
2. port forward to the IBS `outsystems-identitybusiness-service` lets use 2222 for example
   a. get one of the pods name
      i. `kubectl get pods --namespace platform-services -l app=outsystems-identitybusiness-service`
   b. `kubectl port-forward pod/outsystems-identitybusiness-service-6774b9c8c6-48855 -n platform-services 2222:8080`
      i. `outsystems-identitybusiness-service-6774b9c8c6-48855` you would replace that with the pod you grabbed in step 2)a)i)
3. `curl --location --request POST 'http://localhost:<local-port>/identity/v2/realms?realmId=<realm-id>' \ --header 'X-OSTenant: <realm-id>' \ --header 'api-key: dummy-api-key'`
   a. `<realm-id>` should be filled in (see the “Inputs for execution” section above).
   b. `<local_port>` should be substituted with the port that you are using in the port forward.

Testing and validation plan

KCM will log `"Realm '{realmId}' was successfully created or updated."` After that it should be ready almost immediately, usually between 1-5 minutes. Then check that the well-known discovery document returns a successful response. It should return a 200 with a JSON response body.

The URL for the discovery document looks like `https://<tenant-prefix>.outsystems.dev/auth/realms/<realm-id>/.well-known/openid-configuration`.

in our case

https://woningnet.outsystems.dev/auth/realms/8a424fac-f6bb-4c26-9eed-8eb20ce8c839/.well-known/openid-configuration

Updated Sep 19, 2025

Edit

None.

Related content

Send feedback

[Normal] Realm replay
Smruthi Mohan

[Normal] Realm Replay GA Realms
Yang Yang

Realm Replay (Catalog Entry Version)
Rodrigo Bernardo

[Normal] Replay odc-trial-e2861 tenant in ring OSALL
Emanuel Brici

[Normal] Realm Replay, then send message to cmcp to continue onboarding
Michael Vaz

[Emergency] Replay demoteam tenant in ring OSRD
Rodrigo Bernardo

Add a comment

CHANGE-CATALOG-ID-CORE

Add a reaction