

MiniProject - Pathway Analysis from RNA-Seq Results

Vera Sophia Beliaev

2/27/2022

Pathway analysis helps to interpret gene lists by mapping the gene lists to known biological pathways, processes, and functions.

Section 1. Differential Expression Analysis

```
library(DESeq2)
```

```
## Loading required package: S4Vectors
```

```
## Loading required package: stats4
```

```
## Loading required package: BiocGenerics
```

```
##
```

```
## Attaching package: 'BiocGenerics'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##      IQR, mad, sd, var, xtabs
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      anyDuplicated, append, as.data.frame, basename, cbind, colnames,  
##      dirname, do.call, duplicated, eval, evalq, Filter, Find, get, grep,  
##      grepl, intersect, is.unsorted, lapply, Map, mapply, match, mget,  
##      order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,  
##      rbind, Reduce, rownames, sapply, setdiff, sort, table, tapply,  
##      union, unique, unsplit, which.max, which.min
```

```
##
```

```
## Attaching package: 'S4Vectors'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      expand.grid, I, unname
```

```
## Loading required package: IRanges
```

```

##
## Attaching package: 'IRanges'

## The following object is masked from 'package:grDevices':
##
##     windows

## Loading required package: GenomicRanges

## Loading required package: GenomeInfoDb

## Loading required package: SummarizedExperiment

## Loading required package: MatrixGenerics

## Loading required package: matrixStats

##
## Attaching package: 'MatrixGenerics'

## The following objects are masked from 'package:matrixStats':
##
##     colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,
##     colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
##     colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
##     colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
##     colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
##     colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
##     colWeightedMeans, colWeightedMedians, colWeightedSds,
##     colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,
##     rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
##     rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
##     rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
##     rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
##     rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
##     rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
##     rowWeightedSds, rowWeightedVars

## Loading required package: Biobase

## Welcome to Bioconductor
##
##     Vignettes contain introductory material; view with
##     'browseVignettes()'. To cite Bioconductor, see
##     'citation("Biobase")', and for packages 'citation("pkgname)".

##
## Attaching package: 'Biobase'

## The following object is masked from 'package:MatrixGenerics':
##
##     rowMedians

```

```
## The following objects are masked from 'package:matrixStats':
##
## anyMissing, rowMedians
```

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"
```

```
# Import metadata and take a peak
colData = read.csv(metaFile, row.names=1)
head(colData)
```

```
##              condition
## SRR493366 control_sirna
## SRR493367 control_sirna
## SRR493368 control_sirna
## SRR493369      hoxa1_kd
## SRR493370      hoxa1_kd
## SRR493371      hoxa1_kd
```

```
# Import countdata
countData = read.csv(countFile, row.names=1)
head(countData)
```

```
##              length SRR493366 SRR493367 SRR493368 SRR493369 SRR493370
## ENSG00000186092    918         0         0         0         0         0
## ENSG00000279928    718         0         0         0         0         0
## ENSG00000279457   1982        23        28        29        29        28
## ENSG00000278566    939         0         0         0         0         0
## ENSG00000273547    939         0         0         0         0         0
## ENSG00000187634   3214        124        123        205        207        212
##              SRR493371
## ENSG00000186092         0
## ENSG00000279928         0
## ENSG00000279457        46
## ENSG00000278566         0
## ENSG00000273547         0
## ENSG00000187634       258
```

Q1. Complete the code below to remove the troublesome first column from countData

We need to remove the “length” col from the countData to make it match the metadata

```
# Note we need to remove the odd first $length col
countData$length <- NULL
countData <- as.matrix(countData)
head(countData)
```

```
##              SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000186092         0         0         0         0         0         0
## ENSG00000279928         0         0         0         0         0         0
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000278566         0         0         0         0         0         0
## ENSG00000273547         0         0         0         0         0         0
## ENSG00000187634       124       123       205       207       212       258
```

Q2. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
#delete the rows which have no counts across all samples i.e. rowSums=0, subset fn dels the rows
countData <- subset(countData, rowSums(countData) != 0 )
head(countData)
```

```
##                SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000279457         23         28         29         29         28         46
## ENSG00000187634        124        123        205        207        212        258
## ENSG00000188976       1637       1831       2383       1226       1326       1504
## ENSG00000187961        120        153        180        236        255        357
## ENSG00000187583         24         48         65         44         48         64
## ENSG00000187642          4          9         16         14         16         16
```

```
dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

```
## Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
## design formula are characters, converting to factors
```

```
dds = DESeq(dds)
```

```
## estimating size factors
```

```
## estimating dispersions
```

```
## gene-wise dispersion estimates
```

```
## mean-dispersion relationship
```

```
## final dispersion estimates
```

```
## fitting model and testing
```

```
dds
```

```
## class: DESeqDataSet
## dim: 15975 6
## metadata(1): version
## assays(4): counts mu H cooks
## rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
##      ENSG00000271254
## rowData names(22): baseMean baseVar ... deviance maxCooks
## colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
## colData names(2): condition sizeFactor
```

```
res = results(dds, contrast=c("condition", "hoxa1_kd", "control_sirna"))
```


Q3. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff. 27% are upregulated and 28% are downregulated

```
summary(res)
```

```
##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)      : 4349, 27%
## LFC < 0 (down)    : 4396, 28%
## outliers [1]      : 0, 0%
## low counts [2]    : 1237, 7.7%
## (mean count < 0)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

```
#Make a volcano plot
```

```
plot( res$log2FoldChange, -log(res$padj) )
```



> Q4. Improve this plot by completing the below code, which adds color and axis labels

```


# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.01 ) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col="blue", xlab="Log2(FoldChange)", ylab="-Log(P-value)" )

```



Adding Gene Annotation

Q5. Use the `mapIDs()` function multiple times to add SYMBOL, ENTREZID and GENENAME annotation to our results by completing the code below.

```

library("AnnotationDbi")
library("org.Hs.eg.db")

```

```
##
```

```
columns(org.Hs.eg.db)
```

```
## [1] "ACCNUM"      "ALIAS"       "ENSEMBL"     "ENSEMBLPROT" "ENSEMBLTRANS"
## [6] "ENTREZID"    "ENZYME"      "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"    "GO"          "GOALL"        "IPI"          "MAP"
## [16] "OMIM"        "ONTOLOGY"    "ONTOLOGYALL"  "PATH"         "PFAM"
## [21] "PMID"        "PROSITE"     "REFSEQ"       "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

```
res$symbol = mapIds(org.Hs.eg.db,
                     keys=row.names(res),
                     keytype="ENSEMBL",
                     column="SYMBOL",
                     multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$entrez = mapIds(org.Hs.eg.db,
                     keys=row.names(res),
                     keytype="ENSEMBL",
                     column="ENTREZID",
                     multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$name = mapIds(org.Hs.eg.db,
                   keys=row.names(res),
                   keytype="ENSEMBL",
                   column="GENENAME",
                   multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
head(res, 10)
```

```
## log2 fold change (MLE): condition hoxa1_kd vs control_sirna
## Wald test p-value: condition hoxa1 kd vs control sirna
## DataFrame with 10 rows and 9 columns
##           baseMean log2FoldChange      lfcSE      stat      pvalue
##           <numeric>      <numeric> <numeric> <numeric> <numeric>
## ENSG00000279457  29.913579      0.1792571 0.3248216  0.551863 5.81042e-01
## ENSG00000187634 183.229650      0.4264571 0.1402658  3.040350 2.36304e-03
## ENSG00000188976 1651.188076    -0.6927205 0.0548465 -12.630158 1.43990e-36
## ENSG00000187961 209.637938      0.7297556 0.1318599  5.534326 3.12428e-08
## ENSG00000187583  47.255123      0.0405765 0.2718928  0.149237 8.81366e-01
## ENSG00000187642  11.979750      0.5428105 0.5215598  1.040744 2.97994e-01
## ENSG00000188290 108.922128      2.0570638 0.1969053 10.446970 1.51282e-25
## ENSG00000187608 350.716868      0.2573837 0.1027266  2.505522 1.22271e-02
## ENSG00000188157 9128.439422      0.3899088 0.0467163  8.346304 7.04321e-17
## ENSG00000237330   0.158192      0.7859552 4.0804729  0.192614 8.47261e-01
```

##		padj	symbol	entrez	name
##		<numeric>	<character>	<character>	<character>
##	ENSG00000279457	6.86555e-01	WASH9P	102723897	WAS protein family h..
##	ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..
##	ENSG00000188976	1.76549e-35	NOC2L	26155	NOC2 like nucleolar ..
##	ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..
##	ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..
##	ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..
##	ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..
##	ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..
##	ENSG00000188157	4.21963e-16	AGRN	375790	agrin
##	ENSG00000237330	NA	RNF223	401934	ring finger protein ..

Q6. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res = res[order(res$pvalue),]
write.csv(res, "deseq_results.csv")
```

Section 2. Pathway Analysis

```
library(pathview)
```

```
## #####
## Pathview is an open source software package distributed under GNU General
## Public License version 3 (GPLv3). Details of GPLv3 is available at
## http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
## formally cite the original Pathview paper (not just mention it) in publications
## or products. For details, do citation("pathview") within R.
##
## The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG
## license agreement (details at http://www.kegg.jp/kegg/legal.html).
## #####
```

```
library(gage)
```

```
##
```

```
library(gageData)
```

```
data(kegg.sets.hs)
```

```
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```



```
## $'hsa00232 Caffeine metabolism'
## [1] "10" "1544" "1548" "1549" "1553" "7498" "9"
##
## $'hsa00983 Drug metabolism - other enzymes'
## [1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
## [9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
## [17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
## [25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
## [33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
## [41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
## [49] "8824" "8833" "9" "978"
##
## $'hsa00230 Purine metabolism'
## [1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
## [9] "108" "10846" "109" "111" "11128" "11164" "112" "113"
## [17] "114" "115" "122481" "122622" "124583" "132" "158" "159"
## [25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
## [33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
## [41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
## [49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
## [57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
## [65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
## [73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
## [81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
## [89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
## [97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
## [105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
## [113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
## [121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
## [129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
## [137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
## [145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
## [153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
## [161] "9583" "9615"
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
##      1266      54855      1465      51232      2034      2317
## -2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
attributes(keggres)
```

```
## $names
## [1] "greater" "less" "stats"
```

```
# Look at the first few down (less) pathways
head(keggres$less)
```

```
##                p.geomean stat.mean      p.val
## hsa04110 Cell cycle      8.995727e-06 -4.378644 8.995727e-06
## hsa03030 DNA replication  9.424076e-05 -3.951803 9.424076e-05
## hsa03013 RNA transport    1.375901e-03 -3.028500 1.375901e-03
## hsa03440 Homologous recombination 3.066756e-03 -2.852899 3.066756e-03
## hsa04114 Oocyte meiosis    3.784520e-03 -2.698128 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 8.961413e-03 -2.405398 8.961413e-03
##                q.val set.size      exp1
## hsa04110 Cell cycle      0.001448312    121 8.995727e-06
## hsa03030 DNA replication  0.007586381     36 9.424076e-05
## hsa03013 RNA transport    0.073840037    144 1.375901e-03
## hsa03440 Homologous recombination 0.121861535     28 3.066756e-03
## hsa04114 Oocyte meiosis    0.121861535    102 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 0.212222694     53 8.961413e-03
```

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq
```

```
## Info: Writing image file hsa04110.pathview.png
```

```
# A different PDF based output of the same data
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq
```

```
## Info: Writing image file hsa04110.pathview.pdf
```

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]
```

```
# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
## [1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq
```

```
## Info: Writing image file hsa04640.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa04630.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa00140.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa04142.pathview.png

## Info: some node width is different from others, and hence adjusted!

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa04330.pathview.png
```

Q7. Can you do the same procedure as above to plot the pathview figures for the top 5 down-regulated pathways?

```
## Focus on top 5 downregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$less)[1:5]
```

```
# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
## [1] "hsa04110" "hsa03030" "hsa03013" "hsa03440" "hsa04114"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

```
## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa04110.pathview.png
```

```
## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa03030.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa03013.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa03440.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory C:/Users/belia/OneDrive/Desktop/BIMM143/MiniProject_RNASeq

## Info: Writing image file hsa04114.pathview.png
```

Section 3. Gene Ontology

```
#Contains all GO terms
data(go.sets.hs)
#Named list containing indexes for BP, CC, MF ontologies
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)

lapply(gobpres, head)
```

```
## $greater
##
##           p.geomean stat.mean      p.val
## GO:0007156 homophilic cell adhesion 8.519724e-05 3.824205 8.519724e-05
## GO:0002009 morphogenesis of an epithelium 1.396681e-04 3.653886 1.396681e-04
## GO:0048729 tissue morphogenesis 1.432451e-04 3.643242 1.432451e-04
## GO:0007610 behavior 2.195494e-04 3.530241 2.195494e-04
## GO:0060562 epithelial tube morphogenesis 5.932837e-04 3.261376 5.932837e-04
## GO:0035295 tube development 5.953254e-04 3.253665 5.953254e-04
##           q.val set.size      exp1
## GO:0007156 homophilic cell adhesion 0.1951953      113 8.519724e-05
```

```
## G0:0002009 morphogenesis of an epithelium 0.1951953      339 1.396681e-04
## G0:0048729 tissue morphogenesis          0.1951953      424 1.432451e-04
## G0:0007610 behavior                      0.2243795      427 2.195494e-04
## G0:0060562 epithelial tube morphogenesis 0.3711390      257 5.932837e-04
## G0:0035295 tube development              0.3711390      391 5.953254e-04
##
## $less
##
##           p.geomean stat.mean      p.val
## G0:0048285 organelle fission      1.536227e-15 -8.063910 1.536227e-15
## G0:0000280 nuclear division      4.286961e-15 -7.939217 4.286961e-15
## G0:0007067 mitosis                4.286961e-15 -7.939217 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.169934e-14 -7.797496 1.169934e-14
## G0:0007059 chromosome segregation    2.028624e-11 -6.878340 2.028624e-11
## G0:0000236 mitotic prometaphase     1.729553e-10 -6.695966 1.729553e-10
##
##           q.val set.size      exp1
## G0:0048285 organelle fission      5.841698e-12      376 1.536227e-15
## G0:0000280 nuclear division      5.841698e-12      352 4.286961e-15
## G0:0007067 mitosis                5.841698e-12      352 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.195672e-11      362 1.169934e-14
## G0:0007059 chromosome segregation    1.658603e-08      142 2.028624e-11
## G0:0000236 mitotic prometaphase     1.178402e-07       84 1.729553e-10
##
## $stats
##
##           stat.mean      exp1
## G0:0007156 homophilic cell adhesion    3.824205 3.824205
## G0:0002009 morphogenesis of an epithelium 3.653886 3.653886
## G0:0048729 tissue morphogenesis        3.643242 3.643242
## G0:0007610 behavior                    3.530241 3.530241
## G0:0060562 epithelial tube morphogenesis 3.261376 3.261376
## G0:0035295 tube development            3.253665 3.253665
```

Section 4. Reactome Analysis

Reactome: a db of biological molescs and their relation to pathways and processes

```
#output list of alpha=.05 significant genes as a plain text file
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
## [1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=FALSE)
```

Do pathway analysis online at the Reactome site

Q8: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods? The Endosomal/Vacuolar pathway has the most significant entities p-value. The most significant listed pathways are somewhat similar to the KEGG results but not too close. Many factors could account for the difference such as sources of data, significance procedures, etc.

#Section 5. GO Online

Q9: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods? I was not able to locate an entities p value on the GO site. The most significant raw P value was attributed to “detection of chemical stimulus involved in sensory perception.”