

Technical Acetone 99.5%

PRODUCT DATA SHEET
FT-AK995-2024

1. PRODUCT IDENTIFICATION

CAS No.	67-64-1	EC No.	200-662-2
Formula	$\text{C}_3\text{H}_6\text{O} \text{ — } (\text{CH}_3)_2\text{CO}$	Molar mass	58.08 g/mol
Chemical family	Aliphatic ketone	Grade	Technical

Available pack sizes: 25 L can (HDPE) | 200 L drum (stainless steel) | 1000 L IBC

2. PHYSICO-CHEMICAL PROPERTIES

Property	Value
Physical state	Colourless liquid
Odour	Characteristic, fruity
Boiling point	56.0 °C (1013 hPa)
Flash point	-18 °C (closed cup)
Density at 20°C	0.790 g/mL
Vapour pressure at 20°C	233 hPa
Viscosity at 20°C	0.32 mPa·s
Solubility in water	Miscible in all proportions
Refractive index nD20	1.3588
Auto-ignition temperature	465 °C
Explosive limits (LEL/UEL)	2.5% / 13.0% vol.

3. ANALYTICAL SPECIFICATIONS

Parameter	Specification
Purity (GC)	≥ 99.5%
Water (Karl Fischer)	≤ 0.20%
Acidity (as acetic acid)	≤ 0.002%
Evaporation residue	≤ 0.001%
Colour (Hazen/APHA)	≤ 10
Methanol	≤ 0.05%
Isopropanol	≤ 0.05%

4. APPLICATIONS AND USES

- Solvent for organic synthesis (esterification, aldol condensation)
- Degreasing and cleaning of metal and plastic surfaces
- Thinner for resins, paints and varnishes
- Liquid-liquid extraction in pharmaceutical and food chemistry
- Polymer manufacture (PMMA, polycarbonate)
- Degreasing in electronics (printed circuit board cleaning)

5. HAZARD INFORMATION (CLP/GHS)

Code	Hazard statement
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

6. PRECAUTIONARY STATEMENTS

Code	Precautionary statement
P210	Keep away from heat, sparks and open flames
P233	Keep container tightly closed
P261	Avoid breathing vapours
P305+P351+P338	IF IN EYES: rinse cautiously with water
P370+P378	In case of fire: use CO ₂ or all-purpose foam

7. STORAGE AND SHELF LIFE

Store in a cool, well-ventilated area away from sources of ignition. Recommended storage temperature: 5–25°C. Keep away from strong oxidisers, acids and concentrated bases. Shelf life: 36 months in the unopened original packaging.

8. TRANSPORT AND REGULATIONS

UN 1090 | ADR class 3 | Packing group II | Tunnel code D/E

9. DETAILED APPLICATION NOTES

Material compatibility

Before use at scale, check compatibility with seals, pipework and containers. Give preference to materials tested and validated by ChemCorp Industries. Refer to the chemical compatibility tables available on our technical portal (portail.chemcorp.fr/compat). If in doubt, contact our Technical Application service on +33 4 72 XX XX XX.

Quality control on receipt

On receipt, check the integrity of the packaging and that the batch numbers match the accompanying certificate of analysis. Carry out a density and pH check where available. In the event of an anomaly, keep the original packaging and contact our quality department within 48 hours. Procedure ref.: QC-RECEP-003.

Waste management

Waste from this product must be managed in accordance with local hazardous waste regulations (Directive 2008/98/EC). Contact an approved contractor for disposal. European Waste Code (EWC): 06 01 04* for acid solutions, 07 01 01* for halogenated solvents, 07 01 04* for other organic solvents. Never discharge into drains or watercourses.

First aid (operational summary)

INHALATION: Move the person to fresh air, in a semi-seated position. If breathing is difficult, administer O₂ and call the emergency services (15 in France). SKIN CONTACT: Remove contaminated clothing. Rinse with plenty of water for at least 15 minutes. EYE CONTACT: Rinse with water for at least 15 minutes, holding the eyelids open. Consult an ophthalmologist. INGESTION: Do not induce vomiting. Rinse the mouth. Call the Poison Control Centre (European number: 0800 59 59 59).

Environmental data (in-house results)

BOD₅ (5 days): tested per ISO 5815. COD: tested per ISO 15705. Log Kow (n-octanol/water partition coefficient): measured per OECD 117. Aerobic biodegradability: tested per OECD 301B. Aquatic toxicity (Daphnia magna): EC₅₀ per OECD 202. For the complete numerical values, refer to section 12 of the Safety Data Sheet.

Additional regulatory information

This product is registered under REACH: registration number available on request. It is / is not on the SVHC candidate list (last ECHA update: Jan 2025). IED Directive: applicable to installations using this product in quantities above 200 t/year. French ICPE: check the classification under the ICPE nomenclature (heading 1175, 4110 or 4XXX depending on the product). Certifications: ISO 9001:2015 | Analysed by COFRAC No. 1-5421 | REACH SVHC: not concerned.