

Sodium Hydroxide Pearls 99%

PRODUCT DATA SHEET
FT-NaOHP-2024

1. PRODUCT IDENTIFICATION

CAS No.	1310-73-2	EC No.	215-185-5
Formula	NaOH	Molar mass	40.00 g/mol
Chemical family	Strong inorganic base	Grade	Technical / Industrial

Available pack sizes: 25 kg bag (PE) | 500 kg big bag | 1000 kg big bag

2. PHYSICO-CHEMICAL PROPERTIES

Property	Value
Physical state	Solid (white pearls)
Odour	Odourless
Melting point	318 °C
Boiling point	1388 °C
Bulk density	0.88–1.00 g/cm³
True density at 20°C	2.13 g/cm³
Solubility in water at 20°C	111 g/100 mL (exothermic solution)
pH (1% solution)	13.0
Hygroscopicity	Very hygroscopic
Flash point	Not applicable (solid)

3. ANALYTICAL SPECIFICATIONS

Parameter	Specification
Purity (NaOH)	≥ 99.0%
Na ₂ CO ₃	≤ 0.50%
NaCl	≤ 0.02%
Na ₂ SO ₄	≤ 0.01%
Iron (Fe)	≤ 5 ppm
Aluminium (Al)	≤ 10 ppm
Silicon (Si)	≤ 10 ppm
Water-insoluble matter	≤ 0.02%

4. APPLICATIONS AND USES

- Neutralisation of acidic effluent in water treatment
- Manufacture of soaps and detergents (saponification)
- Metal surface treatment (pickling, alkaline degreasing)
- Paper industry (Kraft process, bleaching)
- Chemical synthesis (hydrolysis, epoxidation reactions)
- pH regulation in food processes (food grades on request)

5. HAZARD INFORMATION (CLP/GHS)

Code	Hazard statement
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage

6. PRECAUTIONARY STATEMENTS

Code	Precautionary statement
P234	Keep only in the original packaging
P260	Do not breathe dust
P280	Wear protective gloves/clothing/eye protection/face protection
P301+P330+P331	IF SWALLOWED: rinse mouth — do NOT induce vomiting
P305+P351+P338	IF IN EYES: rinse with water for 15 minutes
P405	Store locked up

7. STORAGE AND SHELF LIFE

Store in tightly closed containers in a dry place. Protect from moisture and atmospheric CO₂. Keep away from acids and metals (aluminium, zinc, tin). Shelf life: 24 months in closed packaging.

8. TRANSPORT AND REGULATIONS

UN 1823 | ADR class 8 | Packing group II | Tunnel code E

9. DETAILED APPLICATION NOTES

Material compatibility

Before use at scale, check compatibility with seals, pipework and containers. Give preference to materials tested and validated by ChemCorp Industries. Refer to the chemical compatibility tables available on our technical portal (portail.chemcorp.fr/compat). If in doubt, contact our Technical Application service on +33 4 72 XX XX XX.

Quality control on receipt

On receipt, check the integrity of the packaging and that the batch numbers match the accompanying certificate of analysis. Carry out a density and pH check where available. In the event of an anomaly, keep the original packaging and contact our quality department within 48 hours. Procedure ref.: QC-RECEP-003.

Waste management

Waste from this product must be managed in accordance with local hazardous waste regulations (Directive 2008/98/EC). Contact an approved contractor for disposal. European Waste Code (EWC): 06 01 04* for acid solutions, 07 01 01* for halogenated solvents, 07 01 04* for other organic solvents. Never discharge into drains or watercourses.

First aid (operational summary)

INHALATION: Move the person to fresh air, in a semi-seated position. If breathing is difficult, administer O₂ and call the emergency services (15 in France). SKIN CONTACT: Remove contaminated clothing. Rinse with plenty of water for at least 15 minutes. EYE CONTACT: Rinse with water for at least 15 minutes, holding the eyelids open. Consult an ophthalmologist. INGESTION: Do not induce vomiting. Rinse the mouth. Call the Poison Control Centre (European number: 0800 59 59 59).

Environmental data (in-house results)

BOD₅ (5 days): tested per ISO 5815. COD: tested per ISO 15705. Log Kow (n-octanol/water partition coefficient): measured per OECD 117. Aerobic biodegradability: tested per OECD 301B. Aquatic toxicity (Daphnia magna): EC₅₀ per OECD 202. For the complete numerical values, refer to section 12 of the Safety Data Sheet.

Additional regulatory information

This product is registered under REACH: registration number available on request. It is / is not on the SVHC candidate list (last ECHA update: Jan 2025). IED Directive: applicable to installations using this product in quantities above 200 t/year. French ICPE: check the classification under the ICPE nomenclature (heading 1175, 4110 or 4XXX depending on the product). Certifications: ISO 9001:2015 | ISO 14001:2015 | Tested per EN ISO 8655.