

MOMENTO

User Test Manual

A step-by-step acceptance-test guide for every feature shipped in the current release.

Product: Momento — event photo & video sharing

Document type: Manual / User Acceptance Testing (UAT) script

Release branch: `feature/quest-photo-requests` · Build ref: `bdabd5c`

Prepared: 21 July 2026



About this manual

This manual walks a tester through every user-facing feature added to Momento, in the order a real host and guest would meet them. Each feature has a short description, the preconditions it needs, and a numbered set of test cases with the exact expected result.

Who does what

Host	The person who owns an event. Signs in, creates events, shares them, moderates uploads, turns features on/off. Uses the Dashboard .
Guest	Anyone with the event link or QR code. No account needed . Uploads photos/videos, browses the feed, finds their own photos, watches the recap. Uses the Guest feed at <code>/e/<event-slug></code> .
Admin	A Momento super-admin. Moderates host accounts platform-wide from the Admin panel .

Before you start — environment

- Open the app in a modern browser (Chrome, Safari, or Edge). Most of the app is mobile-first — test on a phone *and* a laptop where noted.
- You will need at least: **one host login**, a handful of **test photos/videos** (including at least one clear selfie of a real face for Face Search), and a second device or private window to act as a **guest**.
- Some features depend on external services being configured: **Cloudinary** (uploads), **QStash** (background jobs for recaps, face indexing, account purge), **Azure AI Face** (face search), and email delivery. If a service is not wired up in the environment under test, mark the dependent cases *Blocked* rather than *Fail*.

How to record results

Fill the run sheet below once per test session, then mark each test case **Pass**, **Fail**, or **Blocked** in its right-hand column. For a failure, note the case ID and what actually happened.

Tester name	
Date / time	
Build / commit	
Environment (URL)	
Devices used	

Contents

1. **1** Account & authentication
2. **2** Host profile
3. **3** Dashboard onboarding tour
4. **4** Creating & editing events
5. **5** Event timezone & feed windows
6. **6** Sharing an event with guests
7. **7** QR print packs
8. **8** Guest photo requests
9. **9** Face search (find my photos)
10. **10** AI event recaps
11. **11** Guest uploads
12. **12** Guest feed & filters
13. **13** Media management (host)
14. **14** Admin moderation

1 • Account & authentication

Hosts register, sign in, and recover their password. Guests never need an account.

Who	Host
Where	<code>/auth/register</code> , <code>/auth/login</code> , <code>/auth/forgot-password</code>
Preconditions	A working email inbox for the reset flow.

ID	STEPS	EXPECTED RESULT	RESULT
1.1	1. Go to <code>/auth/register</code> . 2. Choose account type (Individual or Company), fill the required fields, submit.	Account is created and you land on the dashboard (or an email-confirmation prompt if confirmation is enabled).	☐
1.2	1. Sign out, go to <code>/auth/login</code> . 2. Enter the credentials and submit.	You are signed in and redirected to the dashboard.	☐
1.3	1. On login, enter a wrong password.	A clear error appears; you are not signed in.	☐
1.4	1. Open <code>/auth/forgot-password</code> , submit your email. 2. Open the reset link from the email, set a new password.	Reset email arrives; the new password works on next login.	☐
1.5	1. From the dashboard header, choose Sign out . 2. Try to open <code>/dashboard</code> directly.	You are signed out and redirected to the login page when visiting a protected route.	☐

2 • Host profile

Hosts maintain a profile: display identity, a country, an avatar, a short bio, and a contact phone.

Who	Host
Where	Dashboard header →  Profile (/dashboard/profile)
Rules	Avatar must be an image under 8 MB . Bio up to 300 characters. Phone must match a valid phone format. Account type toggles between Individual (first/last name) and Company (company name).

ID	STEPS	EXPECTED RESULT	RESULT
2.1	1. Open Profile from the dashboard header.	Existing values (name, country, bio, phone, avatar) load into the form.	☐
2.2	1. Click the avatar, choose an image under 8 MB.	Avatar uploads and the new picture is shown. Saving persists it.	☐
2.3	1. Try to upload a non-image, or an image over 8 MB.	A friendly error (“Please choose an image file” / “Image must be under 8MB”); no upload.	☐
2.4	1. Type a bio longer than 300 characters.	Input is capped at 300 characters.	☐
2.5	1. Enter an invalid phone (e.g. <code>abc</code>), Save.	“Enter a valid phone number” error; the profile is not saved.	☐
2.6	1. Switch account type Individual ⇌ Company.	Name fields swap between first/last name and company name accordingly.	☐
2.7	1. Make valid edits, Save, then reload the page.	A saved confirmation shows; values persist after reload.	☐

3 · Dashboard onboarding tour

A first-time host is walked through creating their first event with a short guided tour.

Who	Host (new)
Where	Dashboard (/dashboard)
Tour steps	 Welcome →  Create your first event →  Give it a title & category →  You're ready

ID	STEPS	EXPECTED RESULT	RESULT
3.1	1. Sign in as a host with no events (or a fresh account).	The welcome tooltip appears; tour highlights the correct element at each step.	☐
3.2	1. Advance through all four steps.	Each step points to the right control (New event button → title/category → Create event) and the tooltip stays on-screen (no overflow).	☐
3.3	1. Dismiss the tour, reload the dashboard.	The tour does not reappear once completed/dismissed.	☐

4 · Creating & editing events

Hosts create an event, then edit or delete it. Deleting an event permanently removes its uploaded media from storage.

Who	Host
Where	Dashboard → New event · Event dashboard → Edit event / Delete event
Fields	Title (required), Category (drives a matching icon), Location, Description, Date, Time.
Note	Each event uploads to its own Cloudinary folder (<code>Momento/events/<slug></code>); deleting an event destroys those assets — it does not orphan them.

ID	STEPS	EXPECTED RESULT	RESULT
4.1	1. Dashboard → + New event , fill title + category + details, Create event .	Event is created and appears in the list with a shareable link and slug.	☐
4.2	1. Try to create with an empty title.	The Create button is disabled / creation blocked until a title is entered.	☐
4.3	1. Open an event, click Edit event , change title/description/location/date/time, Save changes .	Changes persist and show in the event header.	☐
4.4	1. Have a guest upload at least one photo (see §11). 2. Open the event, Delete event , confirm.	Confirmation warns the action is permanent; after confirming you return to the dashboard and the event (and its stored media) are gone.	☐

5 · Event timezone & feed windows

An event's date/time is a wall clock *at the venue*. The event carries a timezone so “feed closes 24h after start” lands correctly no matter where the host or guest is.

Who	Host sets it; guests see the result
Where	Event dashboard → Edit event → timezone line + Feed visibility
Controls	Timezone (defaults to the host's detected zone, collapsed), Open feed at (optional), Close feed (none / preset / custom date-time).

ID	STEPS	EXPECTED RESULT	RESULT
5.1	1. Edit an event. Note the timezone line under Date/Time.	It defaults to your detected zone and is collapsed; a Change link expands a full timezone picker.	☐
5.2	1. Change the timezone to a different region, Save, reopen Edit.	The typed times stay as typed; the zone label reflects the new choice.	☐
5.3	1. Set Close feed to a preset (e.g. 24h after start) with a venue in another zone. 2. Open the guest feed.	The countdown/close time reflects the venue's wall clock in its zone — not the host's browser zone.	☐
5.4	1. Set Open feed at to a future time, Save. 2. Visit the guest feed before that time.	The feed shows a “not open yet” state until the open time passes.	☐
5.5	1. As a guest, view the event time.	The venue time is shown with its zone (e.g. “2:00 PM EDT”), the same for every viewer regardless of their location.	☐

Legacy check: Events created before timezones existed keep `timezone = null` and must behave exactly as before (resolved in the host's browser zone). Confirm an old event's times don't shift.

6 · Sharing an event with guests

The “Share with guests” card gives every way to hand the event to guests: link, native share, QR code, and a live preview.

Who	Host
Where	Event dashboard → Share with guests card

ID	STEPS	EXPECTED RESULT	RESULT
6.1	1. Click Copy next to the event URL.	Label flips to “Copied!”; the URL is on the clipboard.	☐
6.2	1. Click ↗ Share event link .	On mobile, the native share sheet opens; on desktop it falls back to copying and shows “✓ Link copied!”.	☐
6.3	1. Click Show QR code .	A QR on a cream card appears; scanning it opens the guest feed.	☐
6.4	1. Click ↓ Download QR , then ↗ Share QR .	A high-res PNG downloads; Share offers native share / clipboard fallback.	☐
6.5	1. Click ↗ Preview guest feed .	The guest feed opens in a new tab exactly as guests will see it.	☐

7 · QR print packs

Beyond a bare QR, hosts generate premium, print-ready signage auto-filled from the event: a welcome sign, table cards, and a reception poster — in the app's olive/cream brand.

Who	Host
Where	Event dashboard → ◆ Create print pack
Pieces	Welcome sign (A4), Table cards (A6, laid out multiple-up on an A5/A4 sheet), Reception poster (A3).
Editable	Heading, message, date, time, and accent colour. QR always sits on a white card for scan contrast.
Export	High-res PNG (via canvas) and print-sized PDF (jsPDF, lazy-loaded when the modal opens).

ID	STEPS	EXPECTED RESULT	RESULT
7.1	1. Click ◆ Create print pack .	The modal opens showing a live preview; date & time are pre-filled from the event (timezone-aware).	☐
7.2	1. Switch between Welcome sign, Table cards, Reception poster.	The preview updates to each template at the right proportions; the QR encodes the correct event URL.	☐
7.3	1. Edit the heading, message, date, time, and colour.	The live preview reflects each change immediately; the QR card stays white.	☐
7.4	1. Download the PNG for a piece.	A high-resolution PNG downloads with a sensible filename.	☐
7.5	1. Download the PDF for a piece; open and (optionally) print it.	A correctly-sized print PDF downloads; scanning the printed/PDF QR opens the guest feed.	☐

8 · Guest photo requests

Hosts nudge guests toward a shot they're missing. The newest live request shows as a banner at the top of the guest feed with a one-tap upload link — no guest account or push needed.

Who	Host creates; guests see
Where	Host: event dashboard → Guest photo requests . Guest: banner atop <code>/e/<slug></code> .
Presets	“Need more dance floor photos”, “Show us the toast & speeches”, “Get a big group photo”, “Snap the food & drinks table”, “Capture the decor & details”. Custom text up to 120 chars.
Behaviour	Guest feed shows only the newest live request, and only while the feed is open . The feed polls for new requests every ~20 seconds.

Host side

ID	STEPS	EXPECTED RESULT	RESULT
8.1	1. In Guest photo requests , tap a preset chip (e.g. “Need more dance floor photos”).	The request sends and appears in the active list with a 📷 prefix.	☐
8.2	1. Type custom text in “Or write your own...”, press Send (or Enter).	Custom request is sent; input is capped at 120 characters; empty text can't be sent.	☐
8.3	1. On an active request, click Done .	Button shows “Clearing...” then the request is removed from the active list.	☐

Guest side

ID	STEPS	EXPECTED RESULT	RESULT
8.4	1. With the feed open, send a request from the host, then open/refresh the guest feed.	An olive banner shows “📷 <prompt>” with an Upload → link at the top of the feed.	☐
8.5	1. Send a second request from the host and wait ~20s on the guest feed.	The banner updates to the newest request without a manual refresh; only one banner shows at a time.	☐
8.6	1. Tap Upload → in the banner.	You land on the event's upload page.	☐
8.7	1. Tap the X on the banner.	The banner is dismissed for that guest session.	☐

8.8	1. Close the feed (host, §5) and reload the guest feed.	No request banner shows while the feed is closed.	☐
-----	---	---	--------------------------

9 · Face search — “find my photos”

Off by default, per event. When a host turns it on (attesting to guest consent), guests can upload a selfie and filter the feed down to every photo they appear in. The selfie is never stored.

Who	Host enables; guests search
Where	Host: event dashboard → Face search toggle. Guest: 📷 Find my photos chip in the feed filter bar.
Privacy	The searcher’s selfie is downscaled on-device and used for one request only — never saved, added to the album, or indexed. Face data is per-event and is deleted when the host turns the toggle off or deletes the event.
Depends on	Azure AI Face credentials configured. Newly indexed faces need a brief train step before they’re searchable.

Host side

ID	STEPS	EXPECTED RESULT	RESULT
9.1	1. In the Face search card, toggle from Off to On.	A confirmation asks you to confirm you have guests’ consent; confirming turns it On (“On”). Existing photos are back-indexed.	☐
9.2	1. Toggle it back Off, confirm.	A warning explains face data is deleted immediately and re-enabling re-scans from scratch; after confirm the toggle reads “Off”.	☐

Guest side

ID	STEPS	EXPECTED RESULT	RESULT
9.3	1. With face search on and photos indexed, open the guest feed.	A 📷 Find my photos chip appears in the filter bar. It is absent when the feature is off.	☐
9.4	1. Tap the chip; read the notice; add a clear selfie; search.	The notice states the selfie isn’t saved/shared and is deleted when the search finishes. Results filter to photos containing that face; chip shows “✓ My photos (N)”.	☐
9.5	1. Tap the active “✓ My photos” chip.	The face filter clears and the full feed returns.	☐
9.6	1. Search with a selfie of someone not in any photo.	A graceful “no matches” style result — no crash.	☐

Teardown check: After a guest deletes their photo or the host deletes a photo/event, the corresponding face data should be gone too — a later search must not surface a deleted photo.

10 • AI event recaps

A curated ~90-second highlight reel of an event’s best moments, chosen from engagement, face-count and hashtag signals, and played as a slideshow. Generation runs as a background job.

Who	Host generates; anyone watches
Where	Host: event dashboard → Event recap . Guest: 🎬 Watch recap chip → <code>/e/<slug>/recap</code> .
States	idle → Generating... (processing) → Ready (N moments) or Failed . The dashboard card polls and flips automatically.
Depends on	QStash background jobs and enough uploaded media to curate.

ID	STEPS	EXPECTED RESULT	RESULT
10.1	1. With several photos uploaded, click Generate recap .	The button shows “Generating...”; the card is disabled while processing.	☐
10.2	1. Wait for the job to finish (card auto-polls).	The card flips to Ready , shows “N moments · generated <time ago>”, and a View recap → link — no manual refresh.	☐
10.3	1. Click View recap → (host) or the 🎬 Watch recap chip (guest).	The recap page plays an auto-advancing slideshow of the selected moments.	☐
10.4	1. On the recap page, use ↗ Share .	Native share opens, or the link copies with “✓ Copied”.	☐
10.5	1. Click Regenerate after uploading more media.	A fresh recap is produced reflecting the new uploads.	☐
10.6	1. Open <code>/e/<slug>/recap</code> for an event with no recap yet.	A “No recap yet” (or “being generated” / “couldn’t generate”) state shows gracefully — never a broken page.	☐

11 • Guest uploads

Guests add photos and videos to the feed with no account — an optional name and optional hashtags.

Who	Guest
Where	<code>/e/<slug>/upload</code> (also reached from the feed and the photo-request banner)
Limits	Up to 10 files per upload; each up to 50 MB ; images and videos.

ID	STEPS	EXPECTED RESULT	RESULT
11.1	1. Open the upload page, add a few photos, optionally set a name and hashtags (e.g. <code>#ceremonydance</code>), Upload.	Files upload; an “Uploaded!” confirmation shows with an Upload more option; items appear in the feed and host dashboard.	☐
11.2	1. Select more than 10 files.	The selection is limited to 10 with a clear message.	☐
11.3	1. Include a file larger than 50 MB.	Oversized files are dropped with a warning (“N files over 50MB removed”); the rest still upload.	☐
11.4	1. Upload a short video.	The video uploads and plays back in the feed with a video badge.	☐
11.5	1. Try to upload after the host has closed the feed.	A message explains the event is closed and uploads are no longer accepted.	☐

12 • Guest feed & filters

The public feed shows every upload, with a filter bar for hashtags plus the face-search and recap entry points.

Who	Guest
Where	/e/<slug>

ID	STEPS	EXPECTED RESULT	RESULT
12.1	1. Open the feed for an event with uploads.	Media loads newest-first; new uploads appear on refresh.	☐
12.2	1. Tap a hashtag chip, then All .	The feed filters to that hashtag, then back to everything.	☐
12.3	1. Confirm the filter bar shows the right chips.	 Watch recap appears only when a recap is ready;  Find my photos only when face search is on; hashtag chips reflect actual tags.	☐
12.4	1. Open a feed that isn't open yet / already closed.	Appropriate not-open / closed state shows instead of the upload path.	☐
12.5	1. Visit a non-existent event slug.	A friendly 404 with a call-to-action, not a raw error.	☐

13 · Media management

On the event dashboard, hosts review stats, browse uploads, and download or delete media.

Who	Host
Where	Event dashboard → stats + Uploads list
Tools	Total uploads & total views tiles · list/grid toggle · 12-per-page pagination · per-item download & delete · Download all (zip).

ID	STEPS	EXPECTED RESULT	RESULT
13.1	1. Open an event with uploads.	“Total uploads” and “Total views” tiles show correct counts.	☐
13.2	1. Toggle between ≡ list and  grid views.	Both render media correctly; videos show a badge.	☐
13.3	1. With >12 uploads, use Prev/Next .	Pagination pages through 12 at a time; page indicator is accurate.	☐
13.4	1. Download a single item (↓).	The original file downloads.	☐
13.5	1. Click ↓ Download all (N) .	A zip is built (“Zipping N files...”) and downloaded with all media, sensibly named.	☐
13.6	1. Delete a single upload () , confirm.	Confirmation warns it can’t be undone; the item disappears from the feed and storage.	☐

14 · Admin moderation

Super-admins moderate host accounts platform-wide: restrict (reversible) or delete (soft, purged after 30 days) a host, manage admin roles, and review an audit log. Restricting or deleting a host takes their event feeds dark and emails them the reason.

Who	Super-admin only
Where	Dashboard header → ⚙ Admin (/admin) — link only visible to admins
Sections	Overview · Hosts · Events · Audit logs
Note	Deletion is a <i>soft</i> delete; a scheduled QStash cron performs the irreversible purge after 30 days, so a misclick doesn't immediately destroy a customer's photos.

ID	STEPS	EXPECTED RESULT	RESULT
14.1	1. Sign in as a non-admin host; look for the Admin link. Then as an admin.	The ⚙ Admin link is hidden for non-admins and shown for admins; /admin is not usable by non-admins.	☐
14.2	1. Open Admin, review Overview / Hosts / Events / Audit logs sections.	Each section loads platform data; counts look consistent.	☐
14.3	1. On a test host, choose Restrict , enter a reason, confirm.	The host is marked Restricted; their event feeds go dark; a reason email is sent; an audit entry is recorded.	☐
14.4	1. Restore / un-restrict that host.	Restriction is reversible; the host and their feeds are active again.	☐
14.5	1. On a test host, choose Delete , enter a reason, confirm.	The host is soft-deleted (still listed, feeds dark, reason emailed); dropped from the active count; scheduled for purge in 30 days.	☐
14.6	1. Promote/demote a host's admin role.	The role change takes effect and is logged in the audit log.	☐
14.7	1. Open Audit logs .	Recent restrict/delete/role actions are listed with actor, target, reason, and time.	☐