



## NOTE:

- 1. MATERIAL: LOW-STRENGTH ZINC-PLATED STEEL THREADED ROD, MCMASTER-CARR P/N: 94595A235.
- 2. GENERAL TOLERANCE DIN ISO 2768-m.
- 3. AREAS WHERE MATERIAL HAS BEEN REMOVED SHALL HAVE SMOOTH TRANSITIONS AND BE FREE OF BURRS. SCRATCHES AND DENTS ARE NOT ACCEPTABLE AT THE THREAD.
- 4. FOR MATERIALS AND MANUFACTURING LINKS REFER TO CNC\_BOM.PDF

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>VR</b>	VR		
			BREAK ALL SHARP EDGES DIMENSIONS ARE IN MILLIMETERS TOLERANCES: FRACTIONAL± ANGULAR: MACH± BEND± TWO PLACE DECIMAL± THREE PLACE DECIMAL± INTERPRET GEOMETRIC TOLERANCING PER:	DRAWN				VIC		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VR IS PROHIBITED.				CHECKED			TITLE:			
				ENG APPR.			Threaded Rod N			MZ
				MFG APPR.			11111			
				Q.A.						
				COMMENTS:						
			Alloy Steel	Vladimir Tyrkin veres.pcb@gmail.com		SIZE DWG. NO.		\_	REV	
	NEXT ASSY	USED ON	As machined			<b>A</b> CNC.02.25				
	APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1	WEIGHT: 2.16	SHEET	1 OF 1

2

1

В