


B



B

NOTE:

1. GENERAL TOLERANCE DIN ISO 2768-m.
2. ALL EDGES 0.1..0.3MM MAX RADIUS OR CHAMFER.
3. AREAS WHERE MATERIAL HAS BEEN REMOVED SHALL HAVE SMOOTH TRANSITIONS AND BE FREE OF SCRATCHES, GRIND MARKS, AND BURRS. SCRATCHES AND DENTS ARE NOT ACCEPTABLE AT THE THREAD.
4. FOR MATERIALS AND MANUFACTURING LINKS REFER TO CNC_MILLING_CARRIAGE_BOM.PDF

A

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VR IS PROHIBITED.			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	VR VR TITLE: Lead Screw SIZE A DWG. NO. 002 REV SCALE: 2:1 WEIGHT: 60.10 SHEET 1 OF 1
			BREAK ALL SHARP EDGES DIMENSIONS ARE IN MILLIMETERS TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± INTERPRET GEOMETRIC TOLERANCING PER:	DRAWN			
				CHECKED			
				ENG APPR.			
				MFG APPR.			
			MATERIAL AISI 1020	Q.A.			Vladimir Tyrkin veres.pcb@gmail.com
			FINISH	COMMENTS:			
	NEXT ASSY	USED ON	APPLICATION	DO NOT SCALE DRAWING			

A

2

1