
VERIQTA

# DevOps Architecture Interview Handbook

Real Architectures | Key Concepts | Interview Scenarios
Design Decisions | Trade-offs | Practical Examples




@veriqta @veriqta @veriqta @veriqta @veriqta @veriqta

VERIQTA

# DevOps Architecture Fundamentals

## 1. What is DevOps Architecture?


- DevOps architecture is the overall design of people, processes and technologies used to build, deploy, operate and scale applications reliably and securely.
- Senior engineers design architectures that support fast delivery, high availability, security and ease of operations.

## 2. Why It Matters

- **Scalability** – handle growing users and data.
- **Reliability** – stay available and recover from failures.
- **Security** – protect systems, data and access.
- **Maintainability** – easy to update, operate and improve.

## 3. Monolithic vs Distributed Architecture

### Monolithic Architecture




- All components in one application.
- Easier to develop and deploy initially.
- Becomes harder to scale and maintain as it grows.
- A single failure can affect the whole application.

### Distributed Architecture (Microservices)




- Application is split into smaller independent services.
- Each service can be developed, deployed and scaled separately.
- More resilient and flexible.
- Wore operational complexity (networking, monitoring, security).

## 4. Key Architectural Trade-offs

| Aspect | Monolithic Architecture | Distributed Architecture |
|---|---|---|
| Development Speed | Faster initially | Slower initially (more setup) |
| Scalability | Harder to scale (usually vertical) | Easier to scale (horizontal) |
| Reliability | Single failure can bring everything down | Failures isolated to individual services |
| Maintainability | Becomes complex as it grows | Services can be maintained independently |
| Security | Simpler to secure initially | More components to secure |
| Deployment | Single unit deployment | Independent service deployments |
| Operational Complexity | Lower initially | Higher (requires strong DevOps practices) |

## 5. Senior Engineer Insight

There is no perfect architecture.
Choose the right design based on business needs, team skills, operational maturity and long-term goals.

### Common Interview Questions

- When would you choose a monolithic architecture?
- When would you choose microservices?
- How do you ensure scalability, reliability and security in your design?
- What are the trade-offs and how do you mitigate them?

VERIQTA

# Designing Production-Ready DevOps Platforms


## 1. What Is a DevOps Platform?

- An integrated set of tools, systems and practices that automate the delivery, operation and monitoring of applications.
- It covers the entire lifecycle from code commit to running in production.

## 2. Key Components

- **Source Control** – store and manage code (e.g. Git, GitHub).
- **CI/CD** – build, test and deploy automatically.
- **Infrastructure** – provision and manage environments (e.g. Terraform).
- **Observability** – monitor logs, metrics and traces (e.g. Prometheus, Grafana).

## 3. End-to-End DevOps Platform Architecture




## 4. Control Plane vs Data Plane

| Control Plane | Data Plane |
|---|---|
| Manages, automates and controls the platform. | Runs the actual applications and processes data. |
| Examples: CI/CD, Kubernetes control plane, IaC, GitOps, policy management. | Examples: application containers, databases, storage, networking. |
| Handles configuration, desired state and orchestration. | Handles user requests and business workloads. |

## 5. Identifying Single Points of Failure

- A single component whose failure can bring down the entire system.
- Examples: single CI/CD server, single Kubernetes cluster, single database, single region, single DNS.
- Look for components without redundancy or failover.
- Mitigate by using redundancy, multiple availability zones, load balancers and automated failover.

## 6. Key Design Considerations

- **Scalability** – handle growing workloads.
- **Reliability** – stay available and recover from failures.
- **Security** – protect code, infrastructure and data.
- **Maintainability** – easy to update, operate and troubleshoot.

## 7. Senior Engineer Insight

- Design for failure, not for perfect conditions.
- Eliminate or reduce single points of failure.
- Separate control plane and data plane for better security and resilience.
- Use automation and observability from day one.

VERIQTA

# CI/CD Pipeline Architecture


## 1. What Is a CI/CD Pipeline?

- A CI/CD pipeline automates the process of building, testing, securing, packaging and deploying applications.
- It helps teams deliver changes faster, safer and more reliably.
- Senior engineers design pipelines that are secure, scalable, observable and environment-aware.

## 2. Key Design Goals

- Fast and reliable delivery.
- Secure from code to production.
- Build once, promote immutable artifacts.
- Environment consistency.
- Observable and easy to troubleshoot.
- Support safe deployments with gates and approvals.

## 3. End-to-End CI/CD Pipeline Architecture




## 4. Build Once, Promote Immutable Artifacts

- Build the artifact one time (e.g. container image).
- Use the same artifact across all environments.
- Avoid rebuilding in staging or production.
- Ensures consistency and reduces risk of "it works in staging but not in production".

## 5. Deployment Gates and Approval Strategies

- Automated gates – tests, security scans, policy checks.
- Manual approvals – for staging and production.
- Environment policies – restrict who can deploy.
- Progressive delivery – blue/green, canary, feature flags.

## 6. Common Pipeline Failures and How to Recover

| Failure | Common Cause | How to Troubleshoot / Recover |
|---|---|---|
| Build failure | Dependency issues | Check build logs, fix dependency versions, retry. |
| Test failure | Code bug or flaky test | Check test logs, fix code, rerun. |
| Security scan failure | Vulnerable dependency | Review scan report, update package, rebuild. |
| Deployment failure | Misconfiguration | Check deployment logs, verify configuration, rollback if needed. |
| Pipeline timeout | Resource or network issue | Check runner status, increase resources, rerun. |

## 7. Senior Engineer Insight

- Design for failure, not just success.
- Keep pipelines fast, secure and reliable.
- Use immutable artifacts and clear environment promotion.
- Implement strong observability and alerting for pipeline failures.
- Have a rollback strategy for every deployment.


VERIQTA

# Infrastructure as Code Architecture

## 1. Key Concepts

- **Terraform state** – stores the current state of your infrastructure.
- **Modules** – reusable, versioned infrastructure code.
- **Environment isolation** – separate infrastructure for dev, staging and prod.
- **Remote state and locking** – prevents conflicts when teams work together.
- **Drift detection** – identifies changes made outside of Terraform.
- **Multi-account design** – isolates workloads and improves security.

## 2. High-Level Architecture




## 3. Terraform State and Remote Backend


### Why remote state?

- Shared by team members.
- Prevents state file loss.
- Supports locking.
- Enables collaboration.

### Example (S3 backend)

```
terraform {
  backend "s3" {
    bucket = "veriqta-terraform-state"
    key    = "prod/network/terraform.tfstate"
    region = "us-east-1"
    dynamodb_table = "veriqta-terraform-locks"
  }
}
```

## 4. Using Terraform Modules




### Example (using a module)

```
module "vpc" {
  surce  = "../modules/vpc"
  cidr   = "10.0.0.0/16"
  env    = "prod"
  tags = {
    Project = "veriqta"
    Environment = "prod"
  }
}
```

## 5. Dependency Management

- Use Terraform modules and clear input/output variables.
- Manage provider versions using required_providers.
- Use a consistent directory structure.
- Pin module versions to avoid unexpected changes.

### Example (provider version)

```
terraform {
  required_providers {
    aws = {
      source  = "hashicorp/aws"
      version = "~> 5.0"
    }
  }
}
```


## 6. Drift Detection

- Detects changes made outside of Terraform (e.g. manual console changes).
- Use terraform plan regularly.
- Tools like Terraform Cloud or third-party solutions can continuously check for drift.

### Check for drift

```
terraform plan
# Shows differences between
# actual infrastructure and
# your Terraform code
```

## 7. Multi-Account Infrastructure Design




## 8. Common Issues and Fixes

| Issue | Cause | Fix |
|---|---|---|
| State lock error | Another process is running | Wait or force-unlock (only if safe) |
| Drift detected | Manual changes in console | Review changes and update code |
| Module version conflict | Incompatible versions | Use compatible, pinned versions |
| Permission denied | Incorrect IAM permissions | Update role policies |

## 9. Senior Engineer Insight

- Use a well-structured module design for reusability and consistency.
- Always use remote state with locking.
- Separate environments and accounts for security and blast radius control.
- Run regular drift detection as part of your operational practice.


VERIQTA

# Cloud Network Architecture

## 1. Key Concepts

- **Virtual private cloud (VPC)** – isolated network in the cloud.
- **Subnets** – divide the VPC into smaller networks.
- **Routing** – controls how traffic moves.
- **Security controls** – firewalls, route tables and security groups.
- Design for high availability, security and scalability.

## 2. High-Level Cloud Network Architecture (AWS Example)




## 3. Public vs Private Workloads

| Public Workloads | Private Workloads |
|---|---|
| Need to be accessible from the internet. | Not directly accessible from the internet. |
| Examples: web servers, API gateways, load balancers. | Examples: application servers, databases, internal services. |
| Placed in public subnets with a public IP or via a load balancer. | Placed in private subnets and accessed via internal load balancers or NAT. |

## 4. Key Components

- **Load Balancer** – distributes traffic across multiple targets.
- **NAT Gateway** – allows private instances to access the internet (for updates, etc).
- **Firewall / Security Groups** – control inbound and outbound traffic.
- **Route Table** – defines where traffic goes.
- **Network ACL** – additional layer of subnet level filtering.

## 5. Common Traffic Flows

**Inbound (User to Application)**

User (Internet) → Load Balancer (public subnet) → Application Server (private subnet)

**Outbound (Private Instance to Internet)**

Private Instance (private subnet) → NAT Gateway (public subnet) → Internet (e.g. package updates)

## 6. Network Segmentation and Failure Isolation

- Use multiple subnets across availability zones.
- Separate environments (dev, staging, prod).
- Isolate critical resources (e.g. databases) in private subnets.
- Use different security groups and network ACLs per tier.
- Design so a failure in one subnet or AZ does not bring down the entire system.

## 7. Common Design Considerations

- **High availability** – use multiple AZs.
- **Scalability** – design for growth.
- **Security** – least privilege and network isolation.
- **Cost** – right-size and avoid unnecessary public resources.

## 8. Common Failures and Recovery

| Failure | Possible Cause | How to Fix |
|---|---|---|
| Cannot reach instance | Incorrect route table or security group | Check routes and SG rules |
| No internet access | NAT gateway misconfigured | Verify NAT, routes and SG |
| Load balancer unhealthy | Instance or target failure | Check health checks and logs |
| Cross-AZ failure | Single AZ design | Use multiple AZs and test failover |

## 9. Senior Engineer Insight

- Always design for failure (AZ, subnet and component level).
- Keep network design simple and well documented.
- Use infrastructure as code to maintain consistency.
- Regularly test failover and recovery procedures.

@veriqta @veriqta @veriqta
@veriqta @veriqta @veriqta


VERIQTA

# Kubernetes Cluster Architecture

## 1. Key Concepts

- A Kubernetes cluster consists of a control plane and worker nodes.
- The control plane manages the cluster and makes scheduling decisions.
- Worker nodes run the actual applications (containers).
- Designed for high availability, scalability and self-healing.

## 2. Kubernetes Cluster Architecture (High Level)





## 3. Control Plane Components

| Component | Function |
|---|---|
| API Server | Central point for all requests (e.g. kubectl, UI, controllers). |
| etcd | Distributed key-value store that holds cluster state. |
| Scheduler | Assigns pods to suitable worker nodes. |
| Controller Manager | Runs controllers (e.g. node, replica, endpoint, job). |

## 4. Worker Node Components

| Component | Function |
|---|---|
| Kubelet | Communicates with API server, manages containers on the node. |
| Kube Proxy | Manages network rules and service routing (kube-proxy, iptables/IPVS). |
| Container Runtime | Runs containers (e.g. containerd, CRI-O). |
| Pods | Smallest deployable unit containing one or more containers. |

## 5. High Availability Architecture (Multi-Control Plane)




- Run at least 3 control plane nodes for high availability.
- Use a load balancer in front of API servers.
- etcd should be highly available (clustered).
- Worker nodes can be scaled horizontally.
- Distribute nodes across multiple availability zones for resilience.

## 6. Scaling the Cluster

- Add more worker nodes to handle increased workloads.
- Use Cluster Autoscaler to automatically scale nodes.
- Use Horizontal Pod Autoscaler (HPA) to scale pods.
- Ensure underlying infrastructure (network, storage, etc.) also scales.

## 7. Failure Scenarios and Impact

| Failure Scenario | Impact / Behavior |
|---|---|
| Single control plane node failure | Cluster continues to work (if HA) |
| All control plane nodes down | Cluster becomes unavailable (no API access) |
| etcd node failure | May lose quorum (if not enough etcd nodes) |
| Worker node failure | Pods on that node are rescheduled to healthy nodes |
| Network partition | May cause node isolation or split-brain (etcd) |

## 8. Senior Engineer Insight

- Always design for high availability and multi-AZ deployments.
- Monitor control plane and etcd health continuously.
- Implement proper node drain and graceful shutdown procedures.
- Test failure scenarios regularly.
- Use managed Kubernetes services when appropriate, but understand the underlying architecture.


VERIQTA

# Kubernetes Workload Architecture

## 1. Kubernetes Workload Types

| | |
|---|---|
| **Deployment** | • Manages stateless applications.<br>• Ensures desired number of replicas.<br>• Supports rolling updates and rollbacks. |
| **StatefulSet** | • Used for stateful applications.<br>• Provides stable network identity.<br>• Maintains persistent storage per pod. |
| **DaemonSet** | • Runs a pod on every node (or selected nodes).<br>• Used for logging, monitoring and networking agents. |
| **Job** | • Runs a task to completion.<br>• Used for batch processing and one-time tasks. |
| **CronJob** | • Runs jobs on a schedule.<br>• Used for backups, reports and maintenance tasks. |

## 2. Architecture Overview




## 3. Services, Ingress and Gateway API

### Service Types

| | |
|---|---|
| ClusterIP | Internal access within the cluster. (default) |
| NodePort | Exposes service on each node (static port). |
| LoadBalancer | Provision a cloud load balancer for external access. |

### Ingress

Manages HTTP/HTTPS routing to services based on host and path.

**Use Cases:**
- Expose web applications.
- TLS termination.
- Path based routing.

### Gateway API

Next generation traffic routing (more flexible than Ingress).

**Features:**
- HTTP, TCP, UDP routing.
- Better multi-team support.
- More extensible and production ready.

## 4. Resource Requests, Limits and Scheduling

- Requests – minimum resources required for a pod.
- Limits – maximum resources a pod can use.
- Helps with fair scheduling and prevents resource starvation.
- Scheduler places pods on nodes based on available resources, constraints and affinity rules.

**Example: Resource Requests and Limits**

```yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: web-app
spec:
  replicas: 3
  template:
    spec:
      containers:
      - name: app
        image: nginx:latest
        resources:
          requests:
            cpu: "250m"
            memory: "256Mi"
          limits:
            cpu: "500m"
            memory: "512Mi"
```

### Scheduling Controls

- Node selectors (target specific nodes).
- Taints and tolerations (control where pods run).
- Affinity and anti-affinity (place pods together or apart).
- Topology spread constraints (distribute across zones).

## 5. Probes, Disruption Budgets and Graceful Shutdown

### Probes

- **Liveness Probe** – Checks if container is running. Restart if it fails.
- **Readiness Probe** – Checks if container is ready to receive traffic.
- **Startup Probe** – Used for slow starting applications.

### Pod Disruption Budget (PDB)

Ensures a minimum number of pods are available during voluntary disruptions (e.g. node maintenance, upgrades).

**Example:**

```
minAvailable: 1
or
maxUnavailable: 1
```

### Graceful Shutdown

- Allow ongoing requests to complete before terminating pods.
- Configure termination grace period.
- Use preStop hooks if needed.

## 6. Example: Deployment, Service and Ingress

### Deployment

```yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: web-app
spec:
  replicas: 3
  selector:
    matchLabels:
      app: web-app
  template:
    metadata:
      labels:
        app: web-app
    spec:
      containers:
      - name: app
        image: nginx:latest
```

### Service

```yaml
apiVersion: v1
kind: Service
metadata:
  name: web-service
spec:
  type: ClusterIP
  selector:
    app: web-app
  ports:
  - port: 80
    targetPort: 80
```

### Ingress

```yaml
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: web-ingress
spec:
  rules:
  - host: app.example.com
    http:
      paths:
      - path: /
        pathType: Prefix
        backend:
          service:
            name: web-service
            port:
              number: 80
```

## 7. Common Failure Scenarios

| Failure Scenario | Impact | How to Fix |
|---|---|---|
| Pod stuck in CrashLoopBackOff | Application unavailable | Check logs, fix config, probe settings. |
| Pods not scheduling | Pods stay in Pending state | Check resources, node capacity, taints, affinity. |
| Service not reachable | No network connectivity | Verify service type, endpoints and network policies. |
| Ingress not working | External traffic fails | Check ingress controller, rules, TLS, DNS. |
| Pod terminated too fast | Requests dropped | Increase termination grace period, use preStop hook. |

## 8. Senior Engineer Insight

- Choose the right workload type for the use case.
- Use resource requests and limits for predictable performance.
- Design for high availability with PDBs and multi-zone scheduling.
- Test failure scenarios (node drain, pod kill, network issues).
- Use Gateway API for complex, multi-team environments.


VERIQTA

# Container Platform Architecture


## 1. Key Concepts

- **Container images** – read-only templates used to create containers.
- **Container registries** – store, manage and distribute images.
- **Container runtimes** – run containers (e.g. containerd, Docker, CRI-O).
- A **container platform** – provides tooling, security, networking and orchestration (e.g. Kubernetes).

## 2. Container Platform Architecture




## 3. Container Image Components





**Example Dockerfile**

```
FROM ubuntu:22.04
RUN apt-get update && \
    apt-get install -y python3
WORKDIR /app
COPY . .
RUN pip install -r requirements.txt
CMD ["python3", "app.py"]
```

## 4. Container Registries

| Public Registry | Cloud Registry | Self-Hosted Registry |
|---|---|---|
| Docker Hub | Amazon ECR, Azure ACR, Google Artifact Registry | Harbor |
| • Public images (e.g. nginx, redis) | • Private and public | • On-premises / private cloud |
| • Community maintained | • Integrated with cloud IAM | • Full control |
| | | • Use for sensitive images |

## 5. Secure Image Build and Distribution




- Use minimal base images (e.g. distroless, alpine).
- Scan images for vulnerabilities before deployment.
- Sign images to ensure integrity (e.g. Cosign, Notary).
- Use private registries and restrict access with IAM/RBAC.

## 6. Container Runtimes

| Runtime | Description |
|---|---|
| containerd | Lightweight, standard runtime used by Kubernetes. |
| CRI-O | Kubernetes-native runtime. |
| Docker Engine | Popular runtime, often used outside Kubernetes. |

## 7. Runtime Isolation and Least Privilege

- Use non-root users in containers.
- Apply least privilege (drop unnecessary capabilities).
- Use read-only root filesystem where possible.
- Isolate containers using namespaces and cgroups.
- Use security policies (e.g. Pod Security Standards, AppArmor, SELinux, Seccomp).
- Limit access to host resources.

## 8. Container Startup Flow

1. Image pulled from registry
2. Container created by runtime
3. Resources allocated (CPU, memory, network)
4. Entrypoint / CMD executed
5. Application starts and becomes healthy

## 9. Common Failures and Investigation

| Issue | Possible Cause | How to Investigate |
|---|---|---|
| Image pull error | Wrong image name, authentication issue | Check image name, registry credentials, network connectivity |
| Container exits immediately | Application error, wrong CMD | kubectl logs <pod> Check Dockerfile CMD |
| CrashLoopBackOff | Repeated failures | kubectl describe pod Check logs, events |
| Container not starting | Resource limits, permission issues | Check resource requests, security context, events |
| Health check failing | Application not ready | Check probes, logs, application startup time |

## 10. Useful Commands

```
docker build -t myapp:1.0 .
docker run -p 8080:80 myapp:1.0
docker images
docker ps -a
docker logs <container>
```

## 11. Senior Engineer Insight

- Design secure, minimal and reproducible images.
- Implement image scanning and signing.
- Use private registries with proper access control.
- Understand runtime internals for troubleshooting.
- Always apply least privilege and monitor container security.


VERIQTA

# High Availability and Fault Tolerance


## 1. Key Concepts

- **Redundancy across availability zones** – eliminate single points of failure.
- **Load balancing and health checks** – distribute traffic and detect failures.
- **Failure domains** – understand the boundaries of failure (AZ, region, racks, nodes, services).
- **Graceful degradation** – keep core functionality available during failures.
- **Active-active vs active-passive** – different architectures for resilience, depending on requirements.

## 2. High Availability Architecture (Multi-AZ Example)




## 3. Load Balancing and Health Checks




**Health Check Types**


- HTTP/HTTPS
- TCP
- Application-level checks
- Custom health endpoints

## 4. Redundancy Across Availability Zones

| Multiple instances across AZs | Multi-AZ databases (automatic failover) | Replicated storage (e.g. S3, EBS, RDS) | Cross-AZ networking (load balancers, service discovery) |
|---|---|---|---|


## 5. Active-Active vs Active-Passive Architectures

### Active-Active Architecture




- Both regions handle live traffic.
- Higher availability and scalability.
- Used for global applications.
- More complex (data replication, conflict handling).

### Active-Passive Architecture




- One region handles live traffic.
- Second region on standby.
- Simpler to implement.
- Used for disaster recovery or cost optimization.

## 6. Failure Domains

- **Region** (large geographic area)
- **Availability Zone** (isolated data center)
- **Data Center** (facility)
- **Rack** (hardware group)
- **Node / Instance** (virtual or physical server)
- **Service / Application** (single component)

### Design Considerations

- Distribute resources across failure domains.
- Avoid single points of failure at each layer.
- Use independent power, networking and storage.
- Test failure scenarios regularly.

## 7. Graceful Degradation Strategies

- Return partial functionality instead of complete failure.
- Use caching to reduce dependency on backend systems.
- Implement queues and retries for non-critical tasks.
- Use feature flags to disable non-essential features.
- Set appropriate timeouts and fallback responses.
- Communicate status to users (maintenance pages, clear errors).

## 8. Common Failures and How to Handle Them

| Failure | Impact | How to Handle |
|---|---|---|
| AZ outage | Loss of instances | Use multi-AZ, auto scaling and load balancers |
| Load balancer failure | Traffic not distributed | Use redundant load balancers |
| Database primary failure | Write operations fail | Enable automatic failover |
| Network partition | Partial service outage | Design for retries and failover |
| Region outage | Full regional impact | Use multi-region architecture |
| Service dependency failure | Downstream failures | Use timeouts, circuit breakers and graceful degradation |

## 9. Senior Engineer Insight

- Design for failure, not just for success.
- Eliminate single points of failure.
- Test failover and disaster recovery regularly.
- Understand trade-offs between cost, complexity and resilience.
- Choose the right architecture based on business requirements and RTO/RPO.

VERIQTA

# Disaster Recovery Architecture

## 1. Key Concepts

- **Recovery Time Objective (RTO)** – maximum acceptable time to restore services after a disaster.
- **Recovery Point Objective (RPO)** – maximum acceptable data loss (measured in time).
- **Backup, replication and restoration** – protect and recover data and systems.
- **Disaster recovery (DR) architecture** – design to continue or quickly restore operations after a major failure (e.g. region outage).

## 2. RTO and RPO Explained


### Recovery Time Objective (RTO)

Maximum acceptable time to restore services after a disaster.




### Recovery Point Objective (RPO)

Maximum acceptable data loss measured in time.




## 3. Backup, Replication and Restoration

### 1. Backup

- Regular backups of databases, application data and configuration.
- Stored in durable, separate location (e.g. different region).
- Test backups regularly.

### 2. Replication

- Real-time or near real-time replication.
- Synchronous or asynchronous replication.
- Replicate across availability zones or regions.

### 3. Restoration

- Restore data and infrastructure from backups or replicas.
- Verify data integrity.
- Test restoration procedures regularly.

## 4. Regional Disaster Recovery Patterns

### Active-Passive (Standby)




- Secondary region on standby.
- Lower cost.
- Longer recovery time (RTO).
- Suitable for many applications.

### Active-Active (Multi-Region)





- Both regions handle live traffic.
- Higher cost.
- More complex architecture.
- Better resilience and lower RTO.

### Warm Standby




- Secondary region partially running.
- Faster recovery than cold standby.
- Medium cost.
- Common for critical systems.

## 5. Example Multi-Region DR Architecture (Cloud)




## 6. Recovery Testing and Failover Validation

- Regularly test backup restoration.
- Perform planned failover exercises.
- Validate RTO and RPO targets are met.
- Test application functionality after failover.
- Document and update disaster recovery procedures.
- Include network, security, IAM and DNS in testing.
- Identify and fix gaps from test results.

## 7. Common Failures and Impact

| Failure Scenario | Impact | Notes |
|---|---|---|
| Region outage | Complete service loss | Requires failover to secondary region |
| Database corruption | Data loss | Restore from backup or replica |
| Human error | Configuration or data loss | Use backups and version control |
| Ransomware attack | Data encrypted | Restore from clean backups |
| Network partition | Regional isolation | Use multi-region and DNS failover |
| Backup failure | Inability to restore | Monitor backup jobs and test regularly |

## 8. Senior Engineer Insight

- Design for multiple failure scenarios (region, AZ, network, data, human error, security).
- Automate failover where possible, but test manual procedures.
- Keep RTO and RPO aligned with business requirements and cost.
- Regularly test and update disaster recovery architecture.
- Document everything and ensure the team understands the recovery process.


VERIQTA

# Observability Architecture

## 1. Key Concepts

- **Metrics** – numerical data about system performance (e.g. CPU, memory, latency, request rate).
- **Logs** – detailed, timestamped events for troubleshooting.
- **Traces** – track requests as they flow across multiple services.
- **Telemetry pipelines** – collection, processing and routing of metrics, logs and traces to observability backends.


## 2. Observability Architecture Overview




## 3. Metrics, Logs, Traces and Telemetry Pipelines

| Metrics | Logs | Traces | Telemetry Pipeline |
|---|---|---|---|
| Time-series data (e.g. CPU, memory, latency). | Detailed events with timestamps. | Track a request across services. | Collects data from applications and infrastructure. |
| Used for monitoring, alerting and trends. | Used for troubleshooting and audit. | Show end-to-end latency and service dependencies. | Processes (filter, enrich, sample). |
| Collected at regular intervals (pull or push). | Unstructured or structured (e.g. JSON). | Made of spans with trace IDs. | Routes to the right backends (metrics, logs, traces). |

## 4. OpenTelemetry Architecture





## 5. Cardinality, Sampling and Retention

| Cardinality | Sampling | Retention |
|---|---|---|
| Number of unique values in labels/tags (e.g. user_id, path). | Collects a subset of traces/logs/metrics. | How long to keep observability data. |
| High cardinality increases storage cost and can impact performance. | Reduces cost and overhead. | Balance cost vs troubleshooting needs. |
| Use low-cardinality labels and avoid unbounded values. | Common strategies: head-based, tail-based, probabilistic, adaptive. | Use different retention for metrics, logs and traces. |
| | Keep important transactions and errors. | Apply tiered storage (e.g. hot, warm, cold). |

## 6. Diagnosing Failures Across Distributed Systems

| | |
|---|---|
| 1 **Detect the issue** (Alert or user report) | Identify symptoms in metrics dashboards (e.g. high latency, error rate). |
| 2 **Check traces** (Trace the request flow) | Find where the request is failing across services. |
| 3 **Review logs** (Find detailed errors) | Look for error messages, exceptions and correlated trace IDs. |
| 4 **Correlate data** (Use timestamps and IDs) | Use trace IDs, request IDs and timestamps to connect metrics, logs and traces. |
| 5 **Identify root cause** (Service, dependency, infra) | Determine if it's application code, configuration, resource limits or external dependencies. |
| 6 **Validate the fix** (Monitor after resolution) | Ensure metrics, logs and traces return to normal. |

## 7. Example: End-to-End Observability Flow




## 8. Senior Engineer Insight

- Instrument all services with OpenTelemetry from the start.
- Use meaningful, low-cardinality labels.
- Set appropriate sampling and retention based on cost and needs.
- Build dashboards for golden signals (latency, traffic, errors, saturation).
- Correlate metrics, logs and traces to reduce mean time to resolution (MTTR).
- Regularly test observability during failure scenarios.

VERIQTA

# SRE and Reliability Engineering Architecture

## 1. Key Concepts

- **Service Level Indicators (SLIs)** – measurable indicators of service performance.
- **Service Level Objectives (SLOs)** – target levels for SLIs.
- **Error budgets** – allowed amount of unreliability.
- **Incident response** – structured process to detect, respond and recover.
- **Capacity planning** – ensure sufficient resources for current and future demand.
- **Reliability testing** – validate systems under normal and failure conditions.

## 2. SLI, SLO and SLA Comparison

| Term | Definition | Example | Purpose |
|---|---|---|---|
| SLI | A measurable indicator of service performance. | Request success rate, latency, availability. | Measure performance. |
| SLO | Target level for an SLI over a specific time period. | 99.9% availability per month. | Set reliability targets. |
| SLA | Formal agreement with customers, often with consequences. | 99.9% uptime with credits. | Define customer commitment. |

## 3. SLI and SLO Architecture

Users (Clients) → Service (e.g. web app) → Collect SLIs (Metrics, Logs, Traces) → Define SLOs (Targets)

**Example SLIs**

- Availability (request success rate)
- Latency (p95 response time)
- Throughput (requests per second)
- Error rate (5xx responses)

**Example SLOs**

- 99.9% availability per month
- p95 latency < 200ms
- Error rate < 0.1%
- Throughput meets user demand

## 4. Error Budgets and Reliability Trade-offs

**Error Budget Formula**

Error Budget = (1 – SLO) × Time Period

**Example**

- SLO: 99.9% availability
- Allowed downtime: 0.1%
- In a 30-day month: 0.1% × 720 hours = 43.2 minutes

**Trade-offs**

- Use error budget to innovate and deploy new features faster.
- When error budget is exhausted, pause risky changes.
- Balance reliability, velocity and business needs.

## 5. Incident Response and Escalation Design

| Detect | Triage | Respond | Resolve | Post-Incident |
|---|---|---|---|---|
| Monitoring and alerting detect an issue (e.g. high error rate). | Assess impact and severity (define incident level). | Follow runbooks, engage the right engineers. | Mitigate the issue and restore service. | Conduct blameless post-mortem and implement improvements. |

**Escalation Levels**

- P1 – Critical (major outage, all users)
- P2 – High (significant impact)
- P3 – Medium (limited impact)
- P4 – Low (minor issue)

**Key Elements**

- Clear on-call rotation.
- Defined escalation path.
- Runbooks and playbooks.
- Communication plan (internal and external).
- Incident metrics and post-incident reviews.

## 6. Capacity Planning Architecture

| Load Forecasting | Capacity Modeling | Scaling Strategy | Monitoring |
|---|---|---|---|
| Analyze historical usage and growth trends. | Estimate required compute, storage and network resources. | Vertical scaling or horizontal autoscaling. | Track utilization and set alerts. |

**Key Metrics**

- CPU usage
- Memory usage
- Disk I/O and storage
- Network bandwidth
- Request rate (QPS)
- Queue length

## 7. Reliability Testing

- **Load testing** – validate performance under expected and peak load.
- **Stress testing** – push beyond normal limits to find breaking points.
- **Chaos engineering** – intentionally introduce failures (e.g. kill nodes, network latency).
- **Failover testing** – validate automatic recovery and data consistency.

## 8. Example Reliability Architecture




## 9. Senior Engineer Insight

- Focus on user experience, not just uptime.
- Use SLIs and SLOs to drive decisions.
- Protect the error budget and balance innovation with stability.
- Invest in automation, runbooks and observability.
- Regularly test failure scenarios and recovery.
- Plan capacity ahead of demand spikes.


VERIQTA

# DevSecOps and Zero Trust Architecture


## 1. Key Concepts

- **Identity, authentication, and authorization** – verify who or what can access resources and what they can do.
- **Secrets management and workload identity** – securely manage credentials and identities for humans, services and workloads.
- **Software supply chain security** – secure code, dependencies, artifacts and build pipelines.
- **Policy enforcement and security boundaries** – implement and enforce policies across infrastructure, applications and data.


## 2. Zero Trust Architecture Overview





## 3. Identity, Authentication and Authorization




## 4. Secrets Management and Workload Identity





## 5. Software Supply Chain Security





- Use Software Bill of Materials (SBOM).
- Scan for vulnerabilities in code and dependencies.
- Sign and verify artifacts (e.g. cosign, sigstore).
- Use trusted and private registries.
- Prevent tampered or untrusted images.
- Monitor and enforce supply chain policies.

## 6. Policy Enforcement and Security Boundaries




## 7. Zero Trust End-to-End Flow




## 8. Senior Engineer Insight

- Design security for humans, services and machines from the start.
- Use least privilege and short-lived credentials.
- Integrate security into CI/CD and infrastructure.
- Continuously monitor, detect and respond.
- Assume breach and validate security controls regularly.


VERIQTA

# GitOps Architecture


## 1. Key Concepts

- **Git as the declared source of desired state** – infrastructure and applications are defined in Git repositories.
- **Argo CD and Flux reconciliation** – continuously compare desired state (Git) with actual state (cluster) and apply changes.
- **Environment promotion** – move changes through dev, staging and production in a controlled and repeatable way.
- **Configuration drift** – detect and correct differences between desired and actual state.
- **Rollback and failure scenarios** – quickly revert to a known good state and handle common GitOps failures.


## 2. GitOps Architecture Overview




## 3. Argo CD Architecture




## 4. Flux Architecture




## 5. Environment Promotion and Configuration Drift

| Development | Staging | Production |
|---|---|---|
| Develop and test changes. | Promote from dev (pull request / merge). | Promote from staging (approved release). |
| Automated sync from feature branch. | Run automated tests and security checks. | Strict change control and monitoring. |
| Validate functionality. | Verify configuration matches desired state. | Continuous drift detection and correction by GitOps controller. |

**Configuration Drift Detection**

- Controller continuously compares Git desired state with actual cluster state.
- Detects manual changes made outside Git.
- Automatically reverts or alerts based on policy.

## 6. Rollback, Secrets and GitOps Failure Scenarios

**Rollback**

- Revert to previous Git commit.
- Use Git history for quick rollback.
- Automated rollback on failure (optional).


**Secrets Management**

- Use external secret managers (e.g. AWS Secrets Manager, HashiCorp Vault).
- Integrate with Sealed Secrets, SOPS or External Secrets Operator.
- Avoid storing plaintext secrets in Git.

**Common Failure Scenarios**

- Sync failures (invalid manifests).
- Image pull errors.
- Cluster connectivity issues.
- Drift due to manual changes.
- Secrets misconfiguration.
- Controller or webhook failures.
- Mitigate with monitoring, alerts and clear runbooks.

## 7. Example GitOps Workflow




## 8. Senior Engineer Insight

- Keep Git as the single source of truth.
- Use automated tests and policy checks before promotion.
- Implement strong secrets management.
- Monitor sync status, drift and failures.
- Have a clear rollback and recovery plan.
- Document runbooks for common failures.


VERIQTA

# Microservices and Distributed Systems

## 1. Key Concepts


- **Synchronous vs asynchronous communication** – different patterns for service-to-service communication.
- **API gateways, service discovery, and messaging** – core building blocks for microservices.
- **Timeouts, retries, circuit breakers, and idempotency** – handle failures and improve resilience.
- **Distributed transactions and consistency trade-offs** – manage data across multiple services.

## 2. Microservices Architecture Overview




## 3. Synchronous vs Asynchronous Communication

### Synchronous Communication (e.g. HTTP/REST, gRPC)




- Client waits for a response.
- Simple and easy to understand.
- Suitable for real-time operations.
- Can lead to increased latency and tight coupling.

### Asynchronous Communication (e.g. Message Queues, Events)




- Client does not wait for a response.
- Improves scalability and resilience.
- Suitable for background and long-running tasks.
- Uses message brokers (e.g. Kafka, RabbitMQ, SQS).

## 4. API Gateways, Service Discovery and Messaging

### API Gateway

- Single entry point for clients.
- Routes requests to services.
- Handles authentication, authorization, rate limiting and logging.
- Examples: Kong, NGINX, AWS API Gateway, Istio Ingress.

### Service Discovery

- Helps services find each other dynamically.
- Supports dynamic scaling and resilience.
- Examples: Kubernetes DNS, Consul, Eureka, AWS Cloud Map.

### Messaging

- Enables asynchronous communication.
- Decouples services and improves resilience.
- Examples: Kafka, RabbitMQ, Amazon SQS, NATS.

## 5. Timeouts, Retries, Circuit Breakers and Idempotency

### Timeouts

- Set a maximum time to wait for a response.
- Prevents hanging requests.
- Choose appropriate values based on service behavior.

### Retries

- Automatically retry failed requests.
- Use exponential backoff.
- Set a maximum number of retries to avoid overload.

### Circuit Breakers

- Prevent repeated calls to a failing service.
- Fail fast when a service is unhealthy.
- Automatically recover when the service is healthy again.

### Idempotency

- Ensure repeated requests have the same effect.
- Use idempotency keys (e.g. order ID).
- Important for retries and distributed systems.

## 6. Distributed Transactions and Consistency Trade-offs

### Transaction Patterns

**Two-Phase Commit (2PC)**
Strong consistency but complex and can impact availability.

**Saga Pattern**
Breaks a transaction into a series of local transactions with compensating actions.

**Eventual Consistency**
Data is eventually consistent across services, improving availability and scalability.


### Consistency Trade-offs

**Strong Consistency**
All services see the same data at the same time.
Higher latency, lower availability.

**Eventual Consistency**
Data converges over time.
Higher availability and scalability.

**Choose based on business requirements**
Consistency, availability, and partition tolerance (CAP Theorem).

## 7. Example: Order Processing Flow




## 8. Senior Engineer Insight

- Use asynchronous communication for better scalability and resilience.
- Set realistic timeouts and retry policies.
- Implement circuit breakers for critical services.
- Design idempotent operations.
- Choose the right consistency model for your business needs.
- Monitor and trace requests across services.

VERIQTA


# Database and Stateful Infrastructure Architecture

## 1. Key Concepts

- **Database replication and failover** – keep data available and resilient across failures.
- **Read replicas, partitioning, and scaling** – improve performance and handle growth.
- **Storage durability and consistency** – ensure data is not lost and behaves as expected.
- **Backup verification and schema migration risks** – validate backups and manage database changes safely.

## 2. Database Replication and Failover

### Primary-Replica Setup




### Failover Process

1. Detect Failure (health checks)
2. Promote Replica to Primary
3. Update DNS / Connection (redirect traffic)
4. Resume Operations (minimize downtime)


## 3. Read Replicas, Partitioning and Scaling

### Read Replicas (Scale Reads)




- Offload read traffic from primary.
- Improve performance and availability.
- Used for analytics, reporting and high read workloads.

### Partitioning (Shard Data)




- Split data across multiple partitions.
- Improve performance and scalability.
- Can be horizontal (sharding) or vertical (partitioning by table/column).

### Scaling Strategies

- **Vertical Scaling** (increase CPU, RAM, storage)
- **Horizontal Scaling** (add more instances)
- **Auto Scaling** (scale based on demand)

## 4. Storage Durability and Consistency

### Storage Durability

- Replicate data across availability zones or regions.
- Use durable storage systems (e.g. EBS, EFS, RDS, etc).
- Protect against hardware failures, human errors and disasters.
- Regularly test durability through backup and restore.

### Consistency Models

- **Strong Consistency** – All reads see the latest write (e.g. single primary).
- **Eventual Consistency** – Changes propagate over time (e.g. NoSQL, distributed systems).
- **Read Your Writes** – User always sees their own writes.
- **Monotonic Reads** – Reads never go backwards in time.

## 5. Backup Verification and Recovery

| Create Backup | Store Securely | Verify Backup | Restore |
|---|---|---|---|
| Full / Incremental Backup (automated) | Encrypted and stored in multiple locations (e.g. cross-region) | Regularly test restore from backup (ensure data is usable) | Restore to a test environment (validate integrity) |

**Best Practices**

- Automate backups and retention.
- Regularly test restores (not just assume backups work).
- Monitor backup success and failures.
- Store backups in multiple locations (e.g. different regions).
- Validate data integrity after restore.

## 6. Schema Migration Risks

### Common Risks

- Downtime during migration.
- Data loss or corruption.
- Application incompatibility.
- Long-running migrations impacting performance.
- Failed rollbacks.
- Schema drift between environments.

### Mitigation Strategies

- Test migrations in non-production environments first.
- Use backward-compatible schema changes.
- Apply migrations in small, incremental steps.
- Have a rollback plan.
- Monitor application and database performance during migration.
- Use tools (e.g. Flyway, Liquibase) for controlled migrations.

## 7. Example: Database Architecture




## 8. Senior Engineer Insight

- Design for failure, not just performance.
- Use replication, backups and multi-region strategies for resilience.
- Choose the right consistency model for your use case.
- Test restore procedures regularly.
- Plan schema changes carefully and monitor impact.
- Automate and monitor everything (backups, replication, migrations).


VERIQTA

# Multi-Account and Multi-Region Cloud Architecture

## 1. Key Concepts

- **Account and subscription isolation** – separate accounts for security, governance and blast radius reduction.
- **Centralized identity, networking, and logging** – unified control across multiple accounts and regions.
- **Regional routing and data residency** – route traffic and store data based on requirements and user location.
- **Cross-region resilience and operational complexity** – design for failure and manage the added complexity at scale.

## 2. Multi-Account Architecture




## 3. Centralized Identity, Networking and Logging

### Identity Management

- Centralized identity (e.g. AWS IAM Identity Center, Azure Entra ID).
- Single sign-on (SSO) across all accounts.
- Role-based access control (RBAC) and least privilege.
- Centralized audit logs.


### Networking

- Centralized network architecture (e.g. transit VPC, hub-and-spoke).
- Shared services (DNS, firewall, NAT, load balancers).
- Private connectivity between accounts/regions.
- Network segmentation and security policies.

### Logging and Monitoring

- Centralized log collection (e.g. CloudWatch, Azure Monitor, ELK).
- Cross-account and multi-region visibility.
- Audit trails and compliance logging.
- Real-time alerting and dashboards.

## 4. Multi-Region Architecture




## 5. Regional Routing and Data Residency

### Routing Strategies

- Geo DNS / Anycast
- Latency-based routing
- Health check based failover
- Traffic management (e.g. Route 53, Azure Traffic Manager)

### Data Residency

- Store data in specific regions to meet legal and regulatory requirements.
- Comply with data protection laws (e.g. GDPR).
- Control data movement across regions.
- Use region-specific services and encryption.

### Example Routing Flow

User Request
↓
Global DNS (latency / geo-based)
↓
Route to Nearest Region (healthy)
↓
Application

## 6. Cross-Region Resilience

### Resilience Patterns

- Active-active (multiple regions).
- Active-passive (standby region).
- Data replication (across regions).
- Automated failover and recovery.


### Key Considerations

- Handle regional failures (natural disasters, outages).
- Test failover regularly.
- Ensure data consistency.
- Design for stateless and stateful workloads.
- Use infrastructure as code for repeatability.

### Operational Complexity

- More complex networking and routing.
- Data synchronization and consistency challenges.
- Higher cost and management overhead.
- Need for strong automation and monitoring.
- More complex incident response and troubleshooting.

## 7. Example Multi-Account and Multi-Region Setup




## 8. Senior Engineer Insight

- Use multiple accounts to reduce blast radius and improve security.
- Centralize identity, networking and logging.
- Design for data residency and compliance from the start.
- Implement automated failover and test regularly.
- Manage operational complexity with automation, infrastructure as code, and clear documentation.
- Monitor costs and resource usage across accounts and regions.


VERIQTA

# Platform Engineering and Internal Developer Platforms

## 1. Key Concepts

- **Self-service infrastructure and golden paths** – enable developers to provision, deploy and operate using predefined, secure and compliant paths.
- **Developer portals and reusable templates** – provide a centralized experience to access services, templates and documentation.
- **Platform APIs and infrastructure abstractions** – hide infrastructure complexity behind simple, consistent interfaces.
- **Measuring platform adoption and effectiveness** – track usage, developer satisfaction and business impact.

## 2. Internal Developer Platform Architecture




## 3. Self-Service Infrastructure and Golden Paths

### Golden Path Example

- Developer selects template (e.g. web application)
- Pre-configured, secure and compliant template
- Automated provisioning (Terraform, Crossplane, etc.)
- Ready-to-use environment with best practices (networking, security, monitoring)

### Benefits

- Faster and consistent environments.
- Reduced manual work and errors.
- Enforces security and compliance.
- Improves developer productivity.
- Standardizes infrastructure across teams.

## 4. Developer Portals and Reusable Templates


### Developer Portal Components

- **Service Catalog** (browse and provision services)
- **Templates** (reusable, versioned templates)
- **Documentation** (how-to guides, examples)
- **Access Control** (role-based access)
- **Support and Community** (FAQs, chat, feedback)

### Template Examples

- **Application Template** (e.g. web app, API)
- **Database Template** (e.g. PostgreSQL, MySQL)
- **Kubernetes Template** (e.g. microservice)
- **Infrastructure Template** (e.g. VPC, networking)
- **CI/CD Template** (e.g. GitHub Actions, GitLab CI)

## 5. Platform APIs and Infrastructure Abstractions




## 6. Measuring Platform Adoption and Effectiveness


### Key Metrics

- **Adoption Rate** (number of teams and users)
- **Usage Metrics** (templates, services, API calls)
- **Developer Satisfaction** (surveys and feedback)
- **Time to Provision** (reduced lead time)
- **Reliability and Performance** (uptime, incident rate)
- **Business Impact** (faster delivery, cost savings)

### Ways to Improve

- Continuously improve templates and documentation.
- Gather and act on developer feedback.
- Reduce friction and approval steps.
- Add new services based on demand.
- Ensure security and compliance without slowing developers down.

## 7. Example Platform Engineering Workflow




## 8. Senior Engineer Insight

- Keep the platform simple and easy to use.
- Start with high-value use cases.
- Focus on developer experience.
- Measure real adoption and business impact.
- Continuously iterate based on feedback.
- Balance flexibility with standardization.


VERIQTA

# DevOps Architecture Interview Scenarios

## 1. Design a Deployment Platform for 100 Microservices

### Requirements

- Support 100+ services.
- Automated CI/CD.
- Scalable and secure.
- Self-service for teams.
- Observability and governance.




### Key Design Decisions

- Use Kubernetes with GitOps (Argo CD / Flux).
- Standardize service templates.
- Shared platform services (networking, observability, security).
- Use IaC (Terraform) for reproducibility.
- Implement service mesh (e.g. Istio) for traffic, security and observability.
- Define CI/CD templates and automated testing.
- Set resource quotas and governance policies.

### Trade-offs


- Cost vs scalability.
- Platform standardization vs team flexibility.
- Centralization vs autonomy.
- Complexity of multi-cluster management.
- Speed of delivery vs security and compliance.

## 2. Migrate a Monolith to Kubernetes with Minimal Downtime

### Strategy

- Identify and understand dependencies.
- Containerize the application.
- Incrementally migrate (using strangler pattern).
- Use database migration strategies.
- Implement traffic shifting (blue/green or canary).
- Validate, monitor and rollback if needed.

### Migration Flow




#### Strangler Pattern (Incremental Migration)




### Key Considerations


- Minimize downtime with incremental migration.
- Handle database migration carefully.
- Use feature flags.
- Ensure backward compatibility.
- Monitor performance and errors.
- Have a rollback plan.

### Risks and Mitigations

- Data inconsistency → Use replication and dual writes.
- Service dependency issues → Thorough testing and staging.
- Performance degradation → Load testing and monitoring.
- Deployment failure → Quick rollback strategy.

## 3. Design a Highly Available Multi-Region Application

### Architecture Overview




### Key Components

- Global DNS (latency/health checks).
- Multi-region load balancing.
- Cross-region database replication.
- Shared/static assets (CDN).
- Automated failover and recovery.
- Monitoring, alerting and testing.

### Design Considerations

- Choose region strategy (active-active or active-passive).
- Data residency and compliance requirements.
- Handling stateful services across regions.
- Failover time objectives (RTO/RPO).
- Cost vs resilience trade-offs.
- Regular disaster recovery testing.

### Trade-offs

- Higher cost for multi-region setup.
- Complexity of data synchronization.
- Latency between regions.
- Active-active vs active-passive design.
- Consistency vs availability trade-offs.

## 4. Troubleshoot a Failing Production Deployment

### Troubleshooting Steps

1. Check deployment status and recent changes.
2. Review logs (application, container, infrastructure).
3. Verify resource usage (CPU, memory, network).
4. Check dependencies (databases, external services).
5. Identify root cause (configuration, code, infrastructure).
6. Fix, redeploy and monitor.

### Common Issues

- Application error (code or configuration).
- Database connectivity issues.
- Networking or DNS issues.
- Resource limits (CPU/Memory).
- Image or dependency issues.
- Permission or security issues.

### Tools

- kubectl / CLI
- Logs (e.g. Loki, CloudWatch)
- Metrics (e.g. Prometheus)
- Traces (e.g. Jaeger)
- Deployment history
- Monitoring dashboards

## 5. Explain Design Decisions, Trade-offs and Failure Recovery

### How to Answer

- Clearly state the requirements.
- Explain your architecture and why you chose it.
- Discuss alternative options and trade-offs.
- Highlight failure scenarios and recovery strategy.
- Show awareness of cost, security, scalability and operability.

### Key Areas to Cover

- Scalability (horizontal/vertical).
- Security (identity, network, data).
- Cost (managed vs self-managed).
- Operational complexity.
- Failure recovery (backup, failover).
- Real-world experience and best practices.

## 6. Senior Engineer Insight

- Think out loud and explain your reasoning.
- Be clear about trade-offs (there is no perfect solution).
- Consider real-world constraints (team, budget, compliance, timeline).
- Discuss failure scenarios and how you would recover.
- Demonstrate hands-on experience with tools and technologies.
- Show that you can design, operate and troubleshoot at scale.

VERIQTA

# Senior DevOps Architecture Interview Challenge


## 1. End-to-End Architecture Design Exercise

### Scenario

Design a global, highly available e-commerce platform that can handle:

- Millions of users.
- Multiple microservices (100+ services).
- Multi-region deployment.
- Secure, scalable and cost-efficient.
- Fast feature delivery with minimal downtime.

### High-Level Architecture




## 2. Define Requirements, Constraints and Assumptions

### Business Requirements

- High availability (99.99% uptime).
- Global user base (low latency).
- Support for 100+ microservices.
- Secure and compliant (e.g. GDPR, PCI DSS).
- Scalable to handle traffic spikes.
- Fast and reliable deployments.

### Constraints

- Budget limits.
- Team skills and operational capacity.
- Compliance and regulatory requirements.
- Technology choices (e.g. cloud provider).
- Existing systems (legacy integration).

### Assumptions

- Using a major cloud provider (AWS, Azure or GCP).
- Infrastructure as code (Terraform).
- Kubernetes for container orchestration.
- Managed databases and services where possible.
- Global team and follow the best practices.
- Focus on real-world design and trade-offs.

## 3. Present Infrastructure, CI/CD, Security and Observability

### Infrastructure

- Multi-region architecture (active-active or active-passive).
- VPC/network design (public, private subnets).
- Load balancers and auto scaling groups.
- Managed Kubernetes (EKS/AKS/GKE).
- Managed databases with replication.
- Use of CDN and caching (CloudFront, Cloud CDN, etc).

### CI/CD Pipeline

- Code Commit (GitHub/GitLab/Bitbucket)
- CI (Build, Test, Scan)
- Artifact Registry
- CD (Deploy to Kubernetes)
- Progressive Delivery (Blue/Green, Canary)

### Security

- Identity and access management (IAM, RBAC).
- Secrets management (e.g. AWS Secrets Manager, Vault).
- Network security (VPC, Security Groups, WAF).
- Container and image scanning (Trivy, ECR scan).
- Policy enforcement (e.g. OPA, Kyverno).
- Compliance and audit logging.

### Observability

- Centralized logging (e.g. ELK, Loki).
- Metrics and monitoring (e.g. Prometheus, Grafana).
- Distributed tracing (e.g. OpenTelemetry, Jaeger).
- Application performance monitoring (APM).
- Alerts and incident response (e.g. PagerDuty, Alertmanager).
- Dashboards and SLO-based monitoring.

## 4. Explain Scaling, Resilience, Disaster Recovery and Costs

### Scaling

- Horizontal scaling (auto scaling).
- Vertical scaling (when needed).
- Database scaling (read replicas, sharding).
- Caching and CDN.
- Handle traffic spikes (auto scaling policies, queueing).

### Resilience

- Multi-AZ and multi-region deployment.
- Auto healing (liveness/readiness probes).
- Circuit breakers and retries.
- Stateless services where possible.
- Graceful degradation.

### Disaster Recovery

- RTO and RPO definition.
- Cross-region backups and replication.
- Automated failover.
- Regular DR testing.
- Infrastructure as code for quick recovery.

### Cost Optimization

- Use managed services.
- Right-sizing resources.
- Auto scaling and scheduling.
- Spot instances for non-critical workloads.
- Monitor and optimize with cost tools (e.g. AWS Cost Explorer, Azure Cost Management).

## 5. Defend Architectural Trade-offs Under Interviewer Questioning

### Example Interview Questions

- Why did you choose Kubernetes over serverless?
- How do you handle data consistency across regions?
- What are the trade-offs of active-active vs active-passive?
- How do you ensure security without slowing down delivery?
- What happens if a region goes down?
- How do you balance cost, performance and reliability?
- How would you reduce complexity?

### How to Answer

- Explain your reasoning clearly.
- Discuss alternative options.
- Highlight trade-offs (pros and cons).
- Consider real-world constraints (team, budget, compliance).
- Show awareness of failure scenarios.
- Use metrics and best practices to justify.
- Be honest and practical, not perfect.

### Key Points to Demonstrate

- Deep technical knowledge.
- Ability to design end-to-end systems.
- Clear communication and structured thinking.
- Real-world experience and best practices.
- Awareness of scalability, security, resilience and costs.
- Ability to make and defend trade-offs.
- Focus on business and user impact.