Jammer Configuration			
Jammer type ▼	CW		
Center frequency (MHz)	1575.4	**Tx power (dBm)**	Up-to 40 dB
Spatial angle – Azimuth (°)		**Spatial angle – Elevation (°)**	
Tx antenna gain (dBi)		**Distance to DUT (m)**	6.5m
Est. J/S at DUT (dB)			

4. Jammer Enabled – CRPA Nulling Active

4.1 Interference Suppression

Method	Suppression (dB)	Remarks
RMS (power before vs after nulling)	10	
Peak (Pmax − Pmin)		

4.2 Electronic Phase Angle / Weights

Parameter	Value
Phase (°)	
Weight magnitude	
Complex weight (I + jQ)	

4.3 Normal Start (as powered)

TTFF lock time (s) – Normal Start	116		
TTFF lock time (s) + 1 minute		**Fix type / HDOP**	

Constellation	Satellites tracked	Satellites used in fix	Avg C/N_0 (dB-Hz)	Max C/N_0 (dB-Hz)
GPS (L1 C/A)	4	4	35	37
GLONASS (L1OF)	0	0	0	0
BeiDou (B1I)	0	0	0	0
Galileo (E1)	0	0	0	0
Total / overall (auto)	**4**	**4**	**8.8**	**37**

4.4 Hot Start

TTFF lock time (s) – Hot Start				4
TTFF lock time (s) + 1 minute		Fix type / HDOP		
Constellation	Satellites tracked	Satellites used in fix	Avg C/N_0 (dB-Hz)	Max C/N_0 (dB-Hz)
GPS (L1 C/A)	4	4	35	37
GLONASS (L1OF)	0	0	0	0
BeiDou (B1I)	0	0	0	0
Galileo (E1)	0	0	0	0
Total / overall (auto)	**4**	**4**	**8.8**	**37**

4.5 Cold Start

TTFF lock time (s) – Normal Start				116
TTFF lock time (s) + 1 minute		Fix type / HDOP		
Constellation	Satellites tracked	Satellites used in fix	Avg C/N_0 (dB-Hz)	Max C/N_0 (dB-Hz)
GPS (L1 C/A)	4	4	35	37
GLONASS (L1OF)	0	0	0	0
BeiDou (B1I)	0	0	0	0

Galileo (E1)	0	0	0	0
Total / overall (auto)	**4**	**4**	**8.8**	**37**